



BRB-X3210S1E

32kanálové zařízení BLAZE



Key Features

- Předinstalovaný BLAZE Client, Server a 32ch prémiové licence
- Až 250Mbps šířka pásma pro záznam
- 4 pozice pro HDD (3,5"), až 64TB
- Podpora RAID 1
- Zpevněný OS
- 2 x RJ-45 (1Gbps), 16 x PoE RJ-45 (10/100Mbps), PoE kapacita 200W
- FIPS 140-3 úroveň 3, v souladu s NDAA, certifikováno UL, certifikováno FCC

BRB-X3210S1E

32kanálové zařízení BLAZE



Specifications

System

Video Management Software		BLAZE VMS
Licenses		32 x BLAZE Premium License
Available Channels		Up to 32 channels
Recording Rate		Up to 250Mbps
OS Drive Bays		eMMC 32GB
Data Drive Bays		SATA 4ea
Data Storage		Up to 64TB
RAID Support		RAID 1
Network Interface		2 x RJ-45 (1Gbps), 16 x PoE RJ-45(10/100Mbps)
Memory		16GB DDR4
Operating System		Hardened OS
Decoding	Video Outputs	Duplicate: 1 x HDMI(4K),1 x DP(4K), Extend: 1 x HDMI(FHD),1 x DP(FHD)
	Resolution	Decoding Performance (H.264) - UHD Duplicate Mode: 5CH*8M@15fps,13CH*2M@15fps, 32CH*640x360@7fps - FHD/FHD Extend Mode: (2CH+2CH)*8M@15fps, (6CH+6CH)*2M@15fps,(15CH+15CH)* 640x360@7fps
USB Ports		Front 2 x USB 2.0 Rear 2 x USB 3.0
Audio	Output	1x Audio output
	Audio Communication	2-Way (Audio In: USB Mic)
Keyboard & Mouse		Keyboard, Mouse

Mechanical

Form Factor	Box
Color / Material	Black / Metal
Dimensions (WxHxD)	17.32"(440mm) x 3.54"(89.8mm) x 16.87"(428.4mm)
Weight	12.26lbs (5.56Kg)

Electrical

Power Input	100 ~ 240 VAC $\pm$ 10%, 50/60 Hz
Power Consumption	80W (272.96 BTU, without PoE)

Electrical

PoE Budget	200W
------------	------

Environmental

Operating Temperature	32°F to 104°F(0°C to 40°C)
Operating Humidity	20% to 85% RH (non-condensing)

BRB-X3210S1E

32kanálové zařízení BLAZE



CAD

Unit: mm [inch]

