



BRB-X3210S1E

32-kanalowe urządzenie BLAZE



Key Features

- Preinstalowany BLAZE Client, Server i 32-kanalowe licencje premium
- Do 250 Mbps przepustowości nagrywania
- 4 zatoki na dyski HDD (3,5"), do 64 TB
- Wsparcie RAID 1
- Zahartowany system operacyjny
- 2 x RJ-45 (1 Gbps), 16 x PoE RJ-45 (10/100 Mbps), PoE budżet 200 W
- FIPS 140-3 poziom 3, zgodność z NDAA, certyfikacja UL, certyfikat FCC

BRB-X3210S1E

32-kanalowe urządzenie BLAZE



Specifications

System		
Video Management Software		BLAZE VMS
Licenses		32 x BLAZE Premium License
Available Channels		Up to 32 channels
Recording Rate		Up to 250Mbps
OS Drive Bays		eMMC 32GB
Data Drive Bays		SATA 4ea
Data Storage		Up to 64TB
RAID Support		RAID 1
Network Interface		2 x RJ-45 (1Gbps), 16 x PoE RJ-45(10/100Mbps)
Memory		16GB DDR4
Operating System		Hardened OS
Decoding	Video Outputs	Duplicate: 1 x HDMI(4K),1 x DP(4K), Extend: 1 x HDMI(FHD),1 x DP(FHD)
	Resolution	Decoding Performance (H.264) - UHD Duplicate Mode: 5CH*8M@15fps,13CH*2M@15fps, 32CH*640x360@7fps - FHD/FHD Extend Mode: (2CH+2CH)*8M@15fps, (6CH+6CH)*2M@15fps,(15CH+15CH)* 640x360@7fps
USB Ports		Front 2 x USB 2.0 Rear 2 x USB 3.0
Audio	Output	1x Audio output
	Audio Communication	2-Way (Audio In: USB Mic)
Keyboard & Mouse		Keyboard, Mouse
Mechanical		
Form Factor		Box
Color / Material		Black / Metal
Dimensions (WxHxD)		17.32"(440mm) x 3.54"(89.8mm) x 16.87"(428.4mm)
Weight		12.26lbs (5.56Kg)
Electrical		
Power Input		100 ~ 240 VAC $\pm$ 10%, 50/60 Hz
Power Consumption		80W (272.96 BTU, without PoE)

Electrical

PoE Budget	200W
------------	------

Environmental

Operating Temperature	32°F to 104°F(0°C to 40°C)
-----------------------	----------------------------

Operating Humidity	20% to 85% RH (non-condensing)
--------------------	--------------------------------

BRB-X3210S1E

32-kanalowe urządzenie BLAZE



CAD

Unit: mm [inch]

