

BRB-X3210S1E

Dispositivo BLAZE a 32 canali

Key Features

- Client BLAZE preinstallato, Server e licenze premium per 32 canali
- Fino a 250Mbps di larghezza di banda di registrazione
- 4 alloggiamenti HDD (3.5"), fino a 64TB
- Supporto RAID 1
- Sistema operativo rinforzato
- 2 x RJ-45 (1Gbps), 16 x PoE RJ-45 (10/100Mbps), capacità PoE 200W
- Conforme a FIPS 140-3 livello 3, NDAA, elencato UL, certificato FCC

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

BRB-X3210S1E

Dispositivo BLAZE a 32 canali



Specifications

System

Video Management Software		BLAZE VMS
Licenses		32 x BLAZE Premium License
Available Channels		Up to 32 channels
Recording Rate		Up to 250Mbps
OS Drive Bays		eMMC 32GB
Data Drive Bays		SATA 4ea
Data Storage		Up to 64TB
RAID Support		RAID 1
Network Interface		2 x RJ-45 (1Gbps), 16 x PoE RJ-45(10/100Mbps)
Memory		16GB DDR4
Operating System		Hardened OS
Decoding	Video Outputs	Duplicate: 1 x HDMI(4K),1 x DP(4K), Extend: 1 x HDMI(FHD),1 x DP(FHD)
	Resolution	Decoding Performance (H.264) - UHD Duplicate Mode: 5CH*8M@15fps,13CH*2M@15fps, 32CH*640x360@7fps - FHD/FHD Extend Mode: (2CH+2CH)*8M@15fps, (6CH+6CH)*2M@15fps,(15CH+15CH)* 640x360@7fps
USB Ports		Front 2 x USB 2.0 Rear 2 x USB 3.0
Audio	Output	1x Audio output
	Audio Communication	2-Way (Audio In: USB Mic)
Keyboard & Mouse		Keyboard, Mouse

Mechanical

Form Factor	Box
Color / Material	Black / Metal
Dimensions (WxHxD)	17.32"(440mm) x 3.54"(89.8mm) x 16.87"(428.4mm)
Weight	12.26lbs (5.56Kg)

Electrical

Power Input	100 ~ 240 VAC ±10%, 50/60 Hz
Power Consumption	80W (272.96 BTU, without PoE)

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

Electrical

PoE Budget	200W

Environmental

Operating Temperature	32°F to 104°F(0°C to 40°C)
Operating Humidity	20% to 85% RH (non-condensing)

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.


BRB-X3210S1E

Dispositivo BLAZE a 32 canali



CAD

Unit: mm [inch]



Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.