



BRR-P6410A2E

64CH BLAZE Appliance



Key Features

- Pre-installed BLAZE Client, Server and 64ch premium licenses
- Up to 520Mbps recording bandwidth
- (AI) Semantic Search Support
- 8 HDD bays (3.5"), up to 80TB
- Hardened OS
- RAID 1/5/6 support
- 3 x RJ-45 (1Gbps)
- FIPS 140-3 level 3, NDAA compliant, UL listed, FCC certified

BRR-P6410A2E

64CH BLAZE Appliance



Specifications

System

Video Management Software		BLAZE VMS
Licenses		64 x BLAZE Premium License
Available Channels		Up to 64 channels
Recording Rate		Up to 520Mbps
OS Drive Bays		SSD 128GB
Data Drive Bays		SATA 8ea
Data Storage		Up to 80TB
RAID Support		RAID 1, RAID 5, RAID 6
Network Interface		3 x RJ-45 (1Gbps)
Memory		16GB DDR4
AI Card		Yes
Operating System		Hardened OS
Decoding	Video Outputs	1 x HDMI(FHD), 1 x HDMI(4K)
USB Ports		Front 2 x USB 2.0 Rear 2 x USB 3.0
Audio	Output	1x Audio output
	Audio Communication	2-Way (Audio In: USB Mic)
Keyboard & Mouse		Keyboard, Mouse

Security

Security Certificate	FIPS 140-3 Level3
----------------------	-------------------

Mechanical

Form Factor	2U rack
Color / Material	Black / Metal
Dimensions (WxHxD)	17.24"(438mm) x 3.39"(86mm) x 17.12"(434.9mm)
Weight	20.06lbs (9.10Kg)

Electrical

Power Input	100 ~ 240 VAC $\pm$ 10%, 50/60 Hz
Power Consumption	238W (812.1BTU, Max)

Environmental

Operating Temperature	32°F to 104°F(0°C to 40°C)
Operating Humidity	20% to 85% RH (non-condensing)

BRR-P6410A2E

64CH BLAZE Appliance



CAD

Unit: mm [inch]

