



BRR-P6410A4E

64채널 BLAZE 어플라이언스



Key Features

- 기본 탑재 BLAZE Client, Server 및 64채널 프리미엄 라이선스
- 최대 520Mbps 녹화 대역폭
- (AI) 시맨틱 검색 지원
- 16개의 HDD 베이 (3.5"), 최대 160TB
- 강화된 OS
- RAID 1/5/6 지원
- 3 x RJ-45 (1Gbps)
- NDAA 준수, UL 등재, FCC 인증

BRR-P6410A4E

64채널 BLAZE 어플라이언스



Specifications

System

Video Management Software		BLAZE VMS
Licenses		64 x BLAZE Premium License
Available Channels		Up to 64 channels
Recording Rate		Up to 520Mbps
OS Drive Bays		SSD 128GB
Data Drive Bays		SATA 16ea
Data Storage		Up to 160TB
RAID Support		RAID 1, RAID 5, RAID 6
Network Interface		3 x RJ-45 (1Gbps)
Memory		16GB DDR4
AI Card		Yes
Operating System		Hardened OS
Decoding	Video Outputs	Duplicate: 2 x HDMI (4K), Extend: 1 x HDMI (4K), 1 x HDMI (FHD)
	Resolution	Decoding Performance (H.264) – UHD Duplicate Mode: 26CH*8M@15fps, 64CH*2M@15fps, 64CH*640x360@7fps – UHD/FHD Extend Mode: (14CH+14CH)*8M@15fps, (32CH+32CH)*2M@15fps, (32CH+32CH)*640x360@7fps
USB Ports		Front 2 x USB 2.0 Rear 2 x USB 3.0
Audio	Output	1x Audio output
	Audio Communication	2-Way (Audio In: USB Mic)
Keyboard & Mouse		Keyboard, Mouse

Mechanical

Form Factor	3U rack
Color / Material	Black / Metal
Dimensions (WxHxD)	17.32" (440mm) x 5.20" (132mm) x 22.48" (571.1mm)
Weight	31.3 lbs (14.2kg)

Electrical

Power Input	100 ~ 240 VAC ± 10%, 50/60 Hz
Power Consumption	283W (965.6 BTU)

Environmental

Operating Temperature	32°F to 104°F (0°C to 40°C)
Operating Humidity	20% to 85% RH (non-condensing)

BRR-P6410A4E

64채널 BLAZE 어플라이언스



CAD

Unit: mm [inch]

