

BRR-P6410A4E

Appareil BLAZE 64CH

Key Features

- Client BLAZE préinstallé, serveur et licences premium 64 canaux
- Jusqu'à 520 Mbps de bande passante d'enregistrement
- Prise en charge de la recherche sémantique (AI)
- 16 baies pour disques durs (3,5"), jusqu'à 160 To
- Système d'exploitation renforcé
- Prise en charge RAID 1/5/6
- 3 x RJ-45 (1 Gbps)
- Conforme NDAA, listé UL, certifié FCC

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

BRR-P6410A4E

Appareil BLAZE 64CH



Specifications

System

Video Management Software		BLAZE VMS
Licenses		64 x BLAZE Premium License
Available Channels		Up to 64 channels
Recording Rate		Up to 520Mbps
OS Drive Bays		SSD 128GB
Data Drive Bays		SATA 16ea
Data Storage		Up to 160TB
RAID Support		RAID 1, RAID 5, RAID 6
Network Interface		3 x RJ-45 (1Gbps)
Memory		16GB DDR4
AI Card		Yes
Operating System		Hardened OS
Decoding	Video Outputs	Duplicate: 2 x HDMI(4K), Extend: 1 x HDMI(4K),1 x HDMI(FHD)
	Resolution	Decoding Performance (H.264) - UHD Duplicate Mode: 26CH*8M@15fps,64CH*2M@15fps, 64CH*640x360@7fps - UHD/FHD Extend Mode: (14CH+14CH)*8M@15fps, (32CH+32CH)*2M@15fps,(32CH+32CH)*640x360@7fps
USB Ports		Front 2 x USB 2.0 Rear 2 x USB 3.0
Audio	Output	1x Audio output
	Audio Communication	2-Way (Audio In: USB Mic)
Keyboard & Mouse		Keyboard, Mouse

Mechanical

Form Factor	3U rack
Color / Material	Black / Metal
Dimensions (WxHxD)	17.32"(440mm) x 5.20"(132mm) x 22.48"(571.1mm)
Weight	31.3 lbs (14.2kg)

Electrical

Power Input	100 ~ 240 VAC ±10%, 50/60 Hz

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

Electrical

Power Consumption	283W (965.6 BTU)

Environmental

Operating Temperature	32°F to 104°F(0°C to 40°C)
Operating Humidity	20% to 85% RH (non-condensing)

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.


BRR-P6410A4E

Appareil BLAZE 64CH



CAD

Unit: mm [inch]



© Hanwha Vision Co.,Ltd. All rights reserved.

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.