



BRR-X3210A2E

32채널 BLAZE 어플라이언스



Key Features

- 기본 탑재 BLAZE Client, Server 및 32채널 프리미엄 라이선스
- 최대 250Mbps 녹화 대역폭
- 8 HDD 베이 (3.5"), 최대 80TB
- RAID 1/5/6 지원
- 강화된 OS
- 3 x RJ-45 (1Gbps)
- NDAA 준수, UL 인증, FCC 인증

BRR-X3210A2E

32채널 BLAZE 어플라이언스



Specifications

System		
Video Management Software		BLAZE VMS
Licenses		32 x BLAZE Premium License
Available Channels		Up to 32 channels
Recording Rate		Up to 250Mbps
OS Drive Bays		SSD 128GB
Data Drive Bays		SATA 8ea
Data Storage		Up to 80TB
RAID Support		RAID 1, RAID 5, RAID 6
Network Interface		3 x RJ-45 (1Gbps)
Memory		16GB DDR4
Operating System		Hardened OS
Decoding	Video Outputs	Duplicate: 2 x HDMI (4K), Extend: 1 x HDMI (4K), 1 x HDMI (FHD)
	Resolution	Decoding Performance (H.264) - UHD Duplicate Mode: 9CH*8M@15fps, 27CH*2M@15fps, 32CH*640x360@7fps - UHD/FHD Extend Mode: (3CH+3CH)*8M@15fps, (6CH+6CH)*2M@15fps, (16CH+16CH)*640x360@7fps
USB Ports		Front 2 x USB 2.0 Rear 2 x USB 3.0
Audio	Output	1x Audio output
	Audio Communication	2-Way (Audio In: USB Mic)
Keyboard & Mouse		Keyboard, Mouse
Mechanical		
Form Factor		2U rack
Color / Material		Black / Metal
Dimensions (WxHxD)		17.24" (438mm) x 3.39" (86mm) x 17.12" (434.9mm)
Weight		19.62lbs (8.90Kg)
Electrical		
Power Input		100 ~ 240 VAC ± 10%, 50/60 Hz
Power Consumption		203W (692.7BTU, Max)

Environmental

Operating Temperature	32°F to 104°F (0°C to 40°C)
Operating Humidity	20% to 85% RH (non-condensing)

BRR-X3210A2E
32채널 BLAZE 어플라이언스



CAD

Unit: mm [inch]

