



BioMini

Fingerprint Scanner



Key Features

- Top results in NIST MINEX tests and FVC
- FIPS 201 certified template extractor and matcher
- NIST certified interoperabl format standards ANSI-378/ISO19794-2)
- Image compression standard (WSQ)
- 100,000 match within a second
- Plug and play USB 2.0 high speed interface
- Supports multiple device handling
- 500 dpi optical fingerprint sensor
- Scratch free sensor surface

BioMini

Fingerprint Scanner



Specifications

Fingerprint Scanner (미사용 항목)		
Fingerprint Sensor		Optical (Scratch free sensor surface)
Resolution		500 DPI / 256 gray
Sensing Area		16.0mm x 18.0mm
Image Size		288 x 320 pixels
Interface		USB 2.0 high speed / Full speed, Plug & play
O/S		Microsoft Windows, Linux
Operating temperature		-10° C ~ 50° C
Certification		CE, FCC, KCC, WHQL
Dimensions (WxHxD)		66.0mm x 90.0mm x 58.0mm
SDK	Template Size	384 Bytes (Configurable)
	Enrollement Time	< 0.1 second
	Verification Time	< 0.1 second
	Identification Time	100,000 matches per second
	Database	Microsoft Access
	Encryption	AES 256
	Supported Platforms	Windows XP, Vista, 7, 8, 8.1, 10 (32/64 bit)