EMC TEST REPORT

Test Report No.	:	KES-EM-22T0888-R1
Date of Issue	:	Feb. 24, 2023
Product Name	:	DVR
Model/Type No.	:	ARD-410
Variant Model	:	-
Applicant	:	Hanwha Vision Co., Ltd
Applicant Address	:	6, Pangyo-ro 319Beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, Republic of Korea
Manufacturer	:	1. HANWHA VISION VIETNAM COMPANY LIMITED 2. D-TECH CO.,LTD.
Manufacturer Address	:	1. Lot O-2, Que Vo Industrial Zone extended area, Nam Son commune, Bac Ninh city, Bac Ninh province, Vietnam 2. 173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi- do, Korea (Suwon Industrial Complex)
Equipment authorization	:	**Supplier's Declaration of Conformity**
Date of Receipt	:	Oct. 13, 2022
Test date	:	Oct. 25, 2022
Test Results	:	☒ **In Compliance** ☐ **Not in Compliance**

Tested by

Seong Min, Jang
EMC Test Engineer

Reviewed by

Dong-Hun, Jang
EMC Technical Manager

This test report is not related to KS Q ISO/IEC 17025 and KOLAS.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

REPORT REVISION HISTORY

Date	Test Report No.	Revision History
Nov. 04, 2022	KES-EM-22T0888	Issued
Feb. 24, 2023	KES-EM-22T0888-R1	Change the Applicant and manufacturer at the request of the customer

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.

TABLE OF CONTENTS

1.0 General Product Description 4
1.1 Test Voltage & Frequency 7
1.2 Variant Model Differences 7
1.3 Device Modifications 7
1.4 Equipment Under Test 7
1.5 Support Equipments 8
1.6 External I/O Cabling 9
1.7 EUT Operating Mode(s) 10
1.8 Configuration 10
1.9 Remarks when standards applied 11
1.10 Calibration Details of Equipment Used for Measurement 11
1.11 Test Facility 11
1.12 Laboratory Accreditations and Listings 11
2.0 Test Regulations 12
2.1 Conducted Emissions at Mains Power Ports 13
2.2 Radiated Electric Field Emissions(Below 1 ㎓) 15
2.3 Radiated Electric Field Emissions(Above 1 ㎓) 17
APPENDIX A – TEST DATA 19
Conducted Emissions at Mains Power Ports 19
Radiated Electric Field Emissions(Below 1 ㎓) 21
Radiated Electric Field Emissions(Above 1 ㎓) 23
Test Setup Photos and Configuration 24
Conducted Emissions at Mains Power Ports 24
Radiated Electric Field Emissions(Below 1 ㎓) 25
Radiated Electric Field Emissions(Above 1 ㎓) 26
EUT External Photographs 27
EUT Internal Photographs 28

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

1.0 General Product Description

Main Specifications of EUT are:

			ARD-410
Display	Display		
Analog camera	Analog camera	Input	4CH(1Vp-p 75ohm, BNC)
		Signal Type	AHD(5MP, 4MP, 1080p, 720p) HDTVI(5MP, 4MP, 1080p, 720p) HDCVI(5MP, 4MP, 1080p, 720p) CVBS(NTSC/PAL)
Network camera	Network camera	Input	Additional 2CH (Max. 6CH)
		Resolution	5MP ~ CIF
		Protocols	SUNAP(Wisenet), ONVIF
Decoding	Decoding	Local Display	None
		Multi Screen Display	None
		Resolution	None
Use	Use	Local Display	1x HDMI, 1x VGA [Single Mode] - HDMI: 3840 x 2160, 2560x1440, 1920x1080, 1280x1024, 1280x720 [Dual Mode] Clone - HDMI: 1920x1080, 1280x1024, 1280x720 - VGA: 1920x1080, 1280x1024, 1280x720
		Multi Screen Display	[Local monitor] - Dynamic layout, Virtual channel view - up to 7 division [Web] 1 / 4
		Resolution	[Analog Camera(NTSC/PAL)] 5MP(5M Half 20fps/12fps) 4MP(4M Half 30fps/25fps) 2MP(2M Half 30fps/25fps) 1MP(1M Half 30fps/25fps) [Network Camera] - Typ. 2MP(120fps)
Performance	Performance		
Operating System	Operating System	Embedded	Linux
Record	Record	Compression	H.265, H.264, MJPEG
		Record Rate(Analog)	[Analog Camera(NTSC/PAL)] (Main Stream) 5MP(5M Half 20fps/12fps) 4MP(4M Half 30fps/25fps) 2MP(2M Half 30fps/25fps) 1MP(1M Half 30fps/25fps) (Sub Stream) 720p or higher : 640x360 full fps/CH SD signal : upto CIF 30/25fps/CH * The maximum recording frame rate depends on the frame rate of the input camera.
		Recording Bandwidth	Max. 30Mbps
		Resolution	5MP ~ CIF
		Mode	Manual, Schedule (Continuous/Event), Event(Pre/Post), Dual Track
		Event Trigger	Alarm Input Analog Camera : Video Loss, Motion Detection,Tampering Network Camera : Camera Event (Sensor, MD, Video analytics), VA event (Tampering, Enter / Exit, Passing, Virtual- line, (Dis)Appear, Face Detection, Audio detection), Defocus, camera event, Dynamic camera event
		Event Action	E-mail,PTZ preset,Alarm out,Buzzer,Monitor out
Search & Play	Search & Play	Playback Bandwidth	Max. 32Mbps
		User	Max. 4 users (Set 1, Remote 3)
		Simultaneous playback	6CH(Local Monitor, CMS, Wisenet Mobile) 1Ch(Web)
		Fisheye Dewarping	WEB / CMS
		Mode	Date & Time (Calendar) / Event log list / Text search (POS), Back up, Motion, Smart search (Virtual Line w/ direction, Enter / Exit) * All Search included Preview function ARB search
		Resolution	5MP ~ CIF
		Playback Control	FastForward&Backward (x2,x4,x8,x16,x32,x64,x128,x256) Slow Forward&Backward (x1/2,x1/4,x1/8) X/8slow one step up/down
Storage	Storage	Supported HDD	Up to 6TB
		HDD Slot	SATA 1ea(Max 6TB)
		External	None
		RAID	None

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

Backup	Backup	File backup	BU, EXE(Include Player), AVI(Webviewer only)
		Function	Max. 6 CH play, Date·time/title display
Network	**Network**		
Protocol	Protocol		TCP/IP, UDP/IP, RTP (UDP), RTP (TCP), RTSP, NTP, HTTP, DHCP (Server, Client), PPPoE, SMTP, ICMP, IGMP, ARP, DNS, DDNS, uPnP, HTTPS, SNMP, ONVIF (Profile·S), SUNAPI(Server, Client)
DDNS	DDNS		Wisenet DDNS
Transmission speed	Transmission speed		[Analog Camera(NTSC/PAL)] (Main Stream) 5MP(5M Half 20fps/12fps) 4MP(4M Half 30fps/25fps) 2MP(2M Half 30fps/25fps) 1MP(1M Half 30fps/25fps) (Sub Stream) 720p or higher : 640x368 full fps/CH SD signal : upto CIF 30/25fps/CH * The maximum recording frame rate depends on the frame rate of the input camera.
Transmission Bandwidth	Transmission Bandwidth		Max. 30Mbps
Transmission Bandwidth	Transmission Bandwidth		None
Wireless	Wireless	WiFi	None
		3G/LTE	None
Audio	Audio	Input/Output	1 Line in / 1 Line out
		Compression	G.711 (N/W Cam G.711, 726)
		Audio Communication	2·Way
Max Remote Users			None
		Security	IP address filtering, User access log, 802.1x Authentication, Encryption (ID/PW, Recording, Transmission, Backup) Device Certificate(Hanwha Techwin Root CA)
Web viewer	Web viewer	Supported OS	Windows 10, Mac OS 11 Big Sur and later
		Supported browser	Chrome v89 or above, Edge v89 or above, Safari v14.0.3 or above
Viewer Software	Viewer Software		SSM, Webviewer, Wisenet Viewer, Wisenet mobile Support SDK/CGI(SUNAPI) for integration to 3'rd party VMS
Functions	**Functions**		
Camera Setup	Camera Setup	Register	Auto, Manual
		Item	None
PTZ	PTZ	Control	Via GUI, Webviewer, SSM, Wisenet Viewer, Wisenet Mobile Viewer, System Controller
		Preset	300 presets
Smart phone	Smart phone	Support Model	iOS, Android
		Protocol Support	RTP, RTSP, HTTP, CGI(SUNAPI)
		Control	Live(16ch) : Multi-Profile Support Playback(4Ch Multi Playback., Max 2MP) Event push
		Max. Remote Users	Search(3), Live Unicast(10)
Redundancy	Redundancy	Failover	None
		ARB	Support
Easy configuration	Easy configuration		Setup Wizard (Language Date/Time, Password, Network, Auto Camera Configuration), P2P (QR code)
Coaxial Control	Coaxial Control		CVBS(Pelco·C)/AHD/CVI/TVI

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

Interface	**Interface**		
Front	Front	Indicator	LED(Status indicator) : Power(1), Record(1), Network(1)
Storage	Storage		None
Reset	Reset		Switch(1EA)
HDD Key Lock	HDD Key Lock		None
HDMI	HDMI		1EA
VGA	VGA		1EA
BNC	BNC		4CH In / 1CH Out(Spot Output)
DP	DP		None
DVI	DVI		None
e-SATA	e-SATA		None
Audio	Audio		Out(1EA, RCA, Line)
Ethernet	Ethernet		RJ-45(10/100 BASE-T)
Alarm	Alarm		In 4EA, Out 1EA - Relay Out1(NO)/NC/COM)
USB	USB		2EA(Front/Rear USB2.0)
GPS	GPS		None
WiFi	WiFi		None
Serial(Protocols)	Serial(Protocols)		RS-485 (Samsung-T/Pelco-D/Pelco-p) * for PTZ
Power inlet	Power inlet		1EA DC Input Jack
System	**System**		
Log	Log	Log List	Max. 100,000 (System Log, Event Log each)
System Control	System Control		Mouse, Webviewer, System Controller(SPC-7000, SPC-6000, SPC-2000)
Power Management	Power Management	Shutdown Delay	None
		Startup Delay	None
Language	Language		English, French, German, Italian, Spanish, Russian, Turkish, Polish, Dutch, ~~Swedish~~, Czech, Portuguese, Danish, Rumanian, Serbian, Croatian, Hungarian, Greek, Norwegian, Finnish, Korean, Chinese, Japanese, Thai, Vietnamese
Environmental	**Environmental**		
Operating Temperature			0°C to +40°C(+32°F to +104°F)
Operating Humidity			20% ~ 85% RH
Certification	Certification		UL, CE, FCC, KC
Electrical	**Electrical**		
Power Input			DC12V
Power Consumption			
PoE Budget	PoE Budget		None
Mechanical	**Mechanical**		
Color / Material	Color / Material		Black / Metal
Dimension (WxHxD)	Dimension (WxHxD)		300 x 47 x 208.7mm (11.85" x 1.89" x 8.22")
Weight	Weight		
Control Box	**Control Box**		
Interface	Interface	Indicator	
		Emergency Button	
		Audio/Power Switch	
		Main I/O	
Mechanical	Mechanical	Color / Material	
		Dimension (WxHxD)	
		Weight	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

1.1 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

☒ AC 120 V, 60 Hz

1.2 Variant Model Differences

Not applicable

1.3 Device Modifications

Not applicable

1.4 Equipment Under Test

Description	Model Number	Serial Number	Manufacturer	Remarks
DVR	ARD-410	-	HANWHA VISION VIETNAM COMPANY LIMITED	EUT
Adapter	KPL-048F-VI	-	Channel Well Technology (Guangzhou) Co., Ltd.	-
Mouse	MOKJUO	21H07051	Primax Electronics Ltd.	-
HDD	ST2000VX012	-	SEAGATE	-

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

1.5 Support Equipments

Description	Model Number	Serial Number	Manufacturer	Remarks
Laptop	LG15N54	503NZWY038929	LG	-
Laptop Adapter	PA-1900-14	OF2R263348701 7764	LITE-ON TECHNOLOGY COPORATION	-
Monitor 1	SMT-2232	C95V67VF90003 8B	Weihai Daewoo Electronics Co., Ltd.	-
Monitor 2	SMT-2233	ZC6U67VH50019 4D	Weihai Daewoo Electronics Co., Ltd.	-
Monitor 3	-	-	DELL. INC	-
Speaker	-	-	Britz	-
Controller	SPC-1010	C50E67WG10100 F	SamSung Techwin Co.,Ltd.	-
Controller Adapter	AP-12005A	-	A Power	-
Alarm	PRO-SL	-	SENSOR PRO	-
Button Alarm	-	-	-	-
Camera	SCD-6083RN	-	TB-eye Ltd.	-
Camera Adapter	KP-1220	-	Korea Power	-
USB Memory	-	-	SanDisk	-
NETWORK VIDEO ENCODER	SPE-410	-	HANWHA VISION VIETNAM COMPANY LIMITED	-
NETWORK VIDEO ENCODER Adapter	2ACB022F	-	Channel Well Technology (Guangzhou) Co., Ltd.	-

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

1.6 External I/O Cabling

Start		END		Cable Spec.	
Description	**I/O Port**	**Description**	**I/O Port**	**Length**	**Shield**
DVR (EUT)	DC Jack	Adapter (EUT)	DC Jack	1.4	U
	USB A-type	Mouse (EUT)	USB A-type	1.5	U
	BNC(SPOT)	Monitor #1	BNC	3.5	S
	VGA	Monitor #2	VGA	1.5	U
	HDMI	Monitor #3	HDMI	1.4	S
	AUDIO OUT	Speaker	AUDIO OUT	2.0	U
	RS-485	Controller	RS-485	3.2	U
	Alarm OUT	Alarm	Alarm IN	3.1	U
	Alarm IN	Button Alarm	Alarm OUT	3.2	U
	VIDEO IN	Camera	BNC	3.5	S
	RJ-45	Laptop	RJ-45	3.0	U
	AUDIO IN	Laptop	AUDIO IN	1.5	U
	USB	USB Memory	USB	-	-
	BNC (VIDEO IN)	NETWORK VIDEO ENCODER	BNC	10.0	U
	BNC (VIDEO IN)	NETWORK VIDEO ENCODER	BNC	10.0	U
	BNC (VIDEO IN)	NETWORK VIDEO ENCODER	BNC	10.0	U
	BNC (VIDEO IN)	NETWORK VIDEO ENCODER	BNC	10.0	U
Laptop	DC Jack	Laptop Adapter	DC Jack	1.4	S
Controller	DC Jack	Controller Adapter	DC Jack	1.4	S
Camera	DC Jack	Camera Adapter	DC Jack	1.4	S
NETWORK VIDEO ENCODER	2 Pin	NETWORK VIDEO ENCODER Adapter	2 Pin	2.0	U

* Unshielded=U, Shielded=S

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr


1.7 EUT Operating Mode(s)

Test Mode	operating
Operating Mode	EUT Monitoring, Ping Test

EUT Test operating S/W		
Name	**Version**	**Manufacture Company**
-	-	-

1.8 Configuration

■ AC Main
□ DC Main



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

1.9 Remarks when standards applied

N/A

1.10 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less.

1.11 Test Facility

The measurement facility is located at 473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, 12658, Korea, Republic of. The sites are constructed in conformance with the requirements of ANSI C63.4a-2017 and CISPR 16-1-4:2019

1.12 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
KOREA	**RRA**	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	KR0100
International	**KOLAS**	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	KT489
USA	**FCC**	3 m & 10 m Semi-Anechoic Chamber Conducted test site to perform FCC Part 15/18 measurements.	KR0100
Canada	**ISED**	3 m & 10 m Semi-Anechoic Chamber and Conducted test site	23298
JAPAN	**VCCI**	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site)	C-20136, T-20137, R-20181, G-20176
Europe	**TÜV SÜD**	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	CARAT 001633 0004

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

2.0 Test Regulations

The emissions tests were performed according to following regulations:

☒ **47 CFR Part 15, Subpart B**

☐ CISPR 22:2009 +A1:2010	☐ Class A	☐ Class B
☒ ANSI C63.4a-2017	☒ Class A	☐ Class B

☒ **IC Regulation ICES-003 Issue 7**

☐ CAN/CSA-CISPR 32:17	☐ Class A	☐ Class B
☒ ANSI C63.4a-2017	☒ Class A	☐ Class B

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

2.1 Conducted Emissions at Mains Power Ports


Test Date
Oct. 25, 2022

Test Location
Electro wave Shieldroom #6

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EMC32	R & S	9.12.00	-
☒	EMI TEST RECEIVER	ESR3	R & S	101783	12, 28, 2022
☒	LISN	ENV216	R & S	101787	12, 27, 2022
☒	LISN	ESH2-Z5	R & S	100450	12, 27, 2022
☒	PULSE LIMITER	ESH3-Z2	R & S	101915	12, 27, 2022

Diagram of test setup



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

Test Conditions

Temperature: (23,0 ± 0,2) ℃
Relative Humidity: (47,0 ± 0,1) % R.H.

Frequency Range of Measurement

150 ㎑ to 30 ㎒

Instrument Settings

IF Band Width: 9 ㎑

Test Results

The requirements are:

☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks

See Appendix A for test data.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

2.2 Radiated Electric Field Emissions(Below 1 ㎓)


Test Date
Oct. 25, 2022

Test Location
☐ OPEN AREA TEST SITE #2 ☒ SEMI ANECHOIC CHAMBER #4(10m)

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EP5/RE	TOYO Corporation	6.0.0	-
☒	EMI TEST RECEIVER	ESU26	R & S	100551	03, 31, 2023
☒	AMPLIFIER	SCU 01	R & S	100603	11, 24, 2022
☒	TRILOG-BROADBAND ANTENNA	VULB9163	Schwarzbeck	715	12, 08, 2022
☒	ATTENUATOR	8491A	HP	32173	03, 08, 2023

Diagram of test setup



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

Test Conditions

Temperature: (22,5 ± 0,1) ℃
Relative Humidity: (47,0 ± 0,1) % R.H.

Frequency Range of Measurement

30 ㎒ to 1 ㎓

Instrument Settings

IF Band Width: 120 ㎑

Test Results

The requirements are:

☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks

See Appendix A for test data.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

2.3 Radiated Electric Field Emissions(Above 1 ㎓)


Test Date
Oct. 25, 2022

Test Location
SEMI ANECHOIC CHAMBER #5

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	ES10/RE	TOYO Corporation	2022.01.000	-
☒	EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100552	03, 31, 2023
☒	HORN ANTENNA	BBHA 9120D	SCHWARZBECK	9120D-1802	12, 16, 2022
☒	PREAMPLIFIER	8449B	HP	3008A00538	06, 02, 2023
☒	ATTENUATOR	8491B	HP	23094	04, 21, 2023

Diagram of test setup



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

Test Conditions

Temperature: (22,3 ± 0,1) ℃
Relative Humidity: (47,6 ± 0,2) % R.H.

Frequency Range of Measurement

1 GHz to 5 GHz

Instrument Settings

IF Band Width: 1 MHz

Test Results

The requirements are:
☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks

See Appendix A for test data.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr


APPENDIX A – TEST DATA

Conducted Emissions at Mains Power Ports

HOT LINE

Common Information

Test Description:	Conducted Emission
Model No.:	ARD-410
Phase:	
Mode:	L1
Operator Name:	KES



Final_Result


Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.160000	---	27.96	66.00	38.04	1000.0	9.000	L1	19.4
0.160000	44.26	---	79.00	34.74	1000.0	9.000	L1	19.4
0.530000	---	33.46	60.00	26.54	1000.0	9.000	L1	19.8
0.530000	39.58	---	73.00	33.42	1000.0	9.000	L1	19.8
1.090000	---	17.42	60.00	42.58	1000.0	9.000	L1	20.1
1.090000	23.26	---	73.00	49.74	1000.0	9.000	L1	20.1
2.465000	---	19.22	60.00	40.78	1000.0	9.000	L1	20.2
2.465000	24.71	---	73.00	48.29	1000.0	9.000	L1	20.2
26.490000	---	28.77	60.00	31.23	1000.0	9.000	L1	20.2
26.490000	32.99	---	73.00	40.01	1000.0	9.000	L1	20.2
26.610000	---	31.05	60.00	28.95	1000.0	9.000	L1	20.2
26.610000	34.25	---	73.00	38.75	1000.0	9.000	L1	20.2

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

NEUTRAL LINE

Common Information

Test Description:	Conducted Emission
Model No.:	ARD-410
Phase:	
Mode:	N
Operator Name:	KES



Final_Result


Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.160000	---	27.48	66.00	38.52	1000.0	9.000	N	19.4
0.160000	44.24	---	79.00	34.76	1000.0	9.000	N	19.4
0.545000	---	34.66	60.00	25.34	1000.0	9.000	N	19.8
0.545000	40.87	---	73.00	32.13	1000.0	9.000	N	19.8
1.800000	---	13.24	60.00	46.76	1000.0	9.000	N	20.3
1.800000	20.99	---	73.00	52.01	1000.0	9.000	N	20.3
2.805000	---	17.67	60.00	42.33	1000.0	9.000	N	20.2
2.805000	23.78	---	73.00	49.22	1000.0	9.000	N	20.2
26.610000	---	31.27	60.00	28.73	1000.0	9.000	N	20.2
26.610000	34.35	---	73.00	38.65	1000.0	9.000	N	20.2

◆ Calculation
QuasiPeak[㏈uV] / CAverage [㏈uV] = Reading Value[㏈uV] + Corr. [㏈]
QuasiPeak / CAverage : The Final Value
Reading Value : Not shown in the table.
Corr. : Correction values (LISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

Radiated Electric Field Emissions(Below 1 ㎓)

- 47 CFR Part 15, Subpart B




Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	39.458	V	51.3	-22.7	28.6	39.0	10.4	100.0	349.0	
2	71.104	V	50.8	-25.1	25.7	39.0	13.3	103.0	156.0	
3	106.630	H	44.8	-22.2	22.6	43.5	20.9	380.0	326.0	
4	148.098	V	51.0	-25.1	25.9	43.5	17.6	104.0	226.0	
5	160.465	V	52.3	-24.5	27.8	43.5	15.7	110.0	7.0	
6	240.733	V	50.3	-19.3	31.0	46.5	15.5	123.0	358.0	
7	365.378	V	42.3	-14.6	27.7	46.5	18.8	398.0	354.0	
8	409.755	H	41.3	-13.7	27.6	46.5	18.9	359.0	334.0	
9	597.086	H	38.9	-8.2	30.7	46.5	15.8	376.0	304.0	
10	648.618	H	39.6	-7.8	31.8	46.5	14.7	379.0	315.0	
11	805.030	H	41.5	-6.4	35.1	46.5	11.4	385.0	7.0	
12	882.145	H	38.2	-3.9	34.3	46.5	12.2	369.0	322.0	

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

- IC Regulation ICES-003 Issue 7




Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	39.458	V	51.3	-22.7	28.6	40.0	11.4	100.0	349.0	
2	71.104	V	50.8	-25.1	25.7	40.0	14.3	103.0	156.0	
3	106.630	H	44.8	-22.2	22.6	43.5	20.9	380.0	326.0	
4	148.098	V	51.0	-25.1	25.9	43.5	17.6	104.0	226.0	
5	160.465	V	52.3	-24.5	27.8	43.5	15.7	110.0	7.0	
6	240.733	V	50.3	-19.3	31.0	47.0	16.0	123.0	358.0	
7	365.378	V	42.3	-14.6	27.7	47.0	19.3	398.0	354.0	
8	409.755	H	41.3	-13.7	27.6	47.0	19.4	359.0	334.0	
9	597.086	H	38.9	-8.2	30.7	47.0	16.3	376.0	304.0	
10	648.618	H	39.6	-7.8	31.8	47.0	15.2	379.0	315.0	
11	805.030	H	41.5	-6.4	35.1	47.0	11.9	385.0	7.0	
12	882.145	H	38.2	-3.9	34.3	47.0	12.7	369.0	322.0	

♦ Calculation – SAC #4(10 m)
Result(QP) [dB(㎶/m)] = (Reading(QP)[dB(㎶)] + c.f[dB(1/m)]
Margin(QP)[dB] = Limit[dB(㎶/m)] - Result(QP) [dB(㎶/m)]
Reading(QP) : Reading value, Result(QP) : Reading value + Factor value
Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

Radiated Electric Field Emissions(Above 1 ㎓)



Final Result

No.	Frequency [MHz]	Pol	Reading AV [dB(μV)]	Reading PK [dB(μV)]	c.f [dB(1/m)]	Result AV [dB(μV/m)]	Result PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [deg]	Remark
1	1121.813	V	33.5	56.7	-8.0	25.5	48.7	60.0	80.0	34.5	31.3	133.0	0.1	
2	1192.032	H	32.3	51.7	-7.7	24.6	44.0	60.0	80.0	35.4	36.0	378.0	344.0	
3	1262.749	V	33.0	53.4	-7.3	25.7	46.1	60.0	80.0	34.3	33.9	113.0	359.1	
4	1435.396	H	30.9	47.0	-6.5	24.4	40.5	60.0	80.0	35.6	39.5	376.0	48.6	
5	1621.997	V	31.3	47.5	-5.8	25.5	41.7	60.0	80.0	34.5	38.3	142.0	342.5	
6	1792.925	H	30.5	49.6	-5.1	25.4	44.5	60.0	80.0	34.6	35.5	395.0	73.3	
7	2243.248	H	29.6	45.9	-3.6	26.0	42.3	60.0	80.0	34.0	37.7	377.0	58.4	
8	2389.423	H	29.6	47.2	-3.1	26.5	44.1	60.0	80.0	33.5	35.9	379.0	70.8	
9	2805.816	V	28.4	45.7	-1.6	26.8	44.1	60.0	80.0	33.2	35.9	114.0	47.3	
10	2884.275	H	28.6	42.8	-1.5	27.1	41.3	60.0	80.0	32.9	38.7	377.0	88.7	
11	3599.846	V	28.9	42.4	-0.3	28.6	42.1	60.0	80.0	31.4	37.9	142.0	212.0	
12	4902.744	V	28.9	40.5	4.1	33.0	44.6	60.0	80.0	27.0	35.4	386.0	91.4	

♦ Calculation

Result(PK/CAV) [dB(μV/m)] = (Reading(PK/CAV)[dB(μV)] + c.f[dB(1/m)]

Margin(PK/CAV)[dB] = Limit[dB(μV/m)] - Result(PK/CAV) [dB(μV/m)]

Reading(PK/CAV) : Reading value, Result(PK/CAV) : Reading value + Factor value


Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

Test Setup Photos and Configuration


Conducted Emissions at Mains Power Ports





This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr


Radiated Electric Field Emissions(Below 1 ㎓)






This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

Radiated Electric Field Emissions(Above 1 ㎓)





This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

EUT External Photographs

(Top)




(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

EUT Internal Photographs


(Internal View)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

EUT Internal View – Board 1

(Top)




(Bottom)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

EUT Internal View – Board 2

(Top)




(Bottom)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

EUT Internal View – Board 3

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

EUT Internal View – HDD

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr

Label Photographs

FCC Label

HANWHA VISION VIETNAM COMPANY LIMITED

ARD-410

IC Label

CAN ICES-003(A) / NMB-003(A)

This device complies with Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.
Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes : (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact kes@kes.co.kr