



EMC TEST REPORT

Test Report No. : KES-EM-22T0517
Date of Issue : Jun. 27, 2022
Product name : PC NVR
Model/Type No. : PRO-7310B6
Variant Model : -
Applicant : Hanwha Techwin Co., Ltd.
Applicant Address : 6, Pangyo-ro 319Beon-gil, Bundang-gu, Seongnam-si,
Gyeonggi-do, Republic of Korea
Manufacturer : Dream I System co.,Ltd.
Manufacturer Address : #510.Daerung Post Tower 6. 50-3 Gasan-dong, Geumcheon-gu,
Seoul, Korea
Date of Receipt : Jun. 13, 2022
Test date : Jun. 20, 2022 ~ Jun. 21, 2022
Test Results : ☒ **In Compliance** ☐ **Not in Compliance**

Tested by

Kang Hyeon, Kim
EMC Test Engineer

Reviewed by

Dong-Hun, Jang
EMC Technical Manager

This test report is not related to KS Q ISO/IEC 17025 and KOLAS.

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-EM-22T0517
Page (2) of (68)

REPORT REVISION HISTORY

Date	Test Report No.	Revision History
Jun. 27, 2022	KES-EM-22T0517	Issued

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



TABLE OF CONTENTS

1.0	General Product Description	4
1.1	Test Voltage & Frequency	7
1.2	Variant Model Differences.....	7
1.3	Device Modifications	7
1.4	Equipment Under Test.....	7
1.5	Support Equipments	8
1.6	External I/O Cabling	9
1.7	EUT Operating Mode(s)	10
1.8	Configuration.....	10
1.9	Remarks when standards applied	11
1.10	Calibration Details of Equipment Used for Measurement	11
1.11	Test Facility	11
1.12	Laboratory Accreditations and Listings	11
2.0	Test Regulations.....	12
2.1	Conducted Emissions at Mains Power Ports	13
2.2	Conducted Emissions at Telecommunication Ports	14
2.3	Radiated Electric Field Emissions(Below 1 GHz)	15
2.4	Radiated Electric Field Emissions(Above 1 GHz)	16
2.5	Harmonic Current Emissions	17
2.6	Voltage Fluctuations and Flicker	18
3.0	Criteria for compliance	19
3.1	Electrostatic Discharge.....	21
3.2	Radiated Electric Field Immunity	24
3.3	Electrical Fast Transients/Bursts	27
3.4	Surge Transients	29
3.5	Conducted Disturbance	32
3.6	Voltage Dips and Short Interruptions	35
APPENDIX A – TEST DATA.....		37
Conducted Emissions at Mains Power Ports.....		37
Conducted Emissions at Telecommunication Ports		41
Radiated Electric Field Emissions(Below 1 GHz)		43
Radiated Electric Field Emissions(Above 1 GHz).....		44
Harmonic Current Emissions and Voltage Fluctuations and Flicker		45
Test Setup Photos and Configuration		48
Conducted Emissions at Mains Power Ports.....		48
Conducted Emissions at Telecommunication Ports		49
Radiated Electric Field Emissions(Below 1 GHz)		50
Radiated Electric Field Emissions(Above 1 GHz).....		51
Harmonic Current Emissions and Voltage Fluctuations and Flicker		52
Electrostatic Discharge		53
Radiated Electric Field Immunity		53
Electrical Fast Transients/Bursts		54
Surge Transients.....		54
Conducted Disturbance.....		55
Voltage Dips and Short Interruptions.....		55
EUT External Photographs		56
EUT Internal Photographs		57



1.0 General Product Description

Main Specifications of EUT are:

Features/Performance			
operating system		Windows 10 IoT Enterprise LTSC	
CMS		SSM Server preinstalled (v2.10.13)	
software	camera	input	Max. 128CH
		resolution	CIF ~ 12MP
		protocol	Wisenet, ONVIF Profile-S
		registration	Auto Discovery, Manual
		Set	Automatic device IP scanning, Add profile edit, Resolution, Fisheye dewarping mode, Hallway View Setup, Brightness/Contrast, Viewing the device settings(Device webpage), Exporting/Importing devices settings,, Updating the device firmware
	live	monitor output RLSM	via SSM Workstation
		display	via SSM Workstation
		split screen	via SSM Workstation
	recording	bandwidth	Max. 700Mbps
		recording mode	Normal, Schedule (Continuous / Event), Event (Pre / Post), ARB, Dual-Track
		Event type	Video loss, Camera event(Sensor, MD, Passing, Entering, Exiting, Disappearing (Appearing), Tampering, Tracking, Face Detection, Audio Detection)
		event action	Instant Viewer, Preset, Alarm Out, Pop-up, Sound and E-mail notification
	search / play	playback bandwidth	via SSM Workstation
		search mode	via SSM Workstation
		Simultaneous play	via SSM Workstation

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



		playback control	via SSM Workstation
	back up	file format	AVI, SEC
		function	Manual Backup, Onetime Schedule Backup
	video	compression method	H.265, H.264, MJPEG, WiseStream(H.264, H.265)
		resolution	CIF ~ 12MP
		decoding performance	via SSM Workstation
		Fish Eye Dewarping	via SSM Workstation
	audio	compression method	G.711 u-law(PCM), G723, G726(ADPCM), AAC
		support	2-way
	Date/Time Synchronization		NTP Server
	PTZ	Control	via SSM Workstation
		preset	via SSM Workstation
	system stability	Failover / ARB	Yes(Active&Active)/Yes
	server clustering		Max 28EA (Server Clustering up-to Max 10,000 channels)
	system control		Mouse, Controller
	log information		System, Event, User, Device 180 Days
hardware	PROCESSOR		Intel® Xeon® Processor E3-1275V5(4C, 3.6Ghz)
	MEMORY		8GB ECC Memory DDR4 PC-17000 * 4
	OS DISK		M.2 SSD (2@128GB)(For OS _ Raid 10)
	DRIVER TYPE		NL-SAS / SAS 12Gb/s, SATA 6Gb/s (Recommended to use NL-SAS/SAS for stable performance)
	HDD		16Bay 3.5" HDD / 2.5" M.2 (Maximum Storage 288Tbye, 18TB*16=288Tbyte)
	RAID		Host Raid Controlle Onboard Raid 0, 1, 5, 6,
	DISPLAY PORT		VGA x 1, DVI x 1, HDMI x 1

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-EM-22T0517
Page (6) of (68)

	NETWORK	Gigabit Ethernet RJ-45 (1000 Base-T) x6 (2 ports on board, 4 ports on the Additional NIC)
Power / Environment / Appliance		
Electric	AC INPUT	100 ~ 240VAC, 50 ~ 60Hz
	POWER SUPPLY	2@800W Dual
	CURRENT(Max)	8-4A
Environmental	OPERATING	+5°C to +40°C(+41°F to +104°F) / Less than 80%
Mechanical	COLOR/MATERIAL	Silver/Metal
	FORM FACTOR	3U, 19" Rackmount
	DIMENSIONS (WxHxD)	446.7 x 130.9 x 503.1mm
	WEIGHT	System W/O HDD: 17.6 kg
Warranty	WARRANTY	3 Years limited warranty

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



1.1 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

☒ AC 230 V, 50 Hz

1.2 Variant Model Differences

Not applicable

1.3 Device Modifications

Not applicable

1.4 Equipment Under Test

Description	Model Number	Serial Number	Manufacturer	Remarks
PC NVR	PRO-7310B6	-	Dream I System co.,Ltd.	EUT
CPU	Intel® Xeon® Processor E3-1275V6	-	INTEL	1 EA
M.2 SSD	IM2S3328E-128GM	-	ADATA Technology Co., Ltd	128 GB, 2 EA
RAM	M4C0-AGS1MCSJ-H04	-	Innodisk	16 GB, 1 EA
SMPS	U1A-D10800-DRB	-	SHENZHEN HONOR ELECTRONIC CO.,LTD.	2 EA
Mainboard	115XSBP	-	FOXCONN	1 EA
Network Adapter	00AG522	-	IBM	1 EA



1.5 Support Equipments

Description	Model Number	Serial Number	Manufacturer	Remarks
Monitor1	LG15N54	503NZWY038929	LG	-
Monitor2	HSTND-7041-L	6CM6020YQQ	HP Inc.	-
Monitor3	QTM-OR24.9WB	-	Orion Information and Communication Co., Ltd.	-
Camera	QNO-7010RP	-	HANWHA TECHWIN CO.,LTD.	-
Camera Adapter	ATS065T-P120	-	Adapter Techonlogy Co., Ltd.	-
Headset	K550	-	Britz®	-
USB Memory	-	-	SONY	64 GB
USB Memory	-	-	SONY	64 GB
Router	V504	-	ipTIME	-
Router Adapter	M090080E811	-	MOST Optoelectronics International Limited	-
PC	-	-	DELL	-
Monitor4	27UL550	105NTHM9Z249	LG Electronics Nanjing New Technology Co.,Ltd	-
Monitor4 Adapter	LCAP26B-E	-	Genmao Electronics (Suzhou) Co.,Ltd	-
Keyboard2	SPR-8695TU	-	SEJIN ELECTRON INC.	-
HDD	DC HC550	-	Western Digital	18TB
Mouse	1113	-	Microsoft	-
Keyboard1	SKP-900B	-	Samsung	-
Optical Speaker	BZ-T3400 AV Soundbar	-	AVIM AUDIO	-



1.6 External I/O Cabling

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
PC NVR (EUT)	HDMI	Monitor1	HDMI	1.5	S
	D-SUB	Monitor2	D-SUB	2.0	S
	DVI	Monitor3	DVI	2.0	S
	RJ-45	Camera	RJ-45	3.0	U
	RJ-45	Router	RJ-45	4.0	U
	PS/2	Mouse	PS/2	1.4	U
	USB	Keyboard1	USB	1.5	U
	MIC	Headset	3.5 mm	1.4	U
	Speaker				
	USB	USB Memory	USB	-	-
	USB	USB Memory	USB	-	-
	SATA	HDD	SATA	-	-
	Optical	Optical Speaker	Optical	1.0	-
PC	USB	Keyboard2	USB	1.2	U
	HDMI	Monitor4	HDMI	1.4	S
	RJ-45	Router	RJ-45	3.0	U
Camera	DC Jack (2 Pin)	Camera Adapter	DC Jack (2 Pin)	1.0	U
Router	DC Jack	Router Adapter	DC Jack	1.0	U
Monitor4	DC Jack	Monitor4 Adapter	DC Jack	1.2	U

* Unshielded=U, Shielded=S


1.7 EUT Operating Mode(s)

Test Mode	operating
Operation	- In the test equipment, using the SSM Console program, it was checked whether the image of the camera connected to the test equipment was output normally. - Repeated reading/writing of data in connected memories using EMI TOOL program. - By playing the color bar on the test equipment, it was confirmed that the monitor outputs normally and that the 1 kHz tone sound is normally output from the headset.

EUT Test operating S/W		
Name	Version	Manufacture Company
SSM Console	-	-
EMI TOOL	-	-

1.8 Configuration

■ AC Main
 □ DC Main



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr

1.9 Remarks when standards applied

Optical Port was excluded from testing because it is the management port.

1.10 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less.

1.11 Test Facility

The measurement facility is located at 473-21 Gayeo-ro, Yeoju-si, Gyeonggi-do, 12658, Korea. The sites are constructed in conformance with the requirements of ANSI C63.4a-2017 and CISPR 16-1-4:2019

1.12 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
KOREA	RRA	EMI (3 m & 10 m Semi-Anechoic Chamber , 10 m Open Area and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KR0100
International	KOLAS	EMI (3 m & 10 m Semi-Anechoic Chamber , and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KT489
USA	FCC	3 m & 10 m Semi-Anechoic Chamber, 10 m Open Area and Conducted test site to perform FCC Part 15/18 measurements.	 KR0100
Canada	ISED	3 m & 10 m Semi-Anechoic Chamber and Conducted test site	 23298
JAPAN	VCCI	Mains Ports Conducted Interference Measurement, Telecommunication Ports Conducted Disturbance Measurement and Radiation 10 meter site, Facility for measuring radiated disturbance above 1 GHz	 R-20056, C-20036, T-20040, G-20057
Europe	TÜV SÜD	EMI (3 m & 10 m Semi-Anechoic Chamber , 10 m Open Area and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 CARAT 001633 0004



2.0 Test Regulations

The emissions tests were performed according to following regulations:

☒ **EMC – Directive 2014/30/EU**

☒ EN 55032:2015/A11:2020

☒ Class A

☐ Class B

☒ EN 50130-4:2011

☒ EN 61000-3-2:2014

☒ EN 61000-3-3:2013

☒ **EMC – Regulations 2016**

☒ EN 55032:2015/A11:2020

☒ Class A

☐ Class B

☒ EN 50130-4:2011

☒ EN 61000-3-2:2014

☒ EN 61000-3-3:2013



2.1 Conducted Emissions at Mains Power Ports

Test Date

Jun. 20, 2022

Test Location

Electro wave Shieldroom #6

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EMC32	R & S	9.12.00	-
☒	EMI TEST RECEIVER	ESR3	R & S	101783	12, 28, 2022
☒	LISN	ENV216	R & S	101787	12, 27, 2022
☒	LISN	ESH2-Z5	R & S	100450	12, 27, 2022
☒	PULSE LIMITER	ESH3-Z2	R & S	101915	12, 27, 2022

Test Conditions

Temperature: (24,0 ± 0,4) °C

Relative Humidity: (43,7 ± 0,3) % R.H.

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks

See Appendix A for test data.



2.2 Conducted Emissions at Telecommunication Ports

Test Date

Jun. 20, 2022

Test Location

Electro wave Shieldroom #6

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EMC32	R & S	9.12.00	-
☒	EMI TEST RECEIVER	ESR3	R & S	101783	12, 28, 2022
☒	LISN	ENV216	R & S	101787	12, 27, 2022
☒	LISN	ESH2-Z5	R & S	100450	12, 27, 2022
☒	PULSE LIMITER	ESH3-Z2	R & S	101915	12, 27, 2022
☐	8-WIRE ISN CAT3,5	ENY81	R & S	100174	12, 28, 2022
☒	8-WIRE ISN CAT6	ENY81-CAT6	R & S	101665	12, 28, 2022

Test Conditions

Temperature: (24,2 ± 0,2) °C

Relative Humidity: (43,8 ± 0,2) % R.H.

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks

- See Appendix A for test data.
- For Ethernet interfaces, measurements are required at the highest data rate supported by the interface.



2.3 Radiated Electric Field Emissions(Below 1 GHz)

Test Date

Jun. 20, 2022

Test Location

☐ OPEN AREA TEST SITE #2 ☒ SEMI ANECHOIC CHAMBER #4(10m)

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EP5/RE	TOYO Corporation	6.0.0	-
☒	EMI TEST RECEIVER	ESU26	R & S	100551	03, 31, 2023
☒	AMPLIFIER	SCU 01	R & S	100603	11, 24, 2022
☒	TRILOG-BROADBAND ANTENNA	VULB9163	Schwarzbeck	715	12, 08, 2022
☒	ATTENUATOR	8491A	HP	32173	03, 08, 2023

Test Conditions

Temperature: (24,1 ± 0,3) °C
Relative Humidity: (43,6 ± 0,3) % R.H.

Frequency Range of Measurement

30 MHz to 1 GHz

Instrument Settings

IF Band Width: 120 kHz

Test Results

The requirements are:

☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks

See Appendix A for test data.



2.4 Radiated Electric Field Emissions(Above 1 GHz)

Test Date

Jun. 20, 2022

Test Location

SEMI ANECHOIC CHAMBER #3

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EP5/RE	TOYO Corporation	6.0.0	-
☒	EMI TEST RECEIVER	ESR7	R & S	101190	08, 03, 2022
☒	PREAMPLIFIER	8449B	AGILENT	3008A01967	04, 01, 2023
☒	DOUBLE RIDGED HORN ANTENNA	SAS-571	A.H.SYSTEM,INC	781	03, 03, 2023

Test Conditions

Temperature: (24,0 ± 0,4) °C

Relative Humidity: (43,7 ± 0,4) % R.H.

Frequency Range of Measurement

1 GHz to 6 GHz

Instrument Settings

IF Band Width: 1 MHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks

See Appendix A for test data.



2.5 Harmonic Current Emissions

Test Date

Jun. 20, 2022

Test Location

Electro wave Shieldroom #3

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	net.control	EM TEST	2.1.4	-
☒	DIGITAL POWER ANALYZER	DPA 500N	EM TEST	V1024106759	04, 06, 2023
☒	POWER SOURCE	ACS 500N6	EM TEST	V1024106760	-

Test Conditions

Temperature: (23,5 ± 0,2) °C

Relative Humidity: (44,7 ± 0,2) % R.H.

Classification of Equipment for Harmonic Current Emissions

- ☒ Class A
- ☐ Class B
- ☐ Class C(Below 25 W)
- ☐ Class C(Above 25 W)
- ☐ Class D

Test Results

The requirements are:

- ☒ PASS
- ☐ NOT PASS
- ☐ NOT APPLICABLE

Remarks

See Appendix A for test data.



2.6 Voltage Fluctuations and Flicker

Test Date

Jun. 20, 2022

Test Location

Electro wave Shieldroom #3

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	net.control	EM TEST	2.1.4	-
☒	DIGITAL POWER ANALYZER	DPA 500N	EM TEST	V1024106759	04, 06, 2023
☒	POWER SOURCE	ACS 500N6	EM TEST	V1024106760	-

Test Conditions

Temperature: (23,7 ± 1,2) °C
Relative Humidity: (44,9 ± 1,1) % R.H.

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks

See Appendix A for test data.

3.0 Criteria for compliance

Criteria for compliance was based on the following guidelines:
EN 50130-4:2011 Alarm systems-Part 4: Electromagnetic compatibility Product family
standard: Immunity requirements for components of fire, intruder and social alarm systems

The variety and the diversity of the apparatus within the scope of this document makes it difficult to define precise criteria for the evaluation of the immunity test results.

If as a result of the application of the tests defined in this standard, the apparatus becomes dangerous or unsafe then the apparatus shall be deemed to have failed the test.

A functional description and a definition of performance by the manufacture and noted in the test report, based on the following criteria:

Electrostatic discharge

There shall be no damage, malfunction or change of status due to the conditioning.
Flickering of an indicator during the application of discharge is permissible, providing that is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change.

Radiated electromagnetic fields

There shall be no damage, malfunction or change of status due to the conditioning.
Flickering of an indicator during the application of discharge is permissible, providing which could be interpreted by associated equipment as a change, and no such
Flickering of indicators occurs at a field strength of 3 V/m.

For components of CCTV systems, where the picture is allowed at 10 V/m, providing.

- (a) there is no permanent damage or change to EUT
(e.g. no corruption of memory or changes to programmable setting etc.)
- (b) at 3 V/m, any deterioration of the picture is so minor that the system could still be used;
and
- (c) there is no observable deterioration of the picture at 1 V/m.

Fast transient burst / slow high energy voltage surge

There shall be no damage, malfunction or change of status due to the conditioning.
Flickering of an indicator during the application of discharge is permissible, providing
That there is no residual is permissible, providing that there is no residual change in the EUT or
any
change in outputs, which could be interpreted by associated equipment as a change.

Conducted RF immunity

There shall be no damage, malfunction or change of status due to the conditioning.
Flickering of an indicator during the application of discharge is permissible, providing
That there is no residual is permissible, providing that there is no residual change in the EUT or
any
change in outputs, which could be interpreted by associated equipment as a change,
and no such flickering of indicators oeuvres at $U = 130 \text{ dB}\mu\text{V}$.
For component of CCTV systems, where the status is monitored by observing the TV picture,
then deterioration of the picture is allowed at $U = 140 \text{ dB}\mu\text{V}$, providing:
(a) there is no permanent damage or change to the EUT
(e.g. no corruption of memory or changes to programmable settings etc.)
(b) at $U = 130 \text{ dB}\mu\text{V}$, any deterioration of the picture is so minor that the system could
still be used; and
(c) there in no observable deterioration of the picture at $U = 120 \text{ dB}\mu\text{V}$.

Voltage dip/interruption / Voltage variation

There shall be no damage, malfunction or change of status due to the conditioning.
Flickering of an indicator during the conditioning is permissible, providing that there is no
residual
change in the EUT or any change in outputs, which could be interpreted by associated
equipment
as a change. The EUT shall meet the acceptance criteria for the functional test, after the
conditioning.



3.1 Electrostatic Discharge

Reference Standard

EN 61000-4-2:2009

Test Date

Jun. 21, 2022

Test Location

EMS-ESD: Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	ESD SIMULATOR	ESS-2000	Noise Ken	ESS01Z0454	02, 24, 2023
☒	HCP	-	KES	-	-
☒	VCP	-	Noise Ken	-	-

Test Conditions

Temperature: (24,4 ± 0,2) °C
Relative Humidity: (44,2 ± 0,2) % R.H.
Atmospheric Pressure: (99,7 ± 0,0) kPa

Test Specifications

Discharge Factor: ≥ 1 s

Discharge Impedance: 330 ohm / 150 pF

Kind of Discharge: Air, Contact (direct and indirect)

Polarity: Positive and Negative

Number of Discharge: 10 at all locations for Air discharge
10 at all locations for Contact discharge


Discharge Voltage:	Contact	Air	HCP	VCP
	☐ 2 kV	☒ 2 kV	☐ 2 kV	☐ 2 kV
	☐ 4 kV	☒ 4 kV	☐ 4 kV	☐ 4 kV
	☒ 6 kV	☐ 6 kV	☒ 6 kV	☒ 6 kV
	☐ 8 kV	☒ 8 kV	☐ 8 kV	☐ 8 kV
	☐ 15 kV	☐ 15 kV	☐ 15 kV	☐ 15 kV

Notes: HCP: Horizontal coupling plane
VCP: Vertical coupling plane

Required Performance Criteria: ☒ Complied

Location of Discharge:

Air
Contact



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-EM-22T0517
Page (23) of (68)

Test Data

No.	Test Point	Discharge Method	Observations	Remarks
1	HCP Contact	Contact Discharge	Complied	-
2	VCP Contact	Contact Discharge	Complied	-

Direct Discharge

No.	Test Point	Discharge Method	Observations	Remarks
1	Front USB	Contact Discharge	Complied	-
2	Button, LED	Air Discharge	Complied	-
3	Enclosure	Contact Discharge	Complied	-
4	Back side	Contact Discharge	Complied	-
5	Back port	Contact Discharge	Complied	-

Note: "Blank" = Not performed

Observations:

Complied – No degradation of function

Test Results

- ☒ PASS Required Performance Criteria
☐ NOT PASS Required Performance Criteria

Remarks

PASS Required Performance Criteria

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



3.2 Radiated Electric Field Immunity

Reference Standard

EN IEC 61000-4-3:2020

Test Date

Jun. 21, 2022

Test Location

EMS-RS: ☐ SEMI ANECHOIC CHAMBER #2 ☒ SEMI ANECHOIC CHAMBER #3

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMS Test S/W	EMC32	R & S	10.10.02	-
☒	SIGNAL GENERATOR	SMB 100A	Rohde & Schwarz	108252	08, 03, 2022
☒	HIGH POWER DUAL AMP	SSA532	SUNGSAN	SSA532-001	-
☒	POWER METER	E4419B	Agilent	GB40203000	03, 31, 2023
☒	AVERAGE POWER SENSOR	E9301A	Agilent	MY52170007	04, 04, 2023
☒	AVERAGE POWER SENSOR	E9301A	Agilent	MY41498669	04, 04, 2023
☒	STACKED DOUBLE LOG-PER- ANTENNA	STPL9128 E	Schwarzbeck	9128ES-121	-
☒	DOUBLE RIDGED HORN ANTENNA	SAS-571	A.H.SYSTEM,INC	781	03, 03, 2023

Test Conditions

Temperature: (24,3 ± 1,4) °C
Relative Humidity: (44,2 ± 1,2) % R.H.
Atmospheric Pressure: (99,9 ± 0,0) kPa



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-EM-22T0517
Page (25) of (68)

Test Specifications

Antenna Polarization: Horizontal & vertical unless indicated otherwise

Antenna Distance: ☒ 3 m

Field Strength: ☐ 1 V/m ☐ 3 V/m
☒ 10 V/m

Frequency Range: ☐ 80 MHz to 1 GHz ☐ 1,4 GHz to 2,7 GHz
☒ 80 MHz to 2,7 GHz

Modulation: ☒ AM, 80 %, 1 kHz sine wave
☒ PM, 1 Hz (0,5 s ON : 0,5 s OFF)

Frequency step: ☒ 1 % step

Dwell Time: ☐ 1 s ☒ 3 s

of Sides Radiated: ☒ 4

Required Performance Criteria: ☒ Complied

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:

KES-EM-22T0517

Page (26) of (68)

Test Data

Side Exposed	Observations	
	Horizontal	Vertical
Front	Complied	Complied
Right	Complied	Complied
Back	Complied	Complied
Left	Complied	Complied

Note: "Blank" = Not performed

Observations:

Complied – No degradation of function

Test Results

- ☒ PASS Required Performance Criteria
☐ NOT PASS Required Performance Criteria

Remarks

PASS Required Performance Criteria

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



3.3 Electrical Fast Transients/Bursts

Reference Standard

EN 61000-4-4:2012

Test Date

Jun. 21, 2022

Test Location

EMS-EFT: Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMS Test S/W	iec.control	EM TEST	5.4.8	-
☒	ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	12, 03, 2022
☒	MOTOR VARIAC	MV2616	EM TEST	P1552169719	03, 31, 2023
☒	CAPACITIVE COUPLING CLAMP	HFK	EM TEST	P1633183115	12, 03, 2022

Test Conditions

Temperature: (24,4 ± 0,6) °C
Relative Humidity: (44,3 ± 0,6) % R.H.
Atmospheric Pressure: (99,7 ± 0,0) kPa

Test Specifications

Pulse Amplitude & Polarity:
(AC Power Lines) ☐ ± 1.0 kV ☒ ± 2.0 kV
☐ ± 4.0 kV

Pulse Amplitude & Polarity:
(Other supply / Signal Lines) ☐ ± 0.5 kV ☒ ± 1.0 kV
☐ ± 2.0 kV

Burst Period: ☒ 300 ms ☐ 2 s

Repetition Rate: ☐ 5 kHz ☒ 100 kHz

Duration of Test Voltage: ☒ ≥ 1 min

Required Performance Criteria: ☒ Complied

Test Data

☒ Input a.c. power ports – Coupling/Decoupling Network used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
L	Complied	Complied
N	Complied	Complied
PE	Complied	Complied
L – N	Complied	Complied
L – PE	Complied	Complied
N – PE	Complied	Complied
L – N – PE	Complied	Complied

☐ Input d.c. power ports – Coupling/Decoupling Network used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
-	-	-

☒ Signal ports and telecommunication ports – Coupling Clamp used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
RJ-45 (1)	Complied	Complied
RJ-45 (2)	Complied	Complied

Note: “Blank” = Not performed

Observations:

Complied – No degradation of function

Test Results

☒ PASS Required Performance Criteria

☐ NOT PASS Required Performance Criteria

Remarks

PASS Required Performance Criteria



3.4 Surge Transients

Reference Standard

EN 61000-4-5:2014/A1:2017

Test Date

Jun. 21, 2022

Test Location

EMS-EFT: Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMS Test S/W	iec.control	EM TEST	5.4.8	-
☒	ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	12, 03, 2022
☒	MOTOR VARIAC	MV2616	EM TEST	P1552169719	03, 31, 2023
☒	CDN	CNV 508N1	EM TEST	P1610176296	12, 03, 2022

Test Conditions

Temperature: (24,7 ± 1,3) °C
Relative Humidity: (44,5 ± 1,2) % R.H.
Atmospheric Pressure: (99,7 ± 0,0) kPa

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-EM-22T0517
Page (30) of (68)

Test Specifications**AC Power Lines**

Source Impedance: 12 ohm for common Mode and 2 ohm for differential Mode

Surge Amplitude : Common Mode
☒ (0,5 / 1,0 / 2,0) kV
Differential Mode
☒ (0,5 / 1,0) kV

Number of Surges: ☒ 5 surges per angle

Angle: ☒ 0°, 90°, 180°, 270° (input a.c. power port)

Polarity: ☒ Positive & Negative

Repetition Rate: ☐ 1 surge per min ☒ 1 surge per 30 sec.

Required Performance Criteria: ☒ Complied

Other supply / Signal Lines

Source Impedance: 42 ohm for common Mode

Surge Amplitude: Common Mode
☒ (0,5 / 1,0) kV

Number of Surges: ☒ 5 Surges

Polarity: ☒ Positive & Negative

Repetition Rate: ☒ 1 surge per min ☐ 1 surge per 30 sec.

Required Performance Criteria: ☒ Complied

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-EM-22T0517
Page (31) of (68)

Test Data

☒ Line to Line – Differential Mode

Mode of Application	Observations	
	(+) Surge (kV)	(-) Surge (kV)
L – N	Complied	Complied

☒ Line to Earth – Common Mode

Mode of Application	Observations	
	(+) Surge (kV)	(-) Surge (kV)
L – PE	Complied	Complied
N – PE	Complied	Complied

Signal Lines

☒ Line to Earth – Common Mode

Mode of Application	Coupling Method	Observations	
		(+) Surge (kV)	(-) Surge (kV)
RJ-45 (1)	CDN	Complied	Complied
	LINE	Complied	Complied
RJ-45 (2)	CDN	Complied	Complied
	LINE	Complied	Complied

Note: "Blank" = Not performed

Observations:

Complied – No degradation of function

Test Results

- ☒ PASS Required Performance Criteria
☐ NOT PASS Required Performance Criteria
☐ NOT APPLICABLE

Remarks

PASS Required Performance Criteria



3.5 Conducted Disturbance

Reference Standard

EN 61000-4-6:2014

Test Date

Jun. 21, 2022

Test Location

EMS-CS: Electro wave Shieldroom #6

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMS Test S/W	icd.control	EM TEST	5.3.12	-
☒	CONTINUOUS WAVE SIMULATOR	CWS 500N1.4	EM TEST	P1602169880	11, 24, 2022
☒	ATTENUATOR	ATT 6/80	EM TEST	P1614178148	11, 24, 2022
☒	CDN	CDN M016	TESEQ	43694	11, 24, 2022
☒	CDN	CDN M016	TESEQ	43697	11, 24, 2022
☒	CDN	CDN T8RJ45	EM TEST	0909-09	08, 03, 2022
☐	EM CLAMP	KEMZ 801A	TESEQ	44099	11, 25, 2022

Test Conditions

Temperature: (24,4 ± 1,0) °C
Relative Humidity: (44,0 ± 1,0) % R.H.
Atmospheric Pressure: (99,6 ± 0,0) kPa



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-EM-22T0517
Page (33) of (68)

Test Specifications

Frequency range:

☒ 150 kHz to 100 MHz

☐ 150 kHz to 80 MHz

Voltage Level:

☐ 1 Vrms

☐ 3 Vrms

☒ 10 Vrms

Modulation:

☒ AM, 80 %, 1 kHz sine wave

☒ PM, 1 Hz (0,5 s ON : 0,5 s OFF)

Frequency step:

☒ 1 % step

Dwell Time:

☐ 1 s

☒ 3 s

Required Performance Criteria: ☒ Complied

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-EM-22T0517
Page (34) of (68)

Test Data

☒ Input a.c. power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
L – N – PE	CDN	Complied

☐ Input d.c. power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
-	-	-

☒ Signal ports and telecommunication ports

Coupling Location (Line Stressed)	Coupling Method	Observations
RJ-45 (1)	CDN	Complied
RJ-45 (2)	CDN	Complied

Notes: CDN = Coupling Decoupling Network
"blank" = Not performed

Observations:
Complied – No degradation of function

Test Results

- ☒ PASS Required Performance Criteria
☐ NOT PASS Required Performance Criteria

Remarks

PASS Required Performance Criteria



3.6 Voltage Dips and Short Interruptions

Reference Standard
EN IEC 61000-4-11:2020

Test Date
Jun. 21, 2022

Test Location
EMS-Voltage dip: Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMS Test S/W	iec.control	EM TEST	5.4.8	-
☒	ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	03, 31, 2023
☒	MOTOR VARIAC	MV2616	EM TEST	P1552169719	03, 31, 2023

Test Conditions

Temperature: (24,3 ± 0,2) °C
Relative Humidity: (44,2 ± 0,2) % R.H.
Atmospheric Pressure: (99,7 ± 0,0) kPa



Test Specifications & Observations/Remarks

- Voltage Dips and Short Interruptions

<u>Test Level</u>	<u>Duration [in period/ms (50 Hz)]</u>	<u>Results</u>
☒ 20 % dip	☒ 250 / 5 000	<u>Complied</u>
☒ 30 % dip	☒ 25 / 500	<u>Complied</u>
☒ 60 % dip	☒ 10 / 200	<u>Complied</u>
☒ 100 % dip	☒ 250 / 5 000	<u>Degradation</u>

- Voltage variations

☒ Unom + 10 %	☒ 253.0 V (ac)	<u>Complied</u>
☒ Unom - 15 %	☒ 195.5 V (ac)	<u>Complied</u>

Observations:

Complied – No degradation of function

Degradation - See "Remarks "

Test Results

- ☒ PASS Required Performance Criteria
☐ NOT PASS Required Performance Criteria
☐ NOT APPLICABLE

Remarks

During the test(100%, 250cycle), EUT was turned off but after the test, it was recovered by no operator's intervention.



APPENDIX A – TEST DATA


Conducted Emissions at Mains Power Ports

- POWER 1

[HOT]

Common Information

Test Description:	Conducted Emission
Model No.:	PRO-7310B6
Phase:	L1
Mode:	POWER1
Operator Name:	KES



Final Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.380000	---	62.33	66.00	3.67	1000.0	9.000	L1	19.6
0.380000	64.41	---	79.00	14.59	1000.0	9.000	L1	19.6
0.880000	---	54.28	60.00	5.72	1000.0	9.000	L1	20.1
0.880000	58.35	---	73.00	14.65	1000.0	9.000	L1	20.1
16.595000	---	34.84	60.00	25.16	1000.0	9.000	L1	19.9
16.595000	40.72	---	73.00	32.28	1000.0	9.000	L1	19.9
17.330000	---	34.69	60.00	25.31	1000.0	9.000	L1	19.9
17.330000	40.53	---	73.00	32.47	1000.0	9.000	L1	19.9



KES Co., Ltd.


3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-EM-22T0517
Page (38) of (68)

[NEUTRAL]

Common Information

Test Description:	Conducted Emission
Model No.:	PRO-7310B6
Phase:	N
Mode:	POWER1
Operator Name:	KES



Final Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.380000	---	62.26	66.00	3.74	1000.0	9.000	N	19.6
0.380000	64.24	---	79.00	14.76	1000.0	9.000	N	19.6
0.880000	---	53.22	60.00	6.78	1000.0	9.000	N	20.1
0.880000	57.52	---	73.00	15.48	1000.0	9.000	N	20.1
0.885000	---	54.32	60.00	5.68	1000.0	9.000	N	20.1
0.885000	57.42	---	73.00	15.58	1000.0	9.000	N	20.1
16.825000	---	34.33	60.00	25.67	1000.0	9.000	N	19.9
16.825000	39.95	---	73.00	33.05	1000.0	9.000	N	19.9

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr


Report No.:
KES-EM-22T0517
Page (39) of (68)

- POWER 2

[HOT]

Common Information

Test Description: Conducted Emission
Model No.: PRO-7310B6
Phase: L1
Mode: POWER2
Operator Name: KES



Final Result


Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.600000	---	56.76	60.00	3.24	1000.0	9.000	L1	19.8
0.600000	57.44	---	73.00	15.56	1000.0	9.000	L1	19.8
0.840000	---	56.11	60.00	3.89	1000.0	9.000	L1	20.0
0.840000	56.99	---	73.00	16.01	1000.0	9.000	L1	20.0
1.075000	---	49.42	60.00	10.58	1000.0	9.000	L1	20.1
1.075000	53.55	---	73.00	19.45	1000.0	9.000	L1	20.1
1.080000	---	54.88	60.00	5.12	1000.0	9.000	L1	20.1
1.080000	56.04	---	73.00	16.96	1000.0	9.000	L1	20.1
16.080000	---	33.13	60.00	26.87	1000.0	9.000	L1	19.9
16.080000	39.54	---	73.00	33.46	1000.0	9.000	L1	19.9
28.075000	---	35.15	60.00	24.85	1000.0	9.000	L1	20.3
28.075000	40.14	---	73.00	32.86	1000.0	9.000	L1	20.3

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

[NEUTRAL]

Common Information

Test Description: Conducted Emission
 Model No.: PRO-7310B6
 Phase: N
 Mode: POWER2
 Operator Name: KES



Final Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.365000	---	50.17	66.00	15.83	1000.0	9.000	N	19.6
0.365000	53.44	---	79.00	25.56	1000.0	9.000	N	19.6
0.845000	---	48.64	60.00	11.36	1000.0	9.000	N	20.0
0.845000	53.20	---	73.00	19.80	1000.0	9.000	N	20.0
1.080000	---	54.60	60.00	5.40	1000.0	9.000	N	20.1
1.080000	55.78	---	73.00	17.22	1000.0	9.000	N	20.1
16.025000	---	32.08	60.00	27.92	1000.0	9.000	N	19.9
16.025000	38.91	---	73.00	34.09	1000.0	9.000	N	19.9
28.260000	---	31.19	60.00	28.81	1000.0	9.000	N	20.3
28.260000	36.47	---	73.00	36.53	1000.0	9.000	N	20.3

◆ Calculation

QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]

QuasiPeak / CAverage : The Final Value

Reading Value : Not shown in the table.

Corr. : Correction values (LISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-EM-22T0517
Page (41) of (68)


Conducted Emissions at Telecommunication Ports

- Main

[1 000 Mbps]

Common Information

Test Description: Telecommunication Emission
Model No.: PRO-7310B6
Mode : Main
Speed : 1000
Operator Name: KES



Final Result

Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.705000	---	36.47	74.00	37.53	1000.0	9.000	Single Line	19.9
0.705000	40.43	---	87.00	46.57	1000.0	9.000	Single Line	19.9
1.410000	---	45.63	74.00	28.37	1000.0	9.000	Single Line	20.1
1.410000	50.94	---	87.00	36.06	1000.0	9.000	Single Line	20.1
21.655000	---	43.00	74.00	31.00	1000.0	9.000	Single Line	19.9
21.655000	47.30	---	87.00	39.70	1000.0	9.000	Single Line	19.9
21.685000	---	41.95	74.00	32.05	1000.0	9.000	Single Line	19.9
21.685000	47.42	---	87.00	39.58	1000.0	9.000	Single Line	19.9

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr


Report No.:
KES-EM-22T0517
Page (42) of (68)

- SUB

[1 000 Mbps]

Common Information

Test Description: Telecommunication Emission
Model No.: PRO-7310B6
Mode : SUB
Speed : 1000
Operator Name: KES



Final Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.710000	---	49.43	74.00	24.57	1000.0	9.000	Single Line	19.9
0.710000	51.53	---	87.00	35.47	1000.0	9.000	Single Line	19.9
0.800000	---	26.08	74.00	47.92	1000.0	9.000	Single Line	19.9
0.800000	36.34	---	87.00	50.66	1000.0	9.000	Single Line	19.9
1.410000	---	51.99	74.00	22.01	1000.0	9.000	Single Line	20.1
1.410000	56.87	---	87.00	30.13	1000.0	9.000	Single Line	20.1
18.245000	---	49.48	74.00	24.52	1000.0	9.000	Single Line	19.7
18.245000	51.63	---	87.00	35.37	1000.0	9.000	Single Line	19.7
23.130000	---	49.50	74.00	24.50	1000.0	9.000	Single Line	19.9
23.130000	52.25	---	87.00	34.75	1000.0	9.000	Single Line	19.9

◆ Calculation

QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]

QuasiPeak / CAverage : The Final Value

Reading Value : Not shown in the table.

Corr. : Correction values (ISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr




KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-EM-22T0517
Page (43) of (68)

Radiated Electric Field Emissions(Below 1 GHz)



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	37.396	V	52.6	-24.0	28.6	40.0	11.4	123.0	77.0	
2	143.854	V	50.8	-25.5	25.3	40.0	14.7	157.0	178.0	
3	156.221	H	50.9	-24.9	26.0	40.0	14.0	400.0	303.0	
4	396.903	V	47.9	-14.3	33.6	47.0	13.4	196.0	11.0	
5	500.086	H	32.5	-11.5	21.0	47.0	26.0	387.0	62.0	
6	803.211	H	35.5	-6.9	28.6	47.0	18.4	369.0	311.0	

◆ Calculation – SEMI ANECHOIC CHAMBER #4(10 m)

Result(QP) [dB(μ V/m)] = (Reading(QP)[dB(μ V)] + c.f[dB(1/m)])

Margin(QP)[dB] = Limit[dB(μ V/m)] - Result(QP) [dB(μ V/m)]

Reading(QP) : Reading value, Result(QP) : Reading value + Factor value

Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value




KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-EM-22T0517
Page (44) of (68)

Radiated Electric Field Emissions(Above 1 GHz)



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]	Remark
1	1800.470	H	58.5	48.4	-2.2	56.3	46.2	76.0	56.0	19.7	9.8	100.0	343.3	
2	1801.380	V	57.5	48.7	-2.2	55.3	46.5	76.0	56.0	20.7	9.5	100.0	332.6	
3	1939.789	H	55.3	43.0	-1.3	54.0	41.7	76.0	56.0	22.0	14.3	100.0	38.3	
4	2077.510	V	57.9	45.8	-0.7	57.2	45.1	76.0	56.0	18.8	10.9	100.0	317.4	
5	2078.460	H	51.6	39.3	-0.7	50.9	38.6	76.0	56.0	25.1	17.4	100.0	350.8	
6	2219.210	H	55.0	46.4	-0.2	54.8	46.2	76.0	56.0	21.2	9.8	100.0	322.3	
7	2354.500	H	53.5	46.7	1.0	54.5	47.7	76.0	56.0	21.5	8.3	100.0	281.0	
8	2354.890	V	56.6	50.3	1.0	57.6	51.3	76.0	56.0	18.4	4.7	100.0	340.6	
9	2757.240	V	51.1	41.3	2.4	53.5	43.7	76.0	56.0	22.5	12.3	100.0	312.3	
10	2825.470	V	51.8	43.3	2.7	54.5	46.0	76.0	56.0	21.5	10.0	100.0	312.3	

◆ Calculation

Result(PK/CAV) [dB(μV/m)] = (Reading(PK/CAV)[dB(μV)] + c.f[dB(1/m)])

Margin(PK/CAV)[dB] = Limit[dB(μV/m)] - Result(PK/CAV) [dB(μV/m)]

Reading(PK/CAV) : Reading value, Result(PK/CAV) : Reading value + Factor value

Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value



Harmonic Current Emissions and Voltage Fluctuations and Flicker

Average harmonic current results

Hn	I _{eff} [A]	% of Limit	Limit [A]	Result
1	0.494			
2	0.006	0.575	1.080	PASS
3	0.045	1.968	2.300	PASS
4	0.003	0.646	0.430	n/a
5	0.056	4.945	1.140	PASS
6	0.002	0.638	0.300	n/a
7	0.036	4.740	0.770	PASS
8	0.003	1.095	0.230	n/a
9	0.027	6.674	0.400	PASS
10	0.001	0.811	0.184	n/a
11	0.023	7.070	0.330	PASS
12	0.002	1.289	0.153	n/a
13	0.015	7.152	0.210	PASS
14	0.001	1.100	0.131	n/a
15	0.010	6.480	0.150	PASS
16	0.002	1.599	0.115	n/a
17	0.004	3.264	0.132	n/a
18	0.002	1.645	0.102	n/a
19	0.008	7.030	0.118	PASS
20	0.001	1.402	0.092	n/a
21	0.010	6.297	0.161	PASS
22	0.001	1.604	0.084	n/a
23	0.004	2.760	0.147	n/a
24	0.001	1.622	0.077	n/a
25	0.005	3.468	0.135	n/a
26	0.001	1.572	0.071	n/a
27	0.004	3.227	0.125	n/a
28	0.001	2.236	0.066	n/a
29	0.003	2.825	0.116	n/a
30	0.001	1.729	0.061	n/a
31	0.003	2.543	0.109	n/a
32	0.001	2.065	0.058	n/a
33	0.004	4.084	0.102	n/a
34	0.001	2.414	0.054	n/a
35	0.008	8.326	0.096	PASS
36	0.001	2.869	0.051	n/a
37	0.008	8.793	0.091	PASS
38	0.001	2.445	0.048	n/a
39	0.004	4.318	0.087	n/a
40	0.001	2.137	0.046	n/a

Note: Harmonic currents less than 0.6 % of the input current measured under the test conditions, or less than 5 mA, whichever is greater, are disregarded.

* Application of limits for average is 100% except for odd harmonics from 21 to 39, where 150% applies.



Test Data - Harmonics (continued)

Maximum harmonic current results				
Hn	I _{eff} [A]	% of Limit	Limit [A]	Result
1	0.562			
2	0.010	0.610	1.620	PASS
3	0.064	1.865	3.450	PASS
4	0.004	0.657	0.645	n/a
5	0.058	3.376	1.710	PASS
6	0.003	0.657	0.450	n/a
7	0.046	3.986	1.155	PASS
8	0.003	0.990	0.345	n/a
9	0.040	6.584	0.600	PASS
10	0.004	1.326	0.276	n/a
11	0.027	5.375	0.495	PASS
12	0.002	0.993	0.230	n/a
13	0.020	6.296	0.315	PASS
14	0.002	0.978	0.197	n/a
15	0.015	6.810	0.225	PASS
16	0.002	1.268	0.173	n/a
17	0.014	7.082	0.199	PASS
18	0.002	1.292	0.153	n/a
19	0.013	7.247	0.178	PASS
20	0.003	2.054	0.138	n/a
21	0.015	9.185	0.161	PASS
22	0.003	1.997	0.125	n/a
23	0.009	6.272	0.147	PASS
24	0.001	1.267	0.115	n/a
25	0.006	4.799	0.135	PASS
26	0.001	1.340	0.106	n/a
27	0.006	4.923	0.125	PASS
28	0.002	1.723	0.099	n/a
29	0.007	5.861	0.116	PASS
30	0.001	1.594	0.092	n/a
31	0.007	6.286	0.109	PASS
32	0.001	1.701	0.086	n/a
33	0.006	5.880	0.102	PASS
34	0.002	1.908	0.081	n/a
35	0.010	9.909	0.096	PASS
36	0.002	2.233	0.077	n/a
37	0.009	10.401	0.091	PASS
38	0.001	1.917	0.073	n/a
39	0.005	5.208	0.087	n/a
40	0.001	1.947	0.069	n/a

Note: Harmonic currents less than 0.6 % of the input current measured under the test conditions, or less than 5 mA, whichever is greater, are disregarded.

* Application of limits for average is 100% except for odd harmonics from 21 to 39, where 150% applies.

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:
KES-EM-22T0517
Page (47) of (68)

Test Data - Voltage Fluctuations


Maximum Flicker results

Flicker Measurements					
	Plt	Max Pst	Max Dc	Max Dmax	Max Tmax
Line 1:	0.028	0.028	0.013	< 0.2	0
Limits:	0.65	1	3.3	4	0.5
Results:	PASS	PASS	PASS	PASS	PASS

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Test Setup Photos and Configuration

Conducted Emissions at Mains Power Ports



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Conducted Emissions at Telecommunication Ports




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Radiated Electric Field Emissions(Below 1 GHz)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Radiated Electric Field Emissions(Above 1 GHz)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Harmonic Current Emissions and Voltage Fluctuations and Flicker




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Electrostatic Discharge



Radiated Electric Field Immunity



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Electrical Fast Transients/Bursts



Surge Transients




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

Conducted Disturbance



Voltage Dips and Short Interruptions




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

EUT External Photographs

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

EUT Internal Photographs

(Internal View)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

EUT Internal View – Main Board

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

EUT Internal View – Network Adapter Board

(Top)



(Bottom)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr

EUT Internal View – Board 1

(Top)



(Bottom)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr

EUT Internal View – Board 2

(Top)




(Bottom)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

EUT Internal View – Board 3

(Top)



(Bottom)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

EUT Internal View – RAM

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
 The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
 The authenticity of the test report, contact shchoi@kes.co.kr

EUT Internal View – SSD

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

EUT Internal View – CPU

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

EUT Internal View – SMPS

(Top)



(Bottom)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr

(Label)



Label and Location



PC NVR

Model No : PRO-7310B6

Manufacturer : Dream I System co.,Ltd.

Made in Korea

