



TEST REPORT



Report No. : KES-EM-23T0983

Page 1 / 32

KES Co., Ltd.3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,
Gyeonggi-do, 14057, Korea

Tel : +82-31-425-6200, Fax : +82-31-425-6200

1. Client

Applicant : Hanwha Vision Co., Ltd

Applicant Address : 6, Pangyo-ro 319Beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do,
Republic of Korea

2. Sample Description

Product name : NETWORK CAMERA

Model/Type No. : QNE-C9013RL

Variant Model : -

Manufacturer : 1. HANWHA VISION VIETNAM COMPANY LIMITED
2. D-TECH CO.,LTD.Manufacturer Address : 1. Lot O-2, Que Vo Industrial Zone extended Area, Nam Son Ward,
Bac Ninh City, Bac Ninh Province, Vietnam
2. 173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi- do, Korea
(Suwon Industrial Complex)

3. Equipment authorization : Supplier's Declaration of Conformity

3. Date of Receipt : Nov. 10, 2023

4. Test date : Nov. 12, 2023 ~ Nov. 14, 2023

5. Date of Issue : Nov. 24, 2023

7. Test Results : In Compliance

Tested by

Dong Hyun, Won
EMC Test Engineer

Reviewed by

Dong Il, Lee
EMC Technical Manager

This test report is not related to KS Q ISO/IEC 17025 and KOLAS.

KES-QP16-F01(00-23-01-01)

KES Co., Ltd.

The authenticity of the test report, contact kes@kes.co.kr



REPORT REVISION HISTORY

Date	Test Report No.	Revision History
Nov. 24, 2023	KES-EM-23T0983	Issued

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.




TABLE OF CONTENTS

1.0 General Product Description..... 4

1.1 Test Voltage & Frequency..... 7

1.2 Variant Model Differences..... 7

1.3 Device Modifications..... 7

1.4 Equipment Under Test..... 7

1.5 Support Equipments..... 7

1.6 External I/O Cabling..... 8

1.7 EUT Operating Mode(s)..... 8

1.8 Configuration..... 9

1.9 Remarks when standards applied..... 10

1.10 Calibration Details of Equipment Used for Measurement..... 10

1.11 Test Facility..... 10

1.12 Laboratory Accreditations and Listings..... 10

2.0 Test Regulations..... 11

2.1 Conducted Emissions at Mains Power Ports..... 12

2.2 Radiated Electric Field Emissions(Below 1 GHz)..... 14

2.3 Radiated Electric Field Emissions(Above 1 GHz)..... 16

APPENDIX A – TEST DATA..... 18

 Conducted Emissions at Mains Power Ports..... 18

 Radiated Electric Field Emissions(Below 1 GHz)..... 20

 Radiated Electric Field Emissions(Above 1 GHz)..... 22

 Test Setup Photos and Configuration..... 23


 Conducted Emissions at Mains Power Ports..... 23

 Radiated Electric Field Emissions(Below 1 GHz)..... 24

 Radiated Electric Field Emissions(Above 1 GHz)..... 25

 EUT External Photographs..... 26

 EUT Internal Photographs..... 27




1.0 General Product Description

Main Specifications of EUT are:



Video	
Imaging Device	1/2.8" CMOS
Resolution	3840x2160, 3328x1872, 3072x1728, 2592x1944, 2688x1520, 1920x1080, 1600x1200, 1280x1024,1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240
Max. Framerate	H.265/H.264: Max. 30fps/25fps(60Hz/50Hz) MJPEG: Max. 30fps(@8MP Max. 5fps)
NETD	None
Pixel Size	None
Min. Illumination	Color: 0.03Lux (F1.6, 1/30sec) BW: 0.003Lux (F1.6, 1/30sec, 30IRE), 0Lux(IR LED on) (TBD)
Video Out	None
Video Transmission Distance	None
Lens	
Focal Length (Zoom Ratio)	3.0mm fixed focal
Max. Aperture Ratio	F1.6
Angular Field of View	H: 108°/ V: 59°/ D: 127°
Min. Object Distance	0.5m (1.64ft)
Focus Control	Fixed
Lens Type	Fixed IRIS
Mount Type	M12
Optional Lens	None
Pan / Tilt / Rotate	
Pan / Tilt / Rotate Range	0°~350° / 0°~75° / 0°~360°
Pan Range	None
Pan Speed	None
Tilt Range	None
Tilt Speed	None
Rotate Range	None
Sequence	None
Preset Accuracy	None
Operational	
Camera Title	Displayed up to 85 characters
Direction Indicator	None
Day & Night	Auto(ICR)
Backlight Compensation	BLC, WDR, SDR
Wide Dynamic Range	120dB
Digital Noise Reduction	SSNRV, WiseNRⅡ(Based on AI engine)
Digital Image Stabilization	None
Defog	None
Motion Detection	8ea, 8point Polygonal zones
Privacy Masking	32ea, 4point quadrangle zones
Gain Control	Low / Middle / High
White Balance	ATW / AWC / Manual / Indoor / Outdoor
LDC	Support
Electronic Shutter Speed	Minimum / Maximum / Anti flicker (1/5~1/20,000sec)
Digital PTZ	Support
Video Rotation	Flip, Mirror, Hallway view(90°/270°)
Analytics	Classified object type: Person/Vehicle Attributes: Vehicle(Type:car/bus/truck/motorcycle/bicycle) Support DetectionShot Analytics events based on AI engine - Motion detection*, Object detection, Virtual line*(Crossing/Direction), Virtual area*(Loitering/Intrusion/Enter/Exit) Analytics events - Defocus detection, Tampering, Virtual area(Appear/Disappear) * Some of the video analytics only works with people and vehicle detection
Business Intelligence	Based on AI engine: People counting, Vehicle counting, Queue management, Heatmap



Serial Interface	None
Alarm I/O	None
Alarm Triggers	Analytics, Network disconnect
Alarm Events	When alarm trigger occurred - File upload(image) : e-mail/FTP - Notification : e-mail - Recording : SD/SDHC/SDXC or NAS recording at event triggers - Handover(PTZ preset, Send message by HTTP/HTTPS/TCP)
Audio Streaming	None
Audio In	None
Audio Out	None
Light Type	Dual light (White warm light, IR)
Light Viewable Length	None
IR Viewable Length	White LED : 30m(98.42ft) (TBD) IR : 30m(98.42ft) (TBD)
IR Illuminator (Optional)	None
IR Radiation angle	None
IR LED	None
IR Wavelength	long-life 850 nm IR LED
IR Operation	None
Water Removal	None
Auto Tracking	None
Coaxial Protocol	None
Color Palettes	None
Radiometry	
Temperature Detect Range	None
Temperature Accuracy	None
Temperature Detection	None
Additional	None
Network	
Ethernet	RJ-45(10/100BASE-T)
Video Compression	H.265/H.264: Main/High, MJPEG
Audio Compression	None
Smart Codec	Manual(Sea area), WiseStreamIII(Based on AI engine)
Video Quality Adjustment	H.264/H.265: Target bitrate level control MJPEG: Quality Level control
Bitrate Control	H.264/H.265: CBR or VBR MJPEG: VBR
Streaming	Unicast(20 users) / Multicast Multiple streaming(Up to 5 profiles)
Protocol	IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, CDP, SRTP (TCP, UDP Unicast), MQTT
SIP support (VoIP, Peer-to-peer)	None
Security	None
Application Programming Interface	ONVIF Profile S/G/T/M SUNAPI(HTTP API)
Security	
OS / Firmware Protect	Secure boot, Signed firmware, Firmware encryption
User authentication	Digest Authentication, Prevent brute-force attack
Network authentication	802.1X Authentication(EAP-TLS, EAP-LEAP, EAP-PEAP MSCHAPv2)
Secure Communication	HTTPS, SRTP, WSS(Websocket secure)
Access Control	Access control based on IP address
Data Protect	Authentication information encryption, ZIP compression encryption
Audit	User Access/System/Event log management
Device ID	Device Certificate(Hanwha Private Root CA)
Secure Storage	SDcard partition encrypt
Security Certificate	None
General	
Webpage Language	English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Portuguese, Czech, Polish, Turkish, Dutch, Hungarian, Greek
Web Viewer	None
Edge Storage	Micro SD/SDHC/SDXC 1slot 256GB
Memory	2GB RAM, 1GB Flash



Environmental & Electrical	
Operating Temperature / Humidity	-40°C~+60°C(-40°F~+140°F) / 0~95% RH * Start up should be done at above -30°C Humidity control /w Air vapor control
Storage Temperature / Humidity	-50°C~+60°C(-58°F~+140°F) / 0~95% RH
Certification	IP66, IP67, IK10
Input Voltage	PoE(IEEE802.3af, Class3)
Power Consumption	PoE: Max 0.0W, typical 0.0W (TBD)
Mechanical	
Color / Material	White / Aluminum (TBD)
RAL Code	RAL9003
Product Dimensions / Weight	ø140.0x99.6mm(ø5.51x3.92"), 000g(000 lb) (TBD)
Compatible Conduit hole / Gangbox	Conduit hole : None Gangbox : Single, Double, 4" Octagon
Hanging Mount (Dome)	SBP-140HIMW
Skin Cover	None
Skin Cover (Dome)	None
Weather Cap (Dome)	None
Power Module	None
Backbox	SBV-140BW
Certifications & Standards	
Network	None
EMC	FCC 47 CFR 15 Subpart B Class A ICES-3(A)/NMB-3(A) CE/UKCA - EN 55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3 VCCI CISPR 32 Class A RCM AS/NZS CISPR 32 Class A
Safety	UL 62368-1, CAN/CSA C22.2 NO. 62368-1 IEC/EN 62471
Environment	IEC/EN 63000 IEC/EN 60529 IP66/IP67, IEC/EN 62262 IK10
Video	None
DORI (EN62676-4 standard)	
Detect (25PPM/ 8PPF)	31.4m(103.01ft)
Observe (63PPM/ 19PPF)	12.6m(41.33ft)
Recognize (125PPM/ 38PPF)	6.3m(20.66ft)
Identify (250PPM/ 76PPF)	3.1m(10.17ft)
LPR/ANPR/MMCR	
Speed Description	None
Speed limit	None
Min. Forward Distance	None
Max. Forward Distance	None
Max. Horizontal Angle	None
Max. Vertical Angle	None
Horizontal Offset	None
Camera Height	None
Lane Coverage	None
Vehicle Recognition	None
Available Countries	None
Wisenet Road AI LPR/ANPR/MMCR	
Solution	None
Speed Description	None
Lane Coverage	None
Speed limit	None
Min. Forward Distance	None
Max. Forward Distance	None
Max. Horizontal Angle	None
Max. Vertical Angle	None
Horizontal Offset	None
Camera Height	None
Vehicle Recognition	None
Available Countries	None
Ver	
Ver	202311



1.1 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

☒ AC 120 V, 60 Hz (PoE Adapter)

1.2 Variant Model Differences

Not applicable

1.3 Device Modifications

Not applicable

1.4 Equipment Under Test

Description	Model Number	Serial Number	Manufacturer	Remarks
NETWORK CAMERA	QNE-C9013RL	-	HANWHA VISION VIETNAM COMPANY LIMITED	EUT

1.5 Support Equipments

Description	Model Number	Serial Number	Manufacturer	Remarks
PoE Adapter	POE29U-1AT(PL)	-	Phihong Technology Co., Ltd.	-
Notebook	LG15N54	506NZGK000615	LG Electronics Inc.	-
Notebook Adapter	PA-1650-43(65W)	OF58U63849302Y6 09	LG Electronics Inc.	-
Micro SD Card	-	-	Transcend	8 GB



1.6 External I/O Cabling

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
NETWORK CAMERA (EUT)	RJ-45 (PoE)	PoE Adapter	RJ-45	3.8	- U
	Micro SD Card Slot	Micro SD Card	Micro SD Card Slot	-	-
Notebook	RJ-45 (LAN)	PoE Adapter	RJ-45	1.5	U
	DC Jack	Notebook Adapter	DC Jack	2.0	U

* Unshielded=U, Shielded=S



1.7 EUT Operating Mode(s)

Test mode	operating
Operating	1. Run the Web Viewer on your laptop and check the camera video output 2. PingTest from your laptop to check the network status 3. After the test, the Micro SD Card storage file was checked. And Checked that the LED lights up.

EUT Test operating S/W		
Name	Version	Manufacture Company
Web Viewer	-	Hanwha Vision Co., Ltd



1.8 Configuration



1.9 Remarks when standards applied

N/A

1.10 Calibration Details of Equipment Used for Measurement


Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less.

1.11 Test Facility

The measurement facility is located at 473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, 12658, Korea, Republic of. The sites are constructed in conformance with the requirements of ANSI C63.4a-2017 and CISPR 16-1-4:2019

1.12 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
KOREA	RRA	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KR0100
International	KOLAS	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KT489
USA	FCC	3 m & 10 m Semi-Anechoic Chamber Conducted test site to perform FCC Part 15/18 measurements.	 KR0100
Canada	ISED	3 m & 10 m Semi-Anechoic Chamber and Conducted test site	 23298
JAPAN	VCCI	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site)	 C-20136, T-20137, R-20181, G-20176
Europe	TÜV SÜD	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 CARAT 001633 0004



2.0 Test Regulations

The emissions tests were performed according to following regulations:

- ☒ 47 CFR Part 15, Subpart B
- ☐ CISPR 22:2009 +A1:2010

☐ Class A

☐ Class B
- ☒ ANSI C63.4a-2017

☒ Class A

☐ Class B

☒ IC Regulation ICES-003 Issue 7

☐ CAN/CSA-CISPR 32:17


☐ Class A

☐ Class B

☒ ANSI C63.4a-2017

☒ Class A

☐ Class B



2.1 Conducted Emissions at Mains Power Ports



Test Date
Nov. 12, 2023

Test Location
Electro wave Shieldroom #6

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EMC32	R & S	9.12.00	-
☒	EMI TEST RECEIVER	ESR3	R & S	101783	11, 08, 2024
☒	LISN	ENV216	R & S	101787	11, 08, 2024
☒	LISN	ESH2-Z5	R & S	100450	11, 08, 2024
☒	PULSE LIMITER	ESH3-Z2	R & S	101915	11, 08, 2024

Diagram of test setup



Report No. : KES-EM-23T0983

Page 13 / 32

Test Conditions

Temperature: (22,5 ± 0,1) °C
Relative Humidity: (47,0 ± 0,1) % R.H.

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz


Test Results

The requirements are:

- ☒ PASS
- ☐ NOT PASS
- ☐ NOT APPLICABLE

Remarks

See Appendix A for test data.



2.2 Radiated Electric Field Emissions(Below 1 GHz)



Test Date
Nov. 13, 2023

Test Location
☐ OPEN AREA TEST SITE #2 ☒ SEMI ANECHOIC CHAMBER #4(10m)

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EP5/RE	TOYO Corporation	6.0.0	-
☒	EMI TEST RECEIVER	ESU26	R & S	100551	03, 21, 2024
☒	AMPLIFIER	SCU 01	R & S	100603	11, 08, 2024
☒	TRILOG-BROADBAND ANTENNA	VULB9163	Schwarzbeck	715	11, 17, 2024
☒	ATTENUATOR	8491A	HP	32173	03, 03, 2024

Diagram of test setup



Report No. : KES-EM-23T0983

Page 15 / 32

Test Conditions

Temperature: (22,1 ± 0,1) °C
Relative Humidity: (46,2 ± 0,1) % R.H.

Frequency Range of Measurement

30 MHz to 1 GHz

Instrument Settings

IF Band Width: 120 kHz



Test Results

The requirements are:

- ☒ PASS
- ☐ NOT PASS
- ☐ NOT APPLICABLE

Remarks

See Appendix A for test data.



2.3 Radiated Electric Field Emissions(Above 1 GHz)



Test Date
Nov. 14, 2023

Test Location
SEMI ANECHOIC CHAMBER #5

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	ES10/RE	TOYO Corporation	2022.01.000	-
☒	EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100552	03, 21, 2024
☒	HORN ANTENNA	BBHA 9120D	SCHWARZBECK	9120D-1802	11, 03, 2024
☒	PREAMPLIFIER	8449B	HP	3008A00538	05, 31, 2024
☒	ATTENUATOR	8491B	HP	23094	03, 21, 2024

Diagram of test setup



Report No. : KES-EM-23T0983

Page 17 / 32

Test Conditions

Temperature: (23,4 ± 0,1) °C
Relative Humidity: (48,1 ± 0,1) % R.H.

Frequency Range of Measurement

1 GHz to 6 GHz

Instrument Settings

IF Band Width: 1 MHz

Test Results

The requirements are:

- ☒ PASS
- ☐ NOT PASS
- ☐ NOT APPLICABLE

Remarks

- See Appendix A for test data.
- The Average of the test data is the cispr average result.



APPENDIX A – TEST DATA


Conducted Emissions at Mains Power Ports

HOT LINE

Common Information



Test Description:
Model No.:
Phase:
Mode:
Operator Name:

Conducted Emission
QNE-C9013RL
H
KES



Final_Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.155000	---	30.14	66.00	35.86	1000.0	9.000	L1	19.4
0.155000	48.85	---	79.00	30.15	1000.0	9.000	L1	19.4
0.410000	---	36.15	66.00	29.85	1000.0	9.000	L1	19.4
0.410000	39.18	---	79.00	39.82	1000.0	9.000	L1	19.4
2.445000	---	29.91	60.00	30.09	1000.0	9.000	L1	19.6
2.445000	37.30	---	73.00	35.70	1000.0	9.000	L1	19.6
2.725000	---	31.67	60.00	28.33	1000.0	9.000	L1	19.6
2.725000	37.40	---	73.00	35.60	1000.0	9.000	L1	19.6
28.685000	---	43.33	60.00	16.67	1000.0	9.000	L1	20.4
28.685000	46.86	---	73.00	26.14	1000.0	9.000	L1	20.4



NEUTRAL LINE

Common Information


Test Description:Conducted Emission

Model No.:QNE-C9013RL

Phase:N

Mode:

Operator Name:KES




Final Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.155000	---	29.57	66.00	36.43	1000.0	9.000	N	19.3
0.155000	48.95	---	79.00	30.05	1000.0	9.000	N	19.3
0.405000	---	32.87	66.00	33.13	1000.0	9.000	N	19.4
0.405000	38.64	---	79.00	40.36	1000.0	9.000	N	19.4
2.030000	---	26.87	60.00	33.13	1000.0	9.000	N	19.6
2.030000	35.82	---	73.00	37.18	1000.0	9.000	N	19.6
2.465000	---	30.01	60.00	29.99	1000.0	9.000	N	19.6
2.465000	37.52	---	73.00	35.48	1000.0	9.000	N	19.6
29.235000	---	43.90	60.00	16.10	1000.0	9.000	N	20.4
29.235000	47.44	---	73.00	25.56	1000.0	9.000	N	20.4


◆ Calculation

QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]
QuasiPeak / CAverage : The Final Value
Reading Value : Not shown in the table.
Corr. : Correction values (LISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))





Radiated Electric Field Emissions(Below 1 GHz)

- 47 CFR Part 15, Subpart B




Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	34.608	V	56.4	-24.8	31.6	39.0	7.4	144.0	323.0	
2	42.853	V	51.5	-21.9	29.6	39.0	9.4	102.0	96.0	
3	60.191	V	53.3	-22.1	31.2	39.0	7.8	118.0	100.0	
4	79.713	H	50.9	-27.6	23.3	39.0	15.7	400.0	341.0	
5	98.385	H	53.0	-22.4	30.6	43.5	12.9	365.0	160.0	
6	98.435	V	58.8	-22.4	36.4	43.5	7.1	110.0	8.0	
7	151.250	H	48.5	-25.1	23.4	43.5	20.1	392.0	225.0	
8	161.071	V	54.7	-24.7	30.0	43.5	13.5	124.0	267.0	
9	276.138	H	44.7	-18.2	26.5	46.5	20.0	289.0	229.0	
10	884.206	H	26.2	-3.3	22.9	46.5	23.6	298.0	239.0	
11	938.526	V	26.1	-2.7	23.4	46.5	23.1	150.0	232.0	
12	972.961	H	26.1	-2.3	23.8	49.5	25.7	400.0	252.0	



- IC Regulation ICES-003 Issue 7



Final Result

No.	Frequency	(P)	Reading	c.f	Result	Limit	Margin	Height	Angle	Remark
	[MHz]		QP		QP	QP	QP			
			[dB(uV)]	[dB(1/m)]	[dB(uV/m)]	[dB(uV/m)]	[dB]	[cm]	[deg]	
1	34.608	V	56.4	-24.8	31.6	40.0	8.4	144.0	323.0	
2	42.853	V	51.5	-21.9	29.6	40.0	10.4	102.0	96.0	
3	60.191	V	53.3	-22.1	31.2	40.0	8.8	118.0	100.0	
4	79.713	H	50.9	-27.6	23.3	40.0	16.7	400.0	341.0	
5	98.385	H	53.0	-22.4	30.6	43.5	12.9	365.0	160.0	
6	98.435	V	58.8	-22.4	36.4	43.5	7.1	110.0	8.0	
7	151.250	H	48.5	-25.1	23.4	43.5	20.1	392.0	225.0	
8	161.071	V	54.7	-24.7	30.0	43.5	13.5	124.0	267.0	
9	276.138	H	44.7	-18.2	26.5	47.0	20.5	289.0	229.0	
10	884.206	H	26.2	-3.3	22.9	47.0	24.1	298.0	239.0	
11	938.526	V	26.1	-2.7	23.4	47.0	23.6	150.0	232.0	
12	972.961	H	26.1	-2.3	23.8	49.5	25.7	400.0	252.0	

◆ Calculation

Result(QP) [dB(μV/m)] = (Reading(QP)[dB(μV)] + c.f[dB(1/m)])


Margin(QP)[dB] = Limit[dB(μV/m)] - Result(QP) [dB(μV/m)]

Reading(QP) : Reading value, Result(QP) : Reading value + Factor value

Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value



Radiated Electric Field Emissions(Above 1 GHz)



Final Result

No.	Frequency	Pol	Reading	Reading	c.f	Result	Result	Limit	Limit	Margin	Margin	Height	Angle	Remark
	[MHz]		AV	PK		AV	PK	AV	PK	AV	PK		[deg]	
			[dB(μV)]	[dB(μV)]	[dB(1/m)]	[dB(μV/m)]	[dB(μV/m)]	[dB(μV/m)]	[dB(μV/m)]	[dB]	[dB]	[cm]		
1	1696.975	V	31.7	50.0	1.0	32.7	51.0	60.0	80.0	27.3	29.0	100.0	168.8	
2	1793.148	V	31.9	49.8	1.8	33.7	51.6	60.0	80.0	26.3	28.4	150.0	256.7	
3	1803.963	H	30.3	43.7	1.9	32.2	45.6	60.0	80.0	27.8	34.4	396.0	142.6	
4	1934.301	V	29.8	49.9	2.3	32.1	52.2	60.0	80.0	27.9	27.8	112.0	163.8	
5	2353.028	V	28.9	48.9	4.1	33.0	53.0	60.0	80.0	27.0	27.0	124.0	193.0	
6	2573.331	H	29.2	43.9	4.9	34.1	48.8	60.0	80.0	25.9	31.2	298.0	256.9	
7	2999.778	V	27.2	50.0	6.2	33.4	56.2	60.0	80.0	26.6	23.8	118.0	272.8	
8	3071.943	H	28.2	41.9	6.3	34.5	48.2	60.0	80.0	25.5	31.8	285.0	56.6	
9	3447.782	H	28.7	42.2	6.9	35.6	49.1	60.0	80.0	24.4	30.9	369.0	104.3	
10	4556.958	H	27.8	41.3	10.4	38.2	51.7	60.0	80.0	21.8	28.3	399.0	1.0	
11	4765.698	H	27.8	41.4	11.4	39.2	52.8	60.0	80.0	20.8	27.2	294.0	336.5	
12	4879.348	V	26.7	39.8	11.9	38.6	51.7	60.0	80.0	21.4	28.3	400.0	255.2	


◆ Calculation

Result(PK/CAV) [dB(μV/m)] = (Reading(PK/CAV)[dB(μV)] + c.f[dB(1/m)])

Margin(PK/CAV)[dB] = Limit[dB(μV/m)] - Result(PK/CAV) [dB(μV/m)]

Reading(PK/CAV) : Reading value, Result(PK/CAV) : Reading value + Factor value

Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value



Report No. : KES-EM-23T0983

Page 23 / 32

Test Setup Photos and Configuration

Conducted Emissions at Mains Power Ports



KES-QP16-F01(00-23-01-01)

KES Co., Ltd.


The authenticity of the test report, contact kes@kes.co.kr



Report No. : KES-EM-23T0983

Page 24 / 32



Radiated Electric Field Emissions(Below 1 GHz)



KES-QP16-F01(00-23-01-01)

KES Co., Ltd.


The authenticity of the test report, contact kes@kes.co.kr



Report No. : KES-EM-23T0983

Page 25 / 32

Radiated Electric Field Emissions(Above 1 GHz)



KES-QP16-F01(00-23-01-01)

KES Co., Ltd.

The authenticity of the test report, contact kes@kes.co.kr




EUT External Photographs

(Top)



(Bottom)




EUT Internal Photographs

(Internal View)




EUT Internal View – Board 1

(Top)




(Bottom)






EUT Internal View – Board 2

(Top)




(Bottom)







EUT Internal View – Board 3

(Top)




(Bottom)




EUT Internal View – Board 4

(Top)



(Bottom)



Label Photographs

FCC Label



NETWORK CAMERA

QNE-C9013RL

IC Label

CAN ICES-003(A) / NMB-003(A)

This device complies with Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions:
(1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes :

(1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

