EMC TEST REPORT

Test Report No.	:	KES-E1-18T0047
Date of Issue	:	Jan. 09, 2018
Product name	:	2M LENS MODULE
Model/Type No.	:	SLA-2M3600DN
Variant Mode	:	-
Applicant	:	Hanwha Techwin Co., Ltd.
Applicant Address	:	1204, Changwon-daero, Seongsan-gu, Changwon-si, Gyeongsangnam-do, Korea
Manufacturer	:	Hanwha Techwin (Tianjin) Co., Ltd
Manufacturer Address	:	No.11 Weiliu Rd,Micro-Electronic Industrial Park, TEDA, Tianjin, 300385, People's Republic of China
Equipment authorization	:	☐ **Declaration of Conformity** ☒ **Verification** ☐ **Certification**
Date of Receipt	:	Dec. 21, 2017
Test date	:	Jan. 02, 2018 ~ Jan. 03, 2018
Test Results	:	☒ **In Compliance** ☐ **Not in Compliance**

Tested by



Hyo Jin, Kim
EMC Test Engineer

Reviewed by



Dong-Hun, Jang
EMC Technical Manager

This test report is not related to KOLAS.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

REPORT REVISION HISTORY

Date	Test Report No.	Revision History
Jan. 09, 2018	KES-E1-18T0047	Issued

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document Jul be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.

TABLE OF CONTENTS

1.0 General Product Description 4
1.1 Test Voltage & Frequency 5
1.2 Variant Model Differences 5
1.3 Device Modifications 5
1.4 Equipment Under Test 5
1.5 Support Equipments 5
1.6 External I/O Cabling 6
1.7 EUT Operating Mode(s) 6
1.8 Configuration 7
1.9 Remarks when standards applied 8
1.10 Calibration Details of Equipment Used for Measurement 8
1.11 Test Facility 8
1.12 Laboratory Accreditations and Listings 8
2.0 Test Regulations 9
2.1 Conducted Emissions at Mains Power Ports 11
2.2 Radiated Electric Field Emissions(Below 1 ㎓) 12
2.3 Radiated Electric Field Emissions(Above 1 ㎓) 13
APPENDIX A – TEST DATA 14
Conducted Emissions at Mains Power Ports 14
Radiated Electric Field Emissions(Below 1 ㎓) 16
Radiated Electric Field Emissions(Above 1 ㎓) 17
Test Setup Photos and Configuration 18
Conducted Voltage Emissions 18
Radiated Electric Field Emissions(Below 1 ㎓) 19
Radiated Electric Field Emissions(Above 1 ㎓) 20
EUT External Photographs 21
EUT Internal Photographs 22

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

1.0 General Product Description

Main Specifications of EUT are:

Video	
Imaging Device	1/2.8" 2M CMOS
Total Pixels	1945(H) x 1109(V) 2.16M
Effective Pixels	1945(H) x 1097(V) 2.13M
Scanning System	Progressive Scan
Min. Illumination	Color : 0.055Lux(F2.0, 1/30sec, 30IRE) B/W : 0.055Lux(F2.0, 1/30sec, 30IRE)
S / N Ratio	50dB
Wide Dynamic Range	150dB
Day & Night	Electrical
Lens	
Focal Length (Zoom Ratio)	3.6mm
Max. Aperture Ratio	F2.0
Angular Field of View	**H:94.8°, V:49.3°, D:114.3°**
Min. Object Distance	-
Focus Control	-
Lens Type	Fixed focal
Mount Type	M12 Lens module with main unit
Mechanical	
Color / Material	Black / Plastic
Dimension (WxHxD)	Ø35.5 x 27.9mm
Weight	27g

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

1.1 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

Voltage ☐ 230 Vac ☐ 120 Vac ☐ 24 Vac ☐ 12 Vdc ☒ PoE

Frequency ☐ 50 Hz ☐ 60 Hz ☐ Hz

1.2 Variant Model Differences

Not applicable

1.3 Device Modifications

Not applicable

1.4 Equipment Under Test

Description	Model Number	Serial Number	Manufacturer	Remarks
2M LENS MODULE	SLA-2M3600DN	-	Hanwha Techwin (Tianjin) Co.,Ltd	E.U.T

1.5 Support Equipments

Description	Model Number	Serial Number	Manufacturer	Remarks
PoE Adaptor	GS728TPP	-	NETGEAR, INC.	-
Notebook	NT730U3E	JJRE91CF200065A	Samsung Electronics Co., Ltd.	-
Notebook Adaptor	PA-1600-66	AD-6019P	Li Shin Co., Ltd.	-
Network Camera	PNM-7000VD	-	Hanwha Techwin (Tianjin) Co.,Ltd	-
LENS MODULE	SLA-2M2400D	-	Hanwha Techwin (Tianjin) Co.,Ltd	-

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

1.6 External I/O Cabling

Start		END		Cable Spec.	
Description	**I/O Port**	**Description**	**I/O Port**	**Length**	**Shield**
2M LENS MODULE (E.U.T)	LENS Out	Network Camera	LENS In	-	-
Network Camera	RJ-45 (PoE)	PoE Adaptor	RJ-45 (PoE)	3.0	U
	LENS In	LENS MODULE	LENS Out	-	-
PoE Adaptor	RJ-45 (Data)	Notebook	RJ-45 (Data)	3.0	U

* Unshielded=U, Shielded=S

1.7 EUT Operating Mode(s)

Test mode	operating
PoE	E.U.T Monitoring, Ping Test

E.U.T Test operating S/W		
Name	**Version**	**Manufacture Company**
WebViewer	-	Hanwha Techwin Co., Ltd.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

1.8 Configuration

■ AC Main
□ DC Main



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

1.9 Remarks when standards applied

N/A

1.10 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less.

1.11 Test Facility

The measurement facility is located at 473-21 Gayeo-ro, Yeoju-si, Gyeonggi-do, 12658, Korea. The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22.

1.12 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
USA	**FCC**	3 & 10 meter Open Area Test Sites and one conducted site to perform FCC Part 15/18 measurements.	
JAPAN	**VCCI**	Mains Ports Conducted Interference Measurement, Telecommunication Ports Conducted Disturbance Measurement and Radiation 10 meter site, Facility for measuring radiated disturbance above 1 GHz	R-4308, C-4798, T-2311, G-914
KOREA	**MSIP**	EMI (10 meter Open Area Test Site and two conducted sites) Radio(3 & 10 meter Open Area Test Sites and one conducted site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	KR0100
Canada	**IC**	3 & 10 meter Open Area Test Sites and one conducted site	4769B-1
Europe	**CE**	EMI (10 meter Open Area Test Site and two conducted sites) Radio(3 & 10 meter Open Area Test Sites and one conducted site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	
International	**KOLAS**	EMI (10 meter Open Area Test Site and two conducted sites) Radio(3 & 10 meter Open Area Test Sites and one conducted site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	KOREA LABORATORY ACCREDITATION SCHEME KOLAS TESTING NO. 489

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

2.0 Test Regulations

The emissions tests were performed according to following regulations:

☐ **EMC – Directive 2014/30/EU**

☐ EN 61000-6-3:2011		
☐ EN 61000-6-1:2007		
☐ EN 61000-6-4:2007 +A1:2011		
☐ EN 61000-6-2:2005		
☐ EN 55011:2007 +A1:2010	☐ Group 1 ☐ Class A	☐ Group 2 ☐ Class B
☐ EN 55014-1:2006 +A2:2011		
☐ EN 55014-2:1997 +A2:2008		
☐ EN 55015:2013		
☐ EN 55032:2015	☐ Class A	☐ Class B
☐ EN 55024:2010		
☐ EN 50130-4:2011 +A1:2014		
☐ EN 61000-3-2:2014		
☐ EN 61000-3-3:2013		
☐ EN 61326-1:2013		

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

☐ **VCCI V-3 / 2015.04**	☐ Class A	☐ Class B
☐ **AS/NZS:2013**	☐ Class A	☐ Class B
☒ **47 CFR Part 15, Subpart B**		
☒ CISPR 22:2009 +A1:2010	☒ Class A	☐ Class B
☐ ANSI C63.4-2014	☐ Class A	☐ Class B
☒ **IC Regulation ICES-003 : 2016**		
☒ CAN/CSA CISPR 22-10	☒ Class A	☐ Class B
☐ ANSI C63.4-2014		

☐ **RE– Directive 2014/53/EU**

☐ EN 301 489-1 V1.9.2

- ☐ Equipment for fixed use
- ☐ Equipment for vehicular use
- ☐ Equipment for portable use

☐ EN 301 489-3 V1.6.1

☐ EN 301 489-17 V2.2.1

☐ EN 60945:2002

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

2.1 Conducted Emissions at Mains Power Ports

Test Date
N/A

Test Location
Electro wave Shieldroom

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☐	EMI Test S/W	EMC32	R & S	9.12.00	-
☐	EMI TEST RECEIVER	ESR3	R & S	101781	04, 27, 2018
☐	LISN	ENV216	R & S	101787	01, 11, 2018
☐	LISN	ESH2-Z5	R & S	100450	04, 27, 2018
☐	PULSE LIMITER	ESH3-Z2	R & S	101915	11, 27, 2018
☐	LISN	NNBM8124	SCHWARZBECK	8124-1002	08, 07, 2018
☐	LISN	NNBM8124	SCHWARZBECK	8124-1003	08, 07, 2018

Test Conditions
Temperature: ℃
Relative Humidity: % R.H.

Frequency Range of Measurement
150 ㎑ to 30 ㎒

Instrument Settings
IF Band Width: 9 ㎑

Test Results
The requirements are:

☐ PASS
☐ NOT PASS
☒ NOT APPLICABLE

Remarks
N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

2.2 Radiated Electric Field Emissions(Below 1 ㎓)

Test Date
Jan. 02, 2018

Test Location
☐ OPEN AREA TEST SITE #2 ☒ SEMI ANECHOIC CHAMBER #4(10 m)

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EP5/RE	TOYO Corporation	6.0.0	-
☒	EMI TEST RECEIVER	ESU26	R & S	100551	04, 18, 2018
☒	AMPLIFIER	SCU 01	R & S	100603	11, 27, 2018
☒	TRILOG-BROADBAND ANTENNA	VULB9163	Schwarzbeck	716	11, 28, 2018

Test Conditions
Temperature: 23,9 ℃
Relative Humidity: 41,5 % R.H.

Frequency Range of Measurement
30 ㎒ to 1 ㎓

Instrument Settings
IF Band Width: 120 ㎑

Test Results
The requirements are:

☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks
See Appendix A for test data.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

2.3 Radiated Electric Field Emissions(Above 1 ㎓)

Test Date
Jan. 03, 2018

Test Location
SEMI ANECHOIC CHAMBER #4(10 m)

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EP5/RE	TOYO Corporation	6.0.0	-
☒	EMI TEST RECEIVER	ESU26	R & S	100551	04, 17, 2018
☒	PREAMPLIFIER	8449B	AGILENT	3008A01967	05, 31, 2018
☐	ATTENUATOR	8491A	HP	32173	03, 24, 2018
☒	DOUBLE RIDGED HORN ANTENNA	SAS-571	A.H.SYSTEM,INC	781	05, 02, 2019

Test Conditions
Temperature: 24,1 ℃
Relative Humidity: 42,0 % R.H.

Frequency Range of Measurement
1 ㎓ to 6 ㎓

Instrument Settings
IF Band Width: 1 ㎒

Test Results
The requirements are:
☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks
See Appendix A for test data.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

APPENDIX A – TEST DATA

Conducted Emissions at Mains Power Ports

HOT LINE

N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

NEUTRAL LINE

N/A

◆ Calculation
QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]
QuasiPeak / CAverage : The Final Value
Reading Value : Not shown in the table.
Corr. : Correction values (LISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Radiated Electric Field Emissions(Below 1 ㎓)



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	374.886	H	60.9	-21.3	39.6	47.0	7.4	357.0	203.0	
2	374.956	V	63.1	-21.3	41.8	47.0	5.2	152.0	349.0	
3	433.520	H	52.5	-19.5	33.0	47.0	14.0	324.0	168.0	
4	800.059	V	49.3	-12.5	36.8	47.0	10.2	172.0	260.0	

♦ Calculation – SAC #4(10 m)
Result(QP) [㏈(㎶/m)] = (Reading(QP)[㏈(㎶)] + c.f[㏈(1/m)]
Margin(QP)[㏈] = Limit[㏈(㎶/m)] - Result(QP) [㏈(㎶/m)]
Reading(QP) : Reading value, Result(QP) : Reading value + Factor value
Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Radiated Electric Field Emissions(Above 1 ㎓)



Final Result

No.	Frequency [MHz]	(P)	Reading PK [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB(1/m)]	Result PK [dB(uV/m)]	Result CAV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin CAV [dB]	Height [cm]	Angle [deg]	Remark
1	1124.375	H	47.4	32.7	-5.7	41.7	27.0	76.0	56.0	34.3	29.0	100.0	135.0	
2	1124.981	V	49.6	33.8	-5.7	43.9	28.1	76.0	56.0	32.1	27.9	100.0	155.0	
3	1597.584	H	40.5	25.7	-1.2	39.3	24.5	76.0	56.0	36.7	31.5	100.0	322.0	
4	1599.992	V	44.5	29.8	-1.2	43.3	28.6	76.0	56.0	32.7	27.4	100.0	150.0	

♦ Calculation

Result(PK/CAV) [dB(μV/m)] = (Reading(PK/CAV)[dB(μV)] + c.f[dB(1/m)]

Margin(PK/CAV)[dB] = Limit[dB(μV/m)] - Result(PK/CAV) [dB(μV/m)]

Reading(PK/CAV) : Reading value, Result(PK/CAV) : Reading value + Factor value

Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Test Setup Photos and Configuration

Conducted Voltage Emissions

N/A

N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Radiated Electric Field Emissions(Below 1 ㎓)





This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Radiated Electric Field Emissions(Above 1 ㎓)





This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

EUT External Photographs

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

EUT Internal Photographs

(Internal View)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

EUT Internal View – CCD board

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Label Photographs



This device complies with part 15 of the FCC Rules. Operation in subject to the following two conditions: (1) This device Sep not cause harmful interference, and (2) this device must accept any interference received, including interference that Sep cause undesired operation.

CAN ICES-3(A) / NMB-3(A)

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.