

TEST REPORT

This laboratory is accredited by Voluntary Control Council for Interference and National Voluntary Laboratory Accreditation Program.

The tests reported herein have been performed in accordance with its terms of accreditation.

Test Report No. : LR500172302AH
Issue Date : February 21, 2023
Applied Standard : VCCI V-3/2016.11 CLASS A
Applicant Name : Hanwha Vision Co., Ltd
Product Name : LENS MODULE
Model Name : SLA-T1080F
Brand : -
Serial Number : -

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



NVLAP LAB CODE 200723-0

TABLE OF CONTENTS

<u>Text</u>	<u>Page</u>
Contents -----	2
LTA Certification -----	3
General Information -----	5
Brief Information -----	6
Test site description -----	8
Test Procedure -----	10
List of test equipment used for the test -----	13
Radiated disturbance measurement -----	14
Result & Graph	
Conducted disturbance -----	16
Result & Graph	
Conclusions -----	17
Photograph of the measurements -----	18
Photograph of the EUT -----	20

LTA Certification

Client / Manufacturer

Company name : Hanwha Vision Co., Ltd
Address : 6, Pangyo-ro 319 Beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, 13488,
KOREA
Telephone / Facsimile : +82-70-7147-8753(<http://hanhwa-security.com>)

Factory #1

Company name : HANWHA VISION VIETNAM COMPANY LIMITED
Address : Lot O-2, Que Vo Industrial Zone extended area ,Nam Son commune, Bac Ninh city,Bac Ninh province, Vietnam

Factory #2

Company name : D-TECH CO.,LTD.
Address : 173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi-do, Korea
(Suwon Industrial Complex)

Equipment Under Test (EUT)

Trade name : -
Product name : LENS MODULE
Model name : SLA-T1080F
Variant model name : -
Serial number : -
Intended environment : Residential area
Date of receipt : October 11, 2017
EUT condition : Pre-production, not damaged
Interface Ports : POE
Power Source : DC 5 V
Crystal/Oscillator(s) : -
Firmware version : XXXX

Model Description

- None

Test Performed

Test started & completed : October 27, 2017
Location : LTA Co., Ltd.

*** To be continued next page ***

Test Specification

Purpose of the test : Compliance test to the following standard
Applied standard : VCCI V-3/2016.11 CLASS A

Test Results

Measurement	Results*	Test method
Radiated disturbance	Complies	V-3/2016.11
Radiated disturbance at above 1 GHz	Not Applicable	V-3/2016.11
Conducted disturbance	Not Applicable	V-3/2016.11
Conducted disturbances at telecommunication ports	Not Applicable	V-3/2016.11

* : The compliance statement is based on nominal value only.

Laboratory's Certificate

Report number : LR500172302AH
Issue date : February 21, 2023

This test report is issued under the authority of:

The test was supervised by:



Young Kyu Shin, Technical Manager



Jong Chae Kim , Test Engineer

General information's

Purpose

This document is based on the Electromagnetic Interference (EMI) tests performed on the “SLA-T1080F”.

The measurements were performed according to the measurement procedure described in VCCI V-3/2016.11

Test Performed

Company name : LTA Co., Ltd.
 Address : 243, Jubug-ri, Yangji-Myeon, Cheoin-gu, Youngin-Si, Kyunggi-Do, Korea. 449-822
 Telephone / Facsimile : +82-31-323-6008 / +82-31-323-6010

Measurement uncertainty

Radiated disturbance (30 – 1 000 MHz) : +4.52 [dB] , -4.43 [dB] (k=2)
 Radiated disturbance at above 1 GHz (1 GHz – 6 GHz) : +3.0 [dB] , -3.0 [dB] (k=2)
 Conducted disturbance (0.15 – 30 MHz) : +0.11 [dB] , -0.11 [dB] (k=2)
 Conducted disturbances at telecommunication ports (0.15 – 30 MHz) : +0.11 [dB] , -0.11 [dB] (k=2)

The coverage factor k=2 yields approx. a 95% level of confidence for near-normal distribution typical of most measurement results.

Accredited agencies

LTA Co., Ltd. Is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	Updating	ECT accredited Lab.
RRA	KOREA	KR0049	-	EMC accredited Lab.
FCC	U.S.A	649054	2019-04-13	FCC CAB
VCCI	JAPAN	C-4948,	2020-09-10	VCCI registration
		T-2416,	2020-09-10	
		R-4483(10 m),	2020-10-15	
		G-847	2018-12-13	
IC	CANADA	5799A-1	2019-11-07	IC filing
KOLAS	KOREA	NO.551	2021-08-20	KOLAS accredited Lab.

Brief Information

1-1 Test Summary

Parameter	Applied Standard	Status (note 1)
I. Emission		
Radiated disturbance	V-3/2016.11	C
Radiated disturbance at above 1 GHz	V-3/2016.11	NA
Conducted disturbance	V-3/2016.11	C
Conducted disturbances at telecommunication ports	V-3/2016.11	C
Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable * The data in this test report are traceable to the national or international standards.		

Frequency range to be scanned:

0.15 MHz - 30 MHz as conducted measurement

30 MHz – 1 000 MHz (1 GHz) as radiated measurement

1 000 MHz(1 GHz)-1 000 MHz (1 GHz) as radiated measurement

Bandwidth:

Measured by the CISPR quasi-peak function Bandwidth is 10 kHz in the frequency 0.15 MHz to 30 MHz, 120 kHz in the frequency 30 MHz to 1,000 MHz.

A sample calculation:

COR. F (correction factor)= Antenna factor + Cable loss- Amp.gain- Distance correction

Emission Level= meter reading + COR.F

1-2 Operating Mode of the EUT

The tests have been conducted with the following operational mode(s) of the EUT.

Name of mode in the report Description

Capture mode : -

1-3 Modification

- None


1-4 List of EUT and accessory

EUT				
Category	Model Name	Serial No.	Manufacturer	Remarks
LENS MODULE	SLA-T1080F	N/A	HANWHA VISION VIETNAM COMPANY LIMITED D-TECH CO.,LTD.	-
ACCESSORY				
Category	Model Name	Serial No.	Manufacturer	Remarks
Network Camera	XNB-6001	N/A	HANWHA VISION VIETNAM COMPANY LIMITED D-TECH CO.,LTD.	-
Notebook	PP37L	N/A	DELL	-

1-5 Cable List

Cable List				
Cable Type	Length (m)	Shielding (Cable/backshell)	Remarks	
			From	to
Network Camera	8.0	NO/NO	POE	POE
Notebook	3.0	NO/NO	LAN	LAN
Adapter	1.0	NO/NO	DC IN	DC OUT
Adapter	1.5	NO/NO	DC IN	DC OUT

1-6 Block diagram of the EUT test / Capture mode




2- Test Site Description


1-Facility

All the testing facilities are periodically serviced as a daily check for equipment and cables systems, an every 6 months facility check for the facilities and a monthly check and annual calibration for testing equipment according to ISO/IEC 17025. All the testing facilities are used as the same specifications shown below. There are descriptions both for radiated disturbance measurement and conducted disturbance measurement conformed by VCCI V-3/2016.11

2-1 Radiated Disturbance Measurement – Below 1 GHz



2-2 Conducted Disturbance Measurement



2-3 Conducted Disturbances at telecommunication ports





Diagram 3 : Telecom Port Conducted Emissions Test Setup

2-4 Radiated Disturbance at above 1 GHz



3- Test Procedure

3-1 Radiated Disturbance Measurements

- Test site is met the requirements of VCCI V-3/2016.11 and the distance between the EUT and the antenna is adjusted 3 m or 10m.
- The turntable can be rotated 360 degrees.
- The antenna can be adjusted between 1m and 4m in height above the ground.
- The EUT is placed on the non-conducting table with 0.8m height on the turntable.
- Measurements are carried out using a spectrum analyzer with peak detectors (100kHz bandwidth) and an EMI receiver with quasi-peak detectors(120 kHz bandwidth).
- Refer to the list of test equipment used for the test.
- Biconical antenna and logperiodic antenna are used as wideband antenna.
- The Biconical antenna is used in the frequency range of 30 MHz to 300 MHz and the Logperiodic antenna is used in the frequency range of 300 MHz to 1 GHz.
- A variable attenuator is used for verifying amplifier's linearity.
- Rotating the turntable and adjusting the height of the antenna are carried out by control buttons on the console.
- Refer to "Brief Information"(page 6-9) about details of the EUT and configuration of the cables.
- Measurement is carried out by a LTA operator as manual operation.
 - searching for some of High disturbance frequency points than the other points with the following settings; bandwidth 100 kHz, frequency range 10 MHz between 30 MHz and 300 MHz and frequency range 50 MHz between 300 MHz and 1 GHz.
 - searching the worst direction with the maximum level of the disturbance wave in rotating the turntable 360 degrees at each searched frequency point.
 - setting the height of the antenna with the maximum level of the disturbance wave from 1m to 4 m.
 - reading the disturbance level by the EMI receiver with quasi-peak detectors (120 kHz bandwidth) according to VCCI V-3/2016.11
 - measuring to vertical and horizontal polarization.
 - calculating the measurement result with the following formula or equation:
(Measurement result= measured value + antenna factor + antenna cable loss)

3-2 Conducted Disturbance Measurements

- The measurement is carried out on an open site with horizontal and metallic ground plane.
- An AMN(Artificial Mains Network) with a nominal impedance ($50 \Omega/50 \mu\text{H}$) as defined in VCCI V-3/2016.11. shall be utilized.
- The AMN is grounded on a horizontal metal ground plane.
- Measurement is carried out using a spectrum analyzer with peak detectors (10kHz bandwidth) and an EMI receiver with quasi-peak detectors and average detector. (Refer to the List of test equipment used for the test.)
- The shortest distance between the EUT and the AMN is 0.8 m.
- The EUT is placed on the non-conducting table with 0.8 m height.
- A remote switch is used for changing phases between Line (L) and Neutral (N).
- Refer to "Brief Information"(page 6-9) about details of the EUT and configuration of the cables.
- Measurement is carried out as manual operation.
 - detecting the maximized emission level using the maxhold function after setting the spectrum analyzer bandwidth 1MHz and the frequency range from 150 kHz to 1 MHz , 1 MHz to 5 MHz and 5 MHz to 30 MHz.
 - searching the maximum frequency point of the disturbance wave in each frequency range.
 - reading the disturbance level of quasi-peak, average and Line (L) and Neutral (N) in 10 kHz bandwidth by the EMI receiver.
 - calculating the measurement result with the following formula or equation.
(Result = Reading + Cor.F.)
(Margin = Limit- Result)

3-3 Conducted Disturbances at telecommunication ports Measurements

- In the range of 0.15 MHz to 30 MHz, the conducted disturbance was measured and set-up was made accordance with VCCI V-3/2016.11, CLASS A ITE.
- The EUT is placed on a non-conducting table, which is: 0.8 meters above an earth-grounded floor; 0.4 meters away from a vertical ground plane (i.e. the chamber wall); and 0.8 meter away from all other metal objects. For cables where there is no appropriate CDN / ISN available, measurement was done using a combination of current probe and capacitive voltage probe.
- Measure current with a current probe.
 - Measure voltage with a capacitive probe
- Compare the measured voltage with the voltage limit.
- Compare the measured current with the current limit.
- The EUT shall meet both the voltage and current limits.

3-4 Radiated Disturbance at above 1 GHz

- Test site is met the requirements of VCCI V-3/2016.11 and the distance between the EUT and the antenna is adjusted 3 m.
 - The turntable can be rotated 360 degrees.
 - The antenna can be adjusted between 1m in height above the ground.
 - The EUT is placed on the non-conducting table with 1m height on the turntable.
 - Measurements are carried out using a EMI test receiver with peak detectors (1 MHz bandwidth) and an EMI receiver with peak and average detectors(1 MHz bandwidth).
 - Refer to the list of test equipment used for the test.
 - HORN antenna are used as wideband antenna.
 - The HORN antenna is used in the frequency range of 1 GHz to 18 GHz.
 - A variable attenuator is used for verifying amplifier's linearity.
 - Rotating the turntable and adjusting the height of the antenna are carried out by control buttons on the console.
 - Refer to "Brief Information"(page 6-9) about details of the EUT and configuration of the cables.
 - Measurement is carried out by a LTA operator as manual operation.
 - searching the worst direction with the maximum level of the disturbance wave in rotating the turntable 360 degrees at each searched frequency point.
 - setting the height of the antenna with the maximum level of the disturbance wave from 1m
 - reading the disturbance level by the EMI receiver with peak and average detectors (1 MHz bandwidth) according to ANSI C 63.4:2003.
 - measuring to vertical and horizontal polarization.
 - calculating the measurement result with the following formula or equation:
(Measurement result= measured value + antenna factor + antenna cable loss)

4- List of Equipment Used For the Tests

Radiated Emission – Below 1 GHz

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
☒	EMI TEST Receiver	ESCI7	Rohde & Schwarz	100772	2018.09.07	1 year
☒	Amplifier (25 dB)	8447D	HP	2944A07974	2018.09.07	1 year
☐	DTV Signal Generator	MFG-100	MFLO	15M2002	2018.03.20	1 year
☐	Color TV Pattern Generator	PM-5518-TX	Philips	LO5333	-	-
☒	TRILOG Antenna	VULB9160	SCHWARZBECK	9160-3237	2019.05.16	2 year
☒	TEST PROGRAM	e3_Ver: 6.2009-10-12a	AUDIX	-	-	-

Conducted emissions

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
☒	EMI TEST Receiver	ESR	Rohde & Schwarz	101499	2018.07.11	1 year
☒	Pulse Limiter	ESH3-Z2	Rohde & Schwarz	100710	2018.03.20	1 year
☐	ISN	ISN T800	TESEQ	27109	2018.01.25	1 year
☐	ISN	ENY81-CA6	Rohde & Schwarz	101565	2018.01.25	1 year
☒	CURRENT PROBE	EZ-17	Rohde & Schwarz	100508	2018.01.25	1 year
☐	LISN	ESH3-Z6	Rohde & Schwarz	100378	2018.09.07	1 year
☐	LISN(main)	ENV216	Rohde & Schwarz	100408	2018.09.07	1 year
☒	LISN(sub)	KNW-407	Kyoritsu	8-1430-1	2018.09.07	1 year
☒	TEST PROGRAM	e3_Ver: 5.5.201a	AUDIX	-	-	-

5-1 Radiated Disturbance Measurements (Below 1GHz) / V



4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: SLA-T1080F

Temp/Humi: 18 / 48


Test Mode : Capture mode

Tested by: KANG H J

Data: 1393

File: C:\Program Files (x86)\e3\1710-1.EM6 (1393)

Date: 2017-10-27 Time: 09:10:32



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	QP dBuV/m	dBuV/m	dB	cm	deg	
94.99	44.59	-17.36	27.23	40.00	12.77	104	59	VERTICAL
100.81	46.80	-16.24	30.56	40.00	9.44	108	86	VERTICAL
798.24	36.90	-1.06	35.84	47.00	11.16	107	98	VERTICAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

-Continue
(Below 1GHz) / H



4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

EUT/Model No.: SLA-T1080F

Temp/Humi: 18 / 48


Test Mode : Capture mode

Tested by: KANG H J

Data: 1392

File: C:\Program Files (x86)\e3\1710-1.EM6 (1392)

Date: 2017-10-27 Time: 09:08:35



Freq	Reading	C.F	Result	Limit	Margin	Height	Angle	Polarity
MHz	dBuV	dB	QP dBuV/m	dBuV/m	dB	cm	deg	
790.48	43.91	-1.18	42.73	47.00	4.27	116	102	HORIZONTAL
798.24	43.10	-1.06	42.04	47.00	4.96	109	65	HORIZONTAL
805.03	42.70	-0.96	41.74	47.00	5.26	131	74	HORIZONTAL

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

5-2 Conducted disturbance / TEL




4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel: +82-31-3236008, 9
Fax: +82-31-3236010

EUT / Model No. : SLA-T1080F	Phase : POE
Test Mode : Capture mode	Test Power : 110 / 50
Temp. / Humi. : 18 / 48	Test Engineer : KANG H J

Data: 2497

File: D:\Conducted Data\2017\LTA_Conduction_2017_10 .EM6 (2497)

Date: 2017-10-27



Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin
MHz	QP	AV	dB	QP	AV	QP	AV	QP	AV
	dBuA	dBuA		dBuA	dBuA	dBuA	dBuA	dB	dB
3.374	-10.84	-16.44	19.69	8.85	3.25	43.02	30.02	34.17	26.77
3.445	-9.94	-16.23	19.70	9.76	3.47	43.02	30.02	33.26	26.55
3.457	-10.17	-16.16	19.70	9.53	3.54	43.02	30.02	33.49	26.48
3.513	-10.81	-17.08	19.70	8.89	2.62	43.02	30.02	34.13	27.40
3.562	-11.67	-18.21	19.71	8.04	1.50	43.02	30.02	34.98	28.52
3.627	-13.21	-19.71	19.72	6.51	0.01	43.02	30.02	36.51	30.01



Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conclusions

Product models " **SLA-T1080F** " meets all of the CLASS A requirements of the VCCI V-3/2016.11
(Limits of radio disturbance characteristics of ITE).
(Refer to Test Specification and Test Results in the "LTA certification", page 4 and 5.)



Photograph of the Radiated Disturbance Measurements (Below 1GHz)



Photograph of the Conducted disturbance / TEL



Photograph of the Equipment Under Test





Photograph of the Equipment Under Test



Photograph of the Equipment Under Test



Photograph of the Equipment Under Test



Photograph of the Equipment Under Test

