

TEST REPORT

 CTK Co., Ltd. The Power Leader of Global Regulatory Certification	CTK Co., Ltd. 5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501	Report No.: CTK-2023-02842 Page (1) / (19) pages	
---	--	---	--

1. Applicant

◦ Name : Hanwha Vision Co., Ltd
◦ Address : 6 Pangyo-ro 319Beon-gil, Bundang-gu, Seongnam-si,
Gyeonggi-do, 13488 KOREA
◦ Date of Receipt : 2023-11-09

2. Manufacturer

◦ Name : HANWHA VISION VIETNAM COMPANY LIMITED
◦ Address : Lot O-2, Que Vo Industrial Zone extended area, Nam Son
ward, Bac Ninh city, Bac Ninh province, Vietnam

3. Use of Report : Quality control

4. Test sample / Model : Barcode Reader / TNS-9050IBC

5. Date(s) of test : 2023-11-13 to 2023-11-24

6. Location of Test : ☒ Permanent Testing Lab ☐ On Site Testing

Address: (5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea)

7. Test Standard (Method) used : NEMA 250-2014
Enclosures for Electrical Equipment (1000 Volts
Maximum)

8. Testing Environment : Temperature: (25.0 ± 5.0) °C
Humidity: (40.0 ± 5.0) %.

9. Test Results : Refer to each test items

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
This Test Report cannot be reproduced, except in full.

The test was conducted as one sample, and the test result does not depend on the number of
samples

Affirmation	Tested by	Technical Manager
	HyungUk Jeon (Signature)	SooChan Bae (Signature)

2023-12-15

CTK Co., Ltd



 CTK Co., Ltd. The Pioneer Leader of Global Regulatory Certification	CTK Co., Ltd. 5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501	Report No.: CTK-2023-02842 Page (2) / (19) pages	
---	---	--	--

Test item description: BARCODE READER	
Trade Mark:	
	
Manufacturer	Lot O-2, Que Vo Industrial Zone extended area, Nam Son ward, Bac Ninh city, Bac Ninh province, Vietnam
Model/Type reference:	TNS-9050IBC
Ratings:	Electrical TNS-9050IBC DC 24 V  28.6 W, DC 24 V  1.2 A) Dimension: Ø 7.97 *4 mm by 100.1 mm, Ø 9 *6 mm by 169.56mm, Ø 18.75 *3 mm by 176.6 mm, Ø 9.33 *6 mm by 175.77 mm, Ø 16 mm by 50.24 mm, Ø 18 mm by 56.52 mm, Ø 18.75 *3 mm by 37.68 mm, Ø 9.33 *6 mm by 48.67 mm, 719.8 mm , 584.4, 414 mm

List of Attachments (including a total number of pages in each attachment):	
Attachment 1: 11 pages (Construction Diagram including installation method)	
Attachment 2: 12-14 pages (Parts List)	
Attachment 3: 15-19 pages (photographs)	
Summary of testing:	
Tests performed (name of test and test clause): Clause 5.7(Hose Down Test)	Testing location: CTK Co., Ltd. 5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea

Copy of marking plate: The artwork above may be only a draft.	
제품명칭: BARCODE READER 모델명: TNS-9050IBC 정격전압: DC 24V  28.6W M/C: TNS-9050IBC/KDO Fac. ID: D DATE S/N: Serial No. MAC ADDRESS: XX-XX-XX-XX-XX-XX 인증번호: R-R-StW-TNS9050IBC 상호: 한화비전(주) 제조사/제조국가:한화비전(주)/한국 	       BARCODE READER, TNS-9050IBC DC 24V  1.2A M/C: TNS-9050IBC/KEX Fac.ID:D DATE S/N: Serial No. MAC ADDRESS: XX-XX-XX-XX-XX-XX CAN ICES-3(A)/NMB-3(A) HANWHA VISION CO.,LTD. Made in Korea    Rainproof / Étanche IP66 and IP67

 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. 5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501	Report No.: CTK-2023-02842 Page (3) / (19) pages	
---	---	--	--

Test item particulars.....: Network Camera
Classification of installation and use Outdoor (Watertight/Corrosion Resistant)
Possible test case verdicts: - test case does not apply to the test object: N/A - test object does meet the requirement.....: P (Pass) - test object does not meet the requirement: F (Fail) - test case does not evaluated to the test object : N/E

General remarks: "(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report. Throughout this report a ☐ comma / ☒ point is used as the decimal separator. Clause numbers between brackets refer to clauses in NEMA 250-2014
Name and address of factory (ies): 1. HANWHA VISION VIETNAM COMPANY LIMITED Lot O-2, Que Vo Industrial Zone extended area, Nam Son ward, Bac Ninh city, Bac Ninh province, Vietnam 2. D-TECH CO., LTD. 173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi-do, Korea (Suwon Industrial Complex) Type 4X Enclosures constructed for either indoor or outdoor use to provide a degree of protection to personnel against access to hazardous parts; to provide a degree of protection of the equipment inside the enclosure against ingress of solid foreign objects (falling dirt and windblown dust); to provide a degree of protection with respect to harmful effects on the equipment due to the ingress of water (rain, sleet, snow, splashing water, and hose directed water); that provides an increased level of protection against corrosion; and that will be undamaged by the external formation of ice on the enclosure.

Table 2-1
Comparison of Specific Applications of Enclosures for Indoor Nonhazardous (Unclassified) Locations

Provides a Degree of Protection against the Following Conditions	Type of Enclosure									
	1	2	4	4X	5	6	6P	12	12K	13
Access to hazardous parts	X	X	X	X	X	X	X	X	X	X
Ingress of solid foreign objects (falling dirt)	X	X	X	X	X	X	X	X	X	X
Ingress of water (dripping and light splashing)	...	X	X	X	X	X	X	X	X	X
Ingress of solid foreign objects (circulating dust, lint, fibers, and flyings **)	...	...	X	X	...	X	X	X	X	X
Ingress of solid foreign objects (settling airborne dust, lint, fibers, and flyings **)	...	...	X	X	X	X	X	X	X	X
Ingress of water (hosedown and splashing water)	...	...	X	X	...	X	X	...	...	...
Oil and coolant seepage	...	...	...	...	...	...	...	X	X	X
Oil or coolant spraying and splashing	...	...	...	...	...	...	...	...	...	X
Corrosive agents	...	...	...	X	...	...	X	...	...	...
Ingress of water (occasional temporary submersion)	...	...	...	...	...	X	X	...	...	...
Ingress of water (occasional prolonged submersion)	...	...	...	...	...	...	X	...	...	...

** These fibers and flyings are not considered Class III type ignitable fibers or combustible flyings. For Class III type ignitable fibers or flyings see the *National Electrical Code®*, Article 500.5(D).

Table 2-2
Comparison of Specific Applications of Enclosures for Indoor & Outdoor Nonhazardous (Unclassified) Locations

Provides a Degree of Protection Against the Following Conditions	Type of Enclosure									
	3	3X	3R	3RX	3S	3SX	4	4X	6	6P
Access to hazardous parts	X	X	X	X	X	X	X	X	X	X
Ingress of solid foreign objects (falling dirt)	X	X	X	X	X	X	X	X	X	X
Ingress of water (dripping and light splashing)	X	X	X	X	X	X	X	X	X	X
Ingress of water (rain, snow, and sleet **)	X	X	X	X	X	X	X	X	X	X
Sleet ***	...	...	...	...	X	X	...	...	...	...
Ingress of solid foreign objects (windblown dust, lint, fibers, and flyings****)	X	X	...	...	X	X	X	X	X	X
Ingress of water (hosedown and splashing water)	...	...	...	...	...	...	X	X	X	X
Corrosive agents	...	X	...	X	...	X	...	X	...	X
Ingress of water (occasional temporary submersion)	...	...	...	...	...	...	...	...	X	X
Ingress of water (occasional prolonged submersion)	...	...	...	...	...	...	...	...	...	X

** External operating mechanisms are not required to be operable when the enclosure is ice covered.

*** External operating mechanisms are operable when the enclosure is ice covered. See subsection 5.6.

**** These fibers and flyings are not considered Class III type ignitable fibers or combustible flyings. For Class III type ignitable fibers or flyings see the *National Electrical Code®*, Article 500.5(D).

Table 5-1A
Degrees of Protection Against Access to Hazardous Parts

Enclosure Type	Test Conditions	Degree of Protection		Corresponding IP First Characteristic Numeral
		Brief Description	Definition	
4X	5.7	Protected against access to hazardous parts with a wire	An access probe of 1.0 mm shall not penetrate	6

Table 5-1B
Degrees of Protection Against Solid Foreign Objects

Enclosure Type	Test Conditions	Degree of Protection		Corresponding IP First Characteristic Numeral
		Brief Description	Definition	
4X	<u>Non-vented</u> 5.7	Windblown dust protected	No ingress of dust	6
	<u>Vented</u> 5.5.1 Dust Blast Method			

Table 5-1C
Degrees of Protection against Water

Enclosure Type	Test Conditions	Degree of Protection		Corresponding IP Second Characteristic Numeral
		Brief Description	Definition	
4X	5.7	Protected against hose directed water	Water projected against the enclosure in any direction shall not enter	6 No Ingress Allowed*

Table 5-1D
Additional Protection

Enclosure Type	Test Conditions	Additional Protection		Corresponding IP Second Characteristic Numeral
		Brief Description	Definition	
4X	5.6 5.9 5.10	Special corrosion protection and undamaged by the external formation of ice	Enclosure provides increased corrosion protection and is not damaged by ice that forms on the outside	None

 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. 5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501	Report No.: CTK-2023-02842 Page (6) / (19) pages	
---	---	--	--

NEMA 250-2014

Clause	Requirement + Test	Result - Remark	Verdict
--------	--------------------	-----------------	---------

3	CONSTRUCTION		
----------	---------------------	--	--

3.1	General		P
3.2	Units of Measurement		P
3.3	Materials-General	Enclosures are made of metal or polymeric materials	P
3.4	Materials-Polymeric	More than 650 mm ² (1 in ²) in area Polymeric Materials used is declared as Min. V-2 Used to UL certified material. (See the attachment 2)	N/E
3.5	Corrosion Protection	Stainless steel and/or aluminium are declared as the materials used (See the attachment 2)	N/E
3.6	Openings	No openings in Product	N/A
3.7	Mounting	Mounting means are external to the equipment cavity (See the attachment 1)	P
3.8	Conduit Connection	No conduit connection (See the attachment 1)	N/A
3.9	Hubs and Fittings	No Hubs and Fittings	N/A
3.10	Knockouts	No Knockouts	N/A
3.11	External Operating Mechanisms	No External Operating Mechanisms	N/A
3.12	Access to Interior	Needs tool to open unit	P
3.13	Closing Hardware	No closing Hardware	N/A
3.14	Gaskets	Gaskets made of a silicone Sponge Rubber (no Elastomeric or Thermoplastic used) (See clause 5.14 and the attachment 2)	P
3.15	Observation Windows	No Observation Window	N/A

4	MARKING		
----------	----------------	--	--

 CTK Co., Ltd. The Power Leader of Global Regulatory Certification	CTK Co., Ltd. 5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501	Report No.: CTK-2023-02842 Page (7) / (19) pages	
---	--	---	--

NEMA 250-2014			
Clause	Requirement + Test	Result - Remark	Verdict
4.1	Type Designations	"Type 4X" Marking is declared to be on the product before on the market	P
4.2	Supplemental Markings	Supplemental Marking (watertight/ corrosion resistant) is declared to be used when it is on the market. The required marking shall be added on the product)	P
4.3	Location of Markings	See the Attachment 3	P
4.4	Enclosure Orientation	No Particular Mounting Orientation	N/A
4.5	Conduit Hubs and Closure Plates	No Conduit Hubs and Closure Plates	N/A
4.6	Equipment Openings	No Openings on Unit	N/A
4.7	Drainage Openings	No Drain Openings	N/A

5	DESIGN TESTS	
----------	---------------------	--

5.1	General	See Table 5-1A to 5-1D and 5.1.5 in the General product information	P
5.2	Tests For Protection Against Access to Hazardous Parts	Rated 4X	N/A
5.3	Tests for Protection Against Ingress of Water (Dripping and Light Splashing)	Rated 4X	N/A
5.4	Tests for Protection Against Ingress of Water (Rain)	Rated 4X	N/A
5.5	Tests for Protection Against Ingress of Solid Foreign Objects (Setting Airborne Dust, Lint, Fibers, And Flings)	Non-vented (See clause 5.7)	N/A
5.6	External Icing Test	No external cavities to trap water when mounted in the normal position.	N/A
5.7	Tests for Protection Against Ingress of Water (Hosedown)	No entry of water See the test information	P
5.8	Indoor Corrosion Protection (Rust-Resistance Test (24-Hour Salt Spray Test))	See clause 3.5	N/E
5.9	Outdoor Corrosion Protection	See clause 3.5	N/E
5.10	Corrosion Protection-Type 3X, 3RX, 3SX, 4X Or 6P Enclosures	See clause 3.5	N/E

 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. 5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501	Report No.: CTK-2023-02842 Page (8) / (19) pages	
---	---	--	--

NEMA 250-2014			
Clause	Requirement + Test	Result - Remark	Verdict
5.11	Test for Protection Against Ingress of Water (Temporary Submersion)	Rated 4X	N/A
5.12	Test for Protection Against Ingress of Water (Prolonged Submersion)	Rated 4X	N/A
5.13	Oil Exclusion Test	Rated 4X	N/A
5.14	GASKET MATERIAL TESTS	The product itself(including gaskets) was conditioned at 70 °C for 168 hrs according to 5.14.3(Alternate Evaluation) before performing relevant required tests.	P
5.15	Test for Sharpness of Edges	No sharp edges	P

 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. 5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501	Report No.: CTK-2023-02842 Page (9) / (19) pages	
---	--	---	--

NEMA 250-2014			
Clause	Requirement + Test	Result - Remark	Verdict

Test Information

	Hose Down Test: Clause 5.7	P
--	-----------------------------------	----------

<u>Description of Test</u> The enclosure and its external mechanisms were subjected to a stream of water from a hose that has a 25.4 mm (1 in) inside diameter nozzle and delivers at least 240 L (65 gal) per minute. The nozzle was held from 3.0 to 3.5 m (10 to 12 feet) from the enclosure, and the spray of water was directed at all points of potential water entry such as seams, joints, external operating mechanisms, and such. The nozzle was moved along each test point one time at a uniform rate of 6 mm/sec(1/4 in/sec). Sample Dimension Ø 7.97 *4 mm by 100.1 mm, Ø 9 *6 mm by 169.56mm, Ø 18.75 *3 mm by 176.6 mm, Ø 9.33 *6 mm by 175.77 mm, Ø 16 mm by 50.24 mm, Ø 18 mm by 56.52 mm, Ø 18.75 *3 mm by 37.68 mm, Ø 9.33 *6 mm by 48.67 mm, 719.8 mm , 584.4, 414 mm Test Duration = 407.8 secs <u>Acceptance conditions:</u> The enclosure shall be considered to have met the requirements if at the conclusion of the test no water has entered the enclosure <u>Test Results</u> <table border="1"> <thead> <tr> <th>Sample No (Model)</th><th>Water Flow</th><th>Presence of water inside</th><th>Result</th></tr> </thead> <tbody> <tr> <td>TNS-9050IBC</td><td>240 LPM</td><td>No</td><td>Pass</td></tr> </tbody> </table>				Sample No (Model)	Water Flow	Presence of water inside	Result	TNS-9050IBC	240 LPM	No	Pass
Sample No (Model)	Water Flow	Presence of water inside	Result								
TNS-9050IBC	240 LPM	No	Pass								


 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. 5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501	Report No.: CTK-2023-02842 Page (10) / (19) pages	
---	---	--	--

Attachment 1 – Construction Diagram and installation method

List of test equipment used:

Instr. Code	Instrument Type	Range Used	Mfr./Model	Calibration Date	
				Last	Due
S3-IP18	25.4mm Nozzle	25.4 mm	CTK/S3-IP18	-	Checked by calliper below before using
S1-SW2	Stop Watch	0.01 s	CASIO/ NONE	2022.02.22	2024.02.21
C-S1-D09	Steel Measuring Tape	5 m	KOMELON/KMC-74N	2023.02.02	2025.02.02
S3-IP23	Water flow meter	250LPM	Nuri tech/ Z-6504	2024.01.19	2024.02.12
C-S1-D02	DIGITAL VERNIER CALIPER	150 mm	MITUTOYO/150 mm	2023.07.31	2024.07.31

Attachment 1 – Construction Diagram and installation method



 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. 5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501	Report No.: CTK-2023-02842 Page (12) / (19) pages	
---	---	---	--

Attachment 2 – Parts List

NO.	자재 코드	제품/자재명	수량
1	FC15-010365A	COVER--FRONT_LED-MODULE_TNS-9050IBC;ADC1	1
2	HP07-001865A	GASKET-LED-WINDOW_TNS-9050IBC;SILICONE R	1
3	FC37-001124A	WINDOW-LED-MODULE_TNS-9050IBC;PC	1
4	AM06-011259A	ASSY,PCB-TNS-9050IBC LED	2
5	FC28-003806A	PAD-THERMAL;6X25XT1.5,7W	8
6	EP07-001988A	SINK,HEAT-LED-MODULE_TNS-9050IBC;ADC12	1
7	Z6001053501A	SCREW-MACHINE:BH,+,M3,L6,WHT,FP,NYLOCK	36
8	FC28-002549A	PAD-THERMAL-HRD-1642	1
9	HP07-001864A	GASKET-FRONT_LED-MODULE_TNS-9050IBC;SILI	1
10	AM06-011257B	ASSY,PCB-TNS-9050IBC LED DRIVER	1
11	FC15-010366A	COVER-REAR_LED-MODULE_TNS-9050IBC;ADC12,	1
12	EP02-005369A	CABLE-LED-TO-MAIN	1
13	HP06-002035	VENT-GORE_PMF100318;BLACK, MEMBRANE	1
14	FC09-016248A	BRACKET-PROFILE_INSTALL_TNS-9050IBC;T2.0	2
15	Z6006000101A	SCREW-SEMS:BH,+,M4,L8,SUS,FP,WSP	10
16	FC18-006625A	SCREW-MACHINE,SH,T20,M4,L8	12
17	FC15-010363A	COVER-LENS_TNS-9050IBC;ADC12,-,BLK	1
18	FC18-004000A	SCREW-SPECIAL:PH,TR20,M4,L7+5,SUS,FP	4
19	HP07-001861A	GASKET-WINDOW-LENS_TNS-9050IBC;SILICONE	1
20	EP14-002652A	LENS-TNS-9050IBC_WINDOW GLASS;GLASS	1
21	FC09-016246A	BRACKET-COVER-LENS_TNS-9050IBC;SECC,T1.0	1
22	HP07-001862A	GASKET-COVER-LENS_TNS-9050IBC;SILICONE R	1
23	EP14-001269	LENS-YT0W9X56-12MP_25.17MM;C	2
24	HP07-001728A	GASKET-O-RING-D1_32-D2_2.5_TNM-A49X;RUBB	2
25	FC15-010362A	COVER-FRONT_TNS-9050IBC;ADC12,-,BLK	1
26	AM06-011255A	ASSY,PCB-TNS-9050IBC SENSOR	2
27	FC18-005178A	SCREW-MACHINE;BH,M2,L4,BLK,NYLOCK	6
28	FC28-003728A	PAD-THERMAL-17X17XT6-7W	2
29	EP07-001986A	SINK,HEAT-SENSOR_TNS-9050IBC;ADC12	2
30	EP07-001987A	SINK,HEAT-MAIN_TNS-9050IBC;ADC12	1
31	AM06-011251B	ASSY,PCB-TNS-9050IBC MAIN	1
32	FC28-003418A	PAD-THERMAL-48X30XT5,K=2W/M-K	2
33	FC15-010364A	COVER-REAR_TNS-9050IBC;ACD12,BLK	1
34	FC09-016247A	BRACKET-CAMERA-INSTALL_TNS-9050IBC;T3.0	2

 CTK Co., Ltd. The Prime Leader of Global Regulatory Certification	CTK Co., Ltd. 5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Republic of Korea Tel: +82-31-339-9970 Fax: +82-31-624-9501	Report No.: CTK-2023-02842 Page (13) / (19) pages	
---	---	---	--

Attachment 2 – Parts List

35	FC18-007308A	SCREW-MACHINE	8
36	PT03-002454F	LABEL-RATING-CAMERA-KC-DO	1
37	EP02-005362A	CABLE-TNS-9050IBC MAIN TO LED;1:1,M12,R/	1
38	EP02-005363A	CABLE-CABLE-TNS-9050IBC MAIN TO RJ45;1:1	1
39	EP02-005364A	CABLE-TNS-9050IBC MAIN TO PWR;1:1,M12,R/	1



CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2023-02842
Page (15) / (19) pages

Attachment 3 – Photographs

Test Unit





CTK Co., Ltd.

5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2023-02842
Page (16) / (19) pages


Attachment 3 – Photographs

Hose down test



Attachment 3 – Photographs

Test Result






CTK Co., Ltd.


5 Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si,
Gyeonggi-do, Republic of Korea
Tel: +82-31-339-9970
Fax: +82-31-624-9501

Report No.:
CTK-2023-02842
Page (18) / (19) pages

Attachment 3 – Photographs



Attachment 3 – Photographs



-END-