

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Report No.:

KES-E1-18T0161-R1

Page (1) of (32)

# EMC TEST REPORT For VCCI

Test Report No. : KES-E1-18T0161-R1

Date of Issue : Feb. 24, 2023

Product name : Network Camera

Model/Type No. : XND-L6080RV

Variant Model : -

Applicant : Hanwha Vision Co., Ltd

Applicant Address : 6, Pangyo-ro 319Beon-gil, Bundang-gu, Seongnam-si,  
Gyeonggi-do, Republic of Korea

Manufacturer : 1. HANWHA VISION VIETNAM COMPANY LIMITED  
2. D-TECH CO.,LTD.

Manufacturer Address : 1. Lot O-2, Que Vo Industrial Zone extended area,  
Nam Son commune, Bac Ninh city, Bac Ninh province, Vietnam  
2. 173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi- do,  
Korea (Suwon Industrial Complex)

Equipment authorization : ☐ Declaration of Conformity  
☒ Verification  
☐ Certification

Date of Receipt : Feb. 01, 2018

Test date : Feb. 05, 2018 ~ Feb. 06, 2018

Test Results : ☒ In Compliance ☐ Not in Compliance

Tested by

Sung Min, Choi  
EMC Test Engineer

Reviewed by

Dong-Hun, Jang  
EMC Technical Manager

This test report is not related to KS Q ISO/IEC 17025 and KOLAS.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact kes@kes.co.kr



## REPORT REVISION HISTORY

| Date          | Test Report No.   | Revision History                                                                                               |
|---------------|-------------------|----------------------------------------------------------------------------------------------------------------|
| Feb. 12, 2018 | KES-E1-18T0161    | Issued                                                                                                         |
| Feb. 24, 2023 | KES-E1-18T0161-R1 | Change the Applicant, Applicant addresss and manufacturer, manufacturer address at the request of the customer |
|               |                   |                                                                                                                |
|               |                   |                                                                                                                |
|               |                   |                                                                                                                |
|               |                   |                                                                                                                |
|               |                   |                                                                                                                |
|               |                   |                                                                                                                |
|               |                   |                                                                                                                |
|               |                   |                                                                                                                |

***This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.***



## TABLE OF CONTENTS

|                                                      |                                                             |    |
|------------------------------------------------------|-------------------------------------------------------------|----|
| 1.0                                                  | General Product Description.....                            | 4  |
| 1.1                                                  | Test Voltage & Frequency .....                              | 7  |
| 1.2                                                  | Variant Model Differences .....                             | 7  |
| 1.3                                                  | Device Modifications .....                                  | 7  |
| 1.4                                                  | Equipment Under Test.....                                   | 7  |
| 1.5                                                  | Support Equipments .....                                    | 7  |
| 1.6                                                  | External I/O Cabling .....                                  | 8  |
| 1.7                                                  | EUT Operating Mode(s) .....                                 | 8  |
| 1.8                                                  | Configuration.....                                          | 9  |
| 1.9                                                  | Remarks when standards applied .....                        | 10 |
| 1.10                                                 | Calibration Details of Equipment Used for Measurement ..... | 10 |
| 1.11                                                 | Test Facility .....                                         | 10 |
| 1.12                                                 | Laboratory Accreditations and Listings .....                | 10 |
| 2.0                                                  | Test Regulations.....                                       | 11 |
| 2.1                                                  | Conducted Emissions Mains Power Ports.....                  | 13 |
| 2.2                                                  | Conducted Emissions at Telecommunication Ports.....         | 14 |
| 2.3                                                  | Radiated Electric Field Emissions(Below 1 GHz) .....        | 15 |
| 2.4                                                  | Radiated Electric Field Emissions(Above 1 GHz) .....        | 16 |
| APPENDIX A – TEST DATA.....                          |                                                             | 17 |
| Conducted Emissions at Mains Power Ports.....        |                                                             | 17 |
| Conducted Emissions at Telecommunication Ports ..... |                                                             | 19 |
| Radiated Electric Field Emissions(Below 1 GHz) ..... |                                                             | 21 |
| Radiated Electric Field Emissions(Above 1 GHz).....  |                                                             | 22 |
| Test Setup Photos and Configuration .....            |                                                             | 23 |
| Conducted Voltage Emissions .....                    |                                                             | 23 |
| Conducted Telecommunication Emissions .....          |                                                             | 24 |
| Radiated Electric Field Emissions(Below 1 GHz) ..... |                                                             | 25 |
| Radiated Electric Field Emissions(Above 1 GHz).....  |                                                             | 26 |
| EUT External Photographs .....                       |                                                             | 27 |
| EUT Internal Photographs .....                       |                                                             | 28 |



## 1.0 General Product Description

### Main Specifications of EUT are:

|                            | <b>XND-L6080RV</b>                                                                                                              |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <b>Video</b>               |                                                                                                                                 |
| Imaging Device             | 1/2.8" 2M CMOS                                                                                                                  |
| Total Pixels               | 1945(H) x 1109(V) 2.16M                                                                                                         |
| Effective Pixels           | 1945(H) x 1097(V) 2.13M                                                                                                         |
| Scanning System            | Progressive Scan                                                                                                                |
| Min. Illumination          | Color : 0.1 lux<br>B/W : 0Lux (IR LED On)                                                                                       |
| S / N Ratio                | 50dB                                                                                                                            |
| Video Out                  | CVBS : 1.0 Vp-p / 75Ω composite, 720x480(N), 720x576(P), for installation<br>USB : Micro USB type B, 1280x720, for installation |
| <b>Lens</b>                |                                                                                                                                 |
| Focal Length (Zoom Ratio)  | 3.2~10mm(3.1x) motorized varifocal                                                                                              |
| Max. Aperture Ratio        | 1.6                                                                                                                             |
| Angular Field of View      | H : 109.0°(Wide) ~ 33.2°(Tele) / V : 57.4°(Wide) ~ 18.7°(Tele) / D : 132.0°(Wide) ~ 38.0°(Tele)                                 |
| Min. Object Distance       | 0.5m (1.64ft)                                                                                                                   |
| Focus Control              | Simple focus(Motorized V/F) / Manual, Remote control via network<br>(Manual, Simple focus)                                      |
| Lens Type                  | DC Auto Iris                                                                                                                    |
| Mount Type                 | Board-in type                                                                                                                   |
| <b>Pan / Tilt / Rotate</b> |                                                                                                                                 |
| Pan / Tilt / Rotate range  | 0° ~ 354° / 0° ~ 67° / 0° ~ 355°                                                                                                |

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Report No.:

KES-E1-18T0161-R1

Page (5) of (32)

| Operational                 |                                                                                                                                                                                                                                                                    |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IR Viewable Length          | 30m(98.4ft)                                                                                                                                                                                                                                                        |
| Camera Title                | Off / On (Displayed up to 85 characters)<br>- WW : English/Numeric/Special Characters<br>- China : English/Numeric/Special/Chinese Characters<br>- Common : Multi-line (Max 5), Color (Grey/Green/Red/Blue/Black/White),<br>Transparency, Auto Scale by Resolution |
| Day & Night                 | Auto (ICR) / Color / B/W / External / Schedule                                                                                                                                                                                                                     |
| Backlight Compensation      | Off / BLC / HLC(Masking/Dimming), WDR                                                                                                                                                                                                                              |
| Wide Dynamic Range          | 120dB                                                                                                                                                                                                                                                              |
| Contrast Enhancement        | SSDR (Off / On)                                                                                                                                                                                                                                                    |
| Digital Noise Reduction     | SSNR5 (2D+3D Noise Filter) (Off / On)                                                                                                                                                                                                                              |
| Digital Image Stabilization | Off / On                                                                                                                                                                                                                                                           |
| Defog                       | Auto(input from fog detection) / Manual / Off                                                                                                                                                                                                                      |
| Motion Detection            | Off/ On(8ea, 8point Polygonal zones), Handover                                                                                                                                                                                                                     |
| Privacy Masking             | Off / On (32ea, polygonal zones)<br>- Color : Grey/Green/Red/Blue/Black/White<br>- Mosaic                                                                                                                                                                          |
| Gain Control                | Off / Low / Middle / High                                                                                                                                                                                                                                          |
| White Balance               | ATW / AWC / Manual / Indoor / Outdoor((included Mercury & Sodium)                                                                                                                                                                                                  |
| Contrast                    | level adjustment                                                                                                                                                                                                                                                   |
| LDC                         | On/Off (5 levels with Min/Max)                                                                                                                                                                                                                                     |
| Electronic Shutter Speed    | Minimum / Maximum / Anti flicker (2 ~ 1/12,000sec)                                                                                                                                                                                                                 |
| Digital PTZ                 | 24X, 'Digital PTZ(Preset, Group)                                                                                                                                                                                                                                   |
| Flip / Mirror               | Flip : On/Off<br>Mirror : On/Off<br>Hallway view : 90°/270°                                                                                                                                                                                                        |
| Video & Audio Analytics     | Tampering, Loitering, Directional Detection, Defocus Detection, Fog Detection, Virtual Line, Enter/Exit, (Dis)Appear, Face Detection, Motion Detection, Digital auto tracking                                                                                      |
| Alarm I/O                   | No                                                                                                                                                                                                                                                                 |
| Alarm Triggers              | Motion Detection, Video Analytics, , Network Disconnect                                                                                                                                                                                                            |
| Alarm events                | File upload via FTP, E-Mail<br>Notification via E-Mail<br>local storage(SD/SDHC/SDXC) or NAS recording at Event Triggers                                                                                                                                           |
| Audio In                    | No                                                                                                                                                                                                                                                                 |
| Audio out                   | No                                                                                                                                                                                                                                                                 |
| Pixel Counter               | Support                                                                                                                                                                                                                                                            |

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact kes@kes.co.kr



**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Report No.:

KES-E1-18T0161-R1

Page (6) of (32)

|                                  |                                                                                                                                                                                                                          |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Network</b>                   |                                                                                                                                                                                                                          |
| Ethernet                         | RJ-45 (10/100BASE-T)                                                                                                                                                                                                     |
| Video Compression Form           | H.265/H.264 (MPEG-4 Part 10/AVC) : Main/Baseline/High , Motion JPEG                                                                                                                                                      |
| Resolution                       | 1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240                                                                                                        |
| Max. Framerate                   | H.265/H.264 : Max. 60fps at all resolutions<br>Motion JPEG : Max. 30fps                                                                                                                                                  |
| Smart Codec                      | Manual Mode (area-based : 5EA)                                                                                                                                                                                           |
| WiseStream II                    | Support                                                                                                                                                                                                                  |
| Video Quality Adjustment         | H.264/H.265 : Target Bitrate Level Control<br>MJPEG : Target Bitrate Level Control                                                                                                                                       |
| Bitrate Control Method           | H.264/H.265 : CBR or VBR<br>MJPEG : VBR                                                                                                                                                                                  |
| Streaming Capability             | Multiple Streaming (Up to 5 Profiles)                                                                                                                                                                                    |
| Audio Compression Form           | No                                                                                                                                                                                                                       |
| Audio Communication              | No                                                                                                                                                                                                                       |
| IP                               | IPv4, IPv6                                                                                                                                                                                                               |
| Protocol                         | TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour                                          |
| Security                         | HTTPS(SSL) Login Authentication<br>Digest Login Authentication<br>IP Address Filtering<br>User access Log<br>802.1X Authentication (EAP-TLS, EAP-LEAP)                                                                   |
| Streaming Method                 | Unicast / Multicast                                                                                                                                                                                                      |
| Max. User Access                 | 20 users at Unicast Mode                                                                                                                                                                                                 |
| Edge Storage                     | SD/SDHC/SDXC 1slot (up to 256 GB)<br>- Motion Images recorded in the SD/SDHC/SDXC memory card can be downloaded.<br>NAS(Network Attached Storage)<br>Local PC for Instant Recording                                      |
| Application Programming          | ONVIF Profile S/G<br>SUNAPI(HTTP API)<br>Open Platform                                                                                                                                                                   |
| Webpage Language                 | English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Swedish, Portuguese, Czech, Polish, Turkish, Dutch, Hungarian, Greek                                                                      |
| Web Viewer                       | Supported OS: Windows 7, 8.1, 10, Mac OS X 10.10, 10.11, 10.12<br><b>Non-plugin Webviewer</b><br>Supported Browser: Google Chrome 54, MS Edge 38, Mozilla Firefox 49(Window 64bit only) , Apple Safari 9 (Mac OS X only) |
| Central Management Soft          | SmartViewer, SSM                                                                                                                                                                                                         |
| <b>Environmental</b>             |                                                                                                                                                                                                                          |
| Operating Temperature / Humidity | -10°C ~ +55°C (-14°F ~ +131°F) / Less than 90% RH                                                                                                                                                                        |
| Storage Temperature / Humidity   | -50°C ~ +60°C (-22°F ~ +140°F) / Less than 90% RH                                                                                                                                                                        |
| Vandal Resistance                | IK08                                                                                                                                                                                                                     |
| <b>Electrical</b>                |                                                                                                                                                                                                                          |
| Input Voltage / Current          | PoE                                                                                                                                                                                                                      |
| Power Consumption                | Max 8W                                                                                                                                                                                                                   |
| <b>Mechanical</b>                |                                                                                                                                                                                                                          |
| Color / Material                 | Ivory / Aluminum                                                                                                                                                                                                         |
| Dimension (WxHxD)                | Ø 140.8 X 113.0mm(Ø5.54" x 4.45")                                                                                                                                                                                        |
| Weight                           | 724g(1.60lb)                                                                                                                                                                                                             |

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact kes@kes.co.kr



## 1.1 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

Voltage ☐ 230 Vac ☐ 100 Vac ☐ 24 Vac ☐ 5 Vdc ☒ PoE

Frequency ☐ 50 Hz ☐ 60 Hz ☐ Hz

## 1.2 Variant Model Differences

Not applicable

## 1.3 Device Modifications

Not applicable

## 1.4 Equipment Under Test

| Description    | Model Number | Serial Number | Manufacturer                                | Remarks |
|----------------|--------------|---------------|---------------------------------------------|---------|
| Network Camera | XND-L6080RV  | -             | HANWHA VISION<br>VIETNAM COMPANY<br>LIMITED | EUT     |

## 1.5 Support Equipments

| Description       | Model Number  | Serial Number   | Manufacturer                              | Remarks |
|-------------------|---------------|-----------------|-------------------------------------------|---------|
| PoE Adapter       | POE 36U-1AT-R | P90215791A1     | PHIHONG                                   | -       |
| Notebook Computer | NT-R410Y      | Z9YJ93CS300631H | SAMSUNG                                   | -       |
| Adapter           | AD-6019       | -               | LI SHIN INTERNATIONAL<br>ENTERPRISE CORP. | -       |



## 1.6 External I/O Cabling

### ■ PoE Mode

| Start                |             | END         |             | Cable Spec. |        |
|----------------------|-------------|-------------|-------------|-------------|--------|
| Description          | I/O Port    | Description | I/O Port    | Length      | Shield |
| Network Camera (EUT) | RJ-45(POE)  | POE Adaptor | RJ-45(POE)  | 3.2         | U      |
| Notebook Computer    | RJ-45(DATA) | POE Adaptor | RJ-45(DATA) | 3.2         | U      |

\* Unshielded=U, Shielded=S

## 1.7 EUT Operating Mode(s)

| Test mode | operating                 |
|-----------|---------------------------|
| POE       | EUT Monitoring, Ping Test |


| EUT Test operating S/W |         |                        |
|------------------------|---------|------------------------|
| Name                   | Version | Manufacture Company    |
| WebViewer              | -       | Hanwha Vision Co., Ltd |



## 1.8 Configuration

■ AC Main

□ DC Main



## 1.9 Remarks when standards applied

N/A

## 1.10 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less.

## 1.11 Test Facility

The measurement facility is located at 473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, 12658, Korea, Republic of. The sites are constructed in conformance with the requirements of ANSI C63.4a-2017 and CISPR 16-1-4:2019

## 1.12 Laboratory Accreditations and Listings

| Country       | Agency  | Scope of Accreditation                                                                                                                  | Logo                                                                                                                           |
|---------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| KOREA         | RRA     | EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site)<br>EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions) | <br>KR0100                                 |
| International | KOLAS   | EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site)<br>EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions) | <br>KT489                                 |
| USA           | FCC     | 3 m & 10 m Semi-Anechoic Chamber<br>Conducted test site to perform FCC Part 15/18 measurements.                                         | <br>KR0100                                |
| Canada        | ISED    | 3 m & 10 m Semi-Anechoic Chamber and Conducted test site                                                                                | <br>23298                                 |
| JAPAN         | VCCI    | EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site)                                                                          | <br>C-20136, T-20137,<br>R-20181, G-20176 |
| Europe        | TÜV SÜD | EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site)<br>EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions) | <br>CARAT 001633 0004                     |



## 2.0 Test Regulations

The emissions tests were performed according to following regulations:

☐ **EMC – Directive 2014/30/EU**

☐ EN 61000-6-3:2011

☐ EN 61000-6-1:2007

☐ EN 61000-6-4:2007 +A1:2011

☐ EN 61000-6-2:2005

☐ EN 55011:2007 +A1:2010

☐ Group 1  
☐ Class A

☐ Group 2  
☐ Class B

☐ EN 55014-1:2006 +A2:2011

☐ EN 55014-2:1997 +A2:2008

☐ EN 55015:2013

☐ EN 61547 :2009

☐ EN 55032:2015

☐ Class A

☐ Class B

☐ EN 55024:2010 +A1:2015

☐ EN 50130-4:2011 +A1:2014

☐ EN 61000-3-2:2014

☐ EN 61000-3-3:2013

☐ EN 61326-1:2013



# KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Report No.:

KES-E1-18T0161-R1

Page (12) of (32)

☒ **VCCI V-3 / 2015.04**

☒ Class A

☐ Class B

☐ **AS/NZS CISPR22:2009 +A1:2010**

☐ Class A

☐ Class B

☐ **47 CFR Part 15, Subpart B**

☐ CISPR 22:2009 +A1:2010

☐ Class A

☐ Class B

☐ ANSI C63.4-2009

☐ **IC Regulation ICES-003 : 2016**

☐ CAN/CSA CISPR 22-10

☐ Class A

☐ Class B

☐ ANSI C63.4-2014

☐ **RE- Directive 2014/53/EU**

☐ EN 301 489-1 V1.9.2

☐ Equipment for fixed use

☐ Equipment for vehicular use

☐ Equipment for portable use

☐ EN 301 489-3 V1.6.1

☐ EN 301 489-17 V2.2.1

☐ EN 60945:2002

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact kes@kes.co.kr

**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Report No.:

KES-E1-18T0161-R1

Page (13) of (32)

## 2.1 Conducted Emissions Mains Power Ports

**Test Date**

N/A

**Test Location**

Electro wave Shieldroom #6

**Test Equipment**

| Used                     | Description       | Model Number | Manufacturer | Serial Number | Cal. Due     |
|--------------------------|-------------------|--------------|--------------|---------------|--------------|
| <input type="checkbox"/> | EMI Test S/W      | EMC32        | R & S        | 9.12.00       | -            |
| <input type="checkbox"/> | EMI TEST RECEIVER | ESR3         | R & S        | 101781        | 04, 27, 2018 |
| <input type="checkbox"/> | LISN              | ENV216       | R & S        | 101787        | 01, 05, 2019 |
| <input type="checkbox"/> | LISN              | ESH2-Z5      | R & S        | 100450        | 04, 27, 2018 |
| <input type="checkbox"/> | PULSE LIMITER     | ESH3-Z2      | R & S        | 101915        | 11, 27, 2018 |
| <input type="checkbox"/> | LISN              | NNBM8124     | SCHWARZBECK  | 8124-1002     | 08, 07, 2018 |
| <input type="checkbox"/> | LISN              | NNBM8124     | SCHWARZBECK  | 8124-1003     | 08, 07, 2018 |

**Test Conditions**

Temperature:

°C

Relative Humidity:

% R.H.

**Frequency Range of Measurement**

150 kHz to 30 MHz

**Instrument Settings**

IF Band Width: 9 kHz

**Test Results**

The requirements are:

- ☐ PASS  
☐ NOT PASS  
☒ NOT APPLICABLE

**Remarks**N/A : Because the EUT power is PoE, limits are not specified.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact kes@kes.co.kr

## 2.2 Conducted Emissions at Telecommunication Ports

### Test Date

Feb. 05, 2018

### Test Location

Electro wave Shieldroom #6

### Test Equipment

| Used                                | Description       | Model Number | Manufacturer | Serial Number | Cal. Due     |
|-------------------------------------|-------------------|--------------|--------------|---------------|--------------|
| <input checked="" type="checkbox"/> | EMI Test S/W      | EMC32        | R & S        | 9.12.00       | -            |
| <input checked="" type="checkbox"/> | EMI TEST RECEIVER | ESR3         | R & S        | 101781        | 04, 27, 2018 |
| <input checked="" type="checkbox"/> | LISN              | ENV216       | R & S        | 101787        | 01, 05, 2019 |
| <input checked="" type="checkbox"/> | LISN              | ESH2-Z5      | R & S        | 100450        | 04, 27, 2018 |
| <input checked="" type="checkbox"/> | PULSE LIMITER     | ESH3-Z2      | R & S        | 101915        | 11, 27, 2018 |
| <input checked="" type="checkbox"/> | 8-WIRE ISN CAT3,5 | ENY81        | R & S        | 100174        | 01, 07, 2019 |
| <input type="checkbox"/>            | 8-WIRE ISN CAT6   | ENY81-CAT6   | R & S        | 101665        | 01, 07, 2019 |
| <input type="checkbox"/>            | ISN               | ISN S8       | SCHWARZBECK  | ISN-S8-0019   | 05, 12, 2018 |
| <input type="checkbox"/>            | CDN               | CDNS502A     | TESEQ        | 40431         | 01, 05, 2019 |

### Test Conditions

Temperature: 22,0 °C  
Relative Humidity: 41,7 % R.H.

### Frequency Range of Measurement

150 kHz to 30 MHz

### Instrument Settings

IF Band Width: 9 kHz

### Test Results

The requirements are:

- ☒ PASS  
☐ NOT PASS  
☐ NOT APPLICABLE

### Remarks

See Appendix A for test data.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact kes@kes.co.kr





## 2.3 Radiated Electric Field Emissions(Below 1 GHz)

### Test Date

Feb. 06, 2018

### Test Location

☐ OPEN AREA TEST SITE #2 ☒ SEMI ANECHOIC CHAMBER #4(10m)

### Test Equipment

| Used                                | Description              | Model Number | Manufacturer     | Serial Number | Cal. Due     |
|-------------------------------------|--------------------------|--------------|------------------|---------------|--------------|
| <input checked="" type="checkbox"/> | EMI Test S/W             | EP5/RE       | TOYO Corporation | 6.0.0         | -            |
| <input checked="" type="checkbox"/> | EMI TEST RECEIVER        | ESU26        | R & S            | 100551        | 04, 18, 2018 |
| <input checked="" type="checkbox"/> | AMPLIFIER                | SCU 01       | R & S            | 100603        | 11, 27, 2018 |
| <input checked="" type="checkbox"/> | TRILOG-BROADBAND ANTENNA | VULB9163     | Schwarzbeck      | 716           | 11, 28, 2018 |

### Test Conditions

Temperature: 19,2 °C  
Relative Humidity: 43,6 % R.H.

### Frequency Range of Measurement

30 MHz to 1 GHz

### Instrument Settings

IF Band Width: 120 kHz

### Test Results

The requirements are:

☒ PASS  
☐ NOT PASS  
☐ NOT APPLICABLE

### Remarks

See Appendix A for test data.

## 2.4 Radiated Electric Field Emissions(Above 1 GHz)

**Test Date**

Feb. 06, 2018

**Test Location**

SEMI ANECHOIC CHAMBER #3

**Test Equipment**

| Used                                | Description                | Model Number | Manufacturer     | Serial Number | Cal. Due     |
|-------------------------------------|----------------------------|--------------|------------------|---------------|--------------|
| <input checked="" type="checkbox"/> | EMI Test S/W               | EP5/RE       | TOYO Corporation | 6.0.0         | -            |
| <input checked="" type="checkbox"/> | EMI TEST RECEIVER          | ESR7         | R & S            | 101190        | 08, 07, 2018 |
| <input checked="" type="checkbox"/> | PREAMPLIFIER               | 8449B        | AGILENT          | 3008A01967    | 05, 31, 2018 |
| <input type="checkbox"/>            | ATTENUATOR                 | 8491A        | HP               | 32173         | 03, 24, 2018 |
| <input checked="" type="checkbox"/> | DOUBLE RIDGED HORN ANTENNA | SAS-571      | A.H.SYSTEM,INC   | 781           | 05, 02, 2019 |

**Test Conditions**

Temperature: 20,9 °C

Relative Humidity: 46,3 % R.H.

**Frequency Range of Measurement**

1 GHz to 6 GHz

**Instrument Settings**

IF Band Width: 1 MHz

**Test Results**

The requirements are:

- ☒ PASS  
☐ NOT PASS  
☐ NOT APPLICABLE

**Remarks**See Appendix A for test data.



**KES Co., Ltd.**

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Report No.:

KES-E1-18T0161-R1

Page (17) of (32)

---

## **APPENDIX A – TEST DATA**

### **Conducted Emissions at Mains Power Ports**

HOT LINE

N/A

---

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact kes@kes.co.kr



## KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Report No.:

KES-E1-18T0161-R1

Page (18) of (32)

---

### NEUTRAL LINE

N/A

#### ◆ Calculation

QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]

QuasiPeak / CAverage : The Final Value

Reading Value : Not shown in the table.

Corr. : Correction values (LISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

---


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact kes@kes.co.kr

## Conducted Emissions at Telecommunication Ports

■ POE Mode  
**[10 Mbps]**

### Common Information

Test Description: Telecommunication Emission  
 Model No.: XND-L6080RV  
 Mode: LAN\_10M  
 Operator Name: KES




### Final Result

| Frequency (MHz) | QuasiPeak (dBμV) | CAverage (dBμV) | Limit (dBμV) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Line        | Corr. (dB) |
|-----------------|------------------|-----------------|--------------|-------------|-----------------|-----------------|-------------|------------|
| 0.320000        | ---              | 50.37           | 77.71        | 27.34       | 1000.0          | 9.000           | Single Line | 19.4       |
| 0.320000        | 53.94            | ---             | 90.71        | 36.77       | 1000.0          | 9.000           | Single Line | 19.4       |
| 0.930000        | ---              | 48.01           | 74.00        | 25.99       | 1000.0          | 9.000           | Single Line | 19.7       |
| 0.930000        | 51.38            | ---             | 87.00        | 35.62       | 1000.0          | 9.000           | Single Line | 19.7       |
| 3.955000        | ---              | 51.15           | 74.00        | 22.85       | 1000.0          | 9.000           | Single Line | 19.5       |
| 3.955000        | 54.74            | ---             | 87.00        | 32.26       | 1000.0          | 9.000           | Single Line | 19.5       |
| 29.235000       | ---              | 63.32           | 74.00        | 10.68       | 1000.0          | 9.000           | Single Line | 20.6       |
| 29.235000       | 66.97            | ---             | 87.00        | 20.03       | 1000.0          | 9.000           | Single Line | 20.6       |

## [100 Mbps]

### Common Information

|                   |                            |
|-------------------|----------------------------|
| Test Description: | Telecommunication Emission |
| Model No.:        | XND-L6080RV                |
| Mode              | LAN_100M                   |
| Operator Name:    | KES                        |



### Final Result

| Frequency (MHz) | QuasiPeak (dBμV) | CAverage (dBμV) | Limit (dBμV) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Line        | Corr. (dB) |
|-----------------|------------------|-----------------|--------------|-------------|-----------------|-----------------|-------------|------------|
| 0.320000        | ---              | 49.59           | 77.71        | 28.12       | 1000.0          | 9.000           | Single Line | 19.3       |
| 0.320000        | 51.00            | ---             | 90.71        | 39.71       | 1000.0          | 9.000           | Single Line | 19.3       |
| 1.265000        | ---              | 39.60           | 74.00        | 34.40       | 1000.0          | 9.000           | Single Line | 19.7       |
| 1.265000        | 43.02            | ---             | 87.00        | 43.98       | 1000.0          | 9.000           | Single Line | 19.7       |
| 3.005000        | ---              | 41.49           | 74.00        | 32.51       | 1000.0          | 9.000           | Single Line | 19.7       |
| 3.005000        | 46.27            | ---             | 87.00        | 40.73       | 1000.0          | 9.000           | Single Line | 19.7       |
| 28.685000       | ---              | 55.75           | 74.00        | 18.25       | 1000.0          | 9.000           | Single Line | 20.4       |
| 28.685000       | 59.24            | ---             | 87.00        | 27.76       | 1000.0          | 9.000           | Single Line | 20.4       |

#### ◆ Calculation

QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]

QuasiPeak / CAverage : The Final Value

Reading Value : Not shown in the table.

Corr. : Correction values (ISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))



## KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr


Report No.:

KES-E1-18T0161-R1

Page (21) of (32)

## Radiated Electric Field Emissions(Below 1 GHz)

### ■ POE Mode



### Final Result

| No. | Frequency<br>[MHz] | (P) | Reading<br>QP<br>[dB(uV)] | c.f<br>[dB(1/m)] | Result<br>QP<br>[dB(uV/m)] | Limit<br>QP<br>[dB(uV/m)] | Margin<br>QP<br>[dB] | Height<br>[cm] | Angle<br>[deg] | Remark |
|-----|--------------------|-----|---------------------------|------------------|----------------------------|---------------------------|----------------------|----------------|----------------|--------|
| 1   | 47.096             | V   | 50.9                      | -28.3            | 22.6                       | 40.0                      | 17.4                 | 400.0          | 75.0           |        |
| 2   | 136.094            | V   | 61.0                      | -32.5            | 28.5                       | 40.0                      | 11.5                 | 100.0          | 279.0          |        |
| 3   | 325.001            | V   | 63.9                      | -24.1            | 39.8                       | 47.0                      | 7.2                  | 100.0          | 118.0          |        |
| 4   | 374.956            | V   | 62.9                      | -22.3            | 40.6                       | 47.0                      | 6.4                  | 100.0          | 195.0          |        |
| 5   | 450.010            | H   | 61.3                      | -20.3            | 41.0                       | 47.0                      | 6.0                  | 200.0          | 102.0          |        |
| 6   | 624.974            | H   | 50.9                      | -15.8            | 35.1                       | 47.0                      | 11.9                 | 200.0          | 18.0           |        |

### ◆ Calculation

Corrected Amplitude [dBuV] = Amplitude[dBuV] + Correction Factor [dB]

Corrected Amplitude : The Final Value, Amplitude : Reading Value,

Correction Factor : ANT FACTOR + Cable loss

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.


The authenticity of the test report, contact kes@kes.co.kr





## Radiated Electric Field Emissions(Above 1 GHz)

### ■ POE Mode



#### Final Result

| No. | Frequency [MHz] | (P) | Reading PK [dB(uV)] | Reading CAV [dB(uV)] | c.f [dB(1/m)] | Result PK [dB(uV/m)] | Result CAV [dB(uV/m)] | Limit PK [dB(uV/m)] | Limit AV [dB(uV/m)] | Margin PK [dB] | Margin CAV [dB] | Height [cm] | Angle [deg] | Remark |
|-----|-----------------|-----|---------------------|----------------------|---------------|----------------------|-----------------------|---------------------|---------------------|----------------|-----------------|-------------|-------------|--------|
| 1   | 1375.170        | V   | 66.7                | 48.5                 | -6.8          | 59.9                 | 41.7                  | 76.0                | 56.0                | 16.1           | 14.3            | 101.0       | 113.5       |        |
| 2   | 1441.431        | V   | 64.8                | 44.4                 | -6.3          | 58.5                 | 38.1                  | 76.0                | 56.0                | 17.5           | 17.9            | 101.0       | 144.1       |        |
| 3   | 1895.467        | V   | 57.6                | 40.3                 | -2.1          | 55.5                 | 38.2                  | 76.0                | 56.0                | 20.5           | 17.8            | 101.0       | 270.3       |        |
| 4   | 2066.139        | V   | 48.4                | 32.3                 | -1.1          | 47.3                 | 31.2                  | 76.0                | 56.0                | 28.7           | 24.8            | 101.0       | 348.3       |        |
| 5   | 2753.830        | V   | 51.4                | 33.3                 | 1.9           | 53.3                 | 35.2                  | 76.0                | 56.0                | 22.7           | 20.8            | 101.0       | 319.2       |        |

### ◆ Calculation

Result(PK/CAV) [dB( $\mu$ V/m)] = (Reading(PK/CAV)[dB( $\mu$ V)] + c.f[dB(1/m)])

Margin(PK/CAV)[dB] = Limit[dB( $\mu$ V/m)] - Result(PK/CAV) [dB( $\mu$ V/m)]

Reading(PK/CAV) : Reading value, Result(PK/CAV) : Reading value + Factor value

Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamplifier Factor), Margin: Margin value



## KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,  
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea  
Tel: +82-31-425-6200 / Fax: +82-31-424-0450  
www.kes.co.kr

Report No.:

KES-E1-18T0161-R1

Page (23) of (32)

---

## Test Setup Photos and Configuration

### Conducted Voltage Emissions

N/A

N/A

---

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact kes@kes.co.kr

## Conducted Telecommunication Emissions



### ■ POE Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact kes@kes.co.kr

## adiated Electric Field Emissions(Below 1 GHz)


### ■ POE Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact kes@kes.co.kr

## Radiated Electric Field Emissions(Above 1 GHz)

### ■ POE Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact kes@kes.co.kr



## **EUT External Photographs**

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact kes@kes.co.kr

## EUT Internal Photographs

(Internal View)



## EUT Internal View – Main board

(Top)



(Bottom)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact kes@kes.co.kr




## EUT Internal View – Sensor board

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact kes@kes.co.kr

**EUT Internal View – LED board**

(Top)



(Bottom)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact kes@kes.co.kr

## EUT Internal View – Lens

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.  
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
The authenticity of the test report, contact kes@kes.co.kr