



TEST REPORT



Report No. : KES-EM250228

Page 1 / 56

KES Co., Ltd.

#3002, #3503, #3701, 40, Simin-daero365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Republic of Korea
Tel : +82-31-425-6200, Fax : +82-31-341-3838

1. Client

Applicant : Hanwha Vision Co., Ltd

Applicant Address : 6, Pangyo-ro 319Beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, Republic of Korea

2. Sample Description

Product name : NETWORK CAMERA

Model/Type No. : XNO-A8084R

Variant Model : -

Manufacturer : 1. HANWHA VISION VIETNAM COMPANY LIMITED
2. D-TECH CO.,LTD.

Manufacturer Address : 1. Lot O-2, Que Vo Industrial Zone extended Area, Nam Son Ward, Bac Ninh City, Bac Ninh Province, Vietnam
2. 173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi- do, Korea (Suwon Industrial Complex)

3. Date of Receipt : Jan. 20, 2025

4. Test date : Jan. 24, 2025 ~ Jan. 26, 2025

5. Date of Issue : Feb. 24, 2025

6. Test Results : In Compliance

Tested by

Reviewed by

Eun Gu, Jeon
EMC Test Engineer

Dong Hun, Jang
EMC Technical Manager

This test report is not related to KS Q ISO/IEC 17025 and KOLAS.

**REPORT REVISION HISTORY**

Date	Test Report No.	Revision History
Feb. 24, 2025	KES-EM250228	Issued

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.





TABLE OF CONTENTS

1.0	General Product Description.....	4
1.1	Test Voltage & Frequency.....	6
1.2	Variant Model Differences.....	6
1.3	Device Modifications.....	6
1.4	Equipment Under Test.....	6
1.5	Support Equipments.....	6
1.6	External I/O Cabling.....	7
1.7	EUT Operating Mode(s).....	7
1.8	Configuration.....	8
1.9	Remarks when standards applied.....	9
1.10	Calibration Details of Equipment Used for Measurement.....	9
1.11	Test Facility.....	9
1.12	Laboratory Accreditations and Listings.....	10
2.0	Test Regulations.....	11
2.1	Conducted Emissions at Mains Power Ports.....	12
2.2	Conducted Emissions at Telecommunication Ports.....	13
2.3	Radiated Electric Field Emissions(Below 1 GHz).....	14
2.4	Radiated Electric Field Emissions(Above 1 GHz).....	15
2.5	Harmonic Current Emissions.....	16
2.6	Voltage Fluctuations and Flicker.....	17
3.0	Criteria for compliance.....	18
3.1	Electrostatic Discharge.....	20
3.2	Radiated Electric Field Immunity.....	23
3.3	Electrical Fast Transients/Bursts.....	26
3.4	Surge Transients.....	28
3.5	Conducted Disturbance.....	31
3.6	Voltage Dips and Short Interruptions.....	33
APPENDIX A – TEST DATA.....		35
Conducted Emissions at Mains Power Ports.....		35
Conducted Emissions at Telecommunication Ports.....		37
Radiated Electric Field Emissions(Below 1 GHz).....		38
Radiated Electric Field Emissions(Above 1 GHz).....		39
Harmonic Current Emissions and Voltage Fluctuations and Flicker.....		40
Test Setup Photos and Configuration.....		43
Conducted Emissions at Mains Power Ports.....		43
Conducted Emissions at Telecommunication Ports.....		44
Radiated Electric Field Emissions(Below 1 GHz).....		45
Radiated Electric Field Emissions(Above 1 GHz).....		46
Harmonic Current Emissions and Voltage Fluctuations and Flicker.....		47
Electrostatic Discharge.....		48
Radiated Electric Field Immunity.....		48
Electrical Fast Transients/Bursts.....		49
Surge Transients.....		49
Conducted Disturbance.....		50
Voltage Dips and Short Interruptions.....		50
EUT External Photographs.....		51
EUT Internal Photographs.....		52



1.0 General Product Description

Main Specifications of EUT are:

Division		Specificity
Internal highest clock frequency		3 200 MHz
Power	Rated Power	PoE
	Test Power	AC 230 V, 50 Hz
Ports	I/O Port	RJ-45(PoE) 1 EA, Micro SD Slot 1 EA, ALARM AUDIO 1 EA
	Unused Port	USB C Type 1 EA
Components		EUT 1 EA, ALARM AUDIO Cable 1 EA
Ethernet Speed		100 Mbps

Video			
Imaging Device	1/2.8" CMOS		
Resolution	2560x1920, 2560x1440, 1920x1080, 1600x1200, 1280x960, 1280x720, 1024x768, 800x600, 640x480, 640x360, 320x240, 320x180		
Max. Framerate	H.265/H.264: Max. 30fps/25fps(60Hz/50Hz) MPEG: Max. 30fps(@5MP Max. 5fps)		
NETD	None	Analytics	Classified object type: Person/Face/Vehicle(Type: car/bus/truck/motorcycle/bicycle)/License plate Attributes: Person(Gender, Clothing top/bottom color, Bag), Face(Age, Gender, Mask, Glasses), Vehicle(Type: car/bus/truck/motorcycle/bicycle, Color) Support BestShot Support Re-ID(Person)
Pixel Size	None		Analytics events based on AI engine - Motion detection, Object detection, Virtual line(Crossing/Direction), Virtual area(Lottering/Intrusion/Enter/Exit/Appear/Disappear), Slip & fall detection, Face mask detection, Social distancing detection, Sound classification(To be released)
Video Out	USB: Micro USB Type C for installation		
Video Transmission Distance	None		
Lens			
Focal Length (Zoom Ratio)	3.3~9.3mm(2.8x) motorized varifocal		Analytics events - Defocus detection, Tampering, Shock detection, Audio detection
Optical Zoom	None	Business Intelligence	Based on AI engine: People/Vehicle/Crowd counting, Queue management, Heatmap
Max. Aperture Ratio	F1.3(Wide)~F2.3(Tele)	Serial Interface	None
Min. Object Distance	0.5m(1.64ft)	Alarm I/O	2 configurable I/O ports *Support extra alarm I/O via optional I/O box
Focus Control	Simple focus, manual	Alarm Triggers	Analytics, Network disconnection, Alarm input, Time schedule, MQTT subscription, Day/Night, Storage disruption
Lens Type	P-iris(IR corrected)		When alarm trigger occurred - File upload(image): e-mail/FTP/SFTP - File upload(video clip): FTP/SFTP - Notification: e-mail - Recording: SD/SDHC/SDXC or NAS recording at event triggers - Alarm output - Handover: PTZ preset, send message by HTTP/HTTPS/TCP - Audio clip playback(WAV, MP3) - MQTT: publication - SIP: call generation
Mount Type	None	Alarm Events	
Optional Lens	None		
Pan / Tilt / Rotate			
Pan / Tilt / Rotate Range	0°~360° / 0°~90° / 0°~360°		
Pan Range	None		
Pan Speed	None		
Tilt Range	None		
Tilt Speed	None		
Rotate Range	None		
Sequence	None	Audio Streaming	None
Preset Accuracy	None	Audio In	Selectable(mic in/line in)
Operational		Audio Out	Line out
Camera Title	Displayed up to 85 characters	Light Type	IR LED
Direction Indicator	None	Light Viewable Length	WiseIR 40m(131.23ft)
Day & Night	Auto(ICR)	IR Viewable Length	None
Backlight Compensation	BLC, HLC, WDR, SDR	IR Illuminator (Optional)	None
Wide Dynamic Range	120dB	IR Radiation angle	None
Digital Noise Reduction	SSNR V, WiseNR II (Based on AI engine)	IR LED	None
Digital Image Stabilization	Support	IR Wavelength	850nm
Defog	Support	IR Operation	None
Motion Detection	Bea, 8point polygonal zones	Water Removal	None
Gain Control	Off / Max Gain / Manual	Auto Tracking	None
White Balance	ATW / NarrowATW / AWC / Manual / Indoor / Outdoor	Coaxial Protocol	None
LDC	Support(Fill/Stretch mode)	Color Palettes	None
Digital PTZ	None	Radiometry	
Video Rotation	Flip, mirror, hallway view(90°/270°)	Temperature Detect Range	None
		Temperature Accuracy	None
		Temperature Detection	None
		Additional	None



Report No. : KES-EM250228

Network		Mechanical	
Ethernet	Metal shielded RJ-45(10/100BASE-T)	Color / Material	White / Aluminum Hard-coated window Recycled plastic: 77%
Video Compression	H.265/H.264: Main/Baseline/High MJPEG	RAL Code	RAL9003
Audio Compression	G.711(PCM): 8kHz(64Kbps)	Product Dimensions / Weight	ø93.4x276.6mm(3.68x10.89"), 1630g(3.59lb)
	G.726(ADPCM): 8kHz(16/24/32/40Kbps)	Compatible Conduit hole / Gang	Single, double, 4" octagon, 4" square
	AAC-LC: 16kHz(48Kbps)		
	OPUS: 48kHz(64Kbps)		
Smart Codec	WiseStream(Based on AI engine)	Certifications & Standards	
Video Quality Adjustment	None	Network	None
Bitrate Control	H.264/H.265: CBR or VBR MJPEG: VBR	EMC	FCC 47 CFR 15 Subpart B Class A ICES-3(A)/NMB-3(A) CE/UKCA - EN 55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3 VCCI CISPR 32 Class A RCM AS/NZS CISPR 32 Class A KS C 9832 Class A, KS C 9835
Streaming	Unicast(20 users) / Multicast Multiple streaming(Up to 5 profiles, 3 virtual channel support)		
Protocol	IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP/SFTP, SMTP(StartTLS), ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTPTCP, UDP Unicast), CDP, MQTT, Syslog, SIP		
SIP support (VoIP, Peer-to-peer, Security)	Support None	Safety	UL 62368-1, CAN/CSA C22.2 NO. 62368-1 IEC/EN 62471
Application Programming Interface	ONVIF Profile S/G/T/M SUNAPI(HTTP API) Hanwha Vision Open Platform	Environment	IEC/EN 60529 IP66/IP67, IEC/EN 62262 IK10, NEMA 250 Type 4X, NEMA-TS 2(2.2.7.2-8, 2.2.8, 2.2.9) IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78
Security		Video	None
OS / Firmware Protect	Encrypted Firmware, Secure boot, Signed Firmware	Compatible Models	
User authentication	Digest Authentication, Prevent brute-force attack	Hanging Adaptor	SBP-160HMMW1
Network authentication	802.1X Authentication(EAP-TLS, EAP-LEAP, EAP-PEAP MSCHAPv2)	Back Box	Included
Secure Communication	HTTPS, SRTP, WSS(Websocket secure)	Ceiling Mount (Assy)	SBP-150CMI, SBP-300CMI, SBP-300CMW1, SBP-900CMW, SBP-300CMTW, SBP-300CMTS
Access Control	IP-based access control, MAC-based access control, Auto logout	Ceiling Mount (Single Unit)	SBP-180CMB, SBP-140CMB, SBP-180CMS, SBP-900CMP, SBP-300CMP, SBP-150CMP, SBP-C15P, SBP-C15H
Data Protect	Encryption Credentials, Encrypt compress for live recording file export	Wall Mount	SBP-160WMW1, SBP-400WMW, SBP-250WMW, SBP-300WMW, SBP-300WMW1
Audit	Access / System / Event Log management	Wall Mount Adaptor	None
Device ID	Device Certificate(Hanwha vision Root CA)	Pole Mount	SBP-180PMW, SBP-300PMW2
Secure Storage	Secure element, SDcard partition encrypt	In-ceiling Mount	None
General		Corner Mount	SBP-156KMW, SBP-300KMW1, SBP-180KMA
Webpage Language	English, Korean, Simplified Chinese, Traditional Chinese, French, Italian, Spanish, German, Japanese, Russian, Portuguese, Czech, Polish, Turkish, Dutch, Hungarian, Greek	Parapet Mount	SBP-156LMW1, SBP-300LMW
Web Viewer	None	Tilt Mount	None
Edge Storage	Micro SD/SDHC/SDXC 1slot 1TB	Cabinet	SBP-150NBW, SBP-300NBW
Memory	4GB RAM, 8GB eMMC	Housing	None
Environmental & Electrical		Gang Plate	None
Operating Temperature / Humidity	-40°C~+60°C(-40°F~+140°F) +74°C(+165°F)(MAX) based on NEMA-TS 2(2.2.7) * Start up should be done at above -30°C 0~100%RH(Condensing) Humidity control with AIR vent	Skin Cover	None
		Weather Cap	None
		Dome Cover	None
Storage Temperature / Humidity	-50°C~+60°C(-58°F~+140°F) / 0~90% RH	Conduit Adaptor	SBP-0608A
Wind Load	None	Power Module	None
Certification	IP66/IP67, NEMA4X, IK10, NEMA-TS 2(2.2.7.2-8, 2.2.8, 2.2.9)	Interface Box	SPM-4210
Input Voltage	PoE(IEEE802.3af, Class3)	Other Compatible Models	SPP-C7400, SBP-115PFA
Power Consumption	PoE: Max. 12.95W		



1.1 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

☒ AC 230 V 50 Hz

1.2 Variant Model Differences

Not applicable

1.3 Device Modifications

Not applicable

1.4 Equipment Under Test

Description	Model Number	Serial Number	Manufacturer	Remarks
NETWORK CAMERA	XNO-A8084R	-	HANWHA VISION VIETNAM COMPANY LIMITED	EUT

1.5 Support Equipments

Description	Model Number	Serial Number	Manufacturer	Remarks
PoE Injector	PT-PSE109GBRO-AH	-	Dongguan PROCET Network Technology Co.,Ltd	-
Laptop	P95G001	9JM8HT2	DELL INC.	-
Laptop Adapter	HA65NM130	-	Chicony Power Technology(Suzhou)Co.,Ltd	-
Micro SD Card	-	-	-	-
Headset	K550	-	Britz®	-
Alarm	-	-	-	-
Button Alarm	-	-	-	-



1.6 External I/O Cabling

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
NETWORK CAMERA (EUT)	RJ-45 (PoE)	PoE Injector	RJ-45 (PoE)	3.1	U
	Micro SD Slot	Micro SD Card	Micro SD Slot	-	-
	ALARM AUDIO (SPEAKER)	Headset	Line	1.8	U
	ALARM AUDIO (MIC)				
	ALARM AUDIO (ALARM IN)	Alarm	Line	3.1	U
	ALARM AUDIO (ALARM OUT)	Button Alarm	Line	3.1	U
PoE Adapter	RJ-45 (LAN)	Laptop	RJ-45 (LAN)	1.8	U
Laptop	DC Jack	Laptop Adapter	Line	1.2	U

* Unshielded=U, Shielded=S


1.7 EUT Operating Mode(s)

Test mode	Normal operating
Operating	- Check the network behavior of the EUT with the laptop's ping test - View images of the camera through the Web Viewer - Insert 1 kHz tone through the web viewer to see if the sound is output to the headset - Enable the MIC through the Web Viewer to check the operation of the headset microphone - After testing, check the recording with Micro SD Card

EUT Test operating S/W		
Name	Version	Manufacture Company
Web Viewer	-	HANWHA VISION VIETNAM COMPANY LIMITED



1.8 Configuration





1.9 Remarks when standards applied

USB C Type Port is not tested because it is for unused port.



1.10 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less.

1.11 Test Facility

The measurement facility is located at 473-21, Gayeo-ro, Yeoju-si, Gyeonggi-do, 12658, Korea, Republic of. The sites are constructed in conformance with the requirements of ANSI C63.4a-2017 and CISPR 16-1-4:2019



1.12 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
KOREA	RRA	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KR0100
International	KOLAS	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KT489
USA	FCC	3 m & 10 m Semi-Anechoic Chamber Conducted test site to perform FCC Part 15/18 measurements.	 KR0100
Canada	ISED	3 m & 10 m Semi-Anechoic Chamber and Conducted test site	 23298
JAPAN	VCCI	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site)	 C-20136, T-20137, R-20181, G-20176
Europe	TÜV SÜD	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 CARAT 001633 0008



2.0 Test Regulations

The emissions tests were performed according to following regulations:

☒ **EMC – Directive 2014/30/EU**

☒ EN 55032:2015/A11:2020

☒ Class A

☐ Class B

☒ EN 50130-4:2011/A1:2014

☐ EN IEC 61000-3-2:2019

☐ EN 61000-3-3:2013/A2:2021

☒ **EMC – Regulations 2016**

☒ EN 55032:2015/A11:2020

☒ Class A

☐ Class B

☒ EN 50130-4:2011/A1:2014

☐ EN IEC 61000-3-2:2019

☐ EN 61000-3-3:2013/A2:2021



2.1 Conducted Emissions at Mains Power Ports

Test Date

N/A

Test Location

Electro wave Shieldroom #6

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☐	EMI Test SW	EMC32	R & S	9.12.00	-
☐	EMI TEST RECEIVER	ESR3	R & S	101783	11, 06, 2025
☐	LISN	ENV216	R & S	101786	01, 09, 2026
☐	ARTIFICIAL MAINS NETWORK	ESH2-Z5	R & S	100450	11, 06, 2025
☐	PULSE LIMITER	ESH3-Z2	R & S	101915	11, 06, 2025

Test Conditions

Temperature:

°C

Relative Humidity:

% R.H.

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Results

The requirements are:

- ☐ PASS
☐ NOT PASS
☒ NOT APPLICABLE

Remarks

The LAN port is regarded as a wired communication network port and power-related ports are not tested.



2.2 Conducted Emissions at Telecommunication Ports

Test Date

Jan. 25, 2025

Test Location

Electro wave Shieldroom #6

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EMC32	R & S	9.12.00	-
☒	EMI TEST RECEIVER	ESR3	R & S	101783	11, 06, 2025
☒	LISN	ENV216	R & S	101786	01, 09, 2026
☒	ARTIFICIAL MAINS NETWORK	ESH2-Z5	R & S	100450	11, 06, 2025
☒	PULSE LIMITER	ESH3-Z2	R & S	101915	11, 06, 2025
☒	8-WIRE ISN CAT3,5	ENY81	R & S	100174	11, 12, 2025

Test Conditions

Temperature: (23,6 ± 0,1) °C
Relative Humidity: (46,2 ± 0,1) % R.H.

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

RemarksSee Appendix A for test data.



2.3 Radiated Electric Field Emissions(Below 1 GHz)

Test Date

Jan. 25, 2025

Test Location☒ SEMI ANECHOIC CHAMBER #4(10m)**Test Equipment**

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EP5/RE	TOYO Corporation	6.0.0	-
☒	EMI TEST RECEIVER	ESU26	R & S	100551	02, 13, 2025
☒	AMPLIFIER	SCU 01	R & S	100603	11, 06, 2025
☒	BILOG ANTENNA	VULB 9168	SCHWARZBECK	9168-461	05, 09, 2026
☒	ATTENUATOR	6806.17.A	HUBER+SUHNER	-	02, 13, 2025

Test Conditions

Temperature: (22,7 ± 0,1) °C

Relative Humidity: (46,0 ± 0,1) % R.H.

Frequency Range of Measurement

30 MHz to 1 GHz

Instrument Settings

IF Band Width: 120 kHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

RemarksSee Appendix A for test data.



2.4 Radiated Electric Field Emissions(Above 1 GHz)

Test Date

Jan. 26, 2025

Test Location

SEMI ANECHOIC CHAMBER #5

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test SW	ES10/RE	TOYO Corporation	2022.01.000	-
☒	EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100552	02, 13, 2025
☒	HORN ANTENNA	BBHA 9120D	SCHWARZBECK	9120D-1802	11, 04, 2025
☒	PREAMPLIFIER	8449B	HP	3008A00538	04, 30, 2025
☒	ATTENUATOR	8491B	HP	23094	02, 13, 2025

Test Conditions

Temperature: (22,7 ± 0,1) °C

Relative Humidity: (45,8 ± 0,1) % R.H.

Frequency Range of Measurement

1 GHz to 6 GHz

Instrument Settings

IF Band Width: 1 MHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

RemarksSee Appendix A for test data.



2.5 Harmonic Current Emissions

Test Date

N/A

Test Location

Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☐	EMI Test S/W	net.control	EM TEST	2.1.4	-
☐	DIGITAL POWER ANALYZER	DPA 500N	EM TEST	V1024106759	03, 28, 2025
☐	POWER SOURCE	ACS 500N6	EM TEST	V1024106760	-

Test Conditions

Temperature:

°C

Relative Humidity:

% R.H.

Classification of Equipment for Harmonic Current Emissions

- ☒ Class A
- ☐ Class B
- ☐ Class C(Below 25 W)
- ☐ Class C(Above 25 W)
- ☐ Class D

Test Results

The requirements are:

- ☐ PASS
- ☐ NOT PASS
- ☒ NOT APPLICABLE

Remarks

The LAN port is regarded as a wired communication network port and power-related ports are not tested.



2.6 Voltage Fluctuations and Flicker

Test Date

N/A

Test Location

Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☐	EMI Test SW	net.control	EM TEST	2.1.4	-
☐	DIGITAL POWER ANALYZER	DPA 500N	EM TEST	V1024106759	03, 28, 2025
☐	POWER SOURCE	ACS 500N6	EM TEST	V1024106760	-

Test Conditions

Temperature:

°C

Relative Humidity:

% R.H.

Test Results

The requirements are:

- ☐ PASS
☐ NOT PASS
☒ NOT APPLICABLE

Remarks

The LAN port is regarded as a wired communication network port and power-related ports are not tested.



3.0 Criteria for compliance

Criteria for compliance was based on the following guidelines:

EN 50130-4:2011/A1 :2014 Alarm systems-Part 4: Electromagnetic compatibility Product family standard:

Immunity requirements for components of fire, intruder and social alarm systems

The variety and the diversity of the apparatus within the scope of this document makes it difficult to define precise criteria for the evaluation of the immunity test results.

If as a result of the application of the tests defined in this standard, the apparatus

becomes dangerous or unsafe then the apparatus shall be deemed to have failed the test.

A functional description and a definition of performance by the manufacture and noted in the test report, based on the following criteria:

Electrostatic discharge

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing that is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change.

Radiated electromagnetic fields

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing which could be interpreted by associated equipment as a change, and no such

Flickering of indicators occurs at a field strength of 3 V/m .

For components of CCTV systems, where the picture is allowed at 10 V/m , providing.

(a) there is no permanent damage or change to EUT

(e.g. no corruption of memory or changes to programmable setting etc.)

(b) at 3 V/m , any deterioration of the picture is so minor that the system could still be used; and

(c) there is no observable deterioration of the picture at 1 V/m .



Fast transient burst / slow high energy voltage surge

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing

That there is no residual is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change.

Conducted RF immunity

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the application of discharge is permissible, providing

That there is no residual is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change, and no such flickering of indicators oeuvres at $U = 130 \text{ dB}\mu\text{V}$.

For component of CCTV systems, where the status is monitored by observing the TV picture, then deterioration of the picture is allowed at $U = 140 \text{ dB}\mu\text{V}$, providing:

- (a) there is no permanent damage or change to the EUT
(e.g. no corruption of memory or changes to programmable settings etc.)
- (b) at $U = 130 \text{ dB}\mu\text{V}$, any deterioration of the picture is so minor that the system could still be used; and
- (c) there in no observable deterioration of the picture at $U = 120 \text{ dB}\mu\text{V}$.

Voltage dip/interruption / Voltage variation

There shall be no damage, malfunction or change of status due to the conditioning.

Flickering of an indicator during the conditioning is permissible, providing that there is no residual change in the EUT or any change in outputs, which could be interpreted by associated equipment as a change. The EUT shall meet the acceptance criteria for the functional test, after the conditioning.



3.1 Electrostatic Discharge

Reference Standard

EN 61000-4-2

Test Date

Jan. 26, 2025

Test Location

EMS-ESD: Electro wave Shieldroom #6

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	ESD SIMULATOR	ESS-2000	Noise Ken	ESS01Z0454	01, 21, 2026
☒	HCP	-	KES	-	-
☒	VCP	-	Noise Ken	-	-

Test Conditions

Temperature: (23,1 ± 0,1) °C
Relative Humidity: (46,1 ± 0,1) % R.H.
Atmospheric Pressure: (100,1 ± 0,1) kPa

Test Specifications

Discharge Factor: ≥ 1 s

Discharge Impedance: 330 ohm / 150 pF

Kind of Discharge: Air, Contact (direct and indirect)

Polarity: Positive and Negative

Number of Discharge: 10 at all locations for Air discharge
10 at all locations for Contact discharge



Discharge Voltage:	Contact	Air	HCP	VCP
	☐ 2 kV	☒ 2 kV	☐ 2 kV	☐ 2 kV
	☐ 4 kV	☒ 4 kV	☐ 4 kV	☐ 4 kV
	☒ 6 kV	☐ 6 kV	☒ 6 kV	☒ 6 kV
	☐ 8 kV	☒ 8 kV	☐ 8 kV	☐ 8 kV
	☐ 15 kV	☐ 15 kV	☐ 15 kV	☐ 15 kV

Notes: HCP: Horizontal coupling plane
VCP: Vertical coupling plane

Required Performance Criteria: ☒ Complied



Location of Discharge:



**Test Data**

No.	Test Point	Discharge Method	Observations	Remarks
1	HCP Contact	Contact Discharge	Complied	-
2	VCP Contact	Contact Discharge	Complied	-

Direct Discharge

No.	Test Point	Discharge Method	Observations	Remarks
1	Enclosure 1	Air Discharge	Complied	-
2	Enclosure 2, Screw	Contact Discharge	Complied	-
3	Port	Contact Discharge	Complied	-

Note: "Blank" = Not performed

Observations:

Complied – No degradation of function

Test Results

- ☒ PASS Required Performance Criteria
☐ NOT PASS Required Performance Criteria

Remarks

PASS Required Performance Criteria



3.2 Radiated Electric Field Immunity

Reference Standard

EN IEC 61000-4-3

Test Date

Jan. 24, 2025

Test LocationEMS-RS: ☐ SEMI ANECHOIC CHAMBER #2☒ SEMI ANECHOIC CHAMBER #3**Test Equipment**

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMS Test S/W	EMC32	R & S	10.10.02	-
☒	SIGNAL GENERATOR	SMB 100A	Rohde & Schwarz	108252	07, 29, 2025
☒	HIGH POWER DUAL AMP	SSA532	SUNGSAN	SSA532-001	-
☒	POWER METER	E4419B	Agilent	GB40203000	02, 13, 2025
☒	AVERAGE POWER SENSOR	E9301A	Agilent	MY52170007	02, 13, 2025
☒	AVERAGE POWER SENSOR	E9301A	Agilent	MY41498669	02, 13, 2025
☒	STACKED DOUBLE LOG-PER- ANTENNA	STPL9128 E	Schwarzbeck	9128ES-121	-
☒	DOUBLE RIDGED HORN ANTENNA	SAS-571	A.H.SYSTEM,INC	781	03, 05, 2025

Test Conditions

Temperature: (23,3 ± 0,1) °C
Relative Humidity: (45,9 ± 0,1) % R.H.
Atmospheric Pressure: (100,9 ± 0,2) kPa



Test Specifications

Antenna Polarization: Horizontal & vertical unless indicated otherwise

Antenna Distance: ☒ 3 m

Field Strength: ☐ 1 V/m ☐ 3 V/m
☒ 10 V/m

Frequency Range: ☐ 80 MHz to 1 GHz ☐ 1,4 GHz to 2,7 GHz
☒ 80 MHz to 2,7 GHz

Modulation: ☒ AM, 80 %, 1 kHz sine wave
☒ PM, 1 Hz (0,5 s ON : 0,5 s OFF)

Frequency step: ☒ 1 % step

Dwell Time: ☐ 1 s ☒ 3 s

of Sides Radiated: ☒ 4

Required Performance Criteria: ☒ Complied

**Test Data**

Side Exposed	Observations	
	Horizontal	Vertical
Front	Complied	Complied
Right	Complied	Complied
Back	Complied	Complied
Left	Complied	Complied

Note: "Blank" = Not performed

Observations:

Complied – No degradation of function

Test Results

- ☒ PASS Required Performance Criteria
☐ NOT PASS Required Performance Criteria

Remarks

PASS Required Performance Criteria



3.3 Electrical Fast Transients/Bursts

Reference Standard

EN 61000-4-4

Test Date

Jan. 26, 2025

Test Location

EMS-EFT: Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMS Test S/W	iec.control	EM TEST	5.4.8	-
☒	ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	11, 06, 2025
☒	MOTOR VARIAC	MV2616	EM TEST	P1552169719	11, 07, 2025
☒	CAPACITIVE COUPLING CLAMP	HFK	EM TEST	P1633183115	11, 06, 2025

Test Conditions

Temperature: (23,2 ± 0,1) °C
Relative Humidity: (46,0 ± 0,1) % R.H.
Atmospheric Pressure: (100,2 ± 0,1) kPa

Test Specifications

Pulse Amplitude & Polarity:
(AC Power Lines) ☐ ± 1.0 kV ☐ ± 2.0 kV
☐ ± 4.0 kV

Pulse Amplitude & Polarity:
(Other supply / Signal Lines) ☐ ± 0.5 kV ☒ ± 1.0 kV
☐ ± 2.0 kV

Burst Period: ☒ 300 ms ☐ 2 s

Repetition Rate: ☐ 5 kHz ☒ 100 kHz

Duration of Test Voltage: ☒ ≥ 1 min

Required Performance Criteria: ☒ Complied

**Test Data**☐ Input a.c. power ports – Coupling/Decoupling Network used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
-	-	-

☐ Input d.c. power ports – Coupling/Decoupling Network used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
-	-	-

☒ Signal ports and telecommunication ports – Coupling Clamp used

Mode of Application	Observations	
	(+) Burst (kV)	(-) Burst (kV)
RJ-45 (PoE)	Complied	Complied
ALARM AUDIO (ALARM IN, ALARM OUT)	Complied	Complied

Note: “Blank” = Not performed

Observations:

Complied – No degradation of function

Test Results

- ☒ PASS Required Performance Criteria
☐ NOT PASS Required Performance Criteria

RemarksPASS Required Performance Criteria



3.4 Surge Transients

Reference Standard

EN 61000-4-5

Test Date

Jan. 26, 2025

Test Location

EMS-Surge: Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMS Test S/W	iec.control	EM TEST	5.4.8	-
☒	ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	11, 07, 2025
☒	MOTOR VARIAC	MV2616	EM TEST	P1552169719	11, 07, 2025
☒	CDN	CNV 508N1	EM TEST	P1610176296	11, 08, 2025

Test Conditions

Temperature: (23,2 ± 0,1) °C
Relative Humidity: (46,0 ± 0,1) % R.H.
Atmospheric Pressure: (100,2 ± 0,1) kPa



Test Specifications

AC Power Lines

Source Impedance: 12 ohm for common Mode and 2 ohm for differential Mode

Surge Amplitude :

Common Mode

☐ (0,5 / 1,0 / 2,0) kV

Differential Mode

☐ (0,5 / 1,0) kV

Number of Surges:

☐ 5 surges per angle

Angle:

☐ 0°, 90°, 180°, 270° (input a.c. power port)

Polarity:

☐ Positive & Negative

Repetition Rate:

☐ 1 surge per min ☐ 1 surge per 30 sec.

Required Performance Criteria:

☐ Complied

Other supply / Signal Lines

Source Impedance:

42 ohm for common Mode

Surge Amplitude:

Common Mode

☒ (0,5 / 1,0) kV

Number of Surges:

☒ 5 Surges

Polarity:

☒ Positive & Negative

Repetition Rate:

☐ 1 surge per min ☒ 1 surge per 30 sec.

Required Performance Criteria:

☒ Complied

**Test Data**☐ Line to Line – Differential Mode

Mode of Application	Observations	
	(+) Surge (kV)	(-) Surge (kV)
-	-	-

☐ Line to Earth – Common Mode

Mode of Application	Observations	
	(+) Surge (kV)	(-) Surge (kV)
-	-	-

Signal Lines☒ Line to Earth – Common Mode

Mode of Application	Coupling Method	Observations	
		(+) Surge (kV)	(-) Surge (kV)
RJ-45(PoE)	CDN	Complied	Complied
	LINE	Complied	Complied

Note: "Blank" = Not performed

Observations:

Complied – No degradation of function

Test Results

- ☒ PASS Required Performance Criteria
☐ NOT PASS Required Performance Criteria

RemarksPASS Required Performance Criteria



3.5 Conducted Disturbance

Reference Standard

EN 61000-4-6

Test Date

Jan. 25, 2025

Test Location

EMS-CS: Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMS Test S/W	icd.control	EM TEST	7.2.0	-
☒	TEST SYSTEM FOR CONDUCTED AND RADIATED	NSG4070	TESEQ	65585	11, 18, 2025
☒	ATTENUATOR	ATT 6/80	EM TEST	P1614178148	11, 06, 2025
☒	CDN	CDN M016	TESEQ	43694	11, 07, 2025
☒	CDN	CDN M016	TESEQ	43697	11, 07, 2025
☒	CDN	CDN T8RJ45	EM TEST	0909-09	07, 29, 2025
☒	EM CLAMP	KEMZ 801A	TESEQ	44099	11, 08, 2025

Test Conditions

Temperature: (23,5 ± 0,1) °C
Relative Humidity: (46,3 ± 0,1) % R.H.
Atmospheric Pressure: (100,2 ± 0,1) kPa

Test Specifications

Frequency range: ☒ 150 kHz to 100 MHz ☐ 150 kHz to 80 MHz

Voltage Level: ☐ 1 Vrms ☐ 3 Vrms
☒ 10 Vrms

Modulation: ☒ AM, 80 %, 1 kHz sine wave
☒ PM, 1 Hz (0,5 s ON : 0,5 s OFF)

Frequency step: ☒ 1 % step

Dwell Time: ☐ 1 s ☒ 3 s

Required Performance Criteria: ☒ Complied

**Test Data**☐ Input a.c. power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
-	-	-

☐ Input d.c. power ports

Coupling Location (Line Stressed)	Coupling Method	Observations
-	-	-

☒ Signal ports and telecommunication ports

Coupling Location (Line Stressed)	Coupling Method	Observations
RJ-45 (PoE)	CDN	Complied
ALARM AUDIO (ALARM IN, ALARM OUT)	Clamp	Complied

Notes: CDN = Coupling Decoupling Network
"blank" = Not performed

Observations:

Complied – No degradation of function

Test Results☒ PASS Required Performance Criteria☐ NOT PASS Required Performance Criteria**Remarks**

PASS Required Performance Criteria



3.6 Voltage Dips and Short Interruptions

Reference Standard

EN IEC 61000-4-11

Test Date

N/A

Test Location

EMS-Voltage dip: Electro wave Shieldroom #7

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☐	EMS Test S/W	iec.control	EM TEST	5.4.8	-
☐	ULTRA COMPACT SIMULATOR	UCS 500N7	EM TEST	P1608172950	11, 07, 2025
☐	MOTOR VARIAC	MV2616	EM TEST	P1552169719	11, 07, 2025

Test Conditions

Temperature:

°C

Relative Humidity:

% R.H.

Atmospheric Pressure:

kPa

**Test Specifications & Observations/Remarks****- Voltage Dips and Short Interruptions**

<u>Test Level</u>	<u>Duration [in period/ms (50 Hz)]</u>	<u>Results</u>
☐ 20 % dip	☐ 250 / 5 000	<u>N/A</u>
☐ 30 % dip	☐ 25 / 500	<u>N/A</u>
☐ 60 % dip	☐ 10 / 200	<u>N/A</u>
☐ 100 % dip	☐ 250 / 5 000	<u>N/A</u>

- Voltage variations

☐ Unom + 10 %	☐ 253.0 V (ac)	<u>N/A</u>
☐ Unom - 15 %	☐ 195.5 V (ac)	<u>N/A</u>

Observations:

Complied – No degradation of function

Degradation - See "Remarks "

Test Results

- ☐ PASS Required Performance Criteria
☐ NOT PASS Required Performance Criteria
☒ NOT APPLICABLE

Remarks

The LAN port is regarded as a wired communication network port and power-related ports are not tested.



APPENDIX A – TEST DATA

Conducted Emissions at Mains Power Ports

[HOT]

N/A



[NEUTRAL]

N/A

◆ Calculation

QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]


QuasiPeak / CAverage : The Final Value

Reading Value : Not shown in the table.

Corr. : Correction values (LISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

**Conducted Emissions at Telecommunication Ports****[100 Mbps]****Common Information**

Test Description: Telecommunication Emission
Job No.: KES-EM250228
Mode :
Speed : 100 Mbps
Operator Name: KES

**Final_Result**

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.835000	---	59.19	74.00	14.81	1000.0	9.000	Single Line	19.5
0.835000	60.48	---	87.00	26.52	1000.0	9.000	Single Line	19.5
1.355000	---	64.27	74.00	9.73	1000.0	9.000	Single Line	19.5
1.355000	67.59	---	87.00	19.41	1000.0	9.000	Single Line	19.5
8.020000	---	60.41	74.00	13.59	1000.0	9.000	Single Line	19.6
8.020000	63.84	---	87.00	23.16	1000.0	9.000	Single Line	19.6
8.960000	---	59.26	74.00	14.74	1000.0	9.000	Single Line	19.6
8.960000	64.29	---	87.00	22.71	1000.0	9.000	Single Line	19.6


◆ Calculation

QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]

QuasiPeak / CAverage : The Final Value

Reading Value : Not shown in the table.

Corr. : Correction values (ISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

**Radiated Electric Field Emissions(Below 1 GHz)****Final Result**

No.	Frequency [MHz]	(P)	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	77.166	H	53.4	-25.0	28.4	40.0	11.6	381.0	213.0	
2	91.474	V	64.5	-26.2	38.3	40.0	1.7	152.0	272.0	
3	92.686	V	63.9	-26.1	37.8	40.0	2.2	155.0	246.0	
4	106.348	H	54.9	-24.1	30.8	40.0	9.2	385.0	202.0	
5	106.824	V	61.4	-24.0	37.4	40.0	2.6	100.0	249.0	
6	288.061	H	45.1	-17.7	27.4	47.0	19.6	388.0	353.0	


◆ Calculation

Result(QP) [dB(μV/m)] = (Reading(QP)[dB(μV)] + c.f[dB(1/m)])

Margin(QP)[dB] = Limit[dB(μV/m)] - Result(QP) [dB(μV/m)]

Reading(QP) : Reading value, Result(QP) : Reading value + Factor value

Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

**Radiated Electric Field Emissions(Above 1 GHz)****Final Result**

No.	Frequency [MHz]	Pol	Reading AV [dB(μV)]	Reading PK [dB(μV)]	c.f [dB(1/m)]	Result AV [dB(μV/m)]	Result PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [deg]	Remark
1	2398.346	V	27.5	43.9	4.4	31.9	48.3	56.0	76.0	24.1	27.7	100.0	150.3	
2	2556.346	H	27.8	44.1	5.1	32.9	49.2	56.0	76.0	23.1	26.8	100.0	0.0	
3	3594.635	H	27.8	41.8	7.3	35.1	49.1	60.0	80.0	24.9	30.9	100.0	161.2	
4	3596.724	V	27.4	43.1	7.3	34.7	50.4	60.0	80.0	25.3	29.6	100.0	187.7	
5	4792.537	V	28.9	43.6	11.4	40.3	55.0	60.0	80.0	19.7	25.0	100.0	359.9	
6	5672.755	H	23.7	38.8	13.4	37.1	52.2	60.0	80.0	22.9	27.8	100.0	304.5	

◆ Calculation

Result(PK/CAV) [dB(μV/m)] = (Reading(PK/CAV)[dB(μV)] + c.f[dB(1/m)])

Margin(PK/CAV)[dB] = Limit[dB(μV/m)] - Result(PK/CAV) [dB(μV/m)]

Reading(PK/CAV) : Reading value, Result(PK/CAV) : Reading value + Factor value

Limit(PK/CAV) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

**Harmonic Current Emissions and Voltage Fluctuations and Flicker*****Average harmonic current results***

Hn	I _{eff} [A]	% of Limit	Limit [A]	Result
N/A				

Note: Harmonic currents less than 0.6 % of the input current measured under the test conditions, or less than 5 mA, whichever is greater, are disregarded.

* Application of limits for average is 100% except for odd harmonics from 21 to 39, where 150% applies.



Test Data - Harmonics (continued)

Maximum harmonic current results

Hn	I _{eff} [A]	% of Limit	Limit [A]	Result
N/A				

Note: Harmonic currents less than 0.6 % of the input current measured under the test conditions, or less than 5 mA, whichever is greater, are disregarded.

* Application of limits for average is 100% except for odd harmonics from 21 to 39, where 150% applies.



Report No. : KES-EM250228

Page 42 / 56

Test Data - Voltage Fluctuations

Maximum Flicker results

Flicker Measurements					
	Plt	Max Pst	Max Dc	Max Dmax	Max Tmax
Line 1:	N/A				
Limits:					
Results:					





Test Setup Photos and Configuration

Conducted Emissions at Mains Power Ports

N/A







Conducted Emissions at Telecommunication Ports






Radiated Electric Field Emissions(Below 1 GHz)





Radiated Electric Field Emissions(Above 1 GHz)





Harmonic Current Emissions and Voltage Fluctuations and Flicker

N/A






Electrostatic Discharge




Radiated Electric Field Immunity





Electrical Fast Transients/Bursts



Surge Transients





Conducted Disturbance




Voltage Dips and Short Interruptions

N/A




EUT External Photographs

(Top)



(Bottom)





EUT Internal Photographs


(Internal View)






EUT Internal View – Main Board

(Top)




(Bottom)





EUT Internal View – Board

(Top)



(Bottom)






EUT Internal View – Camera board

(Top)



(Bottom)





Label and Location



NETWORK THERMAL CAMERA

Model No : XNO-A8084R

Manufacturer : HANWHA VISION VIETNAM COMPANY LIMITED

Made in Vietnam



The End.