



TEST REPORT



Report No. : KES-EM-23T0915

Page 1 / 46

KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si,
Gyeonggi-do, 14057, Korea
Tel : +82-31-425-6200, Fax : +82-31-425-6200

1. Client

Applicant : Hanwha Vision Co., Ltd

Applicant Address : 6, Pangyo-ro 319Beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, Republic of Korea

2. Sample Description

Product name : NETWORK CAMERA

Model/Type No. : XNP-C9310R

Variant Model : -

Manufacturer : 1. HANWHA VISION VIETNAM COMPANY LIMITED
2. D-TECH CO.,LTD.

Manufacturer Address : 1. Lot O-2, Que Vo Industrial Zone extended area, Nam Son commune,
Bac Ninh city, Bac Ninh province, Vietnam
2. 173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi- do, Korea
(Suwon Industrial Complex)

3. Equipment authorization

 : Supplier's Declaration of Conformity

3. Date of Receipt

 : Oct. 13, 2023

4. Test date

 : Oct. 23, 2023 ~ Oct. 24, 2023

5. Date of Issue

 : Oct. 26, 2023

7. Test Results

 : In Compliance

Tested by

Dong In, Kim
EMC Test Engineer

Reviewed by


Dong Il, Lee
EMC Technical Manager

This test report is not related to KS Q ISO/IEC 17025 and KOLAS.

KES-QP16-F01(00-23-01-01)

KES Co., Ltd.

The authenticity of the test report, contact kes@kes.co.kr



REPORT REVISION HISTORY

Date	Test Report No.	Revision History
Oct. 26, 2023	KES-EM-23T0915	Issued

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.




TABLE OF CONTENTS

1.0 General Product Description..... 4

1.1 Test Voltage & Frequency..... 8

1.2 Variant Model Differences..... 8

1.3 Device Modifications..... 8

1.4 Equipment Under Test..... 8

1.5 Support Equipments..... 8

1.6 External I/O Cabling..... 9

1.7 EUT Operating Mode(s)..... 9

1.8 Configuration..... 10

1.9 Remarks when standards applied..... 11

1.10 Calibration Details of Equipment Used for Measurement..... 11

1.11 Test Facility..... 11

1.12 Laboratory Accreditations and Listings..... 11

2.0 Test Regulations..... 12

2.1 Conducted Emissions at Mains Power Ports..... 13

2.2 Radiated Electric Field Emissions(Below 1 GHz)..... 15

2.3 Radiated Electric Field Emissions(Above 1 GHz)..... 17

APPENDIX A – TEST DATA..... 19

 Conducted Emissions at Mains Power Ports..... 19

 Radiated Electric Field Emissions(Below 1 GHz)..... 21

 Radiated Electric Field Emissions(Above 1 GHz)..... 23

 Test Setup Photos and Configuration..... 24

 Conducted Emissions at Mains Power Ports..... 24

 Radiated Electric Field Emissions(Below 1 GHz)..... 25

 Radiated Electric Field Emissions(Above 1 GHz)..... 26

 EUT External Photographs..... 27


 EUT Internal Photographs..... 28





1.0 General Product Description

Main Specifications of EUT are:

Video	
Imaging Device	1/1.8" CMOS
Resolution	3840x2160, 2592x1944, 2592x1464, 1920x1080, 1600x1200, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240
Max. Framerate	H.265/H.264: Max. 30fps/25fps(60Hz/50Hz) MJPEG: Max. 30fps(@4K Max. 5fps)
NETD	None
Pixel Size	None
Min. Illumination	Color: 0.06 Lux(F1.36, 1/30sec, 30 IRE) BW: 0.006 Lux(F1.36, IR LED Off), 0Lux (IR LED On)
Video Out	None
Video Transmission Distance	None
Lens	
Focal Length (Zoom Ratio)	6.91 ~ 214.7mm(31x) zoom (digital 32x, total 992x zoom)
Max. Aperture Ratio	F1.36(Wide)~F4.6(Tele)
Angular Field of View	H : 60.6°(Wide)~2.59°(Tele) V : 35.1°(Wide)~1.45°(Tele) D : 68.8°(Wide)~2.97°(Tele)
Min. Object Distance	3m(9.84ft)
Focus Control	Oneshot AF, Focus save, Focus scan, Wise auto focus
Lens Type	P-iris(IR corrected)
Mount Type	None
Optional Lens	None
Pan / Tilt / Rotate	
Pan / Tilt / Rotate Range	None
Pan Range	360° Endless
Pan Speed	Preset: 550°/sec, Manual: 0.024°/sec~200°/sec
Tilt Range	110° (90° ~ -20°)
Tilt Speed	Preset: 550°/sec, Manual: 0.024°/sec~200°/sec
Rotate Range	None
Sequence	Preset(300ea), Swing, Group(6ea), Trace, Tour, Auto Run, Schedule
Preset Accuracy	±0.07° (±20°C by temperature at preset setting)



Operational	
Camera Title	Displayed up to 85 characters
Direction Indicator	Support
Day & Night	Auto(ICR)
Backlight Compensation	BLC, HLC, WDR, SDR
Wide Dynamic Range	120dB
Digital Noise Reduction	WiseNR II (Based on AI engine), SSNR V
Digital Image Stabilization	Support (built-in gyro sensor)
Defog	Support
Motion Detection	8ea, 8point polygonal zones
Privacy Masking	32ea, 4point quadrangle zones - Color: Gray/Green/Red/Blue/Black/White - Mosaic
Gain Control	Off / Max gain / Manual
White Balance	ATW / NarrowATW / AWC / Manual / Indoor / Outdoor / Mercury / Sodium
LDC	None
Electronic Shutter Speed	Minimum / Maximum / Anti flicker (2~1/12,000sec) Prefer shutter control (Based on AI engine)
Digital PTZ	None
Video Rotation	Flip&Mirror
Analytics	Classified object type : Person/Face/Vehicle/License plate Attributes : Vehicle(Type:car/bus/truck/motorcycle/bicycle) Support DetectionShot Analytics events based on AI engine - Object detection, Virtual line(Crossing/Direction), Virtual area(Loitering/Intrusion/Enter/Exit) Analytics events - Motion detection, Tampering, Fog detection, Shock detection, Virtual area(Appear/Disappear) * Audio detection, Sound classification (Via optional I/O box SPM-4210)
Business Intelligence	None
Serial Interface	None
Alarm I/O	None
Alarm Triggers	Analytics, Network disconnect * Alarm input (Via optional I/O box SPM-4210)
Alarm Events	When alarm trigger occurred - File upload (image) : e-mail/FTP - Notification : e-mail - Recording : SD/SDHC/SDXC or NAS recording at event triggers - Handover: PTZ preset, send message by HTTP/HTTPS/TCP - MQTT: publication * Alarm output / Audio clip playback (Via optional I/O box SPM-4210)
Audio Streaming	None
Audio In	None
Audio Out	None
Light Type	IR LED (850nm)
Light Viewable Length	None
IR Viewable Length	Wise IR 250m(820ft)
IR Illuminator (Optional)	None
IR Radiation angle	None
IR LED	None
IR Wavelength	None
IR Operation	None
Water Removal	Support (Spin dry)
Auto Tracking	Support Object auto tracking (Person/Vehicle) Target lock tracking
Coaxial Protocol	None
Color Palettes	None
Radiometry	
Temperature Detect Range	None
Temperature Accuracy	None
Temperature Detection	None
Additional	None



Report No. : KES-EM-23T0915

Page 6 / 46

Network	
Ethernet	Metal shielded RJ-45(10/100BASE-T)
Video Compression	H.265/H.264: Main/Baseline/High, MJPEG
Audio Compression	None
Smart Codec	Manual(Sea area), WiseStreamII, WiseStreamIII(Based on AI engine)
Video Quality Adjustment	H.264/H.265: Target bitrate level control MJPEG: Target bitrate level control
Bitrate Control	H.264/H.265: CBR or VBR MJPEG: VBR
Streaming	Unicast(20 users) / Multicast Multiple streaming(Up to 10 profiles)
Protocol	IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, CDP, SRTP(TCP, UDP Unicast), NTCIP 1205,
SIP support (VoIP, Peer-to-peer)	None
Security	None
Application Programming Interface	ONVIF Profile S/G/T/M SUNAPI(HTTP API) Wisenet open platform
Security	
OS / Firmware Protect	Secure boot, Signed firmware, Firmware encryption
User authentication	Digest Authentication, Prevent brute-force attack
Network authentication	802.1X Authentication(EAP-TLS, EAP-LEAP, EAP-PEAP MSCHAPv2)
Secure Communication	HTTPS, SRTP, WSS(Websocket secure)
Access Control	Access control based on IP address
Data Protect	Authentication information encryption, ZIP compression encryption
Audit	User Access/System/Event log management
Device ID	Device Certificate(Hanwha Private Root CA)
Secure Storage	TPM(Trusted platform module), HTPM(Hanwha trusted platform module), SDcard partition encrypt
Security Certificate	TPM with FIPS 140-2 level 2
General	
Webpage Language	English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Portuguese, Czech, Polish, Turkish, Dutch, Hungarian, Greek
Web Viewer	None
Edge Storage	Micro SD/SDHC/SDXC 2slot 1TB (512MBx2)
Memory	4GB RAM, 512MB Flash
Environmental & Electrical	
Operating Temperature / Humidity	Normal : -50°C~-+55°C(-58°F ~ +131°F)/ +74°C(165°F)(Max) based on NEMA TS-2(2.2.7) * Start up should be done at above -30°C Less than 95%RH(Non-condensing)
Storage Temperature / Humidity	-50°C~-+60°C(-58°F~-+140°F) / 0~90% RH
Certification	IP66/IP67, IK10, NEMA4X Safety(UL, KC-SDOC), EMC(FCC, CE, VCCI, RCM, KC) NEMA-TS 2(2.2.7, 2.2.8, 2.2.9)
Input Voltage	HPoE(IEEE802.3bt type4, Class8, Injector included)
Power Consumption	HPoE: Max 62W, typical 23W
Mechanical	
Color / Material	White / Aluminum
RAL Code	RAL9003
Product Dimensions / Weight	ø188x264.9mm(ø7.40x10.47") / 4400g (9.70lb)
Compatible Conduit hole / Gang	None
Hanging Mount (Dome)	SBP-156HWW
Skin Cover	None
Skin Cover (Dome)	None
Weather Cap (Dome)	None
Power Module	None
Backbox	None
Ceiling Mount (Assy)	SBP-156CMW, SBP-300CMTS, SBP-300CMW1/900CMW, SBP-150CMI/300CMI
Wall Mount	SBP-156WMW, SBP-390WMW2
Pole Mount	SBP-300PMW2
In-ceiling Mount	None
Parapet Mount	SBP-156LMW, SBP-300LMW
Corner Mount	SBP-156KMW, SBP-300KMW1
Tilt Mount	None
Housing (Box)	None
Cabinet	SBP-300NBW
Gang Plate	None
Conduit Adaptor	None
Other Compatible Models	None

KES-QP16-F01(00-23-01-01)

KES Co., Ltd.

The authenticity of the test report, contact kes@kes.co.kr



Report No. : KES-EM-23T0915

Page 7 / 46

Certifications & Standards	
Network	None
EMC	FCC 47 CFR 15 Subpart B Class A ICES-3(A)/NMB-3(A) CE/UKCA - EN 55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3 VCCI CISPR 32 Class A RCM AS/NZS CISPR 32 Class A KS C 9832 Class A , KS C 9835
Safety	UL 62368-1, CAN/CSA C22.2 NO. 62368-1 IEC/EN 62471
Environment	IEC/EN 63000 IEC/EN 60529 IP66/IP67, IEC/EN 62262 IK10 NEMA TS 2-2013 (2.2.7, 2.2.8, 2.2.9) NEMA 250 type 4X
Video	None
DORI (EN62676-4 standard)	
Detect (25PPM/ 8PPF)	Wide: 131.4m(431.19ft) / Tele: 3397.3m(11146.16ft)
Observe (63PPM/ 19PPF)	Wide: 52.6m(172.48ft) / Tele: 1358.9m(4458.46ft)
Recognize (125PPM/ 38PPF)	Wide: 26.3m(86.24ft) / Tele: 679.5m(2229.23ft)
Identify (250PPM/ 76PPF)	Wide: 13.1m(43.12ft) / Tele: 339.7m(1114.62ft)
LPR/ANPR/MMCR	
Speed Description	None
Speed limit	None
Min. Forward Distance	None
Max. Forward Distance	None
Max. Horizontal Angle	None
Max. Vertical Angle	None
Horizontal Offset	None
Camera Height	None
Lane Coverage	None
Vehicle Recognition	None
Available Countries	None
Wisenet Road AI LPR/ANPR/M	
Solution	None
Speed Description	None
Lane Coverage	None
Speed limit	None
Min. Forward Distance	None
Max. Forward Distance	None
Max. Horizontal Angle	None
Max. Vertical Angle	None
Horizontal Offset	None
Camera Height	None
Vehicle Recognition	None
Available Countries	None
Ver	
Ver	2311

KES-QP16-F01(00-23-01-01)

KES Co., Ltd.

The authenticity of the test report, contact kes@kes.co.kr



1.1 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

☒ AC 120 V, 60 Hz

1.2 Variant Model Differences

Not applicable

1.3 Device Modifications


Not applicable

1.4 Equipment Under Test

Description	Model Number	Serial Number	Manufacturer	Remarks
NETWORK CAMERA	XNP-C9310R	-	HANWHA VISION VIETNAM COMPANY LIMITED	EUT
PoE Adapter	PT-PSE109GBRO-AH-S	PT2332221941	Dongguan PROCET Network Technology Co.,Ltd	R-R-LJ9- PSE109G BRO-A02

1.5 Support Equipments

Description	Model Number	Serial Number	Manufacturer	Remarks
Notebook 1	LG15N54	507NZET040180	LG	-
Notebook 1 Adapter	PA-1900-14	OF4A263348701J2 47	LITE-ON TECHNOLOGY COPORATION	-
Notebook 2	LG15N54	509NZSJ043910	LG	-
Notebook 2 Adapter	PA-1650-43(65W)	OF8DS63849302K 347(1.2)	LITE-ON TECHNOLOGY (CHANGZHOU) CO.,LTD.	-
Optical Converter	SOL-SFC2000SFP(A)	S200150803588	Soltech Company	-
Optical Converter Adapter	FJ-SW1260502000DK	-	SHENZHEN FUJAI APPLIANCE CO., LTD.	-
Optical Module 1	TXC432-CU1M	-	-	-
Optical Module 2	TXC432-CU1M	-	-	-
Micro SD Card 1	-	-	Transcend	8GB
Micro SD Card 2	-	-	Snadisk	32GB



1.6 External I/O Cabling

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
NETWORK CAMERA (EUT)	RJ-45 (PoE)	PoE Adapter (EUT)	RJ-45 (PoE)	2.0	U
	Micro SD Card Slot	Micro SD Card 1	Micro SD Card Slot	-	-
	Micro SD Card Slot	Micro SD Card 2	Micro SD Card Slot	-	-
Notebook 1 Adapter	DC Jack	Notebook 1	DC Jack	1.5	U
PoE Adapter (EUT)	RJ-45 (LAN)		RJ-45 (LAN)	3.1	U
	SFP		SFP	-	-
	Ground	Enclosure Ground	Ground	2.0	-
Optical Converter	SFP	Optical Module 2	SFP	-	-
	DC Jack	Optical Converter Adapter	DC Jack	1.4	U
	RJ-45 (LAN)	Notebook 2	RJ-45 (LAN)	2.0	U
Notebook 2 Adapter	DC Jack		DC Jack	1.5	U

* Unshielded=U, Shielded=S




1.7 EUT Operating Mode(s)

Test mode	operating
Operating	1. Run the Web Viewer on your Notebook and check the camera video output 2. PingTest from your Notebook to check the network status 3. After the test, the Micro SD Card storage file was checked.

EUT Test operating S/W		
Name	Version	Manufacture Company
Web Viewer	-	Hanwha Vision Co., Ltd



1.8 Configuration



1.9 Remarks when standards applied

N/A

1.10 Calibration Details of Equipment Used for Measurement


Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less.

1.11 Test Facility

The measurement facility is located at 473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, 12658, Korea, Republic of. The sites are constructed in conformance with the requirements of ANSI C63.4a-2017 and CISPR 16-1-4:2019

1.12 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
KOREA	RRA	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KR0100
International	KOLAS	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KT489
USA	FCC	3 m & 10 m Semi-Anechoic Chamber Conducted test site to perform FCC Part 15/18 measurements.	 KR0100
Canada	ISED	3 m & 10 m Semi-Anechoic Chamber and Conducted test site	 23298
JAPAN	VCCI	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site)	 C-20136, T-20137, R-20181, G-20176
Europe	TÜV SÜD	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 CARAT 001633 0004



2.0 Test Regulations

The emissions tests were performed according to following regulations:

- ☒ 47 CFR Part 15, Subpart B
- ☐ CISPR 22:2009 +A1:2010

☐ Class A

☐ Class B
- ☒ ANSI C63.4a-2017

☒ Class A

☐ Class B

☒ IC Regulation ICES-003 Issue 7

☐ CAN/CSA-CISPR 32:17

☐ Class A

☐ Class B

☒ ANSI C63.4a-2017

☒ Class A

☐ Class B



2.1 Conducted Emissions at Mains Power Ports



Test Date
Oct. 23, 2023

Test Location
Electro wave Shieldroom #6

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test SW	EMC32	R & S	9.12.00	-
☒	EMI TEST RECEIVER	ESR3	R & S	101783	11, 11, 2023
☒	LISN	ENV216	R & S	101787	11, 10, 2023
☒	LISN	ESH2-Z5	R & S	100450	11, 10, 2023
☒	PULSE LIMITER	ESH3-Z2	R & S	101915	11, 10, 2023

Diagram of test setup



Report No. : KES-EM-23T0915

Page 14 / 46

Test Conditions

Temperature: (22,8 ± 0,0) °C
Relative Humidity: (46,8 ± 0,0) % R.H.

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz


Test Results

The requirements are:

- ☒ PASS
- ☐ NOT PASS
- ☐ NOT APPLICABLE

Remarks

See Appendix A for test data.



2.2 Radiated Electric Field Emissions(Below 1 GHz)





Test Date
Oct. 23, 2023

Test Location
☐ OPEN AREA TEST SITE #2 ☒ SEMI ANECHOIC CHAMBER #4(10m)

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EP5/RE	TOYO Corporation	6.0.0	-
☒	EMI TEST RECEIVER	ESU26	R & S	100551	03, 21, 2024
☒	AMPLIFIER	SCU 01	R & S	100603	11, 10, 2023
☒	TRILOG-BROADBAND ANTENNA	VULB9163	Schwarzbeck	715	11, 17, 2024
☒	ATTENUATOR	8491A	HP	32173	03, 03, 2024

Diagram of test setup



Report No. : KES-EM-23T0915

Page 16 / 46

Test Conditions

Temperature: (22,5 ± 0,1) °C
Relative Humidity: (46,9 ± 0,2) % R.H.

Frequency Range of Measurement

30 MHz to 1 GHz

Instrument Settings

IF Band Width: 120 kHz


Test Results

The requirements are:

- ☒ PASS
- ☐ NOT PASS
- ☐ NOT APPLICABLE

Remarks

See Appendix A for test data.



2.3 Radiated Electric Field Emissions(Above 1 GHz)



Test Date
Oct. 24, 2023

Test Location
SEMI ANECHOIC CHAMBER #5

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	ES10/RE	TOYO Corporation	2022.01.000	-
☒	EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100552	03, 21, 2024
☒	HORN ANTENNA	BBHA 9120D	SCHWARZBECK	9120D-1802	11, 08, 2023
☒	PREAMPLIFIER	8449B	HP	3008A00538	05, 31, 2024
☒	ATTENUATOR	8491B	HP	23094	03, 21, 2024

Diagram of test setup



Report No. : KES-EM-23T0915

Page **18** / **46**

Test Conditions

Temperature: (24,0 ± 0,1) °C
Relative Humidity: (45,7 ± 0,2) % R.H.

Frequency Range of Measurement

1 GHz to 6 GHz

Instrument Settings

IF Band Width: 1 MHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE


Remarks

- See Appendix A for test data.
-The Average of the test data is the cispr average result.

KES-QP16-F01(00-23-01-01)

KES Co., Ltd.

The authenticity of the test report, contact kes@kes.co.kr



APPENDIX A – TEST DATA

Conducted Emissions at Mains Power Ports


HOT LINE

Common Information

Test Description:
Model No.:
Phase:
Mode:
Operator Name:


Conducted Emission
XNP-C9310R
L1

KES



Final Result


Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.165000	---	23.42	66.00	42.58	1000.0	9.000	L1	19.4
0.165000	41.14	---	79.00	37.86	1000.0	9.000	L1	19.4
0.410000	---	30.32	66.00	35.68	1000.0	9.000	L1	19.4
0.410000	32.14	---	79.00	46.86	1000.0	9.000	L1	19.4
0.915000	---	18.51	60.00	41.49	1000.0	9.000	L1	19.5
0.915000	20.86	---	73.00	52.14	1000.0	9.000	L1	19.5
2.390000	---	17.86	60.00	42.14	1000.0	9.000	L1	19.5
2.390000	22.23	---	73.00	50.77	1000.0	9.000	L1	19.5
19.710000	---	37.61	60.00	22.39	1000.0	9.000	L1	20.2
19.710000	40.88	---	73.00	32.12	1000.0	9.000	L1	20.2



NEUTRAL LINE

Common Information


Test Description: Conducted Emission
Model No.: XNP-C9310R
Phase: N
Mode:
Operator Name: KES



Final Result


Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.165000	---	22.09	66.00	43.91	1000.0	9.000	N	19.4
0.165000	41.16	---	79.00	37.84	1000.0	9.000	N	19.4
0.440000	---	34.74	66.00	31.26	1000.0	9.000	N	19.4
0.440000	35.79	---	79.00	43.21	1000.0	9.000	N	19.4
0.940000	---	15.70	60.00	44.30	1000.0	9.000	N	19.5
0.940000	18.98	---	73.00	54.02	1000.0	9.000	N	19.5
3.365000	---	9.42	60.00	50.58	1000.0	9.000	N	19.6
3.365000	19.07	---	73.00	53.93	1000.0	9.000	N	19.6
19.710000	---	38.24	60.00	21.76	1000.0	9.000	N	20.2
19.710000	41.51	---	73.00	31.49	1000.0	9.000	N	20.2
25.205000	---	33.46	60.00	26.54	1000.0	9.000	N	20.3
25.205000	40.47	---	73.00	32.53	1000.0	9.000	N	20.3

◆ Calculation
 $\text{QuasiPeak [dBμV]} / \text{CAverage [dBμV]} = \text{Reading Value [dBμV]} + \text{Corr. [dB]}$
QuasiPeak / CAverage : The Final Value
Reading Value : Not shown in the table.
Corr. : Correction values (LISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))



Radiated Electric Field Emissions(Below 1 GHz)

- 47 CFR Part 15, Subpart B



Final Result


No.	Frequency	(P)	Reading	c.f	Result	Limit	Margin	Height	Angle	Remark
	[MHz]		QP		QP	QP	QP			
			[dB(uV)]	[dB(1/m)]	[dB(uV/m)]	[dB(uV/m)]	[dB]	[cm]	[deg]	
1	58.694	V	49.4	-21.3	28.1	39.0	10.9	104.0	239.0	
2	87.490	V	54.2	-24.9	29.3	39.0	9.7	109.0	109.0	
3	96.345	V	52.1	-22.3	29.8	43.5	13.7	109.0	89.0	
4	108.817	V	52.4	-22.5	29.9	43.5	13.6	115.0	262.0	
5	199.865	V	53.5	-21.0	32.5	43.5	11.0	123.0	355.0	
6	227.066	H	52.7	-19.3	33.4	46.5	13.1	388.0	211.0	
7	250.006	H	59.6	-18.8	40.8	46.5	5.7	382.0	222.0	
8	312.514	H	55.2	-16.8	38.4	46.5	8.1	383.0	241.0	
9	375.030	H	53.3	-14.0	39.3	46.5	7.2	389.0	23.0	
10	437.530	V	51.5	-12.7	38.8	46.5	7.7	166.0	11.0	
11	437.537	H	56.7	-12.7	44.0	46.5	2.5	379.0	330.0	
12	687.553	H	45.0	-7.2	37.8	46.5	8.7	384.0	350.0	



Report No. : KES-EM-23T0915

Page 22 / 46

- IC Regulation ICES-003 Issue 7



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	58.694	V	49.4	-21.3	28.1	40.0	11.9	104.0	239.0	
2	87.490	V	54.2	-24.9	29.3	40.0	10.7	109.0	109.0	
3	96.345	V	52.1	-22.3	29.8	43.5	13.7	109.0	89.0	
4	108.817	V	52.4	-22.5	29.9	43.5	13.6	115.0	262.0	
5	199.865	V	53.5	-21.0	32.5	43.5	11.0	123.0	355.0	
6	227.066	H	52.7	-19.3	33.4	46.4	13.0	388.0	211.0	
7	250.006	H	59.6	-18.8	40.8	47.0	6.2	382.0	222.0	
8	312.514	H	55.2	-16.8	38.4	47.0	8.6	383.0	241.0	
9	375.030	H	53.3	-14.0	39.3	47.0	7.7	389.0	23.0	
10	437.530	V	51.5	-12.7	38.8	47.0	8.2	166.0	11.0	
11	437.537	H	56.7	-12.7	44.0	47.0	3.0	379.0	330.0	
12	687.553	H	45.0	-7.2	37.8	47.0	9.2	384.0	350.0	

◆ Calculation – SAC #4(10 m)

Result(QP) [dB(μV/m)] = (Reading(QP)[dB(μV)] + c.f[dB(1/m)])

Margin(QP)[dB] = Limit[dB(μV/m)] - Result(QP) [dB(μV/m)]

Reading(QP) : Reading value, Result(QP) : Reading value + Factor value

Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value


KES-QP16-F01(00-23-01-01)

KES Co., Ltd.

The authenticity of the test report, contact kes@kes.co.kr



Radiated Electric Field Emissions(Above 1 GHz)



Final Result

No.	Frequency [MHz]	Pol	Reading AV [dB(μV)]	Reading PK [dB(μV)]	c.f [dB(1/m)]	Result AV [dB(μV/m)]	Result PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [deg]	Remark
1	4787.168	H	28.0	47.3	11.4	39.4	58.7	60.0	80.0	20.6	21.3	138.0	323.3	
2	3694.289	V	28.5	42.0	7.3	35.8	49.3	60.0	80.0	24.2	30.7	121.0	278.1	
3	1063.999	H	32.9	52.5	-1.6	31.3	50.9	60.0	80.0	28.7	29.1	118.0	227.2	
4	3602.473	H	28.5	40.7	7.0	35.5	47.7	60.0	80.0	24.5	32.3	279.0	182.2	
5	2393.976	V	29.0	52.5	4.3	33.3	56.8	60.0	80.0	26.7	23.2	185.0	140.6	
6	4256.426	V	29.7	49.9	9.2	38.9	59.1	60.0	80.0	21.1	20.9	171.0	130.2	
7	2660.012	H	35.6	65.8	5.2	40.8	71.0	60.0	80.0	19.2	9.0	322.0	127.8	
8	3192.071	V	32.3	58.7	6.5	38.8	65.2	60.0	80.0	21.2	14.8	156.0	117.8	
9	2660.478	V	36.8	69.1	5.2	42.0	74.3	60.0	80.0	18.0	5.7	134.0	109.1	
10	4256.007	H	29.8	49.7	9.2	39.0	58.9	60.0	80.0	21.0	21.1	289.0	89.7	
11	3191.974	H	28.4	47.4	6.5	34.9	53.9	60.0	80.0	25.1	26.1	133.0	82.1	
12	4787.961	V	28.4	50.2	11.4	39.8	61.6	60.0	80.0	20.2	18.4	118.0	46.5	




◆ Calculation

Result(PK/CAV) [dB(μV/m)] = (Reading(PK/CAV)[dB(μV)] + c.f[dB(1/m)]

Margin(PK/CAV)[dB] = Limit[dB(μV/m)] - Result(PK/CAV) [dB(μV/m)]

Reading(PK/CAV) : Reading value, Result(PK/CAV) : Reading value + Factor value

Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value



Report No. : KES-EM-23T0915

Page 24 / 46

Test Setup Photos and Configuration



Conducted Emissions at Mains Power Ports



KES-QP16-F01(00-23-01-01)

KES Co., Ltd.



The authenticity of the test report, contact kes@kes.co.kr



Report No. : KES-EM-23T0915

Page 25 / 46

Radiated Electric Field Emissions(Below 1 GHz)



KES-QP16-F01(00-23-01-01)

KES Co., Ltd.


The authenticity of the test report, contact kes@kes.co.kr



Report No. : KES-EM-23T0915

Page 26 / 46


Radiated Electric Field Emissions(Above 1 GHz)



KES-QP16-F01(00-23-01-01)

KES Co., Ltd.

The authenticity of the test report, contact kes@kes.co.kr





EUT External Photographs

(Top)




(Bottom)




EUT Internal Photographs

(Internal View)





EUT Internal View – Main Board

(Top)



(Bottom)




Report No. : KES-EM-23T0915


Page 30 / 46

EUT Internal View – Lens Board

(Top)




(Bottom)



KES-QP16-F01(00-23-01-01)


KES Co., Ltd.

The authenticity of the test report, contact kes@kes.co.kr





EUT Internal View – Lens

(Top)



(Bottom)



Report No. : KES-EM-23T0915


Page 32 / 46

EUT Internal View – FAN 1

(Top)



(Bottom)



KES-QP16-F01(00-23-01-01)

KES Co., Ltd.

The authenticity of the test report, contact kes@kes.co.kr



Report No. : KES-EM-23T0915


Page 33 / 46

EUT Internal View – FAN 2

(Top)



(Bottom)



KES-QP16-F01(00-23-01-01)

KES Co., Ltd.

The authenticity of the test report, contact kes@kes.co.kr




Report No. : KES-EM-23T0915

Page 34 / 46

EUT Internal View – IR Board 1

(Top)




(Bottom)



KES-QP16-F01(00-23-01-01)

KES Co., Ltd.

The authenticity of the test report, contact kes@kes.co.kr




Report No. : KES-EM-23T0915


Page 35 / 46

EUT Internal View – IR Board 2

(Top)



(Bottom)



KES-QP16-F01(00-23-01-01)


KES Co., Ltd.

The authenticity of the test report, contact kes@kes.co.kr





EUT Internal View – SD Card Board

(Top)



(Bottom)




Report No. : KES-EM-23T0915


Page 37 / 46

EUT Internal View – SUB Board 1

(Top)



(Bottom)



KES-QP16-F01(00-23-01-01)


KES Co., Ltd.

The authenticity of the test report, contact kes@kes.co.kr




EUT Internal View – SUB Board 2

(Top)




(Bottom)





EUT Internal View – SUB Board 3

(Top)



(Bottom)




EUT Internal View – SUB Board 4

(Top)




(Bottom)




EUT Internal View – SUB Board 5

(Top)




(Bottom)





EUT Internal View – SUB Board 6

(Top)




(Bottom)






EUT Internal View – SUB Board 7

(Top)




(Bottom)





EUT Internal View – SUB Board 8

(Top)




(Bottom)





EUT Internal View – SUB Board 9

(Top)



(Bottom)



Label Photographs

FCC Label



NETWORK CAMERA

XNP-C9310R

IC Label

CAN ICES-003(A) / NMB-003(A)

This device complies with Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions:
(1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes :

(1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

