



4, Songju-ro 236beon-gil, Yangji-myeon, Cheoin-gu, Yongin-si, Gyeonggi-do,
17159, Korea
Tel: +82-31-323-6008 Fax: +82-31-323-6010
<http://www.ltalab.com>

EMC TEST REPORT

Dates of Tests: October 29 – November 3, 2020
Test Report S/N: LR500172011X
Test Site : LTA Co., Ltd.

Model No.

XRN-1620B2

APPLICANT

Hanwha Techwin Co., Ltd.

Equipment Name : NVR
Manufacturer : HANWHA TECHWIN SECURITY VIETNAM CO.,LTD.
Model name : XRN-1620B2
Test Device Serial No.: : Identification
Rule Part(s) : VCCI-CISPR 32:2016

Date of issue : November 06, 2020

This test report is issued under the authority of:

The test was supervised by:

Young Kyu Shin, Technical Manager

Yu Hyeon Nam, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory. The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.



Revision history

Revision	Date of issue	Test report No.	Description
0	06.11.2020	LR500172011X	Initial

TABLE OF CONTENTS

1. General information's.....	4
2. Information's about test item.....	5
3. Test Report.....	8
3.1 Summary of tests	8
4. EMISSION	9
4.1 Conducted Emissions.....	9
4.2 Radiated Emissions.....	17
APPENDIX A TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS	22
APPENDIX B PHOTOGRAPHS	24

1. General information's

1-1 Test Performed

Company name : **LTA Co., Ltd**
 Address : 4, Songju-ro 236beon-gil, Yangji-myeon, Cheoin-gu, Yongin-si, Gyeonggi-do, 17159, Korea
 Web site : <http://www.ltalab.com>
 E-mail : chahn@ltalab.com
 Telephone : +82-31-323-6008
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
NVLAP	U.S.A	200723-0	2021-09-30	ECT accredited Lab.
RRA	KOREA	KR0049	-	RRA accredited Lab.
	U.S.A		2021-04-11	
	CANADA		2021-06-16	
	VIETNAM		2021-04-12	
VCCI	JAPAN	C-14948	2023-09-10	VCCI registration
		T-12416	2023-09-10	
		R-14483	2023-10-15	
		G-10847	2021-12-13	
KOLAS	KOREA	KT551	2021-08-20	KOLAS accredited Lab.

2. Information's about test item

2-1 Client / Manufacturer

Company name : Hanwha Techwin Co., Ltd.
Address : 6, Pangyo-ro 319 Beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, 13488, KOREA
Telephone /Facsimile : +82-70-7147-8753(<http://hanhwa-security.com>)

Factory #1

Company name : HANWHA TECHWIN SECURITY VIETNAM CO.,LTD.
Address : Lot O-2, Que Vo Industrial Zone extended area ,Nam Son commune, Bac Ninh city,Bac Ninh province, Vietnam

Factory #2

Company name : D-TECH CO.,LTD.
Address : 173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi-do, Korea (Suwon Industrial Complex)

2-2 Equipment Under Test (EUT)

Class : A
Category : NVR
Model name : XRN-1620B2
Serial number : Identification
Date of receipt : October 13, 2020
EUT condition : Pre-production, not damaged
Interface Ports : AC IN, USB(3EA), AUDIO OUT, VGA OUT, HDMI, ALARM IN, ALARM OUT, ALARM GROUND, NETWORK 1, NETWORK 2
Power rating : AC 100 V, 50 Hz

2-3 Modification

-NONE

2-4 Test conditions

Temp. / Humid. / Pressure : (21 - 23) °C / (43) % R.H.
Tested Model : XRN-1620B2
Test mode : REC mode
Test Voltage : AC 100 V, 50 Hz

2-5 List of EUT and ACCESSORY

EUT				
Equipment Name	Model Name	Serial No.	Manufacturer	Remarks
NVR	XRN-1620B2	N/A	HANWHA TECHWIN SECURITY VIETNAM CO.,LTD. D-TECH CO.,LTD.	-
Mouse	MOKJUO	08F03755	Primax Electronics Ltd.	-
ACCESSORY				
Equipment Name	Model Name	Serial No.	Manufacturer	Remarks
PoE Injector	SFC501G	N/A	Soltech Infonet Co., Ltd.	-
JIG board	MR9-V-0	N/A	N/A	-
Ear Phone	N/A	N/A	N/A	-
Notebook PC	H57	HKN650DU0007G00276	HANSUNG	-
Notebook PC Adapter	A10-090P3A	F180261621014661	Chicony	-
Network Camera	QND-8021	N/A	HANWHA TECHWIN CO.,LTD	-
Monitor #1	24BK550YW	902NTSU7P406	LG	-
Monitor #2	24BK550YW	902NTLE7P384	LG	-
USB Memory Stick #1	N/A	N/A	N/A	8 GB
USB Memory Stick #2	N/A	N/A	N/A	8 GB
HDD	SC HA500	WCC7K5JKX30E	Westem Digital	4 TB

2-6 Cable List

Cable List / REC mode (Adapter)						
From		To		Length (m)	Shielding	
Type	I/O Port	Type	I/O Port		Cable	backshell
EUT	AC IN	AC Power Source	3 Pin AC Line	1.2	NO	Plastic
	USB	Mouse	USB	1.0	NO	Plastic
	USB	USB Memory Stick #1	USB	-	-	Plastic
	USB	USB Memory Stick #2	USB	-	-	Plastic
	AUDIO OUT	Ear Phone	AUX	0.9	NO	Plastic
	NETWORK 1	PoE Injector	DATA IN	1.0	NO	Plastic
	NETWORK 2	Notebook PC	LAN	1.2	NO	Plastic
	VGA OUT	Monitor #1	VGA	1.2	YES	Plastic
	HDMI	Monitor #2	HDMI	1.1	YES	Plastic
	ALARM IN	JIG board	ALARM OUT	0.4	NO	Plastic
	ALARM OUT	JIG board	ALARM IN	0.4	NO	Plastic
	ALARM GROUND	JIG board	ALARM GROUND	0.4	NO	Plastic
PoE Injector	AC IN	AC Power Source	3 Pin AC Line	1.1	NO	Plastic
	P+D/OUT	Network Camera	LAN	1.0	NO	Plastic
Notebook PC	DC IN	Notebook PC Adapter	DC OUT	1.1	NO	Plastic
Notebook PC Adapter	AC IN	AC Power Source	3 Pin AC Line	1.0	NO	Plastic
Monitor #1	AC IN	AC Power Source	3 Pin AC Line	1.1	NO	Plastic
Monitor #2	AC IN	AC Power Source	3 Pin AC Line	1.3	NO	Plastic
HDD	DC IN	EUT	DC OUT	0.3	NO	Plastic
	SATA	EUT	SATA	0.3	NO	Plastic

3. Test Report

3.1 Summary of tests

Parameter	Applied Standard	Status
I. Emission		
Conducted Emissions	VCCI-CISPR 32:2016	C
Conducted Emissions at telecommunication ports	VCCI-CISPR 32:2016	C
Radiated Emissions	VCCI-CISPR 32:2016	C
Radiated Emissions at above 1 GHz	VCCI-CISPR 32:2016	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

4. EMISSION

4.1 Conducted Emissions

Definition:

The test assesses the ability of the EUT to limit its internal noise from being present on the AC mains Power In/Output/Telecommunication ports.

We were performed the test according to LTA procedure LTA-QI-04.

Test method	: VCCI-CISPR 32:2016
Measurement Frequency range	: 150 kHz - 30 MHz
Measurement RBW	: 9 kHz
Test mode	: REC mode
Result	: Complies

Measurement Data:

- Refer to the Next page (Maximum emission configuration)

A sample calculation:

COR. F (correction factor)= LISN Insertion loss + Cable loss + Pulse Limiter Factor

Emission Level= meter reading + COR.F

Limits for Conducted Emissions at the mains ports of class A ITE

Frequency Range	Quasi-peak	Average
(0.15 - 0.5) MHz	79 dB μ V	66 dB μ V
(0.5 – 30) MHz	73 dB μ V	60 dB μ V

Note: The limits will decrease with the frequency logarithmically within 0.15MHz to 0.5MHz

Limits for Conducted Emissions at the mains ports of class B ITE

Frequency Range	Quasi-peak	Average
(0.15 – 0.5) MHz	(66 – 56) dB μ V	(56 - 46) dB μ V
(0.5 – 5) MHz	56 dB μ V	46 dB μ V
(5 – 30) MHz	60 dB μ V	50 dB μ V

Note: The limits will decrease with the frequency logarithmically within 0.15 MHz to 0.5 MHz

Limits of conducted common mode (asymmetric mode) disturbance at telecommunication ports in the frequency range 0.15 MHz to 30 MHz for class A equipment

Frequency Range	Voltage limits		Current limits	
	Quasi-peak	Average	Quasi-peak	Average
(0.15 - 0.5) MHz	(97 – 87) dB μ V	(84 – 74) dB μ V	(53 – 43) dB μ V	(40 – 30) dB μ V
(0.5 – 30) MHz	87 dB μ V	74 dB μ V	43 dB μ V	30 dB μ V

Note 1: The limits decrease linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Note 2: The current and voltage disturbance limits are derived for use with an impedance stabilization network (ISN) which presents a common mode (asymmetric mode) impedance of 150 Ω to the telecommunication port under test (conversion factor is $20 \log_{10} 150/I = 44$ dB)

Limits of conducted common mode (asymmetric mode) disturbance at telecommunication ports in the frequency range 0.15 MHz to 30 MHz for class B equipment

Frequency Range	Voltage limits		Current limits	
	Quasi-peak	Average	Quasi-peak	Average
(0.15 - 0.5) MHz	(84 – 74) dB μ V	(74 – 64) dB μ V	(40 – 30) dB μ V	(30 – 20) dB μ V
(0.5 – 30) MHz	74 dB μ V	64 dB μ V	30 dB μ V	20 dB μ V

Note 1: The limits decrease linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Note 2: The current and voltage disturbance limits are derived for use with an impedance stabilization network (ISN) which presents a common mode (asymmetric mode) impedance of 150 Ω to the telecommunication port under test (conversion factor is $20 \log_{10} 150/I = 44$ dB)

Conducted Emissions (LINE)



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel: +82-31-3236008,9
Fax: +82-31-3236010

EUT /Model No. : XRN-1620B2


Phase : Line

Test Mode : REC mode

Test Power : 100 V / 50 Hz

Temp./ Humi. : 23 °C / 43 % R.H.

Test Engineer : NAM Y H



No.	Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB	Phase
2.	18.100	23.02	19.94	20.01	43.03	39.95	73.00	60.00	29.97	20.05	Line
4.	20.601	23.52	13.13	20.05	43.57	33.18	73.00	60.00	29.43	26.82	Line
6.	21.194	25.77	13.59	20.06	45.83	33.65	73.00	60.00	27.17	26.35	Line
8.	21.420	25.13	11.76	20.07	45.20	31.83	73.00	60.00	27.80	28.17	Line
10.	28.118	32.67	12.19	20.16	52.83	32.35	73.00	60.00	20.17	27.65	Line
12.	28.248	24.98	12.27	20.16	45.14	32.43	73.00	60.00	27.86	27.57	Line

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted Emissions (NEUTRAL)



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT /Model No. : XRN-1620B2


Phase : Neutral

Test Mode : REC mode

Test Power : 100 V / 50 Hz

Temp./ Humi. : 23 °C / 43 % R.H.

Test Engineer : NAM Y H



No.	Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB	Phase
2.	19.923	22.87	13.87	20.08	42.95	33.95	73.00	60.00	30.05	26.05	neutral
4.	20.796	24.68	12.24	20.09	44.77	32.33	73.00	60.00	28.23	27.67	neutral
6.	21.291	25.98	14.43	20.11	46.09	34.54	73.00	60.00	26.91	25.46	neutral
8.	21.798	25.06	12.38	20.12	45.18	32.50	73.00	60.00	27.82	27.50	neutral
10.	27.697	24.90	13.39	20.22	45.12	33.61	73.00	60.00	27.88	26.39	neutral
12.	28.160	25.46	12.21	20.24	45.70	32.45	73.00	60.00	27.30	27.55	neutral

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted Emissions (TEL_10 M) / LAN #1)



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT /Model No. : XRN-1620B2


Phase : TEL_10M

Test Mode : REC mode (LAN #1)

Test Power : 100 V / 50 Hz

Temp./ Humi. : 23 °C / 43 % R.H.

Test Engineer : NAM Y H



No.	Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB	Phase
2.	16.478	28.43	22.94	19.65	48.08	42.59	87.00	74.00	38.92	31.41	Line
4.	17.148	29.66	24.22	19.66	49.32	43.88	87.00	74.00	37.68	30.12	Line
6.	18.633	31.02	25.24	19.74	50.76	44.98	87.00	74.00	36.24	29.02	Line
8.	19.113	31.38	27.05	19.75	51.13	46.80	87.00	74.00	35.87	27.20	Line
10.	21.200	29.89	23.69	19.86	49.75	43.55	87.00	74.00	37.25	30.45	Line
12.	27.980	27.62	21.91	20.23	47.85	42.14	87.00	74.00	39.15	31.86	Line

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted Emissions (TEL_1000 M) / LAN #1)



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT /Model No. : XRN-1620B2

Phase : TEL_1000M


Test Mode : REC mode (LAN #1)

Test Power : 100 V / 50 Hz

Temp./ Humi. : 23 °C / 43 % R.H.

Test Engineer : NAM Y H

Date: 2020-10-29



No.	Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB	Phase
2.	17.516	27.01	21.99	19.55	46.56	41.54	87.00	74.00	40.44	32.46	Line
4.	18.273	27.33	22.58	19.56	46.89	42.14	87.00	74.00	40.11	31.86	Line
6.	19.517	30.96	25.90	19.60	50.56	45.50	87.00	74.00	36.44	28.50	Line
8.	20.385	30.41	26.09	19.60	50.01	45.69	87.00	74.00	36.99	28.31	Line
10.	21.102	30.73	27.22	19.62	50.35	46.84	87.00	74.00	36.65	27.16	Line
12.	23.940	28.37	23.85	19.69	48.06	43.54	87.00	74.00	38.94	30.46	Line

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted Emissions (TEL_10 M) / LAN #2)



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT /Model No. : XRN-1620B2


Phase : TEL_10M

Test Mode : REC mode (LAN #2)

Test Power : 100 V / 50 Hz

Temp./ Humi. : 23 °C / 43 % R.H.

Test Engineer : NAM Y H



No.	Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB	Phase
2.	17.858	30.41	25.59	19.70	50.11	45.29	87.00	74.00	36.89	28.71	Line
4.	20.255	31.60	27.98	19.80	51.40	47.78	87.00	74.00	35.60	26.22	Line
6.	24.577	27.21	21.48	20.04	47.25	41.52	87.00	74.00	39.75	32.48	Line
8.	25.580	26.70	21.18	20.09	46.79	41.27	87.00	74.00	40.21	32.73	Line
10.	26.709	27.67	22.17	20.15	47.82	42.32	87.00	74.00	39.18	31.68	Line
12.	27.451	27.91	22.46	20.21	48.12	42.67	87.00	74.00	38.88	31.33	Line

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted Emissions (TEL_1000 M) / LAN #2)



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

EUT /Model No. : XRN-1620B2


Phase : TEL_1000M

Test Mode : REC mode (LAN #2)

Test Power : 100 V / 50 Hz

Temp./ Humi. : 23 °C / 43 % R.H.

Test Engineer : NAM Y H



No.	Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB	Phase
2.	17.924	26.69	21.69	19.56	46.25	41.25	87.00	74.00	40.75	32.75	Line
4.	19.518	30.44	24.94	19.60	50.04	44.54	87.00	74.00	36.96	29.46	Line
6.	20.259	33.16	28.90	19.60	52.76	48.50	87.00	74.00	34.24	25.50	Line
8.	20.758	31.23	28.29	19.62	50.85	47.91	87.00	74.00	36.15	26.09	Line
10.	23.066	29.58	24.10	19.67	49.25	43.77	87.00	74.00	37.75	30.23	Line
12.	23.229	26.10	21.31	19.67	45.77	40.98	87.00	74.00	41.23	33.02	Line

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

4.2 Radiated Emissions

Definition:

The test assesses the ability of ancillary equipment to limit their internal noise from being radiated from the enclosure.

We were performed the test according to LTA procedure LTA-QI-04.

Test method	: VCCI-CISPR 32:2016
Measuring Distance	: 10 m below 1 GHz / 3 m above 1 GHz
Measurement Frequency range	: 30 MHz – 6 000 MHz
Measurement RBW	: 120 kHz @ 10 m / 1 MHz @ 3 m
Test mode	: REC mode
Result	: Complies

Measurement Data:

- Refer to the Next page (Maximum emission configuration)
- The highest internal source of an EUT is higher than 108 MHz, the measurement shall only be made up to 6 GHz.
(The highest internal source of an EUT : 1.8 GHz)

A sample calculation:

COR. F (correction factor)= Antenna factor + Cable loss- Amp.gain- Distance correction

Emission Level= meter reading + COR.F

Limit of 10 m below 1 GHz

CLASS A

Frequency Range	Quasi-peak
(30 – 230) MHz	40 dB μ V/m
(230 – 1 000) MHz	47 dB μ V/m

CLASS B

Frequency Range	Quasi-peak
(30 – 230) MHz	30 dB μ V/m
(230 – 1 000) MHz	37 dB μ V/m

Limit of 3m above 1 GHz

CLASS A

Frequency Range	Average Limit @ 3m (dB μ V/m)	Peak limit @ 3m (dB μ V/m)
(1 000 – 3 000) MHz	56	76
(3 000 – 6 000) MHz	60	80

NOTE: The lower limit applies at the transition frequency.

CLASS B

Frequency Range	Average Limit @ 3m (dB μ V/m)	Peak limit @ 3m (dB μ V/m)
(1 000 – 3 000) MHz	50	70
(3 000 – 6 000) MHz	54	74

NOTE: The lower limit applies at the transition frequency.

Radiated Emissions (Below 1 GHz) / V



4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com


EUT/Model No.: XRN-1620B2

Temp/Humi: 21 'C / 43 % R.H.

Test Mode : REC mode

Tested by: NAM Y H

Power : 100 V / 50 Hz



No.	Freq MHz	Reading dBuV	C.F dB	Result QP dBuV/m	Limit dBuV/m	Margin dB	Height cm	Angle deg	Polarity
1.	77.19	49.85	-16.94	32.91	40.00	7.09	136	15	vertical
2.	81.21	50.78	-17.72	33.06	40.00	6.94	215	13	vertical
3.	203.79	49.80	-14.97	34.83	40.00	5.17	158	69	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions (Below 1 GHz) / H



4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com


EUT/Model No.: XRN-1620B2

Temp/Humi: 21 'C / 43 % R.H.

Test Mode : REC mode

Tested by: NAM Y H

Power : 100 V / 50 Hz



No.	Freq MHz	Reading dBμV	C.F dB	Result QP dBμV/m	Limit dBμV/m	Margin dB	Height cm	Angle deg	Polarity
1.	172.15	44.55	-13.10	31.45	40.00	8.55	399	10	horizontal
2.	178.84	45.76	-13.65	32.11	40.00	7.89	385	24	horizontal
3.	203.26	48.94	-14.99	33.95	40.00	6.05	374	71	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions

(Above 1 GHz) / V


EUT/Model No.: XRN-1620B2

Temp/Humi: 21 °C / 43 % R.H.

Test Mode : REC mode

Tested by: NAM Y H

Power : 100 V / 50 Hz



(Above 1 GHz) / H


EUT/Model No.: XRN-1620B2

Temp/Humi: 21 °C / 43 % R.H.

Test Mode : REC mode

Tested by: NAM Y H

Power : 100 V / 50 Hz



Manufacture : HANWHA TECHWIN SECURITY VIETNAM CO.,LTD.
D-TECH CO.,LTD.

Test Date	Temp.: [°C]	Humidity: [%]	Distance (m)
2020-11-03	21.00	43.00	3.8

Model : XRN-1620B2

TEST mode : REC mode

Frequency MHz	Reading(PK) dBUV	Reading(AV) dBUV	C.F dB	Result(PK) dBUV/m	Result(AV) dBUV/m	Limit(PK) dBUV/m	Limit(AV) dBUV/m	Margin(PK) dB	Margin(AV) dB	Height cm	Angle deg	Polarity H/V
1349.72	63.93	44.93	-4.76	59.17	40.17	76.00	56.00	16.83	15.83	100	151	H
1754.86	57.21	40.21	-1.43	55.78	38.78	76.00	56.00	20.22	17.22	100	163	H
1889.90	57.80	40.80	-0.10	57.70	40.70	76.00	56.00	18.30	15.30	100	138	H
1350.02	59.37	41.37	-4.76	54.61	36.61	76.00	56.00	21.39	19.39	100	171	V
1889.90	56.77	38.77	-0.10	56.67	38.67	76.00	56.00	19.33	17.33	100	146	V
2639.75	51.10	34.10	2.94	54.04	37.04	76.00	56.00	21.96	18.96	100	343	V

APPENDIX A

TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment are identified by the Test Laboratory.

Conducted Emissions

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
☒	EMI TEST Receiver	ESR	Rohde & Schwarz	101499	2021.07.02	1 year
☒	Pulse Limiter	ESH3-Z2	Rohde & Schwarz	100710	2021.03.16	1 year
☐	ISN	ISN T800	TESEQ	27109	2021.09.07	1 year
☒	ISN	ENY81-CA6	Rohde & Schwarz	101565	2021.09.07	1 year
☒	ISN	ISN S8	Schwarzbeck	79	2021.09.04	1 year
☐	CURRENT PROBE	EZ-17	Rohde & Schwarz	100508	2021.09.03	1 year
☐	CDN	TSCDN-C1-BNC-75	F.C.C	07004	2021.05.08	1 year
☐	LISN	ESH3-Z6	Rohde & Schwarz	100378	2021.09.03	1 year
☐	LISN	ESH3-Z6	Rohde & Schwarz	101468	2021.09.03	1 year
☒	LISN(main)	ENV216	Rohde & Schwarz	100408	2021.09.04	1 year
☒	LISN(sub)	LT32C/10	AFJ	32031518210	2021.09.03	1 year
☒	TEST PROGRAM	e3_ce 20181212a (V9)	AUDIX	-	-	-

Radiated Emissions – Below 1 GHz

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
☒	EMI TEST Receiver	ESU	Rohde & Schwarz	100092	2021.09.03	1 year
☒	Amplifier (25 dB)	8447D	HP	2944A07684	2021.03.16	1 year
☒	BILOG Antenna	VULB 9168	SCHWARZBECK	775	2021.03.26 (KOLAS)	2 year
☐	BILOG Antenna	VULB 9168	SCHWARZBECK	775	2021.11.12 (RRA)	2 year
☒	TEST PROGRAM	e3 20181212a (V9)	AUDIX	-	-	-

Radiated Emissions – Above 1 GHz

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
☒	EMI TEST Receiver	ESU	Rohde & Schwarz	100092	2021.09.03	1 year
☒	Amplifier	8449B	Agilent	3008A02126	2021.03.17	1 year
☐	Amplifier	PAM-840A	COM-POWER	461314	2021.03.16	1 year
☐	HORN ANTENNA	3116B	ETS	133350	2022.05.12	2 year
☐	HORN ANTENNA	3116B	ETS	81109	2022.05.12	2 year
☒	HORN ANTENNA	3115	ETS	114105	2021.09.17 (KOLAS)	2 year
☐	HORN ANTENNA	3115	ETS	114105	2021.11.11 (RRA)	2 year
☒	TEST PROGRAM	e3 20181212a (V9)	AUDIX	-	-	-

APPENDIX B

PHOTOGRAPHS

Conducted Emissions





Conducted Emissions (TEL)



Radiated Emissions - Below 1 GHz



Radiated Emissions - Above 1 GHz



EUT



EUT

