



4, Songju-ro 236beon-gil, Yangji-myeon, Cheoin-gu, Yongin-si, Gyeonggi-do,
17159, Korea

Tel: +82-31-323-6008 Fax: +82-31-323-6010

<http://www.ltalab.com>

EMC TEST REPORT

Dates of Tests: June 13 - 17, 2025

Project No: 250609-0861

Test Site : LTA Co., Ltd.

Model No.

CGR-3210B1

APPLICANT

Hanwha Vision Co., Ltd

Equipment Name : Cloud Gateway Recorder
Manufacturer : Hanwha Vision Co., Ltd
Model Name : CGR-3210B1
Additional Model Name : -
Test Device Serial No.: : Identification
Rule Part(s) : VCCI-CISPR 32:2016

Date of issue : July 01, 2025

This test report is issued under the authority of:

The test was supervised by:

Young Kyu Shin, Technical Manager

Min Su Han, Test Engineer

This test result only responds to the tested sample. It is not allowed to copy this report even partly without the allowance of the test laboratory.

This test report is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.

Revision history

Revision	Date of issue	Test report No.	Description
0	01.07.2025	LR500172507D	Initial

TABLE OF CONTENTS

1. General information’s4

2. Information’s about test item5

3. Test Report8

 3.1 Summary of tests8

4. EMISSION.....9

 4.1 Conducted Emissions9

 4.2 Radiated Emissions19

APPENDIX A TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS.....29

APPENDIX B PHOTOGRAPHS31

1. General information's

1-1 Test Performed

Company name : **LTA Co., Ltd**
 Address : 4, Songju-ro 236beon-gil, Yangji-myeon, Cheoin-gu, Yongin-si, Gyeonggi-do, 17159, Korea
 Web site : <http://www.ltalab.com>
 E-mail : chahn@ltalab.com
 Telephone : +82-31-323-6008
 Facsimile : +82-31-323-6010

Quality control in the testing laboratory is implemented as per ISO/IEC 17025 which “General requirements for the competents of calibration and testing laboratory”.

1-2 Accredited agencies

LTA Co., Ltd. is approved to perform EMC testing by the following agencies:

Agency	Country	Accreditation No.	Validity	Reference
RRA	KOREA		-	RRA accredited Lab.
	U.S.A	KR0049	2027-02-27	
	CANADA		2026-08-05	
VCCI	JAPAN	C-14948	2026-09-10	VCCI registration
		T-12416	2026-09-10	
		R-14483	2026-10-15	
		G-10847	2027-12-13	
KOLAS	KOREA	KT551	2025-10-12	KOLAS accredited Lab.

2. Information's about test item

2-1 Client / Manufacturer

Company name : Hanwha Vision Co., Ltd
 Address : 6, Pangyo-ro 319 Beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, 13488, KOREA
 Telephone /Facsimile : +82-10-2667-4196 / +82-70-7147-8361

Factory #1

Company name : HANWHA VISION VIETNAM COMPANY LIMITED
 Address : Lot O-2, Que Vo Industrial Zone extended area ,Nam Son commune, Bac Ninh city,Bac Ninh province, Vietnam

Factory #2

Company name : D-TECH CO.,LTD.
 Address : 173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi-do, Korea (Suwon Industrial Complex)

2-2 Equipment Under Test (EUT)

Class : A
 Category : Cloud Gateway Recorder
 Model Name : CGR-3210B1
 Additional Model Name : -
 Serial number : Identification
 Date of receipt : June 09, 2025
 EUT condition : Pre-production, not damaged
 Interface ports : AC IN, WAN, LAN, GROUND
 Engineer Port: USB #1~4, HDMI, DP, Console
 Unused Port: AUDIO OUT
 Power rating : AC 100 V, 50, 60 Hz

2-3 Modification

- None

2-4 Test conditions

Tested Model : CGR-3210B1
 Test mode : Operating mode
 Test Voltage : AC 100 V, 50, 60 Hz

2-5 List of EUT and ACCESSORY

EUT				
Equipment Name	Model Name	Serial No.	Manufacturer	Remarks
Cloud Gateway Recorder	CGR-3210B1	N/A	HANWHA VISION VIETNAM COMPANY LIMITED D-TECH CO., LTD.	EUT
ACCESSORY				
Equipment Name	Model Name	Serial No.	Manufacturer	Remarks
VIEWER	N/A	N/A	HANWHA VISION VIETNAM COMPANY LIMITED D-TECH CO.,LTD.	-
CAMERA	XNO-8030RP	ZEQD6V2J2 0008X	HANWHA TECHWIN CO., TLD	-
MONITOR	N/A	N/A	SAMSUNG	-
POE ADAPTER	SFC501G	S058512049 3936	Shenzhen Gospell Digital Technology Co.Ltd	-
KEYBOARD	N/A	N/A	N/A	-
MOUSE	N/A	N/A	N/A	-

2-6 Cable List

Cable List					
From		To		Length (m)	Shield
Type	I/O Port	Type	I/O Port		
EUT	AC IN	AC POWER SOURCE	AC OUT	1.5	NO
	WAN	VIEWER	WAN	3.0	NO
	LAN	POE ADAPTER	LAN	3.0	NO
	GROUND	GROUND	GROUND	1.0	NO
VIEWER	AC IN	AC POWER SOURCE	AC OUT	1.5	NO
	USB #1	KEYBOARD	USB	1.2	NO
	USB #2	MOUSE	USB	1.2	NO
	HDMI	MONITOR	HDMI	1.3	YES
POE ADAPTER	AC IN	AC POWER SOURCE	AC OUT	1.5	NO
	POE	CAMERA	POE	3.0	NO
MONITOR	AC IN	AC POWER SOURCE	AC OUT	1.4	NO

3. Test Report

3.1 Summary of tests

Parameter	Applied Standard	Status
I. Emission		
Conducted Emissions	VCCI-CISPR 32:2016	C
Conducted Emissions at telecommunication ports	VCCI-CISPR 32:2016	C
Radiated Emissions	VCCI-CISPR 32:2016	C
Radiated Emissions at above 1 GHz	VCCI-CISPR 32:2016	C

Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable

Note 2: The data in this test report are traceable to the national or international standards.

4. EMISSION

4.1 Conducted Emissions

Definition:

The test assesses the ability of the EUT to limit its internal noise from being present on the AC mains Power In/Output/Telecommunication ports.

We were performed the test according to LTA procedure LTA-QI-04.

Test method	: VCCI-CISPR 32:2016
Measurement Frequency range	: 150 kHz - 30 MHz
Measurement RBW	: 9 kHz
Test Location	: Shielded Room
Test mode	: Operating mode
Result	: Complies

Measurement Data:

- Refer to the Next page (Maximum emission configuration)

A sample calculation:

COR. F (correction factor)= LISN Insertion loss + Cable loss + Pulse Limiter Factor

Emission Level= meter reading + COR.F

Limits for Conducted Emissions at the mains ports of class A ITE

Frequency Range	Quasi-peak	Average
(0.15 - 0.5) MHz	79 dB μ V	66 dB μ V
(0.5 – 30) MHz	73 dB μ V	60 dB μ V

Note: The limits will decrease with the frequency logarithmically within 0.15MHz to 0.5MHz

Limits for Conducted Emissions at the mains ports of class B ITE

Frequency Range	Quasi-peak	Average
(0.15 – 0.5) MHz	(66 – 56) dB μ V	(56 - 46) dB μ V
(0.5 – 5) MHz	56 dB μ V	46 dB μ V
(5 – 30) MHz	60 dB μ V	50 dB μ V

Note: The limits will decrease with the frequency logarithmically within 0.15 MHz to 0.5 MHz

Limits of conducted common mode (asymmetric mode) disturbance at telecommunication ports in the frequency range 0.15 MHz to 30 MHz for class A equipment

Frequency Range	Voltage limits		Current limits	
	Quasi-peak	Average	Quasi-peak	Average
(0.15 - 0.5) MHz	(97 – 87) dB μ V	(84 – 74) dB μ V	(53 – 43) dB μ V	(40 – 30) dB μ V
(0.5 – 30) MHz	87 dB μ V	74 dB μ V	43 dB μ V	30 dB μ V

Note 1: The limits decrease linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Note 2: The current and voltage disturbance limits are derived for use with an impedance stabilization network (ISN) which presents a common mode (asymmetric mode) impedance of 150 Ω to the telecommunication port under test (conversion factor is $20 \log_{10} 150/I = 44$ dB)

Limits of conducted common mode (asymmetric mode) disturbance at telecommunication ports in the frequency range 0.15 MHz to 30 MHz for class B equipment

Frequency Range	Voltage limits		Current limits	
	Quasi-peak	Average	Quasi-peak	Average
(0.15 - 0.5) MHz	(84 – 74) dB μ V	(74 – 64) dB μ V	(40 – 30) dB μ V	(30 – 20) dB μ V
(0.5 – 30) MHz	74 dB μ V	64 dB μ V	30 dB μ V	20 dB μ V

Note 1: The limits decrease linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.


Note 2: The current and voltage disturbance limits are derived for use with an impedance stabilization network (ISN) which presents a common mode (asymmetric mode) impedance of 150 Ω to the telecommunication port under test (conversion factor is $20 \log_{10} 150/I = 44$ dB)

Conducted Emissions (LINE) / 50 Hz



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

Project No.	: 250609-0861	Phase	: Line
Test Mode	: Operating	Test Power	: AC 100 V / 50 Hz
Temp./ Humi.	: 23 'C / 41 % R.H.	Test Engineer	: HAN M S



No.	Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB	Phase
2.	9.892	17.74	12.42	19.83	37.57	32.25	73.00	60.00	35.43	27.75	Line
4.	10.903	22.30	17.03	19.85	42.15	36.88	73.00	60.00	30.85	23.12	Line
6.	13.692	18.85	14.65	19.92	38.77	34.57	73.00	60.00	34.23	25.43	Line


Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted Emissions (NEUTRAL) / 50 Hz



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

Project No.	: 250609-0861	Phase	: Neutral
Test Mode	: Operating	Test Power	: AC 100 V / 50 Hz
Temp./ Humi.	: 23 'C / 41 % R.H.	Test Engineer	: HAN M S



No.	Freq MHz	RD QP dBμV	RD AV dBμV	C.F dB	Result QP dBμV	Result AV dBμV	Limit QP dBμV	Limit AV dBμV	Margin QP dB	Margin AV dB	Phase
2.	7.099	14.34	11.34	19.75	34.09	31.09	73.00	60.00	38.91	28.91	neutral
4.	7.860	15.11	9.95	19.78	34.89	29.73	73.00	60.00	38.11	30.27	neutral
6.	11.409	16.64	10.67	19.89	36.53	30.56	73.00	60.00	36.47	29.44	neutral


Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted Emissions (LINE) / 60 Hz



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

Project No.	: 250609-0861	Phase	: Line
Test Mode	: Operating	Test Power	: AC 100 V / 60 Hz
Temp./ Humi.	: 23 'C / 41 % R.H.	Test Engineer	: HAN M S



No.	Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB	Phase
2.	9.511	17.21	12.76	19.82	37.03	32.58	73.00	60.00	35.97	27.42	Line
4.	10.777	22.16	16.95	19.85	42.01	36.80	73.00	60.00	30.99	23.20	Line
6.	13.692	18.63	14.37	19.92	38.55	34.29	73.00	60.00	34.45	25.71	Line


Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted Emissions (NEUTRAL) / 60 Hz



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

Project No.	: 250609-0861	Phase	: Neutral
Test Mode	: Operating	Test Power	: AC 100 V / 60 Hz
Temp./ Humi.	: 23 'C / 41 % R.H.	Test Engineer	: HAN M S



No.	Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB	Phase
2.	7.481	15.02	11.40	19.76	34.78	31.16	73.00	60.00	38.22	28.84	neutral
4.	11.030	17.62	11.35	19.88	37.50	31.23	73.00	60.00	35.50	28.77	neutral
6.	12.237	15.80	11.34	19.90	35.70	31.24	73.00	60.00	37.30	28.76	neutral


Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted Emissions (TEL_1000 M (LAN)) / 50 Hz



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

Project No.	: 250609-0861	Phase	: TEL_1000M (LAN)
Test Mode	: Operating	Test Power	:
Temp./ Humi.	: 23 'C / 41 % R.H.	Test Engineer	: HAN M S



No.	Freq MHz	RD QP dBμV	RD AV dBμV	C.F dB	Result QP dBμV	Result AV dBμV	Limit QP dBμV	Limit AV dBμV	Margin QP dB	Margin AV dB	Phase
2.	1.809	35.02	24.71	19.22	54.24	43.93	87.00	74.00	32.76	30.07	Line
4.	6.694	38.93	29.21	19.29	58.22	48.50	87.00	74.00	28.78	25.50	Line
6.	7.315	36.50	25.37	19.30	55.80	44.67	87.00	74.00	31.20	29.33	Line


Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted Emissions (TEL_1000 M (WAN)) / 50 Hz



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

Project No.	: 250609-0861	Phase	: TEL_1000M (WAN)
Test Mode	: Operating	Test Power	:
Temp./ Humi.	: 23 'C / 41 % R.H.	Test Engineer	: HAN M S



No.	Freq MHz	RD QP dBμV	RD AV dBμV	C.F dB	Result QP dBμV	Result AV dBμV	Limit QP dBμV	Limit AV dBμV	Margin QP dB	Margin AV dB	Phase
2.	7.511	30.69	18.96	19.31	50.00	38.27	87.00	74.00	37.00	35.73	Line
4.	11.161	26.43	18.03	19.41	45.84	37.44	87.00	74.00	41.16	36.56	Line
6.	28.013	28.26	23.85	19.75	48.01	43.60	87.00	74.00	38.99	30.40	Line


Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted Emissions (TEL_1000 M (LAN)) / 60 Hz



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

Project No.	: 250609-0861	Phase	: TEL_1000M (LAN)
Test Mode	: Operating	Test Power	:
Temp./ Humi.	: 23 'C / 41 % R.H.	Test Engineer	: HAN M S



No.	Freq MHz	RD QP dBμV	RD AV dBμV	C.F dB	Result QP dBμV	Result AV dBμV	Limit QP dBμV	Limit AV dBμV	Margin QP dB	Margin AV dB	Phase
2.	1.809	35.02	24.71	19.22	54.24	43.93	87.00	74.00	32.76	30.07	Line
4.	6.694	38.93	29.21	19.29	58.22	48.50	87.00	74.00	28.78	25.50	Line
6.	7.315	36.50	25.37	19.30	55.80	44.67	87.00	74.00	31.20	29.33	Line


Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

Conducted Emissions (TEL_1000 M (WAN)) / 60 Hz



4, Songjuro 236 Beon-gil, Yangji-myeon
Cheoin-gu, Youngin-si, Gyeonggi-do
449-822 Korea
Tel:+82-31-3236008,9
Fax:+82-31-3236010

Project No.	: 250609-0861	Phase	: TEL_1000M (WAN)
Test Mode	: Operating	Test Power	:
Temp./ Humi.	: 23 'C / 41 % R.H.	Test Engineer	: HAN M S



No.	Freq MHz	RD QP dBuV	RD AV dBuV	C.F dB	Result QP dBuV	Result AV dBuV	Limit QP dBuV	Limit AV dBuV	Margin QP dB	Margin AV dB	Phase
2.	7.511	30.69	18.96	19.31	50.00	38.27	87.00	74.00	37.00	35.73	Line
4.	11.161	26.43	18.03	19.41	45.84	37.44	87.00	74.00	41.16	36.56	Line
6.	28.013	28.26	23.85	19.75	48.01	43.60	87.00	74.00	38.99	30.40	Line

Remarks: C.F (Correction Factor) = Insertion loss + Cable loss + Pulse Limiter

4.2 Radiated Emissions

Definition:

The test assesses the ability of ancillary equipment to limit their internal noise from being radiated from the enclosure.

We were performed the test according to LTA procedure LTA-QI-04.

Test method	: VCCI-CISPR 32:2016
Measuring Distance	: 10 m below 1 GHz / 3 m above 1 GHz
Measurement Frequency range	: 30 MHz – 6 000 MHz
Measurement RBW	: 120 kHz @ 10 m / 1 MHz @ 3 m
Test Location	: 10 m Chamber
Test mode	: Operating mode
Result	: Complies

Measurement Data:

- Refer to the Next page (Maximum emission configuration)
- The highest internal source of an EUT is 108 MHz, the measurement shall only be made up to 6 GHz.

A sample calculation:

COR. F (correction factor)= Antenna factor + Cable loss- Amp.gain- Distance correction

Emission Level= meter reading + COR.F

Limit of 10 m below 1 GHz

CLASS A

Frequency Range	Quasi-peak
(30 – 230) MHz	40 dB μ V/m
(230 – 1 000) MHz	47 dB μ V/m

CLASS B

Frequency Range	Quasi-peak
(30 – 230) MHz	30 dB μ V/m
(230 – 1 000) MHz	37 dB μ V/m

Limit of 3m above 1 GHz

CLASS A

Frequency Range	Average Limit @ 3m (dB μ V/m)	Peak limit @ 3m (dB μ V/m)
(1 000 – 3 000) MHz	56	76
(3 000 – 6 000) MHz	60	80

NOTE: The lower limit applies at the transition frequency.

CLASS B

Frequency Range	Average Limit @ 3m (dB μ V/m)	Peak limit @ 3m (dB μ V/m)
(1 000 – 3 000) MHz	50	70
(3 000 – 6 000) MHz	54	74

NOTE: The lower limit applies at the transition frequency.

Radiated Emissions (Below 1 GHz) / H / 50 Hz



4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com


Project No. : 250609-0861

Temp/Humi: 23 'C / 43 % R.H.

Test Mode : Operating

Tested by: HAN M S

Power : AC 100 V / 50 Hz



Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions (Below 1 GHz) / V / 50 Hz



4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com


Project No. : 250609-0861

Temp/Humi: 23 'C / 43 % R.H.

Test Mode : Operating

Tested by: HAN M S

Power : AC 100 V / 50 Hz



Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions (Below 1 GHz) / H / 60 Hz




4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

Project No. : 250609-0861 Temp/Humi: 23 'C / 43 % R.H.

Test Mode : Operating Tested by: HAN M S

Power : AC 100 V / 60 Hz



Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions (Below 1 GHz) / V / 60 Hz




4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

Project No. : 250609-0861 Temp/Humi: 23 'C / 43 % R.H.

Test Mode : Operating Tested by: HAN M S

Power : AC 100 V / 60 Hz




Remarks: C.F (Correction Factor) = Antenna factor + Cable loss - Preamp gain

Radiated Emissions (Above 1 GHz) / H / 50 Hz



4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

Project No.	: 250609-0861	Temp/Humi:	23 'C / 43 % R.H.
Test Mode	: Operating	Tested by:	HAN M S
Power	: AC 100 V / 50 Hz	Measure distance :	3.9 m




Radiated Emissions (Above 1 GHz) / V / 50 Hz



4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

Project No.	: 250609-0861	Temp/Humi:	23 'C / 43 % R.H.
Test Mode	: Operating	Tested by:	HAN M S
Power	: AC 100 V / 50 Hz	Measure distance :	3.9 m



No.	Freq	RD	RD	C.F	Result	Result	Limit	Limit	Margin	Margin	Height	Angle	Polarity
	MHz	PK	AV	dB	PK	AV	PK	AV	PK	AV	cm	deg	
2.	1055.63	45.34	35.13	-4.71	40.63	30.42	76.00	56.00	35.37	25.58	100	88	vertical
4.	1101.25	45.70	34.82	-4.44	41.26	30.38	76.00	56.00	34.74	25.62	100	207	vertical
6.	1200.00	45.43	34.97	-3.34	42.09	31.63	76.00	56.00	33.91	24.37	100	227	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss + Measure distance - Preamp gain

Radiated Emissions (Above 1 GHz) / H / 60 Hz



4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

Project No. : 250609-0861


Temp/Humi: 23 'C / 43 % R.H.

Test Mode : Operating

Tested by: HAN M S

Power : AC 100 V / 60 Hz

Measure distance : 3.9 m



No.	Freq MHz	RD		C.F	Result		Limit		Margin		Height	Angle	Polarity
		PK dBuV	AV dBuV		PK dBuV	AV dBuV	PK dBuV	AV dBuV	PK dB	AV dB			
2.	1139.38	52.12	41.68	-4.28	47.84	37.40	76.00	56.00	28.16	18.60	100	290	horizontal
4.	1194.38	46.34	35.31	-3.44	42.90	31.87	76.00	56.00	33.10	24.13	100	290	horizontal
6.	1268.75	43.98	34.95	-2.66	41.32	32.29	76.00	56.00	34.68	23.71	100	22	horizontal

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss + Measure distance - Preamp gain

Radiated Emissions (Above 1 GHz) / V / 60 Hz



4, Songjuro 236Beon-gil, yanggi-myeon,
Yongin-si, Gyeonggi-do, Korea
Tel : +82-31-3236008,9
Fax : +82-31-3236010
www.ltalab.com

Project No. : 250609-0861


Temp/Humi: 23 'C / 43 % R.H.

Test Mode : Operating

Tested by: HAN M S

Power : AC 100 V / 60 Hz

Measure distance : 3.9 m



No.	Freq MHz	RD		C.F dB	Result		Limit		Margin		Height cm	Angle deg	Polarity
		PK dBuV	AV dBuV		PK dBuV	AV dBuV	PK dBuV	AV dBuV	PK dB	AV dB			
2.	1173.75	47.59	35.99	-3.81	43.78	32.18	76.00	56.00	32.22	23.82	100	241	vertical
4.	1215.63	47.19	36.41	-3.15	44.04	33.26	76.00	56.00	31.96	22.74	100	322	vertical
6.	2986.25	37.87	25.13	7.67	45.54	32.80	76.00	56.00	30.46	23.20	100	282	vertical

Remarks: C.F (Correction Factor) = Antenna factor + Cable loss + Measure distance - Preamp gain

APPENDIX A

TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

To facilitate inclusion on each page of the test equipment used for related tests, each item of test equipment are identified by the Test Laboratory.

Conducted Emissions

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
☒	EMI TEST Receiver	ESR	Rohde & Schwarz	101499	2026.03.05	1 year
☒	Pulse Limiter	ESH3-Z2	Rohde & Schwarz	100710	2026.03.05	1 year
☐	ISN	ISN T800	TESEQ	27109	2025.08.22	1 year
☒	ISN	ENY81-CA6	Rohde & Schwarz	101565	2025.08.22	1 year
☐	ISN	ISN S8	Schwarzbeck	79	2025.08.19	1 year
☐	CURRENT PROBE	EZ-17	Rohde & Schwarz	100508	2025.08.19	1 year
☐	CDN	TSCDN-C1-BNC-75	F.C.C	07004	2026.03.05	1 year
☐	LISN	ESH3-Z6	Rohde & Schwarz	100378	2025.08.19	1 year
☐	LISN	ESH3-Z6	Rohde & Schwarz	101468	2025.08.19	1 year
☒	LISN(main)	ENV216	Rohde & Schwarz	102872	2025.08.19	1 year
☒	LISN(sub)	LT32C/10	AFJ	32031518210	2025.08.19	1 year
☒	TEST PROGRAM	e3_ce 20181212a (V9)	AUDIX	-	-	-

Radiated Emissions – Below 1 GHz

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
☒	EMI TEST Receiver	ESCI7	Rohde & Schwarz	100772	2025.08.19	1 year
☒	Amplifier	310N	SONOMA INSTRUMENT	240504	2026.03.11	1 year
☒	BILOG Antenna	VULB 9168	SCHWARZBECK	749	2027.03.13	2 year
☒	TEST PROGRAM	e3 20181212a (V9)	AUDIX	-	-	-


Radiated Emissions – Above 1 GHz

	Item	Model Name	Manufacturer	Serial No.	Next Cal.	Interval
☒	EMI TEST Receiver	ESCI7	Rohde & Schwarz	100772	2025.08.19	1 year
☒	Amplifier	8449B	Agilent	3008A02126	2026.03.05	1 year
☒	HORN ANTENNA	3115	ETS	114105	2026.03.24	1 year
☒	TEST PROGRAM	e3 20181212a (V9)	AUDIX	-	-	-


APPENDIX B

PHOTOGRAPHS



Conducted Emissions





Conducted Emissions (TEL)



Radiated Emissions - Below 1 GHz



Radiated Emissions - Above 1 GHz



EUT



EUT

