

HCB-7000A



Analog

Корпусные

HCB-7000A

QHD (4МП) аналоговая корпусная камера



Key Features

- Разрешение QHD (2560 x 1440, 30 кад/с)
- 0,16 лк при F1.2 (цветн.), 0,009 лк при F1.2 (Ч/Б)
- Дневной и ночной (с выдвижным ИК-фильтром) режимы, DWDR, обнаружение движения
- Дальность передачи макс. 500 м
- Простая установка (Plug & play), двойное питание

Compatible Devices



SHB-4200H



SHB-4200



SHB-4301HP



STB-4150V



SHB-4300H1

HCB-7000A

QHD (4МП) аналоговая корпусная камера



Specifications

Video

Imaging Device	Size	1/3"
	Type	CMOS
Resolution		2560x1440
Max. Framerate(NTSC/PAL)		30fps/25fps
Min. Illumination	Color(1/30sec, 30IRE)	0.16
	BW(1/30sec, 30IRE)	0.009
Video Out		CVBS: 1.0Vp-p / 75Ω composite, 720x480(N), 720x576(P) for installation, BNC: AHD
Video Transmission Distance		500m(5C2V Coaxial Cable)

Lens

Focus Control	Manual
Lens Type	DC auto iris(IR corrected)
Mount Type	C mount, CS mount

Operational

Day & Night		Auto(ICR)
Backlight Compensation		BLC, HLC, DWDR
Digital Noise Reduction		2DDNR
Motion Detection	Quantity	4ea
Privacy Masking	Quantity	2ea
Gain Control		Low, Middle, High, Very High
White Balance		ATW, AWC, Manual, Indoor, Outdoor
Electronic Shutter	Speed Range	1/30~1/12,000sec(N), 1/25~1/12,000sec(P)
Video Rotation		Flip, Mirror
Serial Interface		RS-485
Alarm Interface	In/Out	Output 1ea
Coaxial Protocol		ACP, CVBS

Analytics

Analytics Events	Normal	Motion detection
------------------	--------	------------------

Environmental & Electrical

Operating Condition	Temperature	-10°C~+55°C(+14°F~+131°F)
	Humidity	0~90% RH(non-condensing)
Input Voltage		24VAC, 12VDC
Power Consumption	12VDC	Max 3.6W
	24VAC	Max 3.6W

Mechanical

Color	Ivory, Black
Material	Aluminum, PC(Polycarbonate)
Product Dimensions	59.6x68.4x92.7mm(2.35x2.69x3.65")
Product Weight	186g(0.41lb)

※ HCB-7000 has been renamed to HCB-7000A. HCB-7000 and HCB-7000A are the same model.

HCB-7000A

QHD (4МП) аналоговая корпусная камера



CAD

Unit: mm [inch]

