

HCB-7000A



Analog

BOX

HCB-7000A

4MP Wisenet HD+ Box Camera



Key Features

- QHD (2560 x 1440, 30fps) resolution
- 0.16 Lux@F1.2 (Color), 0.009 Lux@F1.2 (B/W)
- Day & Night (ICR), DWDR, Motion detection
- Transmission distance Max. 500m
- Easy installation (Plug & play), Dual power

HCB-7000A

4MP Wisenet HD+ Box Camera



Specifications

Video

Imaging Device	Size	1/3"
	Type	CMOS
Resolution		2560x1440
Max. Framerate(NTSC/PAL)		30fps/25fps
Min. Illumination	Color(1/30sec, 30IRE)	0.16
	BW(1/30sec, 30IRE)	0.009
Video Out		CVBS: 1.0Vp-p / 75Ω composite, 720x480(N), 720x576(P) for installation, BNC: AHD
Video Transmission Distance		500m(5C2V Coaxial Cable)

Lens

Focus Control	Manual
Lens Type	DC auto iris(IR corrected)
Mount Type	C mount, CS mount

Operational

Day & Night		Auto(ICR)
Backlight Compensation		BLC, HLC, DWDR
Digital Noise Reduction		2DDNR
Motion Detection	Quantity	4ea
Privacy Masking	Quantity	2ea
Gain Control		Low, Middle, High, Very High
White Balance		ATW, AWC, Manual, Indoor, Outdoor
Electronic Shutter	Speed Range	1/30~1/12,000sec(N), 1/25~1/12,000sec(P)
Video Rotation		Flip, Mirror
Serial Interface		RS-485
Alarm Interface	In/Out	Output 1ea
Coaxial Protocol		ACP, CVBS

Analytics

Analytics Events	Normal	Motion detection
------------------	--------	------------------

Environmental & Electrical

Operating Condition	Temperature	-10°C~+55°C(+14°F~+131°F)
	Humidity	0~90% RH(non-condensing)
Input Voltage		24VAC, 12VDC
Power Consumption	12VDC	Max 3.6W
	24VAC	Max 3.6W

Mechanical

Color	Ivory, Black
Material	Aluminum, PC(Polycarbonate)
Product Dimensions	59.6x68.4x92.7mm(2.35x2.69x3.65")
Product Weight	186g(0.41lb)

※ HCB-7000 has been renamed to HCB-7000A. HCB-7000 and HCB-7000A are the same model.

HCB-7000A

4MP Wisenet HD+ Box Camera



CAD

Unit: mm [inch]

