

HCD-7030RA



Analog

Купольные

HCD-7030RA

QHD (4МП) аналоговая купольная камера с ИК-подсветкой



Key Features

- 0,27 лк при F2.0 (цветн.) (HCD-7020R/7030R), 0 лк (Ч/Б : ИК светодиод вкл.)
- Встроенный объектив 6,0 мм с постоянным фокусом
- Дневной и ночной (с выдвижным ИК-фильтром) режимы, DWDR, обнаружение движения
- Дальность видимости с ИК подсветкой до 30 м
- Дальность передачи макс. 500 м
- Простая установка (Plug & play)

Compatible Devices



SBP-300CM



SBP-120WM



SBP-300PM



SBP-300KM



SBP-300WM1



SPB-IND12



SBP-300LM



SBP-390WM2



SPG-IND12B



SBP-300WM



SBP-300B



SBP-300HM7

HCD-7030RA

QHD (4МП) аналоговая купольная камера с ИК-подсветкой



Specifications

Video

Imaging Device	Size	1/3"
	Type	CMOS
Resolution		2560x1440
Max. Framerate(NTSC/PAL)		30fps/25fps
Min. Illumination	Color(1/30sec, 30IRE)	0.27
	BW(1/30sec, 30IRE)	0.027
Video Out		CVBS: 1.0Vp-p / 75Ω composite, 720x480(N), 720x576(P) for installation, BNC: AHD
Video Transmission Distance		500m(5C2V Coaxial Cable)

Lens

Focal Length (mm)		6.0
Max Aperture Ratio (F number)	Wide	2.0
Angular Field of View	Horizontal	49.02°
	Vertical	27.61°
	Diagonal	55.60°
Min. Object Distance		0.5m(1.64ft)

Pan / Tilt / Rotate

Pan / Tilt / Rotate Range	Pan	0°~350°
	Tilt	0°~67°
	Rotate	0°~355°

Operational

Day & Night		Auto(ICR)
Backlight Compensation		BLC, HLC, DWDR
Digital Noise Reduction		2DDNR
Motion Detection	Quantity	4ea
Privacy Masking	Quantity	2ea
Gain Control		Low, Middle, High, Very High

Operational

White Balance		ATW, AWC, Manual, Indoor, Outdoor
Electronic Shutter	Speed Range	1/30~1/12,000sec(N), 1/25~1/12,000sec(P)
Video Rotation		Flip, Mirror
IR Viewable Length		30m(98.43ft)
Coaxial Protocol		ACP, CVBS

Analytics

Analytics Events	Normal	Motion detection
------------------	--------	------------------

Environmental & Electrical

Operating Condition	Temperature	-10°C~+55°C(+14°F~+131°F)
	Humidity	0~90% RH(non-condensing)
Input Voltage		12VDC
Power Consumption	12VDC	Max 5W

Mechanical

Color		Ivory
Material		PC(Polycarbonate)
Product Dimensions		Ø110.1x86.1mm(4.33x3.39")
Product Weight		240g(0.53lb)

HCD-7030RA

QHD (4МП) аналоговая купольная камера с ИК-подсветкой



CAD

Unit: mm [inch]

