

HCD-7070RA



Analog

Купольные

HCD-7070RA

QHD (4МП) аналоговая купольная камера с ИК-подсветкой



Key Features

- Разрешение QHD (2560 x 1440, 30 кад/с)
- 0,16 лк при F1.6 (цветн.), 0 лк (Ч/Б : ИК светодиоды вкл.)
- 3,2–10 мм (3,1х), вариофокальный объектив
- Дневной и ночной (с выдвижным ИК-фильтром) режимы, DWDR, обнаружение движения
- Дальность передачи макс. 500 м
- Простая установка (Plug & play), двойное питание

Compatible Devices



SHD-1198FW



SBP-300CM



SBP-120WM



SBP-300PM



SBP-300KM



SBP-300WM1



SBP-300LM



SBP-390WM2



SBP-300WM



SBP-300B



SBP-122HM



SHD-3000F2



SPB-IND6

HCD-7070RA

QHD (4МП) аналоговая купольная камера с ИК-подсветкой



Specifications

Video

Imaging Device	Size	1/3"
	Type	CMOS
Resolution		2560x1440
Max. Framerate(NTSC/PAL)		30fps/25fps
Min. Illumination	Color(1/30sec, 30IRE)	0.16
	BW(1/30sec, 30IRE)	0.016
Video Out		CVBS: 1.0Vp-p / 75Ω composite, 720x480(N), 720x576(P) for installation, BNC: AHD
Video Transmission Distance		500m(5C2V Coaxial Cable)

Lens

Focal Length (mm)		3.2~10
Optical Zoom Ratio		3.1x
Max Aperture Ratio (F number)	Wide	1.6
Angular Field of View	Horizontal	93.48°~29.44°
	Vertical	50.47°~16.64°
	Diagonal	112.53°~33.7°
Min. Object Distance		0.5m(1.64ft)
Focus Control		Manual
Lens Type		DC auto iris(IR corrected)

Pan / Tilt / Rotate

Pan / Tilt / Rotate Range	Pan	0°~350°
	Tilt	0°~63°
	Rotate	0°~355°

Operational

Day & Night	Auto(ICR)
Backlight Compensation	BLC, HLC, DWDR
Digital Noise Reduction	2DDNR

Operational

Motion Detection	Quantity	4ea
Privacy Masking	Quantity	2ea
Gain Control		Low, Middle, High, Very High
White Balance		ATW, AWC, Manual, Indoor, Outdoor
Electronic Shutter	Speed Range	1/30~1/12,000sec(N), 1/25~1/12,000sec(P)
Video Rotation		Flip, Mirror
Alarm Interface	In/Out	Output 1ea
IR Viewable Length		20m(65.62ft)
Coaxial Protocol		ACP, CVBS

Analytics

Analytics Events	Normal	Motion detection
------------------	--------	------------------

Environmental & Electrical

Operating Condition	Temperature	-10°C~+55°C(+14°F~+131°F)
	Humidity	0~90% RH(non-condensing)
Input Voltage		24VAC, 12VDC
Power Consumption	12VDC	Max 5.8W
	24VAC	Max 5.8W

Mechanical

Color	Ivory
Material	PC(Polycarbonate)
Product Dimensions	Ø119.8x98.5mm(4.72x3.88")
Product Weight	320g(0.71lb)

※ HCD-7070R has been renamed to HCD-7070RA. HCD-7070R and HCD-7070RA are the same model.