

HCO-8080RVP



Analog

HCO-8080RVP

5MP Analog HD Bullet Camera



Key Features

- 5MP Resolution
- 0.11 Lux @ F1.6 (Color), 0 Lux (B/W: IR LED on)
- Day/Night (ICR), WDR (120dB)
- SSNRIV, Motion Detection
- Up to 500m transmission distance
- Easy installation
- Comparable with VP Controller(SPV-401/801)

HCO-8080RVP

5MP Analog HD Bullet Camera



Specifications

Video

Imaging Device	Size	1/2.8"
	Type	CMOS
Resolution		2592x1944, 2560x1440
Max. Framerate(NTSC/PAL)		30fps (@5MP Max. 20fps)
Min. Illumination	Color(1/30sec, 30IRE)	0.11Lux
	BW(1/30sec, 30IRE)	0.011Lux(IR LED off)
Video Out		BNC(AHD/TVI selectable) AHD: 5M/4M/2M, TVI: 2M
Video Transmission Distance		500m(5C2V Coaxial Cable)

Lens

Focal Length (mm)		3.47~10mm(2.88x) motorized varifocal
Max Aperture Ratio (F number)	Wide	1.64
	Tele	2.9
Angular Field of View	Horizontal	90.92°(Wide) ~ 31.2°(Tele)
	Vertical	66.27°(Wide) ~ 23.5°(Tele)
	Diagonal	119.14°(Wide) ~ 38.8°(Tele)
Min. Object Distance		0.5m(1.64ft)
Focus Control		Simple focus, Manual
Lens Type		DC auto iris(IR corrected)

Operational

Camera Title		Displayed up to 15 characters
Day & Night		Auto(ICR)
Backlight Compensation		BLC, HLC, WDR
Wide Dynamic Range (dB)		120
Digital Noise Reduction		SSNRIV
Defog		Support
Motion Detection	Quantity	4ea

Operational

Privacy Masking	Quantity	16ea
	Shape	Rectangular zones
Gain Control		Low, Middle, High, Off
White Balance		ATW, AWC, Manual, Indoor, Outdoor
Electronic Shutter	Speed Range	1~1/12,000sec
Video Rotation		Flip, Mirror
Alarm Interface	In/Out	Output 1ea
	Others	MD output
Alarm Triggers		Analytics
Alarm Events When Alarm Trigger Occurred		Alarm output
IR Viewable Length		30m (98.43ft)
Coaxial Protocol		ACP, TCP

Environmental & Electrical

Operating Condition	Temperature	-30°C~+55°C(-22°F~+131°F)
	Humidity	0~90% RH(non-condensing)
	Others	Start up should be done at above -10°C
Input Voltage		Compatible with VP controller(SPV-401/801)
Power Consumption	33VDC	Max 8.9W

Mechanical

Color	Dark grey
Material	Aluminum
Product Dimensions	Ø78.0 x 259.8mm (Ø3.07" x 10.23")
Product Weight	897g (Without sunshield)

Certifications & Standards

Environment	IEC 60529 IP66, IEC 62262 IK10
-------------	--------------------------------