

HCP-6320A



Analog

Поворотные

# HCP-6320A

1080p аналоговая HD 32x PTZ купольная камера



## Key Features

- Разрешение Full HD (1920 x 1080, 30 кад/с)
- 0,2 лк при F1.6, Ч/Б : 0,01лк при F1.6
- Мощный зум 32x (4,44 ~ 142,6мм), цифровой зум 16x
- Дневной и ночной (с выдвижным ИК фильтром) режимы, функция Defog, WDR (120 дБ), SSNR III
- Предустановка: 700°/с, азимутально
- IP66 / IK10 (HCP-6320HA), IK10 (только HCP-6320A + SHP-3701H)
- RS-485, Коаксиальное управление

## Compatible Devices



SHP-1520FW



SBP-300CM



SBP-300PM



SBP-300KM



SBP-300WM1



SHP-3701H



SBP-300LM



SBP-390WM2



SBP-301HM3



SHP-3701FB



SBP-300WM



SBP-300B



SPB-PTZ6

# HCP-6320A

1080p аналоговая HD 32x PTZ  
купольная камера



## Specifications

### Video

|                   |                       |                                                                                     |
|-------------------|-----------------------|-------------------------------------------------------------------------------------|
| Imaging Device    | Size                  | 1/2.8"                                                                              |
|                   | Type                  | CMOS                                                                                |
| Resolution        |                       | 1920x1080                                                                           |
| Min. Illumination | Color(1/30sec, 30IRE) | 0.2                                                                                 |
|                   | BW(1/30sec, 30IRE)    | 0.01                                                                                |
| Video Out         |                       | CVBS: 1.0Vp-p / 75Ω composite, 720x480(N), 720x576(P) for installation,<br>BNC: AHD |

### Lens

|                               |      |                            |
|-------------------------------|------|----------------------------|
| Focal Length (mm)             |      | 4.44~142.6                 |
| Optical Zoom Ratio            |      | 32x                        |
| Max Aperture Ratio (F number) | Wide | 1.6                        |
|                               | Tele | 4.4                        |
| Min. Object Distance          |      | 1.4m(4.59ft)               |
| Focus Control                 |      | Manual, Auto, One push     |
| Lens Type                     |      | DC auto iris(IR corrected) |

### Pan / Tilt / Rotate

|                           |        |                     |
|---------------------------|--------|---------------------|
| Pan / Tilt / Rotate Range | Pan    | 360° Endless        |
|                           | Tilt   | -15°~195°           |
| Pan Speed                 | Preset | 700°/sec            |
|                           | Manual | 0.024°/sec~200°/sec |
| Tilt Speed                | Preset | 700°/sec            |
|                           | Manual | 0.024°/sec~200°/sec |
| Sequence                  |        | Preset              |
| Preset Accuracy           |        | ±0.2°               |

### Operational

|                        |               |
|------------------------|---------------|
| Day & Night            | Auto(ICR)     |
| Backlight Compensation | BLC, HLC, WDR |

## Operational

|                                          |          |                                   |
|------------------------------------------|----------|-----------------------------------|
| Wide Dynamic Range (dB)                  |          | 120                               |
| Digital Noise Reduction                  |          | SSNRIII                           |
| Digital Image Stabilization              |          | Support                           |
| Defog                                    |          | Support                           |
| Motion Detection                         | Quantity | 1ea                               |
|                                          | Shape    | Rectangular zones                 |
| Privacy Masking                          | Quantity | 12ea                              |
|                                          | Shape    | Rectangular zones                 |
| Gain Control                             |          | Low, Middle, High                 |
| White Balance                            |          | ATW, AWC, Manual, Indoor, Outdoor |
| Electronic Shutter                       | Mode     | Auto, ESC, Manual                 |
| Video Rotation                           |          | Flip                              |
| Serial Interface                         |          | RS-485                            |
| Alarm Interface                          | In/Out   | Input 4ea, Output 2ea             |
| Alarm Triggers                           |          | Analytics                         |
| Alarm Events When Alarm Trigger Occurred |          | Alarm output                      |
| Coaxial Protocol                         |          | ACP                               |

## Analytics

|                  |        |                                                                                           |
|------------------|--------|-------------------------------------------------------------------------------------------|
| Analytics Events | Normal | Motion detection, Virtual area(Appear, Disappear), Virtual area(Enter/Exit), Virtual line |
|------------------|--------|-------------------------------------------------------------------------------------------|

## Environmental & Electrical

|                     |             |                           |
|---------------------|-------------|---------------------------|
| Operating Condition | Temperature | -10°C~+55°C(+14°F~+131°F) |
|                     | Humidity    | 0~90% RH(non-condensing)  |
| Storage Condition   | Temperature | -50°C~+60°C               |
|                     | Humidity    | 0~90% RH(non-condensing)  |
| Input Voltage       |             | 24VAC                     |
| Power Consumption   | 24VAC       | Max 20W                   |

## Mechanical

|                    |  |                             |
|--------------------|--|-----------------------------|
| Color              |  | Ivory                       |
| Material           |  | PC(Polycarbonate)           |
| Product Dimensions |  | ø152.0x218.0mm(ø5.98x8.58") |
| Product Weight     |  | 3300g(7.28 lb)              |

# HCP-6320A

1080p аналоговая HD 32x PTZ  
купольная камера



## CAD

Unit: mm [inch]

