

HCV-6070R



Analog

Купольные

HCV-6070R

1080p аналоговая HD вандалозащищенная купольная камера с ИК-подсветкой



Key Features

- Разрешение Full HD
- 0,11 лк при F1.6 (цветн.), 0 лк (Ч/Б : ИК светодиод вкл.)
- Вариофокальный объектив 3,2 ~ 10 мм (3,1x)
- Дневной и ночной (с выдвижным ИК фильтром) режимы, WDR (120 дБ)
- SSNRIV, обнаружение движения
- Дальность видимости с ИК подсветкой 30 м, IP66, IK10
- Дальность передачи макс. 500 м
- Простая установка (Plug & play), двойное питание

Compatible Devices



SBP-300CM



SBV-136B



SBP-300PM



SBP-300KM



SBP-300WM1



SBP-300LM



SBP-137WM1



SBP-390WM2



SBP-300WM




SPB-VAN72



SBP-300B



SHD-1408FW



SBP-301HM5

HCV-6070R

1080p аналоговая HD
вандалозащищенная купольная
камера с ИК-подсветкой



Specifications

Video

Imaging Device	Size	1/2.8"
	Type	CMOS
Resolution		1920x1080
Max. Framerate(NTSC/PAL)		30fps/25fps
Min. Illumination	Color(1/30sec, 30IRE)	0.11
	BW(1/30sec, 30IRE)	0.011
Video Out		BNC: AHD/TVI/CVI/CVBS Selectable
Video Transmission Distance		500m(5C2V Coaxial Cable)

Lens

Focal Length (mm)		3.2~10
Optical Zoom Ratio		3.1x
Max Aperture Ratio (F number)	Wide	1.6
Angular Field of View	Horizontal	110.2°~32°
	Vertical	55.4°~18°
	Diagonal	128.4°~36.6°
Min. Object Distance		0.5m(1.64ft)
Focus Control		Manual
Lens Type		DC auto iris(IR corrected)
Optional Lens		0.5m(1.64ft)

Pan / Tilt / Rotate

Pan / Tilt / Rotate Range	Pan	0° ~ 350°
	Tilt	0° ~ 67°
	Rotate	0° ~ 355°

Operational

Day & Night	Auto(ICR)
Backlight Compensation	BLC, HLC, WDR

Operational

Wide Dynamic Range (dB)		120
Digital Noise Reduction		SSNRIV
Defog		Support
Motion Detection	Quantity	4ea
Privacy Masking	Quantity	8ea
	Shape	Rectangular zones
Gain Control		Low, Middle, High, Very High
White Balance		ATW, AWC, Manual, Indoor
Electronic Shutter	Speed Range	1~1/12,000sec
Video Rotation		Flip, Mirror
Alarm Interface	In/Out	Output 1ea
Alarm Triggers		Analytics
Alarm Events When Alarm Trigger Occurred		Alarm output
IR Viewable Length		30m(98.43ft)
Coaxial Protocol		ACP, TCP, CCP, CVBS

Analytics

Analytics Events	Normal	Motion detection
------------------	--------	------------------

Environmental & Electrical

Operating Condition	Temperature	-30°C~+55°C(-22°F~+131°F)
	Humidity	0~90% RH(non-condensing)
Input Voltage		24VAC, 12VDC
Power Consumption	12VDC	Max 4.2W
	24VAC	Max 4.2W

Mechanical

Color		Ivory
Material		Aluminum
Product Dimensions		Ø137x106.1mm(5.39x4.18")
Product Weight		715g(1.58 lb)

Certifications & Standards

Environment	IEC 60529 IP66, IEC 62262 IK10
-------------	--------------------------------

HCV-6070R

HCV-6070R

1080p аналоговая HD
вандалозащищенная купольная
камера с ИК-подсветкой



CAD

Unit: mm [inch]

