

Analog Dome

HCV-7020RA

QHD (4MP) Analog Vandal-Resistant IR Dome Camera

Key Features

- QHD (2560 x 1440, 30fps) resolution
- 0.27 Lux@F2.0 (Colour) (HCV-7020R/7030R),0 Lux (B/W : IR LED on)
- Built-in 4.0mm fixed lens (HCV-7020R)
- Day & Night (ICR), DWDR, Motion detection
- IR Viewable Length 25m(7020R)
- Transmission distance max.500m
- Easy installation (Plug & play), IP66, IK10

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

HCV-7020RA

QHD (4MP) Analog Vandal-Resistant IR Dome Camera



Specifications

Vidéo

Capteur	Taille	1/3"
	Type	CMOS
Résolution		2560x1440
Max. Fréquence d'images (NTSC/PAL)		30fps/25fps
Éclairage min.	Couleur (1/30 s, 30 IRE)	0.27
	N&B (1/30 s, 30 IRE)	0.027
Sortie vidéo		CVBS : 1,0 Vp-p / 75Ω composite,720x480 (N),720x576 (P) pour installation, BNC: AHD
Distance de transmission de la vidéo		500m(5C2V Coaxial Cable)

Objectif

Distance focale (mm)		4.0
Rapport d'ouverture maximal (nombre F)	Grand angle	2.0
Champ de vision angulaire	Horizontal	78.22°
	Vertical	41.21°
	Diagonale	87.91°
Éclairage des objets :		0.5m(1.64ft)

Panoramique / Inclinaison / Rotation

Plage d'orientation panoramique / inclinaison / rotation	Panoramique	0°~350°
	Inclinaison	0°~67°
	Rotation	0°~355°

Opérationnel

Jour / Nuit		Auto (ICR)
Compensation de contre-jour		BLC, HLC, DWDR
Réduction de bruit numérique		2DDNR
Détection de mouvement	Quantité	4 pcs
Masquage de zones privatives	Quantité	2 pcs

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

Opérationnel

Contrôle du gain		Faible, Moyen, Élevé, Très élevé
Balance des blancs		ATW, AWC, Manuel, Intérieur, Extérieur
Obturateur électronique	Plage de vitesse	1/30~1/12,000sec(N), 1/25~1/12,000 s (P)
Rotation de la vidéo		Basculer verticalement, Miroir
Portée infrarouge		25m(82.02ft)
Protocole coaxial		ACP, CVBS

Environnement et électricité

Conditions de fonctionnement	Température	-30°C~+55°C(-22°F~+131°F)
	Humidité	0~90 % HR (sans condensation)
	Autres	Le démarrage doit se faire à plus de -10°C
Tension d'entrée		12VDC
Consommation électrique	12 V CC	Max 5W

Mécanique

Couleur	Ivoire
Matériau	Aluminium
Dimensions du produit	Ø120.3 x 91.7mm(Ø4.74"x3.61")
Poids du produit	510g(1.12 lb)

Certifications et normes

Environnement	IEC 60529 IP66, IEC 62262 IK10

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.


HCV-7020RA

QHD (4MP) Analog Vandal-Resistant
IR Dome Camera



CAD

Unit: mm [inch]



Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

Compatible Devices



SBP-300WM



SBP-300WM1



SBP-300KM



SBP-300NB



SBP-300CM



SBP-300LM



SBP-300PM



SBP-300B

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.