



TEST REPORT



Report No. : KES-EM251784

Page 1 / 40

KES Co., Ltd.

#3002, #3503, #3701, 40, Simin-daero365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Republic of Korea
Tel : +82-31-425-6200, Fax : +82-31-381-3838

1. Client

Applicant : Hanwha Vision Co., Ltd

Applicant Address : 6, Pangyo-ro 319Beon-gil, Bundang-gu, Seongnam-si, Gyeonggi-do, Republic of Korea

2. Sample Description

Product name : NETWORK CAMERA

Model/Type No. : PNB-A9092

Variant Model : -

Manufacturer : 1. HANWHA VISION VIETNAM COMPANY LIMITED
2. D-TECH CO.,LTD.

Manufacturer Address : 1. Lot O-2, Que Vo Industrial Zone Extended Area, Nam Son Ward, Bac Ninh Province, Vietnam
2. 173-25, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi- do, Korea (Suwon Industrial Complex)

3. Date of Receipt : May. 15, 2025

4. Test date : Jun. 01, 2025

5. Date of Issue : Jul. 24, 2025

6. Test Results : In Compliance

Tested by

Reviewed by

Seong Min, Jang
EMC Test Engineer

Dong Hun, Jang
EMC Technical Manager

This test report is not related to KS Q ISO/IEC 17025 and KOLAS.

**REPORT REVISION HISTORY**

Date	Test Report No.	Revision History
Jul. 24, 2025	KES-EM251784	Issued

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.



TABLE OF CONTENTS

1.0	General Product Description.....	4
1.1	Test Voltage & Frequency	8
1.2	Variant Model Differences	8
1.3	Device Modifications	8
1.4	Equipment Under Test	8
1.5	Support Equipments	8
1.6	External I/O Cabling.....	9
1.7	EUT Operating Mode(s).....	9
1.8	Configuration.....	11
1.9	Remarks when standards applied	12
1.10	Calibration Details of Equipment Used for Measurement.....	12
1.11	Test Facility	12
1.12	Laboratory Accreditations and Listings	12
2.0	Test Regulations	13
2.1	Conducted Emissions at Mains Power Ports.....	14
2.2	Conducted Emissions at Telecommunication Ports.....	15
2.3	Radiated Electric Field Emissions(Below 1 GHz).....	16
2.4	Radiated Electric Field Emissions(Above 1 GHz)	17
APPENDIX A – TEST DATA		18
Conducted Emissions at Mains Power Ports		18
Conducted Emissions at Telecommunication Ports		20
Radiated Electric Field Emissions(Below 1 GHz)		22
Radiated Electric Field Emissions(Above 1 GHz).....		24
Test Setup Photos and Configuration.....		26
Conducted Emissions at Mains Power Ports		26
Conducted Emissions at Telecommunication Ports		27
Radiated Electric Field Emissions(Below 1 GHz)		27
Radiated Electric Field Emissions(Above 1 GHz).....		29
EUT External Photographs.....		31
EUT Internal Photographs.....		34



1.0 General Product Description

Main Specifications of EUT are:

Division		Specificity
Internal highest operating frequency		1.6 GHz
Power	Rated Power	DC 12 V, PoE
	Test Power	AC 230 V, 50 Hz
Ports	I/O Port	DC(2 Pin) 1 EA, RJ-45 1 EA, Audio IN 1 EA, Audio OUT 1 EA, 7 Pin 1 EA (Alarm IN 2 EA, Alarm OUT 1 EA, RS 485 1 EA), Micro SD Card Slot 2 EA
	Unused Port	USB Type-C 1 EA
Components		Main Body 1 EA
Ethernet Speed		1 000 Mbps

PNB-A9092	
Video	
Imaging Device	1/1.2" CMOS
Resolution	3840x2160, 3328x1872, 3072x1728, 2592x1944, 2592x1520, 2560x1440, 1920x1080, 1600x1200, 1280x960, 1280x720, 1024x768, 800x600, 640x480, 640x360, 320x240, 320x180
Max. Framerate	H.265/H.264: Max. 30fps/25fps(60Hz/50Hz) MJPEG: Max. 30fps(@8MP Max. 5fps)
NETD	None
Pixel Size	None
Video Out	USB: Micro USB Type C for installation
Video Transmission Distance	None
Lens	
Focal Length (Zoom Ratio)	15~50mm(3.33x) motorized varifocal
Optical Zoom	None
Max. Aperture Ratio	F1.67(Wide)~F3.5(Tele)
Angular Field of View	H: 42.7°(Wide)~12.6°(Tele) V: 24.1°(Wide)~7.2°(Tele) D: 49°(Wide)~14.3°(Tele)
Focus Control	Simple focus
Lens Type	DC auto iris with hall sensor
Mount Type	None
Optional Lens	None
Pan / Tilt / Rotate	
Pan / Tilt / Rotate Range	None
Pan Range	None
Pan Speed	None
Tilt Range	None
Tilt Speed	None
Rotate Range	None
Sequence	None
Preset Accuracy	None
Operational	
Camera Title	Displayed up to 85 characters
Direction Indicator	None
Day & Night	Auto(ICR)
Backlight Compensation	BLC, HLC, WDR, SDR
Wide Dynamic Range	120dB
Digital Noise Reduction	SSNR V, WiseNR II (Based on AI engine)
Digital Image Stabilization	Support
Defog	Support
Motion Detection	8ea, 8point polygonal zones 32ea, 8point polygonal zones
Privacy Masking	- Color: gray/green/red/blue/black/white/purple/yellow - Mosaic Dynamic Privacy Mask(Based on AI engine) - Color: gray/green/red/blue/black/white/purple/yellow - Mosaic
Gain Control	Off / Max Gain / Manual
White Balance	ATW / NarrowATW / AWC / Manual / Indoor / Outdoor
LDC	Support(Fill/Stretch mode)
Electronic Shutter Speed	Minimum / Maximum / Anti flicker(2~1/30,000sec) Prefer shutter control(Based on AI engine)
Digital PTZ	None
Video Rotation	Flip, mirror, hallway view(90°/270°)



Analytics	Classified object type: Person/Face/Vehicle(Type: car/bus/truck/motorcycle/bicycle)/License plate Attributes: Person(Gender, Clothing top/bottom color, Bag), Face(Age, Gender, Mask, Glasses), Vehicle(Type: car/bus/truck/motorcycle/bicycle, Color) Support BestShot Support Re-ID(Person) Analytics events based on AI engine - Motion detection, Object detection, Virtual line(Crossing/Direction), Virtual area(Loitering/Intrusion/Enter/Exit/Appear/Disappear), Slip & fall detection, Face mask detection, Social distancing detection, Sound classification(To be released) Analytics events - Defocus detection, Tampering, Shock detection, Audio detection
Business Intelligence	Based on AI engine: People/Vehicle/Crowd counting, Queue management, Heatmap
Serial Interface	RS-485(Samsung-T, Pelco-D/P, Panasonic, Bosch, AD, GE, Vicon, Honeywell)
Alarm Events	When alarm trigger occurred - File upload(image): e-mail/FTP/SFTP - File upload(video clip): FTP/SFTP - Notification: e-mail - Recording: SD/SDHC/SDXC or NAS recording at event triggers - Alarm output - Handover: PTZ preset, send message by HTTP/HTTPS/TCP - Audio clip playback(WAV, MP3) - MQTT: publication
Audio Streaming	None
Audio In	Selectable(mic in/line in/built-in mic)
Audio Out	Line out
Light Type	None
Light Viewable Length	None
IR Viewable Length	None
IR Illuminator (Optional)	None
IR Radiation angle	None
IR LED	None
IR Wavelength	None
IR Operation	None
Water Removal	None
Auto Tracking	None
Coaxial Protocol	None
Color Palettes	None
Radiometry	
Temperature Detect Range	None
Temperature Accuracy	None
Temperature Detection	None
Additional	None
Network	
Ethernet	Metal shielded RJ-45(10/100/1000BASE-T)
Video Compression	H.265/H.264: Main/Baseline/High MJPEG
Smart Codec	WiseStream(Based on AI engine)
Video Quality Adjustment	None
Bitrate Control	H.264/H.265: CBR or VBR MJPEG: VBR
Streaming	Unicast(20 users) / Multicast Multiple streaming(Up to 5 profiles, 3 virtual channel support)
Protocol	IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP/SFTP, SMTP(StartTLS), ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP(TCP, UDP Unicast), CDP, MQTT, Syslog



SIP support (VoIP, Peer-to-peer)	None
Security	None
Application Programming Interface	ONVIF Profile S/G/T/M SUNAPI(HTTP API) Hanwha Vision Open Platform
Security	
OS / Firmware Protect	Encrypted Firmware, Secure boot, Signed Firmware
User authentication	Digest Authentication, Prevent brute-force attack
Network authentication	802.1X Authentication(EAP-TLS, EAP-LEAP, EAP-PEAP MSCHAPv2)
Secure Communication	HTTPS, SRTP, WSS(Websocket secure)
Access Control	IP-based access control, MAC-based access control, Auto logout
Data Protect	Encryption Credentials, Encrypt compress for live recording file export
Audit	Access / System / Event Log management
Device ID	Device Certificate(Hanwha vision Root CA)
Secure Storage	Secure element, SDcard partition encrypt
Security Certificate	ETSI EN 303 645, Secure element(FIPS 140-3 level3, CC EAL6+)
General	
Webpage Language	English, Korean, Simplified Chinese, Traditional Chinese , French, Italian, Spanish, German, Japanese, Russian, Portuguese, Czech, Polish, Turkish, Dutch, Hungarian, Greek
Web Viewer	None
Edge Storage	Micro SD/SDHC/SDXC 2slots 2TB(1TBx2)
Memory	4GB RAM, 8GB eMMC
Environmental & Electrical	
Operating Temperature / Humidity	-10°C~+55°C(14°F~+131°F) / 0~95% RH
Storage Temperature / Humidity	-50°C~+60°C(-58°F~+140°F) / 0~90% RH
Wind Load	None
EPA(Effective Projected Area)	0.0153m ²
Certification	None
Input Voltage	PoE+(IEEE802.3at type2, Class4), 12VDC
Power Consumption	PoE: Max. 13.6W, typical 12.7W 12VDC: Max. 11.5W, typical 10.9W Support Wisepower - Power monitoring(Max./Current/Avg.) - Power Redundance Failover
Mechanical	
Color / Material	Black / Aluminum
RAL Code	RAL9005
Product Dimensions / Weight	82(W)x76(H)x190(D)mm(3.23x2.99x7.48"), 1020g(2.25lb)
Compatible Conduit hole / Gasket	None
Certifications & Standards	
Network	None
EMC	FCC 47 CFR 15 Subpart B Class A ICES-3(A)/NMB-3(A) CE/UKCA - EN 55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3 VCCI CISPR 32 Class A RCM AS/NZS CISPR 32 Class A KS C 9832 Class A, KS C 9835
Safety	UL 62368-1, CAN/CSA C22.2 NO. 62368-1 IEC/EN 62471
Environment	IEC/EN 63000 IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78
Video	None
Compatible Models	
Hanging Adaptor	None
Back Box	None
Ceiling Mount (Assy)	None
Ceiling Mount (Single Unit)	None
Wall Mount	None
Wall Mount Adaptor	None



Pole Mount	None
In-ceiling Mount	None
Corner Mount	None
Parapet Mount	None
Tilt Mount	None
Cabinet	None
Housing	SHB-4301HP, SHB-4301H2, SHB-4301H1, SHB-4300H, SHB-4200H, SHB-4200
Gang Plate	None
Skin Cover	None
Weather Cap	None
Dome Cover	None
Conduit Adaptor	None
Power Module	None
Interface Box	SPM-4210
Other Compatible Models	None
DORI (EN62676-4 standard)	
Detect (25PPM/ 8PPF)	Wide: 195.0m(639.66ft) / Tele: 730.7m(2,397.32ft)
Observe (63PPM/ 19PPF)	Wide: 78.0m(255.86ft) / Tele: 292.3m(958.93ft)
Recognize (125PPM/ 38PPF)	Wide: 39.0m(127.93ft) / Tele: 146.1m(479.46ft)
Identify (250PPM/ 76PPF)	Wide: 19.5m(63.97ft) / Tele: 73.1m(239.73ft)



1.1 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

☒ AC 240 V, 50 Hz ☒ PoE

1.2 Variant Model Differences

Not applicable

1.3 Device Modifications

Not applicable

1.4 Equipment Under Test

Description	Model Number	Serial Number	Manufacturer	Remarks
NETWORK CAMERA	PNB-A9092	-	HANWHA VISION VIETNAM COMPANY LIMITED	EUT

1.5 Support Equipments

Description	Model Number	Serial Number	Manufacturer	Remarks
PoE Adapter	PT-PSE106GBR-AH-S	-	Dongguan PROCET Network Technology Co.,Ltd	-
LAPTOP	LG15N54	506NZGK000615	LG Electronics	-
LAPTOP Adapter	PA-1650-43(65W)	OF58U63849302Y609	LG Electronics	-
Micro SD Card 1	-	-	SanDisk	-
Micro SD Card 2	-	-	SanDisk	-
LED Alarm	PRO-SL	-	SENSOR PRO	-
Button Alarm	-	-	-	-
HEADSET	K550	-	Britz®	-
AC/DC Adapter	2ACB022F	-	ChAnnel Well Technology (Guangzhou) Co.,Ltd.	-
Controller	SPC-1010	C50E67WG10100F	SamSung Techwin Co.,Ltd.	-
Controller Adapter	AP-12005A	-	APOWER	-



1.6 External I/O Cabling

■ mode 1

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
NETWORK CAMERA (EUT)	2 Pin	AC/DC Adapter	DC JACK	1.6	U
	Micro SD Card Slot	Micro SD Card 1	Micro SD Card Slot	-	-
	Micro SD Card Slot	Micro SD Card 2	Micro SD Card Slot	-	-
	RJ-45 (LAN)	LAPTOP	RJ-45 (LAN)	3.1	U
	Alarm IN	LED Alarm	Alarm OUT	3.1	U
	Alarm OUT	Button Alarm	Alarm IN	3.1	U
	Audio IN	HEADSET	3.5 mm (MIC)	1.4	U
	Audio OUT		3.5 mm (HEADSET)		
	RS 485	Controller	RS 485	3.2	U
	GROUND	GROUND	GROUND	1.5	-
LAPTOP	DC JACK	LAPTOP Adapter	DC JACK	1.6	U
Controller	DC JACK	Controller Adapter	DC JACK	1.5	U

* Unshielded=U, Shielded=S

■ mode 2

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
NETWORK CAMERA (EUT)	RJ-45 (PoE)	PoE Adapter	RJ-45 (PoE)	3.2	U
	Micro SD Card Slot	Micro SD Card 1	Micro SD Card Slot	-	-
	Micro SD Card Slot	Micro SD Card 2	Micro SD Card Slot	-	-
	Alarm IN	LED Alarm	Alarm OUT	3.1	U
	Alarm OUT	Button Alarm	Alarm IN	3.1	U
	Audio IN	HEADSET	3.5 mm (MIC)	1.4	U
	Audio OUT		3.5 mm (HEADSET)		
	RS 485	Controller	RS 485	3.2	U
	GROUND	GROUND	GROUND	1.5	-
PoE Adapter	RJ-45 (LAN)	LAPTOP	RJ-45 (LAN)	1.8	U
Controller	DC JACK	Controller Adapter	DC JACK	1.5	U

* Unshielded=U, Shielded=S



1.7 EUT Operating Mode(s)


Test mode		Normal operating
mode 1	AC/DC Adapter	- Check the network behavior of the EUT with the laptop's ping test - View images of the camera through the Web Viewer - Play the 1 kHz tone through the web viewer to see the sound output with the headset
mode 2	PoE	- Check the operation of the Audio IN port through microphone input on the headset - When the alarm is pressed, make sure the button alarm is working - After testing, check the recording with Micro SD Card

EUT Test operating S/W		
Name	Version	Manufacture Company
Web Viewer	-	HANWHA VISION VIETNAM COMPANY LIMITED




1.8 Configuration

■ mode 1



■ mode 2



**1.9 Remarks when standards applied**

USB Type-C ports are not used and have not been tested.

1.10 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less.

1.11 Test Facility

The measurement facility is located at 473-21, Gayeo-ro, Yeosu-si, Gyeonggi-do, 12658, Korea, Republic of. The sites are constructed in conformance with the requirements of ANSI C63.4a-2017 and CISPR 16-1-4:2019

1.12 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
KOREA	RRA	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KR0100
International	KOLAS	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KT489
USA	FCC	3 m & 10 m Semi-Anechoic Chamber Conducted test site to perform FCC Part 15/18 measurements.	 KR0100
Canada	ISED	3 m & 10 m Semi-Anechoic Chamber and Conducted test site	 23298
JAPAN	VCCI	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site)	 C-20136, T-20137, R-20181, G-20176
Europe	TÜV SÜD	EMI (3 m & 10 m Semi-Anechoic Chamber and conducted test site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 CARAT 001633 0008



2.0 Test Regulations

The emissions tests were performed according to following regulations:

☒ **AS/NZS CISPR 32:2015 AMD 1:2020**

☒ Class A

☐ Class B





2.1 Conducted Emissions at Mains Power Ports

Test Date

Jun. 01, 2025

Test Location

Electro wave Shieldroom #6

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EMC32	R & S	9.12.00	-
☒	EMI TEST RECEIVER	ESR3	R & S	101783	11, 06, 2025
☒	LISN	ENV216	R & S	101786	01, 09, 2026
☒	ARTIFICIAL MAINS NETWORK	ESH2-Z5	R & S	100450	11, 06, 2025
☒	PULSE LIMITER	ESH3-Z2	R & S	101915	11, 06, 2025

Test Conditions

Temperature: (23,6 ± 0,1) °C

Relative Humidity: (46,4 ± 0,1) % R.H.

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks- See Appendix A for test data.- The LAN port is regarded as a wired communication network port and power-related ports are not tested.



2.2 Conducted Emissions at Telecommunication Ports

Test Date

Jun. 01, 2025

Test Location

Electro wave Shieldroom #6

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test SW	EMC32	R & S	9.12.00	-
☒	EMI TEST RECEIVER	ESR3	R & S	101783	11, 06, 2025
☒	LISN	ENV216	R & S	101786	01, 09, 2026
☒	ARTIFICIAL MAINS NETWORK	ESH2-Z5	R & S	100450	11, 06, 2025
☒	PULSE LIMITER	ESH3-Z2	R & S	101915	11, 06, 2025
☒	8-WIRE ISN CAT6	NTFM 8158	SCHWARZBECK	8158-0029	01, 09, 2026

Test Conditions

Temperature: (23,6 ± 0,2) °C
Relative Humidity: (46,4 ± 0,1) % R.H.

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

RemarksSee Appendix A for test data.



2.3 Radiated Electric Field Emissions(Below 1 GHz)

Test Date

Jun. 01, 2025

Test Location☐ OPEN AREA TEST SITE #2☒ SEMI ANECHOIC CHAMBER #4(10m)**Test Equipment**

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	EP5/RE	TOYO Corporation	6.0.0	-
☒	EMI TEST RECEIVER	ESU26	R & S	100551	01, 09, 2026
☒	AMPLIFIER	SCU 01	R & S	100603	11, 06, 2025
☒	BILOG ANTENNA	VULB 9168	SCHWARZBECK	9168-461	05, 09, 2026
☒	ATTENUATOR	6806.17.A	HUBER+SUHNER	-	02, 13, 2026

Test Conditions

Temperature: (24,1 ± 0,3) °C

Relative Humidity: (46,2 ± 0,2) % R.H.

Frequency Range of Measurement

30 MHz to 1 GHz

Instrument Settings

IF Band Width: 120 kHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

RemarksSee Appendix A for test data.



2.4 Radiated Electric Field Emissions(Above 1 GHz)

Test Date

Jun. 01, 2025

Test Location

SEMI ANECHOIC CHAMBER #5

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test S/W	ES10/RE	TOYO Corporation	2022.01.000	-
☒	EMI TEST RECEIVER	ESU26	Rohde & Schwarz	100552	02, 13, 2026
☒	HORN ANTENNA	BBHA 9120D	SCHWARZBECK	9120D-1802	11, 04, 2025
☒	PREAMPLIFIER	8449B	HP	3008A00538	04, 30, 2025
☒	ATTENUATOR	8491B	HP	23094	02, 13, 2026

Test Conditions

Temperature: (23,5 ± 0,2) °C

Relative Humidity: (46,8 ± 0,1) % R.H.

Frequency Range of Measurement

1 GHz to 6 GHz

Instrument Settings

IF Band Width: 1 MHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks

- See Appendix A for test data.
- The Average of the test data is the cispr average result.




APPENDIX A – TEST DATA

Conducted Emissions at Mains Power Ports

■ mode 1

HOT LINE

Test Description: Conducted Emission
Job No.: KES-EM251784
Phase: L
Mode: mode 1
Operator Name: KES




Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.155000	---	35.67	66.00	30.33	1000.0	9.000	L1	19.5
0.155000	52.91	---	79.00	26.09	1000.0	9.000	L1	19.5
5.070000	---	25.46	60.00	34.54	1000.0	9.000	L1	19.9
5.070000	31.15	---	73.00	41.85	1000.0	9.000	L1	19.9
5.125000	---	25.72	60.00	34.28	1000.0	9.000	L1	19.9
5.125000	31.48	---	73.00	41.52	1000.0	9.000	L1	19.9
5.900000	---	26.82	60.00	33.18	1000.0	9.000	L1	20.0
5.900000	33.04	---	73.00	39.96	1000.0	9.000	L1	20.0
5.955000	---	26.78	60.00	33.22	1000.0	9.000	L1	20.0
5.955000	33.21	---	73.00	39.79	1000.0	9.000	L1	20.0



NEUTRAL LINE

Test Description: Conducted Emission
Job No.: KES-EM251784
Phase: N
Mode: mode 1
Operator Name: KES



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.160000	---	36.08	66.00	29.92	1000.0	9.000	N	19.5
0.160000	52.46	---	79.00	26.54	1000.0	9.000	N	19.5
0.180000	---	32.44	66.00	33.56	1000.0	9.000	N	19.5
0.180000	49.39	---	79.00	29.61	1000.0	9.000	N	19.5
4.885000	---	25.64	60.00	34.36	1000.0	9.000	N	19.9
4.885000	31.73	---	73.00	41.27	1000.0	9.000	N	19.9
4.910000	---	25.81	60.00	34.19	1000.0	9.000	N	19.9
4.910000	31.69	---	73.00	41.31	1000.0	9.000	N	19.9
5.610000	---	27.72	60.00	32.28	1000.0	9.000	N	19.9
5.610000	33.68	---	73.00	39.32	1000.0	9.000	N	19.9
5.955000	---	27.37	60.00	32.63	1000.0	9.000	N	19.9
5.955000	33.39	---	73.00	39.61	1000.0	9.000	N	19.9

◆ Calculation

QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]

QuasiPeak / CAverage : The Final Value

Reading Value : Not shown in the table.


Corr. : Correction values (LISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

**Conducted Emissions at Telecommunication Ports**

■ mode 1

[1 000 Mbps]

Test Description: Telecommunication Emission
Job No.: KES-EM251784
Mode : mode 1
Speed : 1 000 Mbps
Operator Name: KES

**Final_Result**


Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.360000	---	29.57	76.73	47.16	1000.0	9.000	Single Line	19.4
0.360000	36.77	---	89.73	52.96	1000.0	9.000	Single Line	19.4
0.790000	---	31.13	74.00	42.87	1000.0	9.000	Single Line	19.3
0.790000	34.12	---	87.00	52.88	1000.0	9.000	Single Line	19.3
1.495000	---	46.19	74.00	27.81	1000.0	9.000	Single Line	19.3
1.495000	46.73	---	87.00	40.27	1000.0	9.000	Single Line	19.3
7.270000	---	35.02	74.00	38.98	1000.0	9.000	Single Line	19.5
7.270000	41.17	---	87.00	45.83	1000.0	9.000	Single Line	19.5
9.680000	---	36.46	74.00	37.54	1000.0	9.000	Single Line	19.6
9.680000	41.97	---	87.00	45.03	1000.0	9.000	Single Line	19.6



■ mode 2

[1 000 Mbps]

Test Description: Telecommunication Emission
Job No.: KES-EM251784
Mode : mode 2
Speed : 1 000 Mbps
Operator Name: KES



Final_Result

Frequency (MHz)	QuasiPeak (dB μ V)	CAverage (dB μ V)	Limit (dB μ V)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.205000	---	66.18	81.41	15.23	1000.0	9.000	Single Line	19.6
0.205000	66.26	---	94.41	28.15	1000.0	9.000	Single Line	19.6
1.495000	---	46.24	74.00	27.76	1000.0	9.000	Single Line	19.3
1.495000	46.66	---	87.00	40.34	1000.0	9.000	Single Line	19.3
1.545000	---	46.27	74.00	27.73	1000.0	9.000	Single Line	19.3
1.545000	49.62	---	87.00	37.38	1000.0	9.000	Single Line	19.3
29.865000	---	52.11	74.00	21.89	1000.0	9.000	Single Line	20.1
29.865000	54.94	---	87.00	32.06	1000.0	9.000	Single Line	20.1
29.965000	---	52.30	74.00	21.70	1000.0	9.000	Single Line	20.1
29.965000	54.96	---	87.00	32.04	1000.0	9.000	Single Line	20.1

◆ Calculation

QuasiPeak[dBuV] / CAverage [dBuV] = Reading Value[dBuV] + Corr. [dB]


QuasiPeak / CAverage : The Final Value

Reading Value : Not shown in the table.

Corr. : Correction values (ISN FACTOR + (Cable Loss + Pulse Limiter FACTOR))

**Radiated Electric Field Emissions(Below 1 GHz)**


■ mode 1

**Final Result**

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	101.053	V	53.2	-24.7	28.5	40.0	11.5	102.0	270.0	
2	122.635	V	53.0	-22.0	31.0	40.0	9.0	101.0	296.0	
3	145.066	V	50.0	-19.5	30.5	40.0	9.5	106.0	259.0	
4	160.465	V	45.2	-19.5	25.7	40.0	14.3	109.0	263.0	
5	186.655	V	51.0	-21.4	29.6	40.0	10.4	100.0	143.0	
6	983.025	H	30.6	-0.1	30.5	47.0	16.5	202.0	351.0	



■ mode 2



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(μV)]	c.f [dB(1/m)]	Result QP [dB(μV/m)]	Limit QP [dB(μV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	94.869	V	54.7	-25.7	29.0	40.0	11.0	114.0	219.0	
2	142.156	V	56.3	-19.8	36.5	40.0	3.5	102.0	203.0	
3	143.611	V	58.5	-19.7	38.8	40.0	1.2	100.0	263.0	
4	145.066	V	57.3	-19.5	37.8	40.0	2.2	101.0	218.0	
5	160.101	V	48.6	-19.4	29.2	40.0	10.8	123.0	261.0	
6	989.330	H	29.5	-0.1	29.4	47.0	17.6	400.0	165.0	

◆ Calculation

Result(QP) [dB(μV/m)] = (Reading(QP)[dB(μV)] + c.f[dB(1/m)])


Margin(QP)[dB] = Limit[dB(μV/m)] - Result(QP) [dB(μV/m)]

Reading(QP) : Reading value, Result(QP) : Reading value + Factor value

Limit(QP) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value

**Radiated Electric Field Emissions(Above 1 GHz)**


■ mode 1

**Final Result**

No.	Frequency [MHz]	Pol	Reading AV [dB (μV)]	Reading PK [dB (μV)]	c.f [dB (1/m)]	Result PK [dB (μV/m)]	Limit AV [dB (μV/m)]	Limit PK [dB (μV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [deg]	Remark
1	2675.462	V	29.1	43.8	5.5	49.3	56.0	76.0	21.4	26.7	100.0	114.0	
2	2793.669	H	28.4	42.5	5.8	48.3	56.0	76.0	21.8	27.7	100.0	0.6	
3	3352.813	V	28.9	43.1	7.1	50.2	60.0	80.0	24.0	29.8	100.0	27.9	
4	3592.704	H	28.9	42.1	7.5	49.6	60.0	80.0	23.6	30.4	100.0	38.6	
5	4701.333	H	28.7	40.8	11.5	52.3	60.0	80.0	19.8	27.7	100.0	102.0	
6	5744.746	V	27.8	41.2	14.0	55.2	60.0	80.0	18.2	24.8	100.0	263.2	



mode 2



No.	Frequency [MHz]	Pol	Reading AV [dB (μV)]	Reading PK [dB (μV)]	c.f [dB (1/m)]	Result PK [dB (μV/m)]	Limit AV [dB (μV/m)]	Limit PK [dB (μV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [deg]	Remark
1	2620.534	V	29.1	43.3	5.3	48.6	56.0	76.0	21.6	27.4	100.0	201.4	
2	2904.367	H	28.3	43.3	6.2	49.5	56.0	76.0	21.5	26.5	100.0	236.6	
3	3199.441	V	28.6	43.4	6.7	50.1	60.0	80.0	24.7	29.9	100.0	239.6	
4	3544.052	H	28.8	43.0	7.4	50.4	60.0	80.0	23.8	29.6	100.0	357.9	
5	4707.365	V	28.5	40.9	11.5	52.4	60.0	80.0	20.0	27.6	100.0	42.6	
6	5624.053	H	27.4	40.7	13.6	54.3	60.0	80.0	19.0	25.7	100.0	78.7	

◆ Calculation

Result(PK/CAV) [dB (μV/m)] = (Reading(PK/CAV) [dB (μV)] + c.f [dB (1/m)])

Margin(PK/CAV) [dB] = Limit [dB (μV/m)] - Result(PK/CAV) [dB (μV/m)]

Reading(PK/CAV) : Reading value, Result(PK/CAV) : Reading value + Factor value

Limit(PK/CAV) : Limit value, c.f : (ANT Factor + Cable Loss - Preamp Factor), Margin: Margin value



Test Setup Photos and Configuration

Conducted Emissions at Mains Power Ports


■ mode 1





Conducted Emissions at Telecommunication Ports

■ mode 1







■ mode 2







Radiated Electric Field Emissions(Below 1 GHz)

■ mode 1







■ mode 2







Radiated Electric Field Emissions(Above 1 GHz)

■ mode 1





■ mode 2






EUT External Photographs

(Top)



(Bottom)









EUT Internal View – Board 1

(Top)




(Bottom)






EUT Internal View – Board 2

(Top)




(Bottom)






EUT Internal View – Board 3

(Top)



(Bottom)






EUT Internal View – Board 4

(Top)




(Bottom)






EUT Internal View – Board 5

(Top)



(Bottom)






EUT Internal View – Lens

(Top)



(Bottom)



The End.