

Network

PNM-9000QB

2МП x 4CH камера с выносным видеомодулем



Key Features

- 2 Мп x 4 канала
- HDMI - поддержка одиночного вида/4-зонального вида
- WDR 120 дБ, WiseStreamII
- Обнаружение расфокусировки, направления движения, движения и т.д.
- До 30 кад/с при 2 Мп
- H.265, H.264, MJPEG

Compatible Devices



SBL-100D

PNM-9000QB

2МП x 4CH камера с выносным видеомодулем



Specifications

Video		
Resolution		1920x1080, 1280x1024, 1280x960, 1280x720, 1024x768, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240
Max. Framerate	H.265/H.264	30fps/25fps(60Hz/50Hz)
	MJPEG	30fps
Video Out		HDMI(Single/Quad view)
Lens		
Optional Lens		SLA-T1080FA, SLA-T2480A, SLA-T2480VA, SLA-T4680A, SLA-T4680VA, SLA-T4680DA, SLA-T4680DSA, SLA-T2480WDA, SLA-T2480WA, SLA-T2880BA
Operational		
Day & Night		Auto(Electrical)
Backlight Compensation		BLC, HLC, WDR, SDR
Wide Dynamic Range (dB)		120
Digital Noise Reduction		SSNR V
Digital Image Stabilization		Support
Defog		Support
Motion Detection	Quantity	8ea
	Shape	8point Polygonal zones
Privacy Masking	Quantity	32ea
	Shape	4point Quadrangle zones
	Color / Option	Gray, Green, Red, Blue, Black, White, Mosaic
Gain Control		Off, Max gain, Manual
White Balance		ATW, NarrowATW, AWC, Manual, Indoor, Outdoor
LDC		Support
Electronic Shutter	Mode	Minimum, Maximum, Anti flicker
	Speed Range	2~1/12,000sec
Video Rotation		Flip, Mirror
Alarm Interface	In/Out	Input 2ea, Output 2ea
Alarm Triggers		Analytics, Network disconnect, Alarm input

Operational

Alarm Events When Alarm Trigger Occurred	File upload(image): e-mail/FTP, Notification: e-mail, Recording: SD/SDHC/SDXC or NAS recording at event triggers,Alarm output
Audio In	Selectable(mic in/line in)
Audio Out	Line out

Analytics

Analytics Events	Normal	Defocus detection, Motion detection, Virtual area(Intrusion/Enter/Exit), Virtual line(Crossing, Direction)
------------------	--------	--

Network

Ethernet		Metal shielded RJ-45(10/100/1000BASE-T)
Video Compression		H.265/H.264: Main/Baseline/High, MJPEG
Audio Compression		G.711 u-law /G.726 selectable,G.726(ADPCM) 8kHz,G.711 8kHz, G.726: 16kbps,24kbps,32kbps,40kbps, AAC-LC: 48kbps at 16kHz
Smart Codec		Manual, WiseStream II
Bitrate Control		H.265/H.264: CBR or VBR, MJPEG: VBR
Streaming	Unicast	Up to 20 users
	Multicast	Support
	Multiple Streaming	Up to 12 profiles
Protocol		IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP
Application Programming Interface	ONVIF	S, T
	Others	SUNAPI(HTTP API)
Direct Cloud Connection		Optional (needs gateway)

Security

OS / Firmware Protect	Encrypted firmware, Secure boot, Signed firmware
User authentication	Digest authentication
Network authentication	IEEE 802.1X(EAP-TLS, EAP-LEAP)
Secure Communication	HTTPS
Access Control	IP-based access control
Data Protect	Encryption credentials, Encrypt compress for live recording file export
Audit	Access / System / Event Log management
Device ID	Device certificate(Hanwha Vision Root CA)

General

Memory	RAM	4GB
	Flash	512MB

General

Edge Storage	Micro SD/SDHC/SDXC	Max. 512GB x 2slot(Total 1TB)
--------------	--------------------	-------------------------------

Environmental & Electrical

Operating Condition	Temperature	-10°C~+45°C(+14°F~+113°F)
	Humidity	0~95% RH(non-condensing)

Storage Condition	Temperature	-50°C~+60°C(-58°F~+140°F)
	Humidity	0~90% RH(non-condensing)

Input Voltage	PoE+(IEEE802.3at, Class4), 12VDC
---------------	----------------------------------

Power Consumption	PoE	Max. 22W, typical 16.7W
	12VDC	Max. 19W, typical 14W

Mechanical

Color	White
Material	Plastic
RAL Code	RAL9003
Product Dimensions	200(W)x37(H)x146(D)mm(7.87x1.46x5.75")
Product Weight	715g(1.58lb)

Compatible lenses



Video		SLA-T4680VA	SLA-T2480A	SLA-T4680A	SLA-T2480VA	SLA-T1080FA
Imaging Device	Size					
	Type					
Min. Illumination (Lux)	Color(1/30sec, 30IRE)					
	BW(1/30sec, 30IRE)					
Lens						
Max. Aperture Ratio (F number)	Wide					
	Tele					
Angular Field of View	Horizontal					
	Vertical					
	Diagonal					
Pan / Tilt / Rotate						
Pan / Tilt / Rotate Range	Pan					
	Tilt					
	Rotate					
Operational						
Environmental & Electrical						
Operating Condition	Temperature					
	Humidity					
	Others					
Storage Condition	Temperature					
	Humidity					
Mechanical						
Certification & Standards						

PNM-9000QB

2МП x 4CH камера с выносным
видеомодулем



CAD

Unit: mm [inch]

