

VERIFICATION OF FCC PART 15 COMPLIANCE

*KES hereby verify that the subject product complies with all the
electromagnetic emission specified in the FCC Rule Part 15*

Product Description:

NETWORK CAMERA

Model/Brand Name:

QNO-6020RN

Variant Model:

QNO-6030RN, QNO-6010RN

FCC Rule Part(s):

FCC 47CFR Part 15 Subpart B Class A
Part 15.107(b) & Part 15.109(b)

FCC Procedure:

Verification

Applicant Name:

Hanwha Techwin Co., Ltd.

Applicant Address:

1204, Changwon-daero, Seongsan-gu, Chang
won-si, Gyeongsangnam-do

Manufacturer Name:

Tianjin Samsung Techwin Opto-Electronic
Co., Ltd.

Manufacturer Address:

No.11 Weiliu Rd, Micro-Electronic Industrial
Park, TEDA, Tianjin, 300385, People's Republic
of China

Test Report Reference No.:

KES-E1-16T0242

NETWORK CAMERA, Model QNO-6020RN has been tested in accordance with the measurement procedures specified in FCC 47CFR Part 15 Subpart B class A and has been shown to be complied with the electromagnetic emission limits specified in FCC Rule Part 15 Subpart B class A. A testing of the sample product has been valid for the sample tested based on the reference test report, KES-E1-16T0242

Date of Issue: 06. 07. 2016

Dong Hun, Jang

Technical Manager

Signature:



KES.Co., Ltd.

C-3701, 40, Simin-daero 365beon-gil, Dongan-gu, Anyang-si, Gyeonggi-do, 431-716, Korea

Tel: +82-31-425-6200 // Fax: +82-31-424-0450



EMC TEST REPORT For FCC

Test Report No. : KES-E1-16T0242

Date of Issue : Jun. 07, 2016

Product name : NETWORK CAMERA

Model/Type No. : QNO-6020RN

Variant Model : QNO-6030RN, QNO-6010RN

Applicant : Hanwha Techwin Co., Ltd.

Applicant Address : 1204, Changwon-daero, Seongsan-gu, Changwon-si,
Gyeongsangnam-do, Korea

Manufacturer : Tianjin Samsung Techwin Opto-Electronic Co., Ltd.

Manufacturer Address : No.11 Weiliu Rd, Micro-Electronic Industrial Park, TEDA,
Tianjin, 300385, People's Republic of China

Equipment authorization : ☐ Declaration of Conformity
☒ Verification
☐ Certification

Date of Receipt : May. 23, 2016

Test date : May. 31, 2016

Test Results : ☒ In Compliance ☐ Not in Compliance

Tested by

Young-Suk, Song
EMC Test Engineer

Reviewed by

Dong-Hun, Jang
EMC Technical Manager

**KES Co., Ltd.**

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-16T0242
Page (2) of (37)

REPORT REVISION HISTORY

Date	Test Report No.	Revision History
Jun. 07, 2016	KES-E1-16T0242	Issued

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document may be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



TABLE OF CONTENTS

1.0	General Product Description.....	4
1.1	Test Voltage & Frequency	5
1.2	Variant Model Differences.....	5
1.3	Device Modifications	5
1.4	Equipment Under Test.....	5
1.5	Support Equipments	5
1.6	External I/O Cabling	6
1.7	EUT Operating Mode(s)	6
1.8	Configuration.....	7
1.9	Calibration Details of Equipment Used for Measurement	8
1.10	Test Facility	8
1.11	Laboratory Accreditations and Listings	8
2.0	Test Regulations.....	9
2.1	Conducted Emissionsat Mains Power Ports.....	11
2.2	Radiated Electric Field Emissions(Below 1 GHz)	12
2.3	Radiated Electric Field Emissions(Above 1 GHz)	13
APPENDIX A	– TEST DATA.....	14
	Conducted Emissions at Mains Power Ports.....	14
	Radiated Electric Field Emissions(Below 1 GHz)	16
	Radiated Electric Field Emissions(Above 1 GHz)	17
	Test Setup Photos and Configuration	25
	Conducted Voltage Emissions	25
	Radiated Electric Field Emissions(Below 1 GHz)	26
	Radiated Electric Field Emissions(Above 1 GHz)	28
	EUT External Photographs	30
	EUT Internal Photographs	31



1.0 General Product Description

Main Specifications of EUT are:

Video		Network	
Imaging Device	1/2.9" 2.19M CMOS	Ethernet	RJ-45 (10/100BASE-T)
Total Pixels	2,000(H) x 1,121(V)	Video Compression Format	H.265, H.264, MJPEG
Effective Pixels	1,984(H) x 1,105(V)	Resolution	1920x1080/ 1280x1024/ 1280x960/ 1280x720/ 1024x768/ 800x600/ 720x576/ 720x480/ 640x480/ 320x240
Scanning System	Progressive	Max. Framerate	H.265 : Max 30fps at all resolutions H.264 : Max 30fps at all resolutions MJPEG : Max 15fps @ all resolution.
Min. Illumination	Color : 0.15Lux, B/W : 0Lux	Smart codec	Wise Stream
Lens		Video Quality Adjustment	H.265 : Target Bitrate Level Control H.264 : Target Bitrate Level Control MJPEG : Quality Level Control
Focal Length (Zoom Ratio)	Fixed 3.6mm	Bitrate control method	H.265 : CBR or VBR H.264 : CBR or VBR MJPEG : VBR
Max. Aperture Ratio	F1.8	Streaming Capability	Multiple Streaming(Up to 3 Profiles)
Angular Field of View	H 86.48° / V 46.22° / D 102.44°	Audio I/O	Line in
Min. Object Distance	-	Audio Compression Format	G.711 u-law / G.726 Selectable G.726(ADPCM) : 8KHz, G.711 : 8KHz G.726 : 16Kbps, 24Kbps, 32Kbps, 40Kbps
Lens Type	Fixed	Audio Communication	Uni-directional
Mount Type	Board type	IP	IPv4, IPv6
Operational		Protocol	TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TSL, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour
IR Viewable Length	30m	Security	HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access Log 802.1X Authentication
Camera Title	Off / On (Displayed up to 20 characters per line) - W/W : English/Numeric/Special Characters - China : English/Numeric/Special/Chinese Characters - Common : Multi-line (Max 5), Color (Grey/Green/Red/Blue/Black/White), Transparency, Auto Scale by Resolution	Streaming Method	Unicast / Multicast
Day & Night	True Day & Night	Max. User Access	6 users at Unicast Mode
Backlight Compensation	Off / BLC	Edge storage	Micro SD/SDHC/SDXC Max 128G, NAS - Motion images recorded in the SD memory card can be downloaded - Manual recording at Local PC
Wide Dynamic Range	120dB	Application Programming Interface	ONVIF Profile S, G SUNAPI(HTTP API)
Digital Noise Reduction	SSNR(Off / On)	Webpage Language	English, French, German, Spanish, Italian, Chinese, Korean, Russian, Japanese, Swedish, Danish, Portuguese, Turkish, Polish, Czech, Rumanian, Serbian, Dutch, Croatia, Hungary, Greek, Finnish, Norwegian
Motion Detection	Off / On (4ea polygon zones)	Web Viewer	Supported OS: Windows 7, 8, 10, Mac OS X 10.8, 10.9, 10.10, 10.11 [Non-plugin Webviewer] Supported Browser: Google Chrome 47, MS Edge 20 Support Codec : Video-H.264, MJPEG (Max. 1M 15fps), Audio-G.711 [Plug-in Webviewer] Supported Browser : MS Explore 11, Mozilla Firefox 43, Apple Safari 9 * Mac OS X only
Privacy Masking	Off / On (6ea rectangler zones)	Central Management Software	SmartViewer
Gain Control	Off / Low / Middle / High	Pixel Counter	Support (plug-in viewer only)
White Balance	ATW / AWC / Manual / Indoor / Outdoor	Environmental	
LDC(Lens distortion control)	On/Off (5 levels with Min/Max)	Operating Temperature / Humidity	-30°C ~ +55°C / Less than 90% RH * Start up should be done at above -20°C
Electronic Shutter Speed	Minimum / Maximum / Anti flicker	Storage Temperature / Humidity	-30°C ~ +60°C (-22°F ~ +140°F) / Less than 90% RH
Flip / Mirror	Flip / Mirror / Hallway view	Ingress Protection	IP66
Intelligent Video Analytics	Motion Detection with metadata, Tampering, Defocus	Vandal Resistance	IK10
Alarm I/O	Input 1 / Output 1	Electrical	
Alarm Triggers	Motion detection, Tampering Detection, SD card error, NAS error, Alarm input, Defocus detection	Input Voltage / Current	PoE(IEEE802.3af, Class3), DC 12V
Alarm Events	File upload via FTP and E-Mail Local storage recording at Event Notification via E-Mail External output	Power Consumption	Max.6.6W(PoE), Max.5.5W(DC12V)
		Mechanical	
		Color / Material	Gray / Metal
		Dimension (WxHxD)	ø70.0x246mm
		Weight	730g



1.1 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

Voltage ☐ 100 Vac ☐ 110 Vac ☐ 120 Vac ☒ PoE ☒ 12 Vdc

Frequency ☐ 50 Hz ☐ 60 Hz ☐ Hz

1.2 Variant Model Differences

Variant Model	Differences
QNO-6030RN	Focus Length differences
QNO-6010RN	

1.3 Device Modifications

Not applicable

1.4 Equipment Under Test

Description	Model Number	Serial Number	Manufacturer	Remarks
NETWORK CAMERA	QNO-6020RN	-	Tianjin Samsung Techwin Opto-Electronic Co., Ltd.	E.U.T

1.5 Support Equipments

Description	Model Number	Serial Number	Manufacturer	Remarks
PoE	ANY4805C-LT1	15030100002	ANY ELECTRONICS CO., LTD.	-
Notebook	ProBook4430s	-	HP	-
Notebook adapter	SeriesPPP0009H	-	Chicony Power Technology (suzhou)Co., Ltd.	-
Alarm	SIE-0001 DO	C54167JB601268 F	SAMSUNG TECHWIN CO., LTD.	-
Mike	-	-	-	-

1.6 External I/O Cabling

- DC 12V Mode

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
NETWORK CAMERA (E.U.T)	Alarm IN	Alarm	Alarm IN	3.0	U
	RJ-45	Notebook	RJ-45	4.0	U

- PoE Mode

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
NETWORK CAMERA (E.U.T)	Alarm IN	Alarm	Alarm IN	3.0	U
	RJ-45	PoE	RJ-45	4.0	U
PoE	RJ-45	Notebook	RJ-45	4.0	U

* Unshielded=U, Shielded=S

1.7 EUT Operating Mode(s)

Equipment under test was operated during the measurement under the following conditions:


Test mode	Normal operating
OP	MONITORING Network ping test

- Input power condition during the measurements was 12 V (dc) , PoE


1.8 Configuration

■ AC Main
□ DC Main

- DC 12V Mode



- PoE Mode




1.9 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less.

1.10 Test Facility

The measurement facility is located at 473-29 Gayeo-ro, Yeosu-si, Gyeonggi-do, 12658, Korea. The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22.

1.11 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
USA	FCC	3 & 10 meter Open Area Test Sites and one conducted site to perform FCC Part 15/18 measurements.	
JAPAN	VCCI	Mains Ports Conducted Interference Measurement, Telecommunication Ports Conducted Disturbance Measurement and Radiation 10 meter site, Facility for measuring radiated disturbance above 1 GHz	 R-4308, C-4798, T-2311, G-914
KOREA	MSIP	EMI (10 meter Open Area Test Site and two conducted sites) Radio(3 & 10 meter Open Area Test Sites and one conducted site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KR0100
Canada	IC	3 & 10 meter Open Area Test Sites and one conducted site	 4769B-1
Europe	CE	EMI (10 meter Open Area Test Site and two conducted sites) Radio(3 & 10 meter Open Area Test Sites and one conducted site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	
International	KOLAS	EMI (10 meter Open Area Test Site and two conducted sites) Radio(3 & 10 meter Open Area Test Sites and one conducted site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	

2.0 Test Regulations

The emissions tests were performed according to following regulations:

☐ **EMC – Directive 2014/30/EU**

☐ EN 61000-6-3:2011

☐ EN 61000-6-1:2007

☐ EN 61000-6-4:2007 +A1:2011

☐ EN 61000-6-2:2005

☐ EN 55011:2007 +A1:2010

☐ Group 1
☐ Class A

☐ Group 2
☐ Class B

☐ EN 55014-1:2006 +A2:2011

☐ EN 55014-2:1997 +A2:2008

☐ EN 55015:2013

☐ EN 55022:2010

☐ Class A

☐ Class B

☐ EN 55024:2010

☐ EN 50130-4:2011 +A1:2014

☐ EN 61000-3-2:2014

☐ EN 61000-3-3:2013

☐ EN 61326-1:2013

☐ VCCI V-3 / 2013.04

☐ Class A

☐ Class B

☐ AS/NZS CISPR22:2009 +A1:2010

☐ Class A

☐ Class B

☒ 47 CFR Part 15, Subpart B / ANSI C63.4-2009 ☒ Class A

☐ Class B

☐ IC Regulation ICES-003 : 2012
/ ANSI C63.4-2014

☐ Class A

☐ Class B

☐ CISPR 22:2009 +A1:2010

☐ Class A

☐ Class B



☐ **R&TTE- Directive 1999/5/EC**

☐ EN 301 489-1 V1.9.2

- ☐ Equipment for fixed use
- ☐ Equipment for vehicular use
- ☐ Equipment for portable use

☐ EN 301 489-3 V1.6.1

☐ EN 301 489-17 V2.2.1

☐ EN 60945:2002



2.1 Conducted Emissions at Mains Power Ports

Test Date

N/A

Test Location

Electro wave Shieldroom

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☐	EMI Test Receiver	ESR3	R&S	101783	05, 03, 2017
☐	LISN	ENV216	R&S	101137	02, 04, 2017
☐	LISN	ENV216	R&S	101786	05, 02, 2017
☐	Electro wave Shieldroom	-	SEMITEC	-	-

Test Conditions

Temperature: °C
Relative Humidity: %

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Results

The requirements are:

- ☐ PASS
☐ NOT PASS
☒ NOT APPLICABLE

Remarks

Input power Condition during the measurements was 12 V (dc), PoE



2.2 Radiated Electric Field Emissions(Below 1 GHz)

Test Date

May. 31, 2016

Test Location

☐ Open Area Test Site #1 ☒ Open Area Test Site #2

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test Receiver	ESR3	R&S	101781	05, 03, 2017
☒	Trilog-Broadband Antenna	VULB 9163	SCHWARZBECK	9168-713	05, 15, 2017
☒	Open Area Test Site	-	KES	-	-
☒	Antenna Mast	-	DAEIL EMC	-	-
☒	Turn Table	-	DAEIL EMC	-	-

Test Conditions

Temperature: 27,0 °C

Relative Humidity: 45,0 %

Frequency Range of Measurement

30 MHz to 1 GHz

Instrument Settings

IF Band Width: 120 kHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks

See Appendix A for test data.



2.3 Radiated Electric Field Emissions(Above 1 GHz)

Test Date

May. 31, 2016

Test Location

Semi Anchoic Chamber #2

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test Receiver	ESU26	R&S	100551	04, 18, 2017
☒	Broadband Coaxial Preamplifier	BBV 9718	Schwarzbeck Mess - Elektronik	9718-246	10, 23, 2016
☒	DOUBLE RIDGED HORN ANTENNA	SAS-571	A.H.SYSTEM,INC	781	05, 07, 2017
☒	Semi Anchoic Chamber #2	-	SEMITEC	-	-
☒	Antenna Mast	-	AUDIX	-	-
☒	Turn Table	-	AUDIX	-	-

Test Conditions

Temperature: 26,4 °C
Relative Humidity: 48,5 %

Frequency Range of Measurement

1 GHz to 5 GHz

Instrument Settings

IF Band Width: 1 MHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks

See Appendix A for test data.



APPENDIX A – TEST DATA

Conducted Emissions at Mains Power Ports

[HOT]

N/A



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-16T0242
Page (15) of (37)

[NEUTRAL]

N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

**Radiated Electric Field Emissions(Below 1 GHz)**

- DC 12V Mode

Frequency	Amplitude	ANT	ANT. Height	Correction Factor		Corrected Amplitude	Applicable Limit	Margin
[MHz]	[dB μ V]	Polar. (H/V)	[m]	ANT. [dB/m]	Cable [dB]	[dB μ V/m]	[dB μ V/m]	[dB]
149.60	15.33	V	1.00	8.19	2.77	26.29	43.50	17.21
222.73	21.13	H	3.80	11.80	3.51	36.44	46.40	9.96
223.01	16.19	V	1.00	11.81	3.51	31.51	46.40	14.89
259.52	15.96	H	4.00	12.59	3.88	32.43	46.40	13.97
297.32	10.89	V	1.00	13.33	4.19	28.41	46.40	17.99
519.78	11.37	H	4.00	17.54	5.86	34.77	46.40	11.63

* H : Horizontal, V : Vertical


- PoE Mode

Frequency	Amplitude	ANT	ANT. Height	Correction Factor		Corrected Amplitude	Applicable Limit	Margin
[MHz]	[dB μ V]	Polar. (H/V)	[m]	ANT. [dB/m]	Cable [dB]	[dB μ V/m]	[dB μ V/m]	[dB]
48.14	16.44	V	1.00	13.86	1.42	31.72	39.00	7.28
222.74	21.23	H	3.93	11.80	3.51	36.54	46.40	9.86
223.05	20.32	V	1.00	11.81	3.51	35.64	46.40	10.76
297.61	14.48	H	4.00	13.33	4.19	32.00	46.40	14.40
519.49	13.71	V	1.00	17.53	5.86	37.10	46.40	9.30
631.09	8.53	H	4.00	19.42	6.61	34.56	46.40	11.84

* H : Horizontal, V : Vertical

Radiated Electric Field Emissions(Above 1 GHz)

- DC 12V Mode



Site : chamber
Condition: FCC 1 GHz - 5 GHz PK(A) 3m HORN781(2015.05.07) horizontal
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : QNO-6020RN
Mode : DC 12V
Memo :

	Freq	Read Level	Ant Factor	Cable Loss	Preamplifier Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	1038.00	32.29	24.06	6.62	40.10	273	60.00	-37.13	horizontal	Average
2	1038.00	46.12	24.06	6.62	40.10	273	80.00	-43.30	horizontal	Peak
3	1246.00	37.85	24.89	7.22	40.00	136	60.00	-30.04	horizontal	Average
4 pk	1246.00	52.48	24.89	7.22	40.00	136	80.00	-35.41	horizontal	Peak
5 pp	1634.00	37.69	26.43	8.34	39.81	345	60.00	-27.35	horizontal	Average
6	1634.00	46.97	26.43	8.34	39.81	345	80.00	-38.07	horizontal	Peak
7	1736.00	27.56	26.83	8.62	39.76	267	60.00	-36.75	horizontal	Average
8	1736.00	43.70	26.83	8.62	39.76	267	80.00	-40.61	horizontal	Peak
9	2596.00	25.08	29.34	10.26	39.98	225	60.00	-35.30	horizontal	Average
10	2596.00	43.21	29.34	10.26	39.98	225	80.00	-37.17	horizontal	Peak


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-16T0242
Page (18) of (37)



Site : chamber
Condition: FCC 1 GHZ - 5 GHZ PK(A) 3m HORN781(2015.05.07) vertical
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : QNO-6020RN
Mode : DC 12V
Memo :

	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	1244.00	32.98	24.88	7.22	40.00	183	60.00	-34.92	vertical	Average
2	1244.00	52.18	24.88	7.22	40.00	183	80.00	-35.72	vertical	Peak
3 pp	1996.00	32.49	27.86	9.34	39.63	194	60.00	-29.94	vertical	Average
4	1996.00	51.15	27.86	9.34	39.63	194	80.00	-31.28	vertical	Peak
5	2156.00	30.79	28.26	9.59	39.72	73	60.00	-31.08	vertical	Average
6 pk	2156.00	50.71	28.26	9.59	39.72	73	80.00	-31.16	vertical	Peak
7	2594.00	25.73	29.34	10.26	39.97	166	60.00	-34.64	vertical	Average
8	2594.00	47.43	29.34	10.26	39.97	166	80.00	-32.94	vertical	Peak


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-16T0242
Page (19) of (37)



Site : chamber
Condition: FCC 1 GHZ - 5 GHZ PK(A) 3m HORN781(2015.05.07) horizontal
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : QNO-6020RN
Mode : DC 12V
Memo :

	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	3735.00	25.88	31.56	12.98	40.36	98	60.00	-29.94	horizontal	Average
2	3735.00	40.92	31.56	12.98	40.36	98	80.00	-34.90	horizontal	Peak
3	4659.00	24.65	35.77	14.72	40.41	53	60.00	-25.27	horizontal	Average
4	4659.00	37.54	35.77	14.72	40.41	53	80.00	-32.38	horizontal	Peak
5 pp	4995.00	23.95	37.69	15.32	40.41	190	60.00	-23.45	horizontal	Average
6 pk	4995.00	37.87	37.69	15.32	40.41	190	80.00	-29.53	horizontal	Peak


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-16T0242
Page (20) of (37)



Site : chamber
Condition: FCC 1 GHZ - 5 GHZ PK(A) 3m HORN781(2015.05.07) vertical
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : QNO-6020RN
Mode : DC 12V
Memo :

	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	3732.00	25.10	31.56	12.97	40.36	144	60.00	-30.73	vertical	Average
2	3732.00	38.63	31.56	12.97	40.36	144	80.00	-37.20	vertical	Peak
3	4491.00	25.10	34.81	14.41	40.41	262	60.00	-26.09	vertical	Average
4	4491.00	38.28	34.81	14.41	40.41	262	80.00	-32.91	vertical	Peak
5 pp	4998.00	25.33	37.71	15.33	40.41	68	60.00	-22.04	vertical	Average
6 pk	4998.00	40.44	37.71	15.33	40.41	68	80.00	-26.93	vertical	Peak

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.




KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-16T0242
Page (21) of (37)


- PoE Mode



Site : chamber
Condition: FCC 1 GHz - 5 GHz PK(A) 3m HORN781(2015.05.07) horizontal
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : QNO-6020RN
Mode : PoE
Memo :

	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	1038.00	33.98	24.06	6.62	40.10	154	60.00	-35.44	horizontal	Average
2	1038.00	48.39	24.06	6.62	40.10	154	80.00	-41.03	horizontal	Peak
3	1246.00	36.75	24.89	7.22	40.00	247	60.00	-31.14	horizontal	Average
4	1246.00	50.89	24.89	7.22	40.00	247	80.00	-37.00	horizontal	Peak
5 pp	1634.00	37.29	26.43	8.34	39.81	331	60.00	-27.75	horizontal	Average
6	1634.00	46.67	26.43	8.34	39.81	331	80.00	-38.37	horizontal	Peak
7	1990.00	29.17	27.84	9.32	39.63	261	60.00	-33.30	horizontal	Average
8 pk	1990.00	46.72	27.84	9.32	39.63	261	80.00	-35.75	horizontal	Peak
9	2590.00	25.42	29.33	10.25	39.97	223	60.00	-34.97	horizontal	Average
10	2590.00	44.50	29.33	10.25	39.97	223	80.00	-35.89	horizontal	Peak

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Site : chamber
Condition: FCC 1 GHZ - 5 GHZ PK(A) 3m HORN781(2015.05.07) vertical
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : QNO-6020RN
Mode : PoE
Memo :


	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1 pp	1248.00	41.41	24.89	7.23	40.00	181	60.00	-26.47	vertical	Average
2	1248.00	55.69	24.89	7.23	40.00	181	80.00	-32.19	vertical	Peak
3	1744.00	32.81	26.86	8.65	39.76	80	60.00	-31.44	vertical	Average
4	1744.00	52.89	26.86	8.65	39.76	80	80.00	-31.36	vertical	Peak
5	1998.00	34.35	27.87	9.34	39.63	353	60.00	-28.07	vertical	Average
6 pk	1998.00	54.11	27.87	9.34	39.63	353	80.00	-28.31	vertical	Peak
7	2160.00	31.14	28.27	9.60	39.72	74	60.00	-30.71	vertical	Average
8	2160.00	49.83	28.27	9.60	39.72	74	80.00	-32.02	vertical	Peak
9	2600.00	24.97	29.35	10.27	39.98	234	60.00	-35.39	vertical	Average
10	2600.00	44.91	29.35	10.27	39.98	234	80.00	-35.45	vertical	Peak



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-16T0242
Page (23) of (37)



Site : chamber
Condition: FCC 1 GHZ - 5 GHZ PK(A) 3m HORN781(2015.05.07) horizontal
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : QNO-6020RN
Mode : PoE
Memo :

	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	3735.00	26.27	31.56	12.98	40.36	119	60.00	-29.55	horizontal	Average
2	3735.00	41.91	31.56	12.98	40.36	119	80.00	-33.91	horizontal	Peak
3	4638.00	24.82	35.65	14.68	40.41	206	60.00	-25.26	horizontal	Average
4	4638.00	37.59	35.65	14.68	40.41	206	80.00	-32.49	horizontal	Peak
5 pp	5025.00	23.61	37.67	15.36	40.41	193	60.00	-23.77	horizontal	Average
6 pk	5025.00	35.97	37.67	15.36	40.41	193	80.00	-31.41	horizontal	Peak


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-16T0242
Page (24) of (37)



Site : chamber
Condition: FCC 1 GHZ - 5 GHZ PK(A) 3m HORN781(2015.05.07) vertical
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : QNO-6020RN
Mode : PoE
Memo :

	Freq	Read Level	Ant Factor	Cable Loss	Preampl Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	3735.00	26.46	31.56	12.98	40.36	36	60.00	-29.36	vertical	Average
2	3735.00	42.37	31.56	12.98	40.36	36	80.00	-33.45	vertical	Peak
3	3993.00	25.58	32.00	13.50	40.41	42	60.00	-29.33	vertical	Average
4	3993.00	40.16	32.00	13.50	40.41	42	80.00	-34.75	vertical	Peak
5 pp	4989.00	24.77	37.66	15.31	40.41	70	60.00	-22.67	vertical	Average
6 pk	4989.00	39.79	37.66	15.31	40.41	70	80.00	-27.65	vertical	Peak

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Test Setup Photos and Configuration

Conducted Voltage Emissions

N/A

N/A

Radiated Electric Field Emissions(Below 1 GHz)

- DC 12V Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

- PoE Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.


Radiated Electric Field Emissions(Above 1 GHz)

- DC 12V Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

- PoE Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

EUT External Photographs

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

EUT Internal Photographs

(Internal View)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Main Board EUT Internal View – Board 1

(Top)



(Bottom)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Main Board EUT Internal View – Board 2

(Top)



(Bottom)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Main Board EUT Internal View – Board 3

(Top)




(Bottom)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Main Board EUT Internal View – Board 4

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Main Board EUT Internal View – Camera

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Label Photographs



This device complies with part 15 of the FCC Rules. Operation in subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.