

Network | Цилиндрические

# QNO-7032R

4MP IR Bullet Camera

## Key Features

- Maximum 4MP resolution
- Color : 0.15Lux (F2.0, 1/30sec) B/W : 0Lux (IR LED On)
- 6mm fixed focal
- H.265, H.264, MJPEG codec supported, Multiple streaming
- Motion detection, Tampering, Defocus detection
- Hallway view (90°/270°), LDC support
- Micro SD/SDHC/SDXC memory slot (128GB)
- IR viewable length 30m (98.42ft)
- IP66, IK10, PoE, 12VDC

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

# QNO-7032R

4MP IR Bullet Camera



## Specifications

### Video

| | | |
|---|---|---|
| **Imaging Device** | Size | 1/3" |
| | Type | CMOS |
| **Resolution** | | 2560x1440, 1920x1080, 1280x960, 1280x720, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360, 320x240 |
| **Max. Framerate** | H.265/H.264 | 30fps/25fps(60Hz/50Hz) |
| | MJPEG | 15fps(@4MP Max. 2fps) |
| **Min. Illumination (Lux)** | Color(1/30sec, 30IRE) | 0.15 |
| | BW(1/30sec, 30IRE) | 0.015 |
| **Video Out** | | CVBS: 1.0 Vp-p / 75Ω composite for installation |

### Lens

| | | |
|---|---|---|
| **Focal Length (mm)** | | 6 |
| **Max Aperture Ratio (F number)** | Wide | 2.0 |
| **Angular Field of View** | Horizontal | 49° |
| | Vertical | 28° |
| | Diagonal | 56° |
| **Focus Control** | | Fixed |

### Pan / Tilt / Rotate

| | | |
|---|---|---|
| **Pan / Tilt / Rotate Range** | Pan | 0°~360° |
| | Tilt | 0°~100° |
| | Rotate | 0°~360° |

### Operational

| | | |
|---|---|---|
| **Day & Night** | | Auto(ICR) |
| **Backlight Compensation** | | BLC, WDR, SSDR |
| **Wide Dynamic Range (dB)** | | 120 |
| **Digital Noise Reduction** | | SSNR |
| **Motion Detection** | Quantity | 4ea |
| | Shape | 8point Polygonal zones |

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

## Operational

| | | |
|---|---|---|
| **Privacy Masking** | Quantity | 6ea |
| | Shape | Rectangular zones |
| **Gain Control** | | Low, Middle, High |
| **White Balance** | | ATW, AWC, Manual, Indoor, Outdoor |
| **LDC** | | Support |
| **Electronic Shutter** | Mode | Minimum, Maximum, Anti flicker |
| | Speed Range | 1/5~1/12,000sec |
| **Video Rotation** | | Flip, Mirror, Hallway view(90°/270°) |
| **Alarm Interface** | In/Out | Input 1ea, Output 1ea |
| **Alarm Triggers** | | Analytics, Network disconnect, Alarm input |
| **Alarm Events When Alarm Trigger Occurred** | | File upload(image): e-mail/FTP,<br>Notification: e-mail,<br>Recording: SD/SDHC/SDXC or NAS recording at event triggers,Alarm output,<br>Handover: PTZ preset |
| **Audio In** | | Selectable(mic in/line in) |
| **Light Type** | | IR LED |
| **Light Viewable Length** | IR | 30m(98.42ft) |
| **IR Wavelength** | | 850nm |

## Analytics

| | | |
|---|---|---|
| **Analytics Events** | Normal | Defocus detection, Motion detection, Tampering, Virtual area(Intrusion, Enter/Exit), Virtual line(Crossing, Direction) |

## Network

| | | |
|---|---|---|
| **Ethernet** | | RJ-45(10/100BASE-T) |
| **Video Compression** | | H.265: Main,<br>H.264: Main/High,MJPEG |
| **Audio Compression** | | G.711 u-law /G.726 selectable, G.726(ADPCM) 8kHz, G.711 8kHz, G.726: 16kbps, 24kbps, 32kbps, 40kbps |
| **Smart Codec** | | Manual, WiseStream II |
| **Bitrate Control** | | H.265/H.264: CBR or VBR,<br>MJPEG: VBR |
| **Streaming** | Unicast | Up to 6 users |
| | Multicast | Support |
| | Multiple Streaming | Up to 3 profiles |
| **Protocol** | | IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMPv2, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour, LLDP, SRTP(TCP, UDP Unicast), PPPoE, PIM-SM |
| **Application Programming Interface** | ONVIF | S, G, T |
| | Others | SUNAPI(HTTP API) |
| **Direct Cloud Connection** | | Optional (needs gateway) |



© Hanwha Vision CO., LTD. All rights reserved.

## Security

| | |
|---|---|
| **OS / Firmware Protect** | Encrypted firmware |
| **User authentication** | Digest authentication, Prevent brute-force attack |
| **Network authentication** | IEEE 802.1X(EAP-TLS, EAP-LEAP, EAP-PEAP, MSCHAPv2) |
| **Secure Communication** | HTTPS, WSS(WebSocket Secure), SRTP |
| **Access Control** | IP-based access control |
| **Data Protect** | Encryption credentials, Encrypt compress for live recording file export |
| **Audit** | Access / System / Event Log management |
| **Device ID** | Device certificate(Hanwha Vision Root CA) |
| **Secure Storage** | SDcard partition encrypt(AES-256) |

## General

| | | |
|---|---|---|
| **Memory** | RAM | 512MB |
| | Flash | 256MB |
| **Edge Storage** | Micro SD/SDHC/SDXC | Max. 128GB x 1slot |

## Environmental & Electrical

| | | |
|---|---|---|
| **Operating Condition** | Temperature | -40°C~+55°C(-40°F~+131°F) |
| | Humidity | 0~95% RH(non-condensing) |
| | Others | Start up should be done at above -30°C |
| **Storage Condition** | Temperature | -40°C~+60°C(-40°F~+140°F) |
| | Humidity | 0~95% RH(non-condensing) |
| **Input Voltage** | | PoE(IEEE802.3af, Class3), 12VDC |
| **Power Consumption** | PoE | Max. 10.7W, typical 8W |
| | 12VDC | Max. 9.1W, typical 6.8W |

## Mechanical

| | |
|---|---|
| **Color** | Dark grey |
| **Material** | Aluminum |
| **Product Dimensions** | ø70.0x246.0mm(2.76x9.69") |
| **Product Weight** | 700g(1.54lb) |
| **Compatible Gang Box** | Single, Double, 4" Octagon |

## Certifications & Standards

| | |
|---|---|
| **EMC** | FCC 47 CFR 15 Subpart B Class A, ICES-3(A)/NMB-3(A), CE/UKCA - EN55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, VCCI CISPR 32 Class A, RCM AS-NZS CISPR 32 Class A, KS C 9832 Class A, KS C 9835 |
| **Safety** | UL 60950-1, CAN/CSA C22.2 NO. 60950-1, IEC 62471 |
| **Environment** | IEC/EN 63000, IEC 60529 IP66, IEC 62262 IK10 |

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.

## DORI (EN62676-4 standard)

| | | |
|---|---|---|
| **Detect (25PPM/ 8PPF)** | Wide | 112.3m(368.60ft) |
| **Observe (63PPM/ 19PPF)** | Wide | 44.9m(147.44ft) |
| **Recognize (125PPM/ 38PPF)** | Wide | 22.5m(73.72ft) |
| **Identify (250PPM/ 76PPF)** | Wide | 11.2m(36.86ft) |

Design and specifications are subject to change without notice. The latest product information / specification can be found at HanwhaVision.com
Hanwha Vision is formerly known as Hanwha Techwin.

© Hanwha Vision CO., LTD. All rights reserved.


# QNO-7032R

4MP IR Bullet Camera



## CAD

**Unit:** mm [inch]






© Hanwha Vision CO., LTD. All rights reserved.