

DECLARATION OF CONFORMITY

We; Hanwha Techwin Co., Ltd.

DECLARE UNDER OUR SOLE RESPONSIBILITY THAT THE PRODUCT;

Report No: KES-E1-16T0302

Type of

equipment: NETWORK CAMERA

Model Name: QNV-6070RP

Variant Model: -

Applicant: Hanwha Techwin Co., Ltd.

Address: 1204,Changwon-daero, Seongsan-gu,
Chang-won-si, Gyeongsangnam-do,Korea

Manufacturer : Tianjin Samsung Techwin Opto-
Electronic Co.,Ltd.

Address: No.11 Weiliu Rd, Micro-Electronic
Industrial Park, TEDA, Tianjin, 300385,
People's Republic of China

Test standards : AS/NZS CISPR22:2009+A1:2010

Classification: C-Tick

The above equipment was tested by EMC compliance Testing Laboratory for with the requirements of C-tick Rules and Regulations. The results of testing in this report apply to the product / system which was tested only.

Jul. 05, 2016

(Date of issue)

(Name and signature of authorized person)



EMC TEST REPORT For C-TICK

Test Report No. : KES-E1-16T0302
Date of Issue : Jul. 05, 2016
Product name : NETWORK CAMERA
Model/Type No. : QNV-6070RP
Variant Model : -
Applicant : Hanwha Techwin Co., Ltd.
Applicant Address : 1204, Changwon-daero, Seongsan-gu, Changwon-si,
Gyeongsangnam-do, Korea
Manufacturer : Tianjin Samsung Techwin Opto-Electronic Co.,Ltd.
Manufacturer Address : No.11 Weiliu Rd, Micro-Electronic Industrial Park, TEDA, Tianjin,
300385, People's Republic of China
Date of Receipt : Jun. 16, 2016
Test date : Jun. 28, 2016 ~ Jul. 03, 2016
Test Results : ☒ **In Compliance** ☐ **Not in Compliance**

Tested by

Kyeng-Sun, Min
EMC Test Engineer

Reviewed by

Dong-Hun, Jang
EMC Technical Manager

**KES Co., Ltd.**

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-16T0302
Page (2) of (42)

REPORT REVISION HISTORY

Date	Test Report No.	Revision History
Jul. 05, 2016	KES-E1-16T0302	Issued

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd. This document Jun be altered or revised by KES Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KES Co., Ltd. will constitute fraud and shall nullify the document.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



TABLE OF CONTENTS

1.0	General Product Description.....	4
1.1	Test Voltage & Frequency	7
1.2	Variant Model Differences.....	7
1.3	Device Modifications	7
1.4	Equipment Under Test.....	7
1.5	Support Equipments	7
1.6	External I/O Cabling	8
1.7	EUT Operating Mode(s)	8
1.8	Configuration.....	9
1.9	Calibration Details of Equipment Used for Measurement	10
1.10	Test Facility	10
1.11	Laboratory Accreditations and Listings	10
2.0	Test Regulations.....	11
2.1	Conducted Emissions at Mains Power Ports	13
2.2	Conducted Emissions at Telecommunication Ports.....	14
2.3	Radiated Electric Field Emissions(Below 1 GHz)	15
2.4	Radiated Electric Field Emissions(Above 1 GHz)	16
APPENDIX A – TEST DATA.....		17
Conducted Emissions at Mains Power Ports.....		17
Conducted Emissions at Telecommunication Ports		19
Radiated Electric Field Emissions(Below 1 GHz)		23
Radiated Electric Field Emissions(Above 1 GHz)		24
Test Setup Photos and Configuration		32
Conducted Voltage Emissions		32
Conducted Telecommunication Emissions		33
Radiated Electric Field Emissions(Below 1 GHz)		35
Radiated Electric Field Emissions(Above 1 GHz)		37
EUT External Photographs.....		39
EUT Internal Photographs		40



1.0 General Product Description

Main Specifications of EUT are:

Video	
Imaging Device	1/2.9" 2.19M CMOS
Total Pixels	2,000(H) x 1,121(V)
Effective Pixels	1,984(H) x 1,105(V)
Scanning System	Progressive
Min. Illumination	Color : 0.095Lux, B/W : 0Lux
Lens	
Focal Length (Zoom Ratio)	Manual 2.8~12mm
Max. Aperture Ratio	F1.4
Angular Field of View	H 103.8~32.4° / V 53.7~18.4° / D 121.9~37.1°
Min. Object Distance	-
Lens Type	Manual
Focus control	DC auto iris
Mount Type	Board type
Pan / Tilt / Rotate	
Pan Range	0~350°
Tilt Range	0~67°
Rotate Range	0~355°
Operational	
IR Viewable Length	30m
Camera Title	Off / On (Displayed up to 20 characters per line) - W/W : English/Numeric/Special Characters - China : English/Numeric/Special/Chinese Characters - Common : Multi-line (Max 5), Color (Grey/Green/Red/Blue/Black/White), Transparency, Auto Scale by Resolution
Day & Night	True Day & Night
Backlight Compensation	Off / BLC
Wide Dynamic Range	120dB
Digital Noise Reduction	SSNR(Off / On)
Motion Detection	Off / On (4ea polygon zones)
Privacy Masking	Off / On (6ea rectangler zones)
Gain Control	Off / Low / Middle / High
White Balance	ATW / AWC / Manual / Indoor / Outdoor
LDC(Lens distortion control)	On/Off (5 levels with Min/Max)
Electronic Shutter Speed	Minimum / Maximum / Anti flicker
Flip / Mirror	Flip / Mirror / Hallway view
Intelligent Video Analytics	Motion Detection with metadata, Tampering, Defocus
Alarm I/O	Input 1 / Output 1
Alarm Triggers	Motion detection, Tampering Detection, SD card error, NAS error, Alarm input, Defocus detection

**KES Co., Ltd.**

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-16T0302
Page (5) of (42)

Alarm Events	File upload via FTP and E-Mail Local storage recording at Event Notification via E-Mail External output
Pixel Counter	Support (plug-in viewer only)
Network	
Ethernet	RJ-45 (10/100BASE-T)
Video Compression Format	H.265, H.264, MJPEG
Resolution	1920x1080/ 1280x1024/ 1280x960/ 1280x720/ 1024x768/ 800x600/ 720x576/ 720x480/ 640x480/ 320x240
Max. Framerate	H.265 : Max 30fps at 2M all resolutions H.264 : Max 30fps at 2M all resolutions MJPEG : Max 5fps
Smart codec	WiseStream
Video Quality Ajustment	H.265 : Target Bitrate Level Control H.264 : Target Bitrate Level Control MJPEG : Quality Level Control
Bitrate control method	H.265 : CBR or VBR H.264 : CBR or VBR MJPEG : VBR
Streaming Capability	Multiple Streaming(Up to 3 Profiles)
Audio I/O	Line in
Audio Compression Format	G.711 u-law /G.726 Selectable G.726(ADPCM) : 8KHz, G.711 : 8KHz G.726 : 16Kbps, 24Kbps, 32Kbps, 40Kbps
Audio Communication	Uni-directional
IP	IPv4, IPv6
Protocol	TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP,RTSP, NTP, HTTP, HTTPS, SSL, DHCP, PPPoE, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM- SM, UPnP, Bonjour
Security	HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access Log 802.1X Authentication
Streaming Method	Unicast / Multicast
Max. User Access	6 users at Unicast Mode
Edge storage	Micro SD/SDHC/SDXC Max 128G, NAS - Motion images recorded in the SD memory card can be downloaded - Manual recording at Local PC

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

**KES Co., Ltd.**

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-16T0302
Page (6) of (42)

Application Programming Inter	ONVIF Profile S, G SUNAPI(HTTP API)
Webpage Language	English, Korean, Chinese, French, Italian, Spanish, German, Japanese, Russian, Swedish, Portuguese, Czech, Polish, Turkish, Dutch, Hungary, Greek
Web Viewer	Supported OS: Windows 7, 8, 10, Mac OS X 10.8, 10.9, 10.10, 10.11 Non-plugin Webviewer Supported Browser: Google Chrome 47, MS Edge 20 Support Codec : Video : H.264, MJPEG (MAX 1M 15FPS) Audio : G.711 Plug-in Webviewer Supported Browser : MS Explore 11 , Mozilla Firefox 43 , Apple Safari 9 * Mac OS X only
Central Management Software	SmartViewer
Environmental	
Operating Temperature / Humi	-30°C ~ +55°C / Less than 90% RH * Start up should be done at above -20°C
Storage Temperature / Humidi	-30°C ~ +60°C (-22°F ~ +140°F) / Less than 90% RH
Ingress Protection	IP66
Vandal Resistance	IK10
Electrical	
Input Voltage / Current	PoE(IEEE802.3af, Class3), DC 12V
Power Consumption	Max.6.7W(PoE), Max.5.5W(DC12V)
Mechanical	
Color / Material	Ivory / Metal
Dimension (WxHxD)	φ120 x H106.1
Weight	670g

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



1.1 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

Voltage ☐ 100 Vac ☐ 110 Vac ☐ 230 Vac ☒ PoE ☒ 12 Vdc
Frequency ☐ 50 Hz ☐ 60 Hz ☐ Hz

1.2 Variant Model Differences

Not applicable

1.3 Device Modifications

Not applicable

1.4 Equipment Under Test

Description	Model Number	Serial Number	Manufacturer	Remarks
NETWORK CAMERA	QNV-6070RP	-	Tianjin Samsung Techwin Opto-Electronic co.,Ltd.	E.U.T

1.5 Support Equipments

Description	Model Number	Serial Number	Manufacturer	Remarks
notebook	NT63025J	JK9091EF400142M	Samsung	-
notebook adapter	A13-040N2A	CN60BA4400313AD0N 843KO200	Chicony Power Technology (suzhou)Co., Ltd.	-
PoE adapter	ANY4805C-LT1	10H300002	ANY ELECTRONICS CO., LTD	-
Alam	SIP-1201DD D0	C53R67JZ301878 L	SAMSUNG TECHWIN CO., LTD.	-
Micro SD Card	-	-	-	-
MIC	CMK-303	-	CAMAC	-

1.6 External I/O Cabling

- DC 12 V Mode

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
NETWORK CAMERA (E.U.T)	Alarm JIG	Alarm	Alarm JIG	3.0	U
	LAN(RJ-45)	notebook	LAN(RJ-45)	3.0	U
	3.5 mm Line	MIC	3.5 mm Line	1.5	U
	Micro SD Card Slot	Micro SD Card	Micro SD Card Slot	-	-

- PoE Mode

Start		END		Cable Spec.	
Description	I/O Port	Description	I/O Port	Length	Shield
NETWORK CAMERA (E.U.T)	Alarm JIG	Alarm	Alarm JIG	3.0	U
	PoE(RJ-45)	PoE	PoE(RJ-45)	3.0	U
	3.5 mm Line	MIC	3.5 mm Line	1.5	U
	Micro SD Card Slot	Micro SD Card	Micro SD Card Slot	-	-
PoE adapter	LAN(RJ-45)	notebook	LAN(RJ-45)	3.3	U

* Unshielded=U, Shielded=S

1.7 EUT Operating Mode(s)

Equipment under test was operated during the measurement under the following conditions:


Test mode	Normal operating
OP	MONITORING NETWORK PING TEST

- Input power condition during the measurements was 12 V (dc) , PoE


1.8 Configuration

■ AC Main
□ DC Main

- DC 12 V Mode



- PoE Mode



1.9 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less.

1.10 Test Facility

The measurement facility is located at 473-29 Gayeo-ro, Yeosu-si, Gyeonggi-do, 12658, Korea. The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22.

1.11 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
USA	FCC	3 & 10 meter Open Area Test Sites and one conducted site to perform FCC Part 15/18 measurements.	
JAPAN	VCCI	Mains Ports Conducted Interference Measurement, Telecommunication Ports Conducted Disturbance Measurement and Radiation 10 meter site, Facility for measuring radiated disturbance above 1 GHz	 R-4308, C-4798, T-2311, G-914
KOREA	MSIP	EMI (10 meter Open Area Test Site and two conducted sites) Radio(3 & 10 meter Open Area Test Sites and one conducted site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 KR0100
Canada	IC	3 & 10 meter Open Area Test Sites and one conducted site	 4769B-1
Europe	CE	EMI (10 meter Open Area Test Site and two conducted sites) Radio(3 & 10 meter Open Area Test Sites and one conducted site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	
International	KOLAS	EMI (10 meter Open Area Test Site and two conducted sites) Radio(3 & 10 meter Open Area Test Sites and one conducted site) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	



2.0 Test Regulations

The emissions tests were performed according to following regulations:

☐ **EMC – Directive 2014/30/EU**

☐ EN 61000-6-3:2011

☐ EN 61000-6-1:2007

☐ EN 61000-6-4:2007 +A1:2011

☐ EN 61000-6-2:2005

☐ EN 55011:2007 +A1:2010

☐ Group 1
☐ Class A

☐ Group 2
☐ Class B

☐ EN 55014-1:2006 +A2:2011

☐ EN 55014-2:1997 +A2:2008

☐ EN 55015:2013

☐ EN 55022:2010

☐ Class A

☐ Class B

☐ EN 55024:2010

☐ EN 50130-4:2011 +A1:2014

☐ EN 61000-3-2:2014

☐ EN 61000-3-3:2013

☐ EN 61326-1:2013



☐ **VCCI V-3 / 2015.04**

☐ Class A

☐ Class B

☒ **AS/NZS CISPR22:2009 +A1:2010**

☒ Class A

☐ Class B

☐ **47 CFR Part 15, Subpart B**

☐ CISPR 22:2009 +A1:2010

☐ Class A

☐ Class B

☐ ANSI C63.4-2009

☐ **IC Regulation ICES-003 : 2016**

☐ CISPR 22:2009 +A1:2010

☐ Class A

☐ Class B

☐ ANSI C63.4-2014

☐ **RE- Directive 2014/53/EU**

☐ EN 301 489-1 V1.9.2

- ☐ Equipment for fixed use
- ☐ Equipment for vehicular use
- ☐ Equipment for portable use

☐ EN 301 489-3 V1.6.1

☐ EN 301 489-17 V2.2.1

☐ EN 60945:2002



2.1 Conducted Emissions at Mains Power Ports

Test Date

N/A

Test Location

Electro wave Shieldroom

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☐	EMI Test Receiver	ESR3	R & S	101783	05, 03, 2017
☐	LISN	ENV216	R & S	101137	02, 04, 2017
☐	LISN	ENV216	R & S	101786	05, 02, 2017
☐	Electro wave Shieldroom	-	AONE SHIELD	-	-

Test Conditions

Temperature: °C
Relative Humidity: %

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

TestResults

The requirements are:

- ☐ PASS
☐ NOT PASS
☒ NOT APPLICABLE

Remarks

Beacause the E.U.T power is 12 V (dc) power and PoE, limits are not specified



2.2 Conducted Emissions at Telecommunication Ports

Test Date

Jun. 28, 2016

Test Location

Electro wave Shieldroom

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI Test Receiver	ESR3	R & S	101783	05, 03, 2017
☒	LISN	ENV216	R & S	101137	02. 04. 2017
☒	LISN	ENV216	R & S	101786	05, 02, 2017
☒	8-Wire ISN CAT3	CAT3 8158	Schwarzbeck Mess	8158-0019	04. 01. 2017
☒	8-Wire ISN CAT5	CAT5 8158	Schwarzbeck Mess	8158-0030	04. 01. 2017
☐	8-Wire ISN CAT6	NTFM 8158	Schwarzbeck Mess	8158-0029	08. 14. 2016
☒	Electro wave Shieldroom	-	SEMITEC	-	-

Test Conditions

Temperature: 24,5 °C

Relative Humidity: 47,7 %

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks

See Appendix A for test data.



2.3 Radiated Electric Field Emissions(Below 1 GHz)

Test Date

Jun. 29, 2016

Test Location

☒ Open Area Test Site #1 ☐ Open Area Test Site #2

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	EMI TEST Receiver	ESU26	R&S	100551	04, 18, 2017
☒	Trilog-Broadband ANT	VULB 9163	Schwarzbeck	9163-715	04, 14, 2018
☒	Open Area Test Site	-	KES	-	-
☒	Antenna Mast	1070/1080	EMC	-	-
☒	Turn Table	-	DAEIL EMC	-	-

Test Conditions

Temperature: 29,4 °C

Relative Humidity: 46,0 %

Frequency Range of Measurement

30 MHz to 1 GHz

Instrument Settings

IF Band Width: 120 kHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks

See Appendix A for test data.



2.4 Radiated Electric Field Emissions(Above 1 GHz)

Test Date

Jul. 03, 2016

Test Location

Semi Anchoic Chamber #2

Test Equipment

Used	Description	Model Number	Manufacturer	Serial Number	Cal. Due
☒	DOUBLE RIDGED HORN ANTENNA	SAS-571	A.H.SYSTEM,INC	781	05, 07, 2017
☒	EMI Test Receiver	ESU26	R&S	100552	04. 24. 2017
☒	Broadband Coaxial Preamplifier	BBV 9718	Schwarzbeck Mess - Elektronik	9718-246	10. 23. 2016
☒	Semi Anchoic Chamber #2	-	SEMITEC	-	-
☒	Antenna Mast	-	AUDIX	-	-
☒	Turn Table	-	AUDIX	-	-

Test Conditions

Temperature: 21,9 °C

Relative Humidity: 50,8 %

Frequency Range of Measurement

1 GHz to 6 GHz

Instrument Settings

IF Band Width: 1 MHz

Test Results

The requirements are:

- ☒ PASS
☐ NOT PASS
☐ NOT APPLICABLE

Remarks

See Appendix A for test data.



APPENDIX A – TEST DATA

Conducted Emissions at Mains Power Ports

[HOT]

N/A



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-16T0302
Page (18) of (42)

[NEUTRAL]

N/A

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.


Conducted Emissions at Telecommunication Ports

- DC 12 V Mode

[10 Mbps]

Common Information

Test Description:	Telecommunication Emission
Model No.:	QNV-6070RP
Mode	12 V (dc) 10 Mbps
Operator Name:	KES



Final Result


Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.155000	—	55.83	83.73	27.90	1000.0	9.000	Single Line	10.1
0.155000	67.47	—	96.73	29.26	1000.0	9.000	Single Line	10.1
1.450000	—	38.79	74.00	35.21	1000.0	9.000	Single Line	9.8
1.450000	49.85	—	87.00	37.15	1000.0	9.000	Single Line	9.8
4.450000	—	37.73	74.00	36.27	1000.0	9.000	Single Line	9.8
4.450000	48.11	—	87.00	38.89	1000.0	9.000	Single Line	9.8
13.750000	—	44.60	74.00	29.40	1000.0	9.000	Single Line	10.1
13.750000	51.09	—	87.00	35.91	1000.0	9.000	Single Line	10.1
16.905000	—	51.08	74.00	22.92	1000.0	9.000	Single Line	10.1
16.905000	54.39	—	87.00	32.61	1000.0	9.000	Single Line	10.1



[100 Mbps]

Common Information

Test Description: Telecommunication Emission
Model No.: QNV-6070RP
Mode: 12 V (dc) 100 Mbps
Operator Name: KES



Final Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.155000	--	55.49	83.73	28.24	1000.0	9.000	Single Line	9.6
0.155000	67.20	--	96.73	29.53	1000.0	9.000	Single Line	9.6
0.195000	--	55.99	81.82	25.83	1000.0	9.000	Single Line	9.6
0.195000	63.09	--	94.82	31.73	1000.0	9.000	Single Line	9.6
3.555000	--	35.06	74.00	38.94	1000.0	9.000	Single Line	9.3
3.555000	46.82	--	87.00	40.18	1000.0	9.000	Single Line	9.3
3.655000	--	35.25	74.00	38.75	1000.0	9.000	Single Line	9.3
3.655000	46.96	--	87.00	40.04	1000.0	9.000	Single Line	9.3
17.060000	--	50.52	74.00	23.48	1000.0	9.000	Single Line	9.5
17.060000	53.80	--	87.00	33.20	1000.0	9.000	Single Line	9.5
17.100000	--	50.57	74.00	23.43	1000.0	9.000	Single Line	9.5
17.100000	54.14	--	87.00	32.86	1000.0	9.000	Single Line	9.5




- PoE Mode

[10 Mbps]

Common Information

Test Description: Telecommunication Emission
Model No.: QNV-6070RP
Mode: PoE 10 Mbps
Operator Name: KES




Final Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.435000	--	55.78	75.16	19.38	1000.0	9.000	Single Line	10.0
0.435000	60.94	--	88.16	27.22	1000.0	9.000	Single Line	10.0
0.440000	--	55.36	75.06	19.70	1000.0	9.000	Single Line	10.0
0.440000	60.05	--	88.06	28.01	1000.0	9.000	Single Line	10.0
1.080000	--	57.40	74.00	16.60	1000.0	9.000	Single Line	9.9
1.080000	57.89	--	87.00	29.11	1000.0	9.000	Single Line	9.9
1.945000	--	57.56	74.00	16.44	1000.0	9.000	Single Line	9.8
1.945000	58.83	--	87.00	28.17	1000.0	9.000	Single Line	9.8
12.960000	--	60.32	74.00	13.68	1000.0	9.000	Single Line	10.1
12.960000	61.09	--	87.00	25.91	1000.0	9.000	Single Line	10.1

[100 Mbps]

Common Information

Test Description:	Telecommunication Emission
Model No.:	QNV-6070RP
Mode	PoE 100 Mbps
Operator Name:	KES



Final Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.435000	--	55.36	75.16	19.80	1000.0	9.000	Single Line	9.5
0.435000	60.45	--	88.16	27.71	1000.0	9.000	Single Line	9.5
1.080000	--	56.95	74.00	17.05	1000.0	9.000	Single Line	9.4
1.080000	57.48	--	87.00	29.52	1000.0	9.000	Single Line	9.4
1.945000	--	57.10	74.00	16.90	1000.0	9.000	Single Line	9.3
1.945000	58.28	--	87.00	28.72	1000.0	9.000	Single Line	9.3
12.960000	--	59.27	74.00	14.73	1000.0	9.000	Single Line	9.6
12.960000	59.87	--	87.00	27.13	1000.0	9.000	Single Line	9.6

**Radiated Electric Field Emissions(Below 1 GHz)**

- DC 12 V Mode

Frequency	Amplitude	ANT	ANT. Height	Correction Factor		Corrected Amplitude	Applicable Limit	Margin
[MHz]	[dB μ V]	Polar. (H/V)	[m]	ANT. [dB/m]	Cable [dB]	[dB μ V/m]	[dB μ V/m]	[dB]
225.15	12.84	V	1.00	12.01	3.10	27.95	40.00	12.05
225.36	14.67	H	4.00	12.02	3.10	29.79	40.00	10.21
425.32	13.40	H	3.30	16.01	4.40	33.81	47.00	13.19
425.73	12.08	V	1.70	16.02	4.41	32.51	47.00	14.49
445.51	21.24	H	2.80	16.36	4.55	42.15	47.00	4.85
475.00	19.62	V	2.20	16.87	4.77	41.26	47.00	5.74

* H : Horizontal, V : Vertical


- PoE Mode

Frequency	Amplitude	ANT	ANT. Height	Correction Factor		Corrected Amplitude	Applicable Limit	Margin
[MHz]	[dB μ V]	Polar. (H/V)	[m]	ANT. [dB/m]	Cable [dB]	[dB μ V/m]	[dB μ V/m]	[dB]
375.99	24.01	H	2.90	15.05	4.06	43.12	47.00	3.88
400.28	21.57	H	3.10	15.57	4.22	41.36	47.00	5.64
425.16	15.24	V	1.50	16.01	4.40	35.65	47.00	11.35
446.10	19.04	H	3.40	16.37	4.56	39.97	47.00	7.03
451.00	17.44	V	1.90	16.45	4.59	38.48	47.00	8.52
500.37	14.87	H	3.50	17.31	4.95	37.13	47.00	9.87

* H : Horizontal, V : Vertical

Radiated Electric Field Emissions(Above 1 GHz)

- DC 12 V Mode



Site : chamber
Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) horizontal
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : QNV-6070RP
Mode : 12 V (dc)
Memo : (1 ~ 3) GHz


	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	1002.00	40.55	23.92	6.52	40.12	164	56.00	-25.13	horizontal	Average
2 pk	1002.00	57.75	23.92	6.52	40.12	164	76.00	-27.93	horizontal	Peak
3	1196.00	29.13	24.69	7.08	40.02	38	56.00	-35.12	horizontal	Average
4	1196.00	51.53	24.69	7.08	40.02	38	76.00	-32.72	horizontal	Peak
5 pp	1634.00	42.84	26.43	8.34	39.81	147	56.00	-18.20	horizontal	Average
6	1634.00	49.46	26.43	8.34	39.81	147	76.00	-31.58	horizontal	Peak
7	1954.00	26.41	27.70	9.22	39.65	269	56.00	-32.32	horizontal	Average
8	1954.00	39.91	27.70	9.22	39.65	269	76.00	-38.82	horizontal	Peak



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-16T0302
Page (25) of (42)



Site : chamber
Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) vertical
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : QNV-6070RP
Mode : 12 V (dc)
Memo : (1 ~ 3) GHz

	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	1000.00	28.45	23.91	6.51	40.12	315	56.00	-37.25	vertical	Average
2	1000.00	41.30	23.91	6.51	40.12	315	76.00	-44.40	vertical	Peak
3	1634.00	40.69	26.43	8.34	39.81	134	56.00	-20.35	vertical	Average
4	1634.00	47.44	26.43	8.34	39.81	134	76.00	-33.60	vertical	Peak
5 pp	1930.00	39.52	27.60	9.16	39.66	318	56.00	-19.38	vertical	Average
6 pk	1930.00	46.70	27.60	9.16	39.66	318	76.00	-32.20	vertical	Peak
7	2972.00	27.55	30.26	11.15	40.19	177	56.00	-27.23	vertical	Average
8	2972.00	41.97	30.26	11.15	40.19	177	76.00	-32.81	vertical	Peak


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-16T0302
Page (26) of (42)



Site : chamber
Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) horizontal
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : QNV-6070RP
Mode : 12 V (dc)
Memo : (3 ~ 6) GHz

		Read	Ant	Cable	Preamp	TPos	Limit	Over		
	Freq	Level	Factor	Loss	Factor		Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	4884.00	24.05	37.06	15.12	40.41	31	60.00	-24.18	horizontal	Average
2	pk 4884.00	37.37	37.06	15.12	40.41	31	80.00	-30.86	horizontal	Peak
3	pp 5262.00	23.38	37.19	15.64	40.37	31	60.00	-24.16	horizontal	Average
4	5262.00	36.24	37.19	15.64	40.37	31	80.00	-31.30	horizontal	Peak
5	5553.00	23.17	36.60	16.02	40.33	180	60.00	-24.54	horizontal	Average
6	5553.00	35.96	36.60	16.02	40.33	180	80.00	-31.75	horizontal	Peak
7	5913.00	22.54	35.88	16.70	40.28	39	60.00	-25.16	horizontal	Average
8	5913.00	35.42	35.88	16.70	40.28	39	80.00	-32.28	horizontal	Peak


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-16T0302
Page (27) of (42)



Site : chamber
Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) vertical
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : QNV-6070RP
Mode : 12 V (dc)
Memo : (3 ~ 6) GHz

	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	4635.00	24.60	35.64	14.67	40.41	226	60.00	-25.50	vertical	Average
2	4635.00	37.17	35.64	14.67	40.41	226	80.00	-32.93	vertical	Peak
3	4758.00	24.48	36.34	14.89	40.41	0	60.00	-24.70	vertical	Average
4	4758.00	37.11	36.34	14.89	40.41	0	80.00	-32.07	vertical	Peak
5 pp	5031.00	23.58	37.66	15.37	40.41	6	60.00	-23.80	vertical	Average
6 pk	5031.00	36.34	37.66	15.37	40.41	6	80.00	-31.04	vertical	Peak
7	5385.00	23.39	36.94	15.78	40.36	155	60.00	-24.25	vertical	Average
8	5385.00	36.03	36.94	15.78	40.36	155	80.00	-31.61	vertical	Peak

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.




KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-16T0302
Page (28) of (42)

- PoE Mode



Site : chamber
Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) horizontal
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : QNV-6070RP
Mode : PoE
Memo : (1 ~ 3) GHz

	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	1396.00	28.25	25.48	7.66	39.93	75	56.00	-34.54	horizontal	Average
2	1396.00	48.03	25.48	7.66	39.93	75	76.00	-34.76	horizontal	Peak
3 pp	1634.00	36.38	26.43	8.34	39.81	24	56.00	-24.66	horizontal	Average
4	1634.00	45.33	26.43	8.34	39.81	24	76.00	-35.71	horizontal	Peak
5	2462.00	25.43	29.01	10.06	39.90	44	56.00	-31.40	horizontal	Average
6	2462.00	39.48	29.01	10.06	39.90	44	76.00	-37.35	horizontal	Peak
7	3000.00	25.26	30.33	11.22	40.21	170	56.00	-29.40	horizontal	Average
8 pk	3000.00	49.06	30.33	11.22	40.21	170	76.00	-25.60	horizontal	Peak


This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr


Test report No.:
KES-E1-16T0302
Page (29) of (42)



Site : chamber
Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) vertical
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : QNV-6070RP
Mode : PoE
Memo : (1 ~ 3) GHz

	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	1076.00	41.13	24.21	6.73	40.08	1	56.00	-24.01	vertical	Average
2 pk	1076.00	56.43	24.21	6.73	40.08	1	76.00	-28.71	vertical	Peak
3 pp	1634.00	40.10	26.43	8.34	39.81	158	56.00	-20.94	vertical	Average
4	1634.00	46.30	26.43	8.34	39.81	158	76.00	-34.74	vertical	Peak
5	1930.00	36.18	27.60	9.16	39.66	294	56.00	-22.72	vertical	Average
6	1930.00	48.89	27.60	9.16	39.66	294	76.00	-30.01	vertical	Peak
7	2598.00	26.05	29.35	10.27	39.98	68	56.00	-30.31	vertical	Average
8	2598.00	44.63	29.35	10.27	39.98	68	76.00	-31.73	vertical	Peak
9	2970.00	31.25	30.26	11.15	40.19	0	56.00	-23.53	vertical	Average
10	2970.00	45.29	30.26	11.15	40.19	0	76.00	-29.49	vertical	Peak

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Site : chamber
Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) horizontal
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : QNV-6070RP
Mode : PoE
Memo : (3 ~ 6) GHz


	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	4125.00	24.89	32.72	13.74	40.41	93	60.00	-29.06	horizontal	Average
2	4125.00	37.29	32.72	13.74	40.41	93	80.00	-36.66	horizontal	Peak
3	4335.00	24.85	33.92	14.13	40.41	127	60.00	-27.51	horizontal	Average
4	4335.00	37.47	33.92	14.13	40.41	127	80.00	-34.89	horizontal	Peak
5	4506.00	24.70	34.90	14.44	40.41	278	60.00	-26.37	horizontal	Average
6	4506.00	38.06	34.90	14.44	40.41	278	80.00	-33.01	horizontal	Peak
7 pp	4698.00	24.71	36.00	14.79	40.41	96	60.00	-24.91	horizontal	Average
8 pk	4698.00	37.71	36.00	14.79	40.41	96	80.00	-31.91	horizontal	Peak



KES Co., Ltd.

C-3701, Simin-daero 365-40,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Test report No.:
KES-E1-16T0302
Page (31) of (42)



Site : chamber
Condition: CISPR22 CLASS-A PK 3m HORN781(2015.05.07) vertical
: RBW:1000.000kHz VBW:1000.000kHz SWT:Auto
Project :
Model : QNV-6070RP
Mode : PoE
Memo : (3 ~ 6) GHz

	Freq	Read Level	Ant Factor	Cable Loss	Preamp Factor	TPos	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	deg	dBuV/m	dB		
1	4245.00	25.01	33.41	13.96	40.41	150	60.00	-28.03	vertical	Average
2	4245.00	37.91	33.41	13.96	40.41	150	80.00	-35.13	vertical	Peak
3	4359.00	24.60	34.06	14.17	40.41	22	60.00	-27.58	vertical	Average
4	4359.00	37.61	34.06	14.17	40.41	22	80.00	-34.57	vertical	Peak
5	4626.00	24.47	35.58	14.66	40.41	164	60.00	-25.70	vertical	Average
6	4626.00	37.07	35.58	14.66	40.41	164	80.00	-33.10	vertical	Peak
7 pp	4671.00	24.79	35.84	14.74	40.41	213	60.00	-25.04	vertical	Average
8 pk	4671.00	37.76	35.84	14.74	40.41	213	80.00	-32.07	vertical	Peak

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.



Test Setup Photos and Configuration

Conducted Voltage Emissions

N/A

N/A

Conducted Telecommunication Emissions

- DC 12 V Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

- PoE Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

Radiated Electric Field Emissions(Below 1 GHz)

- DC 12 V Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.


- PoE Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.


Radiated Electric Field Emissions(Above 1 GHz)

- DC 12 V Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

- PoE Mode



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

EUT External Photographs

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

EUT Internal Photographs

(Internal View)




This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

EUT Internal View – Main Board

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.

EUT Internal View – lens Board

(Top)



(Bottom)



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.