

SAM-21M

■ Specifications

Model		SAM-21M
GENERAL	Color System	NTSC / PAL
	Power Source	90~260VAC,50/60Hz
	Power Consumption	72W
	Picture tube	21" Line Gun,Semi Tinted CRT
	Video Impedence	75Ω BNC
	Speaker	70 x 40mm, 3W 80hm
	Operating temperature	0°C~40°C
	Operating humidity	35 %~80%
	Dimension(W x H x D)	476(W) x 432(H) x 468(D)
	Weight	About 26.8Kg
	Enclosure	Metal
	Resolution	450TV Lines(at center)
VIDEO	Input Level	1.0 ± 0.2Vp-p,75Ω
	Output Level	1.0 ± 0.2Vp-p,75Ω
AUDIO	Input Level	RCA Jack Type 300 ± 50mVrms
	Sound Distortion	Less than 10%
	HUM	Less than 10m Vrms
	BUZZ	Less than 200m Vp-p
Control & Switch JACK & Terminal	Control Front	Rotary Volume:Tint(NTSC System only) Brightness, Contrast, Color, Volume(Speaker) Push Button : Power On/Off MIC & Speaker : One-Way Audio
	Jacks Rear	5 BNC:Video Input/output 4 Audio RCA : Input/output