

CERTIFICATE of EMC Compliance

Report No : EMC-FCC-1841
Type of equipment : CCTV Camera
Model Name : SCB-2004N
Applicant : Samsung Techwin Co., Ltd.
#42 Seongju-Dong, Changwon-Shi,
Kyungsangnam-Do, Korea
Manufacturer#1 : Samsung Techwin Co., Ltd.
#42 Seongju-Dong, Changwon-Shi,
Kyungsangnam-Do, Korea
Manufacturer#2 : TIANJIN SAMSUNG TECHWIN
OPTO-ELECTRONIC CO., LTD
No.11 Weiliu Road. Micro-Electronic Industrial
Park Jingang Road Tianjin 300385, China
Test standards : FCC part 15 subpart B, Class A
Classification : Verification

The above equipment was tested by EMC compliance Testing Laboratory for with the requirements of FCC Rules and Regulations. The results of testing in this report apply to the product / system which was tested only.

These results are deemed satisfactory evidence of compliance with ICES-003 of the Canadian Interference-Causing Equipment Regulations.

Laboratory

EMC compliance Ltd.
480-5 Sin-dong, Yeongtong-gu,
Suwon-city, Gyeonggi-do, 443-390, Korea

Tel: 82 31 336 9919
Fax: 82 505 299 8311



Yeom, Han-Seok/ Manager

EMI TEST REPORT

Test report No : EMC-FCC-1841
Type of Equipment : CCTV Camera
Model Name : SCB-2004N
Applicant : Samsung Techwin Co., Ltd.
#42 Seongju-Dong, Changwon-Shi,
Kyungsangnam-Do, Korea
Manufacturer#1 : Samsung Techwin Co., Ltd.
#42 Seongju-Dong, Changwon-Shi,
Kyungsangnam-Do, Korea
Manufacturer#2 : TIANJIN SAMSUNG TECHWIN
OPTO-ELECTRONIC CO., LTD
No.11 Weiliu Road. Micro-Electronic Industrial
Park Jingang Road Tianjin 300385, China
Test standards : FCC part 15 subpart B, Class A
Classification : Verification
Test Procedure and Items
- Radiated Emissions Measurement : ANSI C63.4-2009
Testing Laboratory : EMC Compliance Ltd.
Test result : Complied

The above equipment was tested by EMC compliance Testing Laboratory for compliance with the requirements of FCC Rules and Regulations. The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

These results are deemed satisfactory evidence of compliance with ICES-003 of the Canadian Interference-Causing Equipment Regulations.

Date of receipt: 2013. 02. 28

Date of testing: 2013. 03. 12

Issued date: 2013. 03. 18

Tested by:

JUNG, HYE-LAN

Approved by:

YEOM, HAN-SEOK

Contents

1. Applicant information	3
2. Laboratory information	4
3. Test system configuration.....	5
3.1 Operation environment	5
3.2 Measurement Uncertainty	6
4. Description of E.U.T.	7
4.1 General information.....	7
4.2 Product description	8
4.3 Auxiliary equipments	8
4.4 Test configuration	9
4.5 Operating conditions	9
5. Summary of test results	9
5.1 Summary of EMI emission test results	10
6. Test results	11
6.1 Radiated Emission	11
7. E.U.T. photographs	19

1. Applicant information

Applicant: SAMSUNG TECHWIN CO., LTD.
Address: #42 Seongju-Dong, Changwon-Shi,
Kyungsangnam-Do, Korea
Telephone: +82-70-7147-8361
Fax: +82-31-277-2784
E-mail: js2002.kang@samsung.com
Contact name: **Kang Jei Soon**

Manufacturer#1: SAMSUNG TECHWIN CO., LTD.
Address: #42 Seongju-Dong, Changwon-Shi,
Kyungsangnam-Do, Korea
Telephone: +82-70-7147-8361
Fax: +82-31-277-2784
E-mail: js2002.kang@samsung.com
Contact name: **Kang Jei Soon**

Manufacturer#2: TIANJIN SAMSUNG TECHWIN OPTO-ELECTRONIC CO., LTD
Address: No.11 Weiliu Road. Micro-Electronic Industrial Park
Jingang Road Tianjin 300385, China

2. Laboratory information

Address

EMC compliance Ltd.

480-5 Sin-dong, Yeongtong-gu, Suwon-city, Gyeonggi-do, 443-390, Korea

Telephone Number: 82 31 336 9919

Facsimile Number: 82 505 299 8311


FCC CAB.: KR0040

VCCI Registration No. : R-3327, G-198, C-3706, T-1849

Industry Canada Registration No.: 8035A

KOLAS NO.: 231

SITE MAP



3. Test system configuration

3.1 Operation environment

	Temperature	Humidity	Pressure
Chamber(10 m)	: 21 °C	28 % R.H.	-

Test site

These testing items were performed following locations;

Test item	Test site
Conducted Emission	Shielded Room
Radiated Emission	10 m Chamber

3.2 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC.

The factors contributing to uncertainties are test receiver, cable loss, antenna factor calibration, Antenna directivity, antenna factor variation with height, antenna phase center variation, antenna frequency interpolation, measurement distance variation, site imperfection, mismatch, and system repeatability. Based on CISPR 16-4-2, the measurement uncertainty level with a 95 % confidence level was applied.

Conducted emission measurement (C.L: Approx 95 %, k = 2)		
Shielded Room (CE#1)	9 kHz ~ 150 kHz: ± 3.82 dB 150 kHz ~ 30 MHz: ± 3.43 dB	
Shielded Room (CE#2)	9 kHz ~ 150 kHz: ± 3.82 dB 150 kHz ~ 30 MHz: ± 3.43 dB	
Shielded Room (CE#3)	9 kHz ~ 150 kHz: ± 4.00 dB 150 kHz ~ 30 MHz: ± 3.63 dB	
Radiated Emission measurement (C.L: Approx 95 %, k = 2)		
10 m Chamber (#F4)	30 MHz ~ 300 MHz	3 m: + 4.56 dB, - 4.58 dB 10 m: + 4.56 dB, - 4.56 dB
	300 MHz ~ 1 000 MHz	3 m: + 4.84 dB, - 4.85 dB 10 m: + 4.71 dB, - 4.72 dB
	1 GHz ~ 6 GHz	3 m: + 6.19 dB, - 6.20 dB
	6 GHz ~ 18 GHz	3 m: + 6.41 dB, - 6.53 dB
10 m Chamber (#F2)	30 MHz ~ 300 MHz	3 m: + 4.86 dB, - 4.88 dB 10 m: + 4.86 dB, - 4.86 dB
	300 MHz ~ 1 000 MHz	3 m: + 4.98 dB, - 4.99 dB 10 m: + 4.85 dB, - 4.87 dB
	1 GHz ~ 6 GHz	3 m: + 6.19 dB, - 6.20 dB
	6 GHz ~ 18 GHz	3 m: + 6.41 dB, - 6.53 dB

4. Description of E.U.T.

4.1 General information

Video	SCB-2004N	SCB-2004ND	SCB-2004P	SCB-2004PD	SCB-2004PH
Imaging Device	1/3" Super HAD CCD II				
Total Pixels	1020(H) x 508(V)		1020(H) x 596(V)		
Effective Pixels	976(H) x 494(V)		976(H) x 582(V)		
Scanning System	2 : 1 Interlace				
Synchronization	Internal / Line Lock	Internal	Internal / Line Lock	Internal	Internal / Line Lock
Frequency	H : 15.734KHz / V : 50Hz		H : 15.625KHz / V : 50Hz		
Horizontal Resolution	Color : 650 TV lines				
Min. Illumination	0.15Lux / 0.002Lux (F1.2, SENS-UP x64)				
S / N Ratio	52dB (AGC off, Weight on)				
Video Output	CVBS : 1.0 Vp-p / 75Ω composite				
Lens Type					
Lens Type	Manual / Auto Iris (Video/DC)				
Mount Type	C/CS				
Operational					
On Screen Display	English, Japanese, Spanish, French, Portuguese, Taiwanese, Korean		English, French, German, Spanish, Italian, Chinese, Russian, Polish, Czech, Romanian, Serbian, Swedish, Danish, Turkish, Portuguese		
Camera Title	Off / On (Displayed 15 characters)				
Day & Night	Auto (Electrical) / Color / B/W				
Backlight Compensation	BLC / HLC / Off				
Contrast Enhancement	SSDR (Off/On)				
Digital Noise Reduction	3D/2D DNR (Off/On)				
Defog	Off/On				
Motion Detection	Off/On				
Privacy Masking	Off / On(8 programmable zones)				
Sens-up (Frame Integration)	2x ~ 64x				
Gain Control	Off / Low / High				
White Balance	ATW / Outdoor / Indoor / Manual / AWC (1,800K° ~ 10,500K°)				
Electronic Shutter Speed	1/60 ~ 1/120,000 sec		1/50 ~ 1/120,000 sec		
Digital Image Stabilization	N/A				
Digital Zoom	N/A				
Reverse	H-Rev (Off/On)				
Communication	Coaxial Control (SPC-300 Compatible)				
Protocol	Coax : Pelco-C (Coaxitron)				
Environmental					
Operating Temperature / Humidity	-10°C ~ +55°C (+14°F ~ +131°F) / Less than 90% RH				
Electrical					
Input Voltage/Current	Dual (24VAC±10% & 12VDC±10%)	12VDC±10%	Dual (24VAC±10% & 12VDC±10%)	12VDC±10%	230V AC ± 10%
Power Consumption	TBD	TBD	TBD	TBD	TBD
Mechanical					
Color / Material	Ivory / Plastic				
Dimension (WxHxD)	TBD				
Weight	TBD	TBD	TBD	TBD	TBD


4.2 Product description

Type of product	CCTV Camera
Model name (Basic)	SCB-2004N
Model name (Variant)	-
Difference	-
Trade name	-
Serial no	C8Z46V2D200004X
Testing voltage	DC 12 V , AC 24 V
Product rating	DC 12 V , AC 24 V
Internal clock frequency	Above 108 MHz
Note	* AC/DC adaptor was not provided by the manufacturer. * AC/AC adaptor was not provided by the manufacturer.

4.3 Auxiliary equipments

Type	Model / Part #	Serial number	Manufacturer
Monitor	PM24KO	YER8HVDBA00057E	SAMSUNG
Lens	-	-	-
AC/DC Adaptor (DC 12 V)	DAD12050DKA	-	SAMSUNG Techwin
AC/AC Adaptor (AC 24 V)	DRL-241500AC	-	SAMSUNG Techwin

4.4 Test configuration



Note	Start		End		Cable	
	Name	I/O port	Name	I/O port	Length (m)	Spec.
1	EUT (CCTV Camera)	Power	AC/DC Adaptor or AC/AC Adaptor	Power	1.7	Non-Shield
2		BNC	Monitor	BNC	3.0	Shield
3		-	Lens	-	Direct	-
4		IRIS	Lens	IRIS	0.1	Non-Shield

4.5 Operating conditions

The EUT was configured as normal intended use.

Test mode	Normal operating
1	Check image with monitor.

* Note: 2 types of powers are available for the product, that are DC 12 V , AC 24 V .

Therefore, tests were performed for 2 different types of powers.

5. Summary of test results

In the above configuration tested, The EUT complied with the requirement of the specification

5.1 Summary of EMI emission test results

FCC Part 15 Subpart B (Class A)

ANSI C63.4 – 2009

Applied	Test items	Test method	Result
☐	Conducted Emission	ANSI C63.4 – 2009	N/A
☒	Radiated Emission	ANSI C63.4 – 2009	Complied

6. Test results

6.1 Radiated Emission

Test specification	FCC Part 15, Section 15.109(g), Class A		
Testing voltage	DC 12 V, AC 24 V		
Test facility	10 m Chamber (#F2)		
Test distance	10 m, 3 m		
Date	2013. 03. 12		
Temperature (°C)	21 °C	Humidity (% R.H.)	28 % R.H.
Remarks	Complied		

6.1.1 Limits of radiated emission measurement

Frequency [MHz]	Class A (dB(μ V/m)) @ 10 m	Class B (dB(μ V/m)) @ 3 m
30-88	39	40
88-216	43.5	43.5
216-960	46.4	46
Above 960	49.5	54

* Note- Alternative standard: CISPR, Pub. 22 *

6.1.2 Measurement procedure

The test was done at a 10 m chamber with a quasi-peak detector. EUT was placed on a non-metallic table height of 0.8 m above the reference ground plane. Cables were folded back and forth forming a bundle 0.3 m to 0.4 m long and were hanged at a 0.4 m height to the ground plane.

Cables connected to EUT were fixed to cause maximum emission. Test was made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength.

6.1.3 Used equipments

Equipment	Model no.	Serial no.	Makers	Next Cal. Date	Used
Test Receiver	ESCI	100710	R&S	2013.11.06	☒
Bi-Log Antenna	VULB 9168	9168-440	SCHWARZBECK	2013.10.04	☒
Amplifier	310N	293004	SONOMA INSTRUMENT	2013.11.06	☒
3 dB Attenuator	8491A	27444	HP	2013.11.06	☒
Antenna Mast	MA4000-EP	303	Innco Systems	-	☒
Turn Table	DT2000S-1t	079	Innco Systems	-	☒
Horn ANT	3115	00086706	ETS	2013.11.21	☒
Amplifier	8449B	3008A02343	AGILENT	2013.11.06	☒
Spectrum Analyzer	FSP7	100289	R&S	2013.12.14	☒

6.1.4 Sample calculation

The field strength is calculated adding the antenna Factor, cable loss and, Antenna pad adding, subtracting the amplifier gain from the measured reading.

The sample calculation is as follow:

$$\text{Result} = \text{M.R} + \text{C.F}(\text{A.F} + \text{C.L} + 3 \text{ dB Att} - \text{A.G})$$

M.R = Meter Reading

C.F = Correction Factor

A.F = Antenna Factor

C.L = Cable Loss

A.G= Amplifier Gain



3 dB Att = 3 dB Attenuator

If M.R is 30 dB, A.F 12 dB, C.L 5 dB, 3 dB, A.G 35 dB


The result is $30 + 12 + 5 + 3 - 35 = 15 \text{ dB}(\mu\text{V/m})$

6.1.5 Photographs of test setup

* 30 MHz ~ 1 GHz




* 1 GHz ~ 5 GHz



6.1.6 Radiated emission measurement result

* Graph and Data


* 30 MHz ~ 1 GHz (SCB-2004N)_DC 12V



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c. f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	65.813	V	40.3	-14.9	25.4	39.0	13.6	199.0	342.8	
2	144.032	V	37.7	-13.7	24.0	43.5	19.5	100.0	117.2	
3	197.886	V	42.8	-16.0	26.8	43.5	16.7	100.0	312.8	
4	234.115	V	41.2	-14.8	26.4	46.5	20.1	100.0	5.0	
5	666.127	H	30.8	-3.1	27.7	46.5	18.8	201.0	353.6	
6	954.055	H	27.8	2.4	30.2	46.5	16.3	100.0	64.6	


* 1 GHz ~ 5 GHz (SCB-2004N)_DC 12V



Final Result

No.	Frequency [MHz]	(P)	Reading AV [dB(μV)]	Reading PK [dB(μV)]	c.f [dB(1/m)]	Result AV [dB(μV/m)]	Result PK [dB(μV/m)]	Limit AV [dB(μV/m)]	Limit PK [dB(μV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [deg]	Remark
1	1921.800	H	35.1	41.8	-2.6	32.5	39.2	60.0	80.0	27.5	40.8	100.0	35.8	
2	2094.986	V	36.0	42.3	-1.7	34.3	40.6	60.0	80.0	25.7	39.4	100.0	200.3	
3	2572.695	H	34.8	40.2	-0.8	34.0	39.4	60.0	80.0	26.0	40.6	100.0	329.0	
4	2988.873	H	31.3	41.9	-0.2	31.1	41.7	60.0	80.0	28.9	38.3	100.0	53.3	
5	3220.698	H	33.0	40.1	0.6	33.6	40.7	60.0	80.0	26.4	39.3	100.0	286.9	


* 30 MHz ~ 1 GHz (SCB-2004N)_AC 24V



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c.f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	101.216	V	42.2	-18.1	24.1	43.5	19.4	100.0	178.0	
2	137.352	V	39.1	-14.2	24.9	43.5	18.6	100.0	165.4	
3	198.003	V	41.6	-16.0	25.6	43.5	17.9	100.0	69.7	
4	234.128	V	38.5	-14.8	23.7	46.5	22.8	100.0	1.7	
5	378.021	H	38.6	-9.8	28.8	46.5	17.7	301.0	94.9	
6	666.133	H	30.0	-3.1	26.9	46.5	19.6	201.0	22.0	

* 1 GHz ~ 5 GHz (SCB-2004N)_AC 24V



Final Result

No.	Frequency [MHz]	(P)	Reading AV [dB(uV)]	Reading PK [dB(uV)]	c.f [dB(1/m)]	Result AV [dB(uV/m)]	Result PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [deg]	Remark
1	1098.306	V	40.1	45.2	-8.6	31.5	36.6	60.0	80.0	28.5	43.4	100.0	12.5	
2	1134.489	V	39.4	45.8	-8.2	31.2	37.6	60.0	80.0	28.8	42.4	100.0	30.7	
3	1421.991	H	39.7	44.6	-5.7	34.0	38.9	60.0	80.0	26.0	41.1	100.0	101.6	
4	2286.307	V	31.9	43.0	-1.3	30.6	41.7	60.0	80.0	29.4	38.3	100.0	108.6	
5	2993.346	V	30.3	39.8	-0.2	30.1	39.6	60.0	80.0	29.9	40.4	100.0	328.7	

7. E.U.T. photographs

Front View



Rear View




Left View




Right View






Label





FCC Label Location

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Inside



Main Board



CCD Board

