

SCB-6005



Analog

BOX

SCB-6005

2MP Analog Box camera



Key Features

- Full HD(1920 x 1080, 30fps) resolution
- 0.04Lux@F1.2 (Color), 0.004Lux@F1.2(B/W)
- Day & Night(ICR)
- SSNRIV, Motion detection
- Transmission distance max.500m

SCB-6005

2MP Analog Box camera



Specifications

Video

Imaging Device	Size	1/2.8"
	Type	CMOS
Resolution		1920x1080
Max. Framerate(NTSC/PAL)		30fps/25fps
Min. Illumination	Color(1/30sec, 30IRE)	0.04
	BW(1/30sec, 30IRE)	0.004
Video Out		BNC: AHD
Video Transmission Distance		500m(5C2V Coaxial Cable)

Lens

Focus Control		Manual
Lens Type		DC auto iris(IR corrected)
Mount Type		C mount, CS mount

Operational

Day & Night		Auto(ICR)
Backlight Compensation		BLC, HLC, DWDR
Digital Noise Reduction		SSNRIV
Defog		Support
Motion Detection	Quantity	4ea
Privacy Masking	Quantity	8ea
	Shape	Rectangular zones
Gain Control		Low, Middle, High, Very High
White Balance		ATW, AWC, Manual, Indoor, Outdoor
Electronic Shutter	Speed Range	1~1/12,000sec
Video Rotation		Flip, Mirror, Hallway view(90°/270°)
Serial Interface		RS-485
Alarm Interface	In/Out	Output 1ea
	Others	External D/N

Operational

Alarm Triggers	Analytics
Alarm Events When Alarm Trigger Occurred	Alarm output
Coaxial Protocol	ACP, CVBS

Analytics

Analytics Events	Normal	Motion detection
------------------	--------	------------------

Environmental & Electrical

Operating Condition	Temperature	-10°C~+55°C(+14°F~+131°F)
	Humidity	0~90% RH(non-condensing)
Input Voltage		24VAC, 12VDC
Power Consumption	12VDC	0.32A (Max 3.5W)
	24VAC	0.37A (Max 3.6W)

Mechanical

Color	Ivory, Black
Material	Aluminum, PC(Polycarbonate)
Product Dimensions	68.4(W) × 59.6(H) × 92.7(D)mm(2.69 × 2.35 × 3.65")
Product Weight	186g(0.41 lb)

SCB-6005

2MP Analog Box camera



CAD

Unit: mm [inch]

