

TESTING CERTIFICATE

EMC Compliance Ltd.

480-5 Sin-dong, Yeongtong-gu,
Suwon-city, Gyeonggi-do,
443-390, Korea
TEL: 82 31 336 9919
FAX: 82 505 299 8311

Certificate No.: EMC-CE-4202

Page(1) / (32) Pages



1. Applicant

Name: Samsung Techwin Co., Ltd.
Address: #42 Seongju-Dong, Changwon-Shi,
Kyungsangnam-Do, Korea
Date of Receipt: July 18, 2013

2. Manufacturer

Name#1: Samsung Techwin Co., Ltd.
Name#2: TIANJIN SAMSUNG TECHWIN
OPTO-ELECTRONIC CO., LTD

3. Use of Report:

Completed report

4. Test Sample:

CCTV Camera, SCP-2373HP

5. Date of Test:

July 26, 2013

6. Test method used:

AS/NZS CISPR 22:2009, Class A

7. Testing Environment:


Temperature: (25.0) °C,
Relative Humidity: (52.0 ± 1.0) % R.H.

8. Test Results:

Refer to page 12 ~ page 21
(Measurement uncertainty: Refer to page 6)

This result shown in this report refer only to the sample(s) tested unless otherwise stated.

This Test Report cannot be reproduced, except in full, without the written approval of
EMC Compliance Laboratory.

Affirmation	Tested by  Name: PARK, GUN-SU	Technical Manager  Name: YEOM, HAN-SEOK
-------------	--	---

The above test certificate is the accredited test results by Korea Laboratory Accreditation Scheme, which signed the ILAC-MRA.

2013. 08. 02

EMC Compliance Ltd.

Accredited by KOLAS, Republic of KOREA

Contents

1. Applicant information	3
2. Laboratory information	4
3. Test system configuration	5
3.1 Operation environment	5
3.2 Measurement Uncertainty	6
4. Description of E.U.T.	7
4.1 General information.....	7
4.2 Product description.....	9
4.3 Auxiliary equipments.....	9
4.4 Test configuration	10
4.5 Operating conditions	10
5. Summary of test results	11
5.1 Summary of EMI emission test results.....	11
6. Test results	12
6.1 Conducted Emission.....	12
6.2 Radiated Emission	16
7. E.U.T. photographs	22

1. Applicant information

Applicant: SAMSUNG TECHWIN CO., LTD.
Address: #42 Seongju-Dong, Changwon-Shi,
Kyungsangnam-Do, Korea
Telephone: +82-70-7147-8361
Fax: +82-31-277-2784
E-mail: js2002.kang@samsung.com
Contact name: **Kang Jei Soon**

Manufacturer#1: SAMSUNG TECHWIN CO., LTD.
Address: #42 Seongju-Dong, Changwon-Shi,
Kyungsangnam-Do, Korea
Telephone: +82-70-7147-8361
Fax: +82-31-277-2784
E-mail: js2002.kang@samsung.com
Contact name: **Kang Jei Soon**

Manufacturer#2: TIANJIN SAMSUNG TECHWIN OPTO-ELECTRONIC CO., LTD
Address: No.11 Weiliu Road, Micro-Electronic Industrial Park
Jingang Road Tianjin 300385, China

2. Laboratory information

Address

EMC compliance Ltd.

480-5 Sin-dong, Yeongtong-gu, Suwon-city, Gyeonggi-do, 443-390, Korea

Telephone Number: 82 31 336 9919

Facsimile Number: 82 505 299 8311


FCC CAB.: KR0040

VCCI Registration No. : R-3327, G-198, C-3706, T-1849

Industry Canada Registration No.: 8035A

KOLAS NO.: 231

SITE MAP



3. Test system configuration

3.1 Operation environment

	Temperature	Humidity	Pressure
Chamber(10 m)	: 25 °C	51 % R.H.	-
Shielded room(CE)	: 25 °C	53 % R.H.	-

Test site

These testing items were performed following locations;

Test item	Test site
Conducted Emission	Shielded Room
Radiated Emission	10 m Chamber

3.2 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC.

The factors contributing to uncertainties are test receiver, cable loss, antenna factor calibration, Antenna directivity, antenna factor variation with height, antenna phase center variation, antenna frequency interpolation, measurement distance variation, site imperfection, mismatch, and system repeatability. Based on CISPR 16-4-2, the measurement uncertainty level with a 95 % confidence level was applied.

Conducted emission measurement (C.L: Approx 95 %, k = 2)		
Shielded Room (CE#1)	9 kHz ~ 150 kHz: ± 3.82 dB	
	150 kHz ~ 30 MHz: ± 3.43 dB	
Shielded Room (CE#2)	9 kHz ~ 150 kHz: ± 3.82 dB	
	150 kHz ~ 30 MHz: ± 3.43 dB	
Shielded Room (CE#3)	9 kHz ~ 150 kHz: ± 4.00 dB	
	150 kHz ~ 30 MHz: ± 3.63 dB	
Radiated Emission measurement (C.L: Approx 95 %, k = 2)		
10 m Chamber (#F4)	30 MHz ~ 300 MHz	3 m: + 4.56 dB, - 4.58 dB 10 m: + 4.56 dB, - 4.56 dB
	300 MHz ~ 1 000 MHz	3 m: + 4.84 dB, - 4.85 dB 10 m: + 4.71 dB, - 4.72 dB
	1 GHz ~ 6 GHz	3 m: + 6.19 dB, - 6.20 dB
10 m Chamber (#F2)	30 MHz ~ 300 MHz	3 m: + 4.86 dB, - 4.88 dB 10 m: + 4.86 dB, - 4.86 dB
	300 MHz ~ 1 000 MHz	3 m: + 4.98 dB, - 4.99 dB 10 m: + 4.85 dB, - 4.87 dB
	1 GHz ~ 6 GHz	3 m: + 6.19 dB, - 6.20 dB

4. Description of E.U.T.

4.1 General information

Video	SCP-2373HN	SCP-2373HP
Imaging Device	1/4" Sony 980H Exview HAD II color CCD	
Total Pixels	1020(H) x 508(V) 520K	1020(H) x 598(V) 610K
Effective Pixels	976(H) x 494(V) 480K	976(H) x 582(V) 570K
Scanning System	2 : 1 Interlace	
Synchronization	Internal / Line Lock	
Frequency	H : 15.734KHz / V : 59.94Hz	H : 15.625KHz / V : 50Hz
Horizontal Resolution	Color : 650 TV lines, B/W : 680 TV lines	
Min. Illumination	Color : 0.2Lux @ F1.6 (50IRE), 0.0004 Lux (Sens-up, 512x) B/W : 0.01 Lux @ F1.6 (50IRE), 0.00002 Lux (Sens-up, 512x)	
S / N Ratio	52dB (AGC off, Weight on)	
Video Output	CVBS : 1.0 Vp-p / 75Ω composite	
Lens Type		
Focal Length (Zoom Ratio)	8.6~129.6mm (Optical 37x)	
Max. Aperture Ratio	1:1.6 (Wide) ~ 3.9 (Tele)	
Angular Field of View	H : 58.26°(Wide) ~ 1.62°(Tele) / V : 43.26°(Wide) ~ 1.22°(Tele)	
Min. Object Distance	1.6m	
Gain Control	Off / Low / Medium / High / Manual	
Zoom Movement Speed	3.1 sec (Fast speed mode)	
Pan / Tilt		
Pan Range	360° Endless	
Pan Speed	Preset : 500°/sec / Manual : 0.024°/sec ~ 120°/sec (Proportional zoom ratio)	
Tilt Range	-5° ~ 185° (Manual Setup : -15° ~ 195°)	
Tilt Speed	Preset : 500°/sec / Manual : 0.024°/sec ~ 120°/sec (Proportional zoom ratio)	
Preset	255	
Preset Accuracy	±0.1°	
Operational		
On Screen Display	English, Japanese, Spanish, French, Portuguese, Korean	English, French, German, Spanish, Italian, Chinese, Russian, Polish, Czech, Turkish, Portuguese
Camera Title	Off / On (Displayed 12 characters)	
Day & Night	Auto / Color / B/W	
Backlight Compensation	BLO / HLO / Off	
Wide Dynamic Range	128x	
Contrast Enhancement	33DR (Off/On)	
Digital Noise Reduction	33NRIII (Off/On)	
Digital Image Stabilization	Off / On	
Motion Detection	Built-In	
Privacy Masking	Off / On (8 programmable zones)	
Sens-up (Frame Integration)	2x ~ 512x	
Gain Control	Off / Low / Medium / High / Manual	
White Balance	ATW / ATW(OUT) / ATW(IN) / Manual / AWC / MERCURY	

Electronic Shutter Speed	1/260 ~ 1/120,000 sec
Digital Zoom	Off / On (2x ~ 16x)
Digital Flip	Off / On
Schedule	Day / Time
Alarm	8 In 8 Out
Communication	Coaxial Control (8PC-800 Compatible), RS-485/422
Protocol	Coax : Pelco-C (Coaxitron) RS-485/422: Samsung-T, Samsung-E, Pelco-D, Pelco-P, Vicon, Honeywell, Panasonic, Bosch, AD, GE
Environmental	
Operating Temperature / Humidity	-50°C ~ +55°C (-58°F ~ +131°F) / Less than 90% RH
Ingress Protection	IP66
Electrical	
Input Voltage/Current	24VAC±10%
Power Consumption	Max. 15W / 60W (Fan & Heater)
Mechanical	
Color / Material	Ivory, Aluminum, Plastic (Dome Cover : Clear)
Dimension (WxHxD)	Φ220 x 293.6mm
Weight	3.1Kg


4.2 Product description

Type of product	CCTV Camera
Model name (Basic)	SCP-2373HP
Model name (Variant)	SCP-2273HP
Difference	-
Trade name	-
Serial no	Engineering Sample
Testing voltage	240 V, 50 Hz
Product rating	* AC/AC Adaptor (STA-230) Input: AC 230 V~, 50 Hz, 450 mA Output: AC 24 V, 2500 mA
Internal clock frequency	Above 108 MHz
Note	AC/AC adaptor was provided by the manufacturer.

4.3 Auxiliary equipments

Type	Model / Part #	Serial number	Manufacturer
Monitor	PM24KO	YER8HVDBA00057E	SAMSUNG
Controller	SCC-1000	EW089028913	SAMSUNG
JIG	-	-	-

4.4 Test configuration



Note	Start		End		Cable	
	Name	I/O port	Name	I/O port	Length (m)	Spec.
1	EUT (CCTV Camera)	Power	AC/AC Adaptor	Power	1.5	Non-Shield
2		BNC	Monitor	BNC	3.0	Shield
3		Alarm In/Out	JIG	Alarm In/Out	3.0	Non-Shield
4		Tx(+,-), Rx(+,-)	Controller	Tx(+,-), Rx(+,-)	3.0	Non-Shield

4.5 Operating conditions

The EUT was configured as normal intended use.

Test mode	Normal operating
1	Camera monitoring test.
	Alarm In/Out test
	Controller test.

5. Summary of test results

5.1 Summary of EMI emission test results

Applied	Test items	Test method	Result
☒	Conducted Emission	AS/NZS CISPR 22:2009, Class A	12 Page ~ 15 Page
☒	Radiated Emission	AS/NZS CISPR 22:2009, Class A	16 Page ~ 21 Page

6. Test results

6.1 Conducted Emission

Test specification	AS/NZS CISPR 22:2009, Class A		
Testing voltage	240 V, 50 Hz		
Test facility	Shielded room (CE#1)		
Date	2013. 07. 26		
Temperature (°C)	25 °C	Humidity (% R.H.)	53 % R.H.
Remarks	Complied		

6.1.1 Limits of conducted emission measurement

☒ AC main

Frequency MHz	Class A $\text{dB}\mu\text{V}$		Class B $\text{dB}\mu\text{V}$	
	Quasi-peak	Average	Quasi-peak	Average
0.15 ~ 0.5	79	66	66 ~ 56 *	56 ~ 46*
0.5 ~ 5	73	60	56	46
5 ~ 30	73	60	60	50

*The limit decreases linearly with the logarithm of frequency.

☐ Telecommunication

Frequency MHz	Class A Voltage Limits $\text{dB}\mu\text{V}$		Current Limits $\text{dB}\mu\text{A}$	
	Quasi-Peak	Average	Quasi-Peak	Average
0.15 ~ 0.5	97 to 87	84 to 74	53 to 43	40 to 30
0.5 ~ 30	87	74	43	30
Frequency MHz	Class B Limits $\text{dB}\mu\text{V}$		Current Limits $\text{dB}\mu\text{A}$	
	Quasi-Peak	Average	Quasi-Peak	Average
0.15 ~ 0.5	84 to 74	74 to 64	40 to 30	30 to 20
0.5 ~ 30	74	64	30	20

* The limits decrease linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz

* The current and voltage disturbance limits are derived for use with an impedance stabilization Network (ISN) which presents a common mode (asymmetric mode) impedance of 150 Ω to the telecommunication port under test (conversion factor is $20 \log_{10} 150/I = 44 \text{ dB}$).

6.1.2 Measurement procedure



The measurements were performed in a shielded room. EUT was setup as shown in photograph and placed on a non-metallic table height of 0.8 m above the reference ground plane. The rear of table was located 0.4 m to the vertical conducted plane. EUT was power through the LISN, which was bonded to the ground plane. The LISN power was filtered. Each EUT power lead, except ground (safety) lead was individually connected through a LISN to input power source. EUT signal cables that hung closer than 0.4 m to the Horizontal metal ground 0.3 m ~ 0.4 m long. The power cord was bundles in the center. All peripheral equipment was powered from a sub LISN. The LISN and ISN were positioned 0.8 m from the EUT. Peak and Average detection were used in preliminary testing and Quasi-peak and Average detections were used at final measurement. Both lines of power cord, hot and neutral, were measured.

6.1.3 Used equipments

Equipment	Model	Serial No.	Makers	Next Cal. Date	Used
Test Receiver	ESHS30	828765/009	R&S	2013.10.22	☐
Test Receiver	ESCI7	100732	R&S	2014.02.18	☐
Test Receiver	ESCI	100001	R&S	2014.07.25	☐
Test Receiver	ESCI	100710	R&S	2013.11.06	☒
LISN	ENV216	101358	R&S	2013.10.22	☒
LISN	ESH3-Z5	100267	R&S	2014.07.08	☒
8-WIRE ISN	NTFM 8158 CAT5	CAT5-8158-0028	SCHWARZBECK	2014.04.13	☐
8-WIRE ISN	NTFM 8158 CAT3	CAT3-8158-0020	SCHWARZBECK	2014.04.13	☐
ISN	ST08	24342	TESEQ	2014.06.21	☐
ISN	ENY81	101545	R&S	2013.08.29	☐


6.1.4 Photographs of test setup

* AC Main



6.1.5 Conducted emission measurement result

* AC Main (SCP-2373HP)



Final Result

--- N Phase ---										
No.	Frequency	Reading QP	Reading CAV	c.f	Result QP	Result CAV	Limit QP	Limit AV	Margin QP	Margin CAV
	[MHz]	[dB(uV)]	[dB(uV)]	[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB]	[dB]
1	0.70254	8.5	3.6	9.9	18.4	13.5	73.0	60.0	54.6	46.5
2	0.77916	5.4	2.6	9.9	15.3	12.5	73.0	60.0	57.7	47.5
3	1.36324	6.8	3.2	9.8	16.6	13.0	73.0	60.0	56.4	47.0
4	13.58854	18.9	17.0	9.8	28.7	26.8	73.0	60.0	44.3	33.2
--- L1 Phase ---										
No.	Frequency	Reading QP	Reading CAV	c.f	Result QP	Result CAV	Limit QP	Limit AV	Margin QP	Margin CAV
	[MHz]	[dB(uV)]	[dB(uV)]	[dB]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB(uV)]	[dB]	[dB]
1	0.15832	6.4	2.5	10.1	16.5	12.6	79.0	66.0	62.5	53.4
2	0.18202	4.0	1.1	10.1	14.1	11.2	79.0	66.0	64.9	54.8
3	0.2366	1.8	0.0	9.9	11.7	9.9	79.0	66.0	67.3	56.1
4	0.3572	7.2	3.1	10.0	17.2	13.1	79.0	66.0	61.8	52.9

6.2 Radiated Emission

Test specification	AS/NZS CISPR 22:2009, Class A		
Testing voltage	240 V, 50 Hz		
Test facility	10 m Chamber (#F2)		
Test distance	10 m, 3 m		
Date	2013. 07. 26		
Temperature (°C)	25 °C	Humidity (% R.H.)	51 % R.H.
Remarks	Complied		

6.2.1 Limits of radiated emission measurement

☒ Limits below 1 GHz

Frequency MHz	Class A dB μ V/m @ 10 m	Class B dB μ V/m @ 10 m
30 ~ 230	40	30
230 ~ 1 000	47	37

☒ Limits above 1 GHz

Frequency MHz	Class A @ 3 m		Class B @ 3 m	
	Average limit dB μ V/m	Peak limit dB μ V/m	Average limit dB μ V/m	Peak limit dB μ V/m
1 ~ 3	56	76	50	70
3 ~ 6	60	80	54	74

Note - The lower limit applies at the transition frequency.

6.2.2 Measurement procedure

The test was done at a 10 m chamber with a quasi-peak detector. EUT was placed on a non-metallic table height of 0.8 m above the reference ground plane. Cables were folded back and forth forming a bundle 0.3 m to 0.4 m long and were hanged at a 0.4 m height to the ground plane. Cables connected to EUT were fixed to cause maximum emission. Test was made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength.

6.2.3 Used equipments

Equipment	Model no.	Serial no.	Makers	Next Cal. Date	Used
Test Receiver	ESCI7	100732	R&S	2014.02.18	☒
Test Receiver	ESCI	100001	R&S	2014.07.25	☐
Test Receiver	ESCI	100710	R&S	2013.11.06	☐
Bi-Log Antenna	VULB 9168	440	SCHWARZBECK	2013.10.04	☒
Amplifier	310N	293004	SONOMA INSTRUMENT	2013.11.06	☒
3 dB Attenuator	8491B	22981	HP	2014.03.19	☒
Antenna Mast	MA4000-EP	303	Innco Systems	-	☒
Turn Table	DT2000S-1t	079	Innco Systems	-	☒
Amplifier	8449B	3008A02343	AGILENT	2013.11.06	☒
Horn ANT	3115	00086706	ETS	2013.11.21	☒
Spectrum Analyzer	FSP7	100289	R&S	2013.12.14	☐

6.2.4 Sample calculation

The field strength is calculated adding the antenna Factor, cable loss and, Antenna pad adding, subtracting the amplifier gain from the measured reading.

The sample calculation is as follow:

$$\text{Result} = \text{M.R} + \text{C.F}(\text{A.F} + \text{C.L} + 3 \text{ dB Att} - \text{A.G})$$

M.R = Meter Reading

C.F = Correction Factor

A.F = Antenna Factor

C.L = Cable Loss

A.G= Amplifier Gain

3 dB Att = 3 dB Attenuator


If M.R is 30 dB, A.F 12 dB, C.L 5 dB, 3 dB, A.G 35 dB

The result is



$$30 + 12 + 5 + 3 - 35 = 15 \text{ dB}\mu\text{V/m}$$

6.2.5 Photographs of test setup

* 30 MHz ~ 1 GHz




* 1 GHz ~ 6 GHz



6.2.6 Radiated emission measurement result

* Graph and Data


* 30 MHz ~ 1 GHz (SCP-2373HP)



Final Result

No.	Frequency [MHz]	(P)	Reading QP [dB(uV)]	c. f [dB(1/m)]	Result QP [dB(uV/m)]	Limit QP [dB(uV/m)]	Margin QP [dB]	Height [cm]	Angle [deg]	Remark
1	82.501	H	49.9	-17.4	32.5	40.0	7.5	400.0	194.5	
2	87.109	V	50.9	-18.3	32.6	40.0	7.4	199.0	200.4	
3	100.075	V	53.9	-17.4	36.5	40.0	3.5	100.0	352.4	
4	132.578	V	43.4	-13.5	29.9	40.0	10.1	100.0	330.2	
5	260.981	V	41.7	-11.9	29.8	47.0	17.2	100.0	253.5	
6	648.011	V	35.3	-1.1	34.2	47.0	12.8	299.0	78.8	
7	828.068	V	27.9	2.8	30.7	47.0	16.3	199.0	75.3	
8	864.079	V	29.8	3.4	33.2	47.0	13.8	199.0	61.7	

* 1 GHz ~ 6 GHz (SCP-2373HP)



Final Result

No.	Frequency [MHz]	(P)	Reading AV [dB(uV)]	Reading PK [dB(uV)]	c.f [dB(1/m)]	Result AV [dB(uV/m)]	Result PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Margin AV [dB]	Margin PK [dB]	Height [cm]	Angle [deg]	Remark
1	1731.250	V	22.7	33.6	-3.1	19.6	30.5	56.0	76.0	36.4	45.5	100.0	134.8	
2	2141.875	H	21.6	32.3	-0.9	20.7	31.4	56.0	76.0	35.3	44.6	100.0	33.6	
3	2772.500	V	21.6	32.3	0.0	21.6	32.3	56.0	76.0	34.4	43.7	100.0	163.4	
4	3388.125	H	21.0	31.9	1.8	22.8	33.7	60.0	80.0	37.2	46.3	100.0	116.3	
5	4810.625	V	17.6	28.5	6.6	24.2	35.1	60.0	80.0	35.8	44.9	100.0	17.5	

7. E.U.T. photographs

Front View



Rear View




Left View




Right View



Top View





Bottom View





Inside





Main Board





CCD Board





Connect Board





SUB Board#1



SUB Board#2



Power Board



AC/AC Adaptor

