

HD-SDI SCV-6081R

1080p HD-SDI WDR Vandal-Resistant IR Dome Camera




Key Features

- Full HD (1920 x 1080, 30fps) mega resolution, HD (1280 x 720, 60fps) resolution
- Min. Illumination 0Lux (IR LED on), IR distance 15m
- 3 ~ 8.5mm (2.8x) motorized varifocal lens
- Simple focus, WDR (100dB)
- True Day & Night (ICR), MD, SSNRIII, IP66, RS-485, Dual power

Dimensions

Unit : mm (inch)



HD-SDI Kit



SPH-120R
Repeater



SPH-110C
Converter

Accessories (Optional)



SBP-300HM6 SBP-300LM SBP-300CM SBP-300WM1 SBP-300WM SBP-300B SBP-300PM SBP-300KM

SCV-6081RN/P

VIDEO

Imaging Device	1/3" Progressive scan CMOS
Total Pixels	2,010(H) x 1,108(V), 2.2M pixels
Effective Pixels	1,944(H) x 1,092(V), 2.1M pixels
Scanning System	Progressive
Min. Illumination	Color : 1Lux@F1.2, 0.015Lux (Sens-up, 60x) B/W : 0Lux (IR LED on)
S / N Ratio	50dB (AGC off, Weight on)
Video Output	SMPTE292M (HD-SDI), Monitoring CVBS

LENS

Focal Length (Zoom Ratio)	3 ~ 8.5mm (2.8x) motorized varifocal
Max. Aperture Ratio	F1.2
Angular Field of View	H : 105.5°(Wide) ~ 37.1°(Tele) / V : 57.5°(Wide) ~ 21°(Tele)
Min. Object Distance	0.5m (1.64ft)
Focus Control	Simple focus (Motorized V/F) / Manual
Lens Type / Mount Type	DC auto iris / Board-in type

PAN / TILT / ROTATE

Pan Range	0° ~ 354°
Tilt Range	0° ~ 67°
Rotate Range	0° ~ 355°

OPERATIONAL

On Screen Display	English, Korean, French, German, Spanish, Italian, Chinese, Russian, Polish, Swedish, Danish, Portuguese, Japanese, Serbian, Czech, Romanian, Turkish
Camera Title	Off / On (Displayed up to 15 characters)
Day & Night	Auto (ICR) / External / Color / B/W
Backlight Compensation	Off / User BLC / HLC / WDR
Wide Dynamic Range	100dB
Contrast Enhancement	SSDR (Off / On)
Digital Noise Reduction	SSNRIII (Off / On)
Digital Image Stabilization	Off / On
Motion Detection	Off / On
Privacy Masking	Off / On (4ea polygonal + 16ea rectangular zones)
Sens-up (Frame Integration)	2x ~ 60x
Gain Control	Off / Low / Medium / High
White Balance	ATW / Outdoor / Indoor / Manual / AWC (1,700°K ~ 11,000°K)
Electronic Shutter Speed	ESC / A.FLK / Manual
Digital Zoom	Off / On (1x ~ 16x)
Reverse	Off / H-Rev / V-Rev / HV-Rev
Profile	Built-in
PIP	Off / On
Intelligent Video Analytics	Tampering, Virtual line, Enter / Exit, (Dis)Appear
Alarm	(MD) output 1, External D/N in 1
Remote Control Interface	RS-485
Protocol	RS-485 : Samsung-T/E, Pelco-D/P, Panasonic, Bosch, Honeywell, Vicon, AD, GE
IR Distance	15m (49.21ft) (IR LED : 12ea)

ENVIRONMENTAL

Operating Temperature / Humidity	-10°C ~ +55°C (+14°F ~ +131°F) / Less than 90% RH
Ingress Protection	IP66

ELECTRICAL

Input Voltage / Current	Dual (24V AC & 12V DC ±10%)
Power Consumption	Max. 6W

MECHANICAL

Color / Material	Ivory / Aluminum
Dimensions (WxH)	Ø160.0 x 118.5mm (Ø6.3" x 4.67")
Weight	952g (2.1 lb)

TRANSMISSION DISTANCE

5C2V (75ohm)	Max. 100 ~ 140m
L-6CHD (75ohm)	Max. 200m

* This transmission distance is theoretically calculated number, and real transmission distance can be affected by installation environment.

* The latest product information / specification can be found at www.samsungsecurity.com