

A&E Specifications

SHB-4300H Weather Proof Housing with Fully Cable Managed Bracket

Version 1.0

1. GENERAL

- a. All equipment and materials used shall be standard components that are regularly manufactured and used in the manufacturer's system.
- b. All systems and components shall have been thoroughly tested and proven in actual use.
- c. All systems and components shall be provided with an explicit manufacturer warranty.

2. ELECTRICAL

- a. Input Voltage 24V AC
- b. Power Consumption Maximum 20W

3. ENVIRONMENTAL

- a. Operating
 - i. Temperature -35°C - +50°C
 - On 5°C ± 5°C
 - ii. Blower +45°C - +5°C

4. MECHANICAL

- a. Dimensions : 147.2 x 107 x 422.4 mm (WxHxD) Outside
84 x 89 x 316 mm (WxHxD) Maximum Camera Lens combination)
- b. Weight: 1.5Kg
- c. Ingress Protection IP66
- d. Material Die Casting ADC 12
- e. Colour Pantone Cool Gray 1C
- f. Cable Glands 3 Separate Nylon Glands
- g. Wall bracket Comes with Fully Cable Managed Wall Bracket

5. CERTIFICATIONS

- CE EMC-Directive 2004 / 108 / EC
- EMC Immunity: EN 50130-4:2003
- EMC Emissions EN 50130-4:2003
- FCC Sub-part 15
- UL US, Canada

6. WARRANTY

3 years, parts and labour