

SLA-3580DN/2812DN/550DV/612DN

Diagonal 8, 6mm (1/2형, 1/3형) CS-Mount 가변 초점 렌즈



SLA-3580DN

SLA-2812DN

SLA-550DV

SLA-612DN



제품특징

SLA-3580DN

- Diagonal 6mm (1/3형) 렌즈
- 초점거리 3.5 ~ 8mm, 2배, F1.0, DCE타입
- Day & Night 지원

SLA-2812DN

- Diagonal 6mm (1/3형) 렌즈
- 초점거리 2.8 ~ 12mm, 4.2배, F1.3, DCE타입

SLA-550DV

- Diagonal 6mm (1/3형) 렌즈
- 초점거리 5 ~ 50mm, 10배, F1.3, DCE타입

SLA-612DN

- Diagonal 8mm (1/2형) 렌즈
- 초점거리 6 ~ 12mm, 2배, F1.6, DCE타입

공통사항


- Simple한 디자인, 간편한 설치
- 주차장 / 건물내외 / 근거리용 / 차량번호 확인 등 원거리용

주요사항

		SLA-3580DN	SLA-2812DN	SLA-550DV	SLA-612DN
촬영소자		Diagonal 6mm (1/3형)	Diagonal 6mm (1/3형)	Diagonal 6mm (1/3형)	Diagonal 8mm (1/2형)
해상도		52만 화소	52만 화소	52만 화소	52만 화소
조리개		DC	DC	DC	DC
촬영거리		0.2m ~ ∞	0.2m ~ ∞	0.2m ~ ∞	0.2m ~ ∞
배율		2.3배	4.2배	10배	2배
렌즈마운트		CS-mount	CS-mount	CS-mount	CS-mount
초점거리		3.5 ~ 8mm	2.8 ~ 12mm	5 ~ 50mm	6 ~ 12mm
최대구경비		F1.0	F1.3	F1.3	F1.6
렌즈화각	D	111.2° ~ 44.7°	133° ~ 29.7°	64° ~ 6.9°	86.4° ~ 38.8°
	H	83.5° ~ 35.6°	102.2° ~ 23.8°	51.8° ~ 5.6°	65.3° ~ 30.8°
	V	60.4° ~ 26.6°	74.2° ~ 17.8°	39.2° ~ 4.3°	47.4° ~ 23°
작동범위	Iris	자동 (F1.0 ~ 360)	자동 (F1.3 ~ 360)	자동 (F1.3 ~ 360)	자동 (F1.6 ~ 300)
	Focus	수동	0.3 ~ ∞	0.8 ~ ∞	수동
	Zoom	수동	수동	수동	수동
후초점거리		8.7 ~ 14.7mm	20.2 ~ 8.1mm	10.5 ~ 10.6mm	7.55 ~ 12.13mm
플랜지거리		12.5mm	12.5mm	12.5mm	12.5mm
동작온도		-10°C ~ +50°C	-10°C ~ +50°C	-10°C ~ +50°C	-10°C ~ +50°C
외형치수 (WxHxD)		38.6 x 45.3 x 46mm	43 x 48 x 56mm	47 x 57.5 x 57.7mm	40.4 x 45.7 x 43.5mm
무게		54.5g	71g	100g	53g


외관도

SLA-3580DN




단위 : mm

SLA-2812DN



SLA-550DV



SLA-612DN

