

SLA-F2480DA



SLA-F2480DA

SLA-F2480DA

Key Features

5MP, Door Jamb Head with 2.45mm lens module, FoV (H:123°, V:91°), Compatible with PNM-C20000QB, 8m (26ft) cable included, Black color, Indoor

SLA-F2480DA

SLA-F2480DA

SLA-F2480DA



Specifications

Video		
Imaging Device	Size	1/2.8"
	Type	CMOS
Min. Illumination (Lux)	Color(1/30sec, 30IRE)	0.08
	BW(1/30sec, 30IRE)	0.08
Lens		
Focal Length (mm)		2.45
Max. Aperture Ratio (F number)	Wide	2.0
	Tele	2.0
Angular Field of View	Horizontal	123°
	Vertical	91°
	Diagonal	159°
Mount Type		RJ12 connected with main unit
Focus Control		Fixed
Pan / Tilt / Rotate		
Pan / Tilt / Rotate Range	Pan	Flexible panning $\pm 30^\circ$
Environmental & Electrical		
Operating Condition	Temperature	-10°C ~ +55°C (+14°F ~ +131°F)
	Humidity	0~95% RH
Storage Condition	Temperature	-50°C~+60°C(-58°F~+140°F)
	Humidity	Less than 90% RH
Mechanical		
Color		Black
Material		Plastic
Product Dimensions		48.29(W)x37.0(H)x174.01(D)mm(1.9x1.46x6.85"), Cable: 8m(26.2ft)
Product Weight		124.5g(0.27lb), Cable: 350g(0.77lb)
Supported Products		SLA-F2480DA

Certification & Standards

EMC	FCC 47 CFR 15 Subpart B Class A, ICES-3(A)/NMB-3(A), CE/UKCA EN 55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, VCCI CISPR 32 Class A, RCM AS/NZS CISPR 32 Class A, KS C 9832 Class A, KS C 9835
Safety	UL 62368-1, CAN/CSA C22.2 NO. 62368-1
Environment	IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78


SLA-F2480DA

SLA-F2480DA



CAD

Unit: mm [inch]



© Hanwha Vision Co., Ltd. All rights reserved.