



# SLA-F2480VA

5MP 렌즈 모듈



## Key Features

- 컴팩트한 원통형 디자인
- 2.45mm 고정 초점 거리
- 122° 수평 시야각 (HFoV)
- 유연한 설치를 위한 8m 케이블
- PNM-C20000QB와 호환 가능

# SLA-F2480VA

5MP 렌즈 모듈



## Specifications

| 영상                        |                  |                                                                                                                                                                                                         |
|---------------------------|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 촬영 소자                     | 크기               | 1/2.8"                                                                                                                                                                                                  |
|                           | 종류               | CMOS                                                                                                                                                                                                    |
| 최저조도 (Lux)                | 컬러(1/30초, 30IRE) | 0.08                                                                                                                                                                                                    |
|                           | 흑(1/30초, 30IRE)  | 0.08                                                                                                                                                                                                    |
| 렌즈                        |                  |                                                                                                                                                                                                         |
| 초점거리 (mm)                 |                  | 2.45                                                                                                                                                                                                    |
| 최대 구경비 (F number)         | 광각               | 2.0                                                                                                                                                                                                     |
|                           | 협각               | 2.0                                                                                                                                                                                                     |
| 화각                        | 수평               | 122°                                                                                                                                                                                                    |
|                           | 수직               | 90°                                                                                                                                                                                                     |
|                           | 대각               | 158°                                                                                                                                                                                                    |
| 마운트 타입                    |                  | 메인유닛과 RJ12 연결                                                                                                                                                                                           |
| 포커스 제어                    |                  | 고정                                                                                                                                                                                                      |
| 동작 환경 및 전원                |                  |                                                                                                                                                                                                         |
| 동작 조건                     | 온도               | -10°C ~ +55°C (+14°F ~ +131°F)                                                                                                                                                                          |
|                           | 습도               | 0~95% RH                                                                                                                                                                                                |
| 보관 조건                     | 온도               | -50°C ~ +60°C                                                                                                                                                                                           |
|                           | 습도               | Less than 90% RH                                                                                                                                                                                        |
| 외관                        |                  |                                                                                                                                                                                                         |
| 색상                        |                  | 블랙                                                                                                                                                                                                      |
| 재질                        |                  | 플라스틱, 메탈                                                                                                                                                                                                |
| 제품 치수                     |                  | 30(W)x24.7(H)x45(D)mm(1.18x0.97x1.77"), Cable: 8m(26.2ft)                                                                                                                                               |
| 제품 무게                     |                  | 46.1g(0.1lb), Cable: 350g(0.77lb)                                                                                                                                                                       |
| Supported Products        |                  | PNM-C20000QB                                                                                                                                                                                            |
| Certification & Standards |                  |                                                                                                                                                                                                         |
| EMC                       |                  | FCC 47 CFR 15 Subpart B Class A, ICES-3(A)/NMB-3(A), CE/UKCA EN 55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, VCCI CISPR 32 Class A, RCM AS/NZS CISPR 32 Class A, KS C 9832 Class A, KS C 9835 |
| 안전                        |                  | UL 62368-1, CAN/CSA C22.2 NO. 62368-1                                                                                                                                                                   |

---

## Certification & Standards

|    |                                                                                             |
|----|---------------------------------------------------------------------------------------------|
| 환경 | IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78 |
|----|---------------------------------------------------------------------------------------------|

# SLA-F2480VA

5MP 렌즈 모듈



CAD

Unit: mm [inch]

