

SLA-F2480WA



# SLA-F2480WA

## 5MP Waterproof Lens Module

### Key Features

- Support 5MP resolution
- 2.4mm fixed focal lens
- IP66, NEMA 4X
- 8m cable included
- Compatible with PNM-C20000QB/XNB-A8004B

# SLA-F2480WA

5MP Waterproof Lens Module



## Specifications

### Video

|                         |                       |        |
|-------------------------|-----------------------|--------|
| Imaging Device          | Size                  | 1/2.8" |
|                         | Type                  | CMOS   |
| Min. Illumination (Lux) | Color(1/30sec, 30IRE) | 0.1    |
|                         | BW(1/30sec, 30IRE)    | 0.1    |

### Lens

|                                |            |                               |
|--------------------------------|------------|-------------------------------|
| Focal Length (mm)              |            | 2.4                           |
| Max. Aperture Ratio (F number) | Wide       | 2.4                           |
|                                | Tele       | 2.4                           |
| Angular Field of View          | Horizontal | 128°                          |
|                                | Vertical   | 92°                           |
|                                | Diagonal   | 172°                          |
| Mount Type                     |            | RJ12 connected with main unit |
| Focus Control                  |            | Fixed                         |

### Environmental & Electrical

|                     |             |                           |
|---------------------|-------------|---------------------------|
| Operating Condition | Temperature | -30°C~+55°C(-22°F~+131°F) |
|                     | Humidity    | 0~95% RH                  |
| Storage Condition   | Temperature | -50°C~+60°C(-58°F~+140°F) |
|                     | Humidity    | Less than 90% RH          |

### Mechanical

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Color              | Black                                                                                 |
| Material           | Metal                                                                                 |
| Product Dimensions | Lens: $\phi 35 \times 63.2 \text{mm} (\phi 1.38 \times 2.49")$ ,<br>Cable: 8m(26.2ft) |
| Product Weight     | Lens: 102.3g(0.23lb),<br>Cable: 350g(0.77lb)                                          |
| Supported Products | PNM-C20000QB                                                                          |

---

### Certification & Standards

|                    |                                                                                                                                                                                                         |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>EMC</b>         | FCC 47 CFR 15 Subpart B Class A, ICES-3(A)/NMB-3(A), CE/UKCA EN 55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, VCCI CISPR 32 Class A, RCM AS/NZS CISPR 32 Class A, KS C 9832 Class A, KS C 9835 |
| <b>Safety</b>      | UL 62368-1, CAN/CSA C22.2 NO. 62368-1                                                                                                                                                                   |
| <b>Environment</b> | IEC 60529 IP66, NEMA 250 type 4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78                                                                           |

# SLA-F2480WA

5MP Waterproof Lens Module



## CAD

Unit: mm [inch]

