

SLA-T16080WA



SLA-T16080WA

2MP, 16mm Waterproof Lens for XNB-6002



Key Features

- Color: 0.045Lux(F1.8, 1/30sec)
- 16mm fixed focal
- Product Dimensions / Weight: ø35x65.1mm(ø1.38x2.56"), 102.25g(0.225lb)
- IP66, NEMA 4X

SLA-T16080WA

2MP, 16mm Waterproof Lens for
XNB-6002



Specifications

Video

Imaging Device	Size	1/2.8"
	Type	CMOS
Min. Illumination (Lux)	Color(1/30sec, 30IRE)	0.045
	BW(1/30sec, 30IRE)	0.045

Lens

Focal Length (mm)		16mm
Max. Aperture Ratio (F number)	Wide	F1.8
	Tele	F1.8
Angular Field of View	Horizontal	19.5°
	Vertical	11°
	Diagonal	22.3°
Min. Object Distance		25m
Mount Type		RJ12 connected with main unit
Focus Control		Fixed

Environmental & Electrical

Operating Condition	Temperature	-30°C~+55°C(-22°F~+131°F)
	Humidity	0~95% RH
Storage Condition	Temperature	-50°C~+60°C(-58°F~+140°F)
	Humidity	0~95% RH

Mechanical

Color	Black
Material	Metal
Product Dimensions	ø35x65.1mm(ø1.38x2.56"), Cable: 8m(26.2ft)
Product Weight	102.25g(0.225lb)

Certification & Standards

EMC	CE/UKCA EN 55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, VCCI CISPR 32 Class A
-----	---

Certification & Standards

Environment	EN IEC 63000, IEC 60529 IP66, NEMA 250 type 4X, IEC 62262 IK10
-------------	--

SLA-T16080WA

2MP, 16mm Waterproof Lens for
XNB-6002



CAD

Unit: mm [inch]

