

SLA-T2480WA



# SLA-T2480WA

## 2MP Lens Module

### Key Features

- Color: 0.045Lux(F2.0, 1/30sec)
- 2.4mm fixed focal
- Product Dimensions / Weight:  $\phi 24 \times 49.8\text{mm}$  ( $\phi 0.94 \times 1.96''$ ), 101g(0.22lb)
- IP66, NEMA 4X

# SLA-T2480WA

2MP Lens Module



## Specifications

### Video

|                         |                       |        |
|-------------------------|-----------------------|--------|
| Imaging Device          | Size                  | 1/2.8" |
|                         | Type                  | CMOS   |
| Min. Illumination (Lux) | Color(1/30sec, 30IRE) | 0.045  |
|                         | BW(1/30sec, 30IRE)    | 0.045  |

### Lens

|                                |            |                               |
|--------------------------------|------------|-------------------------------|
| Focal Length (mm)              |            | 2.4                           |
| Max. Aperture Ratio (F number) | Wide       | 2.0                           |
|                                | Tele       | 2.0                           |
| Angular Field of View          | Horizontal | 138°                          |
|                                | Vertical   | 73°                           |
|                                | Diagonal   | 165°                          |
| Mount Type                     |            | RJ12 connected with main unit |
| Focus Control                  |            | Fixed                         |

### Environmental & Electrical

|                     |             |                                        |
|---------------------|-------------|----------------------------------------|
| Operating Condition | Temperature | -30°C~+55°C(-22°F~+131°F)              |
|                     | Humidity    | 0~95% RH                               |
|                     | Others      | Start up should be done at above -30°C |
| Storage Condition   | Temperature | -50°C~+60°C(-58°F~+140°F)              |
|                     | Humidity    | 0~95% RH                               |

### Mechanical

|                    |                                                |
|--------------------|------------------------------------------------|
| Color              | Black                                          |
| Material           | Plastic                                        |
| Product Dimensions | ø35x63.2mm(ø1.38x2.49"), Cable: 8m(26.2ft)     |
| Product Weight     | 101g(0.22lb)                                   |
| Supported Products | XNB-6002, PNM-9000QB, PNM-C20000QB, XNB-A8004B |

---

### Certification & Standards

|                    |                                                                                                                                                                                                         |
|--------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>EMC</b>         | FCC 47 CFR 15 Subpart B Class A, ICES-3(A)/NMB-3(A), CE/UKCA EN 55032 Class A, EN 50130-4, EN 61000-3-2, EN 61000-3-3, VCCI CISPR 32 Class A, RCM AS/NZS CISPR 32 Class A, KS C 9832 Class A, KS C 9835 |
| <b>Safety</b>      | UL 62368-1, CAN/CSA C22.2 NO. 62368-1                                                                                                                                                                   |
| <b>Environment</b> | EN IEC 63000, IEC 60529 IP66, NEMA 250 type 4X                                                                                                                                                          |

# SLA-T2480WA

2MP Lens Module



CAD

Unit: mm [inch]

