



SLA-T2880BA

2MP Network Bandit Barrier lens

Key Features

- 2 Megapixel (1920 x 1080) resolution
- 2.8mm wide-angle lens
- H.265, H.264, MJPEG codec support, Multiple streaming
- 60fps@2MP (H.265 / H.264)
- WDR (120dB)
- Built-in Analytics
- SD / SDHC / SDXC memory slot (Maximum 256GB)
- Hallway View, WiseStream II support
- LDC, PoE / 12V DC, Bi-directional audio support
- Adjustable height and installation options for various installation types
- Includes XNB-6001 main unit & SLA-T2480 lens with 8m cable

SLA-T2880BA

2MP Network Bandit Barrier lens



Specifications

映像

Imaging Device	サイズ	1/2.8"
	タイプ	CMOS
Min. Illumination (Lux)	Color(1/30sec, 30IRE)	0.045
	BW(1/30sec, 30IRE)	0.045

レンズ

Focal Length (mm)		2.8
Max. Aperture Ratio (F number)	Wide	2.0
	Tele	2.0
視野角度	Horizontal	108°
	Vertical	63°
	Diagonal	122°
Mount Type		RJ12 connected with main unit
Focus Control		Fixed

Environmental & Electrical

動作条件	温度	-10°C ~ +55°C (+14°F ~ +131°F)
	湿度	Less than 90% RH
保管条件	温度	-50°C ~ +60°C (-58°F ~ +140°F)
	湿度	Less than 90% RH

Mechanical

カラー	黒
材料	プラスチック, Metal
Product Dimensions	66.5x46x175~737mm(2.6"x1.8"x6.9~29.0"), Main Unit: 131.1x28x86mm(5.16"x1.10"x3.39"), Cable: 8m(26.2ft)
Product Weight	250~1,000g(0.55~2.205 lb), Camera Body: 245g(0.54 lb)
Supported Products	XNB-6002, PNM-9000QB, PNM-C20000QB, XNB-A8004B