



SLA-T4680DA

Doorjam camera for PNM-9000QB, XNB-6002

Key Features

- Compatible with XNB-6001 not included
- 2 Megapixel (1920 x 1080) resolution
- 4.6mm pinhole lens
- 0.06Lux@F2.5
- 8m cable
- Easy installation
- Flexible panning ± 30 degrees
- Multiple housing color options to match the door jamb
- Hidden security screw for discrete look
- Includes lens & housing

SLA-T4680DA

Doorjam camera for PNM-9000QB,
XNB-6002



Specifications

Video

Imaging Device	Size	1/2.8"
	Type	CMOS
Min. Illumination (Lux)	Color(1/30sec, 30IRE)	0.06
	BW(1/30sec, 30IRE)	0.06

Lens

Focal Length (mm)		4.6
Max. Aperture Ratio (F number)	Wide	2.5
	Tele	2.5
Angular Field of View	Horizontal	73°
	Vertical	39°
	Diagonal	85°
Min. Object Distance		0.3m(0.98ft)
Mount Type		RJ12 connected with main unit
Focus Control		Fixed

Pan / Tilt / Rotate

Pan / Tilt / Rotate Range	Pan	Flexible panning $\pm 30^\circ$
---------------------------	-----	---------------------------------

Environmental & Electrical

Operating Condition	Temperature	-10°C ~ +55°C (+14°F ~ +131°F)
	Humidity	Less than 90% RH
Storage Condition	Temperature	-50°C ~ +60°C (-58°F ~ +140°F)
	Humidity	Less than 90% RH

Mechanical

Color	Black
Material	Plastic
Product Dimensions	Housing: 42.9(W)x33.0(H)x170.0(D)mm(1.69"x1.30"x6.69"), Lens: 30(W)x27.9(H)x45(D)mm(1.18"x1.10"x1.77"), Cable: 8m(26.2ft)

Mechanical

Product Weight	Housing: 70g(0.15lb), Lens: 41g(0.09lb)
Supported Products	XNB-6002, PNM-9000QB, PNM-C20000QB, XNB-A8004B

SLA-T4680DA

Doorjam camera for PNM-9000QB,
XNB-6002



CAD

Unit: mm [inch]

