



SMT-2431

24" LED Monitor



Key Features

- Frameless Design
- Support up to 1920 x 1080 resolution
- Brightness : 250cd/m²
- Contrast : 4000:1
- Viewing Angle(H/V) : 178°/178°
- Response Time : 14ms
- Video Input : HDMI, VGA
- Panel Life : 30,000 hours
- Designed and tested on 24/7 operation

SMT-2431

24" LED Monitor



Specifications

Display

Type	LED Monitor
Screen Size	24inch
Max. Resolution	1920x1080
Brightness	250 cd/m ²
Contrast Ratio	4000:1
Aspect Ratio	16:9
Viewing Angle (H/V)	178°/178°
Display Color	16.7M
Response Time	14ms
Panel Life	30,000 hours

Interface

Video	Connectors	VGA(1), HDMI(1)
VGA	Connector	VGA
	Available Format	1920x1080@60Hz
HDMI	Connector	HDMI
	Available Format	1920x1080@60Hz

On Screen Display

Functions	VESA™ DPMS Compatible
Language	English, French, German, Italian, Simplified Chinese, Traditional Chinese, Korean, Japanese, Espanola, Portuguese, Russian, Arabic

General

Electrical	Input Voltage	AC 100 ~ 240V(50/60Hz)
	Power Consumption	30W
Environmental	Operating Temperature	0 ~ +40°C (+32°F ~ +104°F)
	Operating Humidity	10% ~ 80% (non-condensing)

General

Mechanical	Dimensions with Stand (WxHxD)	540x420.3x224.1mm(21.3x16.5x8.8")
	Dimensions without Stand (WxHxD)	540x324x46mm(21.3x12.8x1.8")
	Weight	3.5Kg(7.7lb)
	Packing Dimension (WxHxD)	606*110*493mm(23.9x4.3x19.4")
	Packing Weight	4.28Kg(9.4lb)
	Cabinet Color	Black
	VESA Mounts Interface	100x100mm

SMT-2431

24" LED Monitor



CAD

Unit: mm [inch]



