



SMT-2710

27" FHD monitor



Key Features

- 27 inch FHD Monitor, support up to 1920×1080 @60Hz
- Brightness 250 cd/m² (Typical), Contrast 3000:1 (Minimum) 4000:1 (Typical)
- Viewing Angle (H/V) : 178°/178°, Response Time : 6.5ms (Typical)
- Video Input : HDMI, DP, VGA
- Panel Life : 30,000 hours
- Designed and tested on 24/7 operation

SMT-2710

27" FHD monitor



Specifications

Display

Type	LED Monitor
Screen Size	27inch
Max. Resolution	1920x1080
Brightness	250 cd/m ²
Contrast Ratio	4000:1
Aspect Ratio	16:9
Viewing Angle (H/V)	178°/178°
Display Color	16.7M
Response Time	6.5ms
Panel Life	30,000 hours

Interface

Video	Connectors	VGA(1), HDMI(1), DP(1)
VGA	Connector	VGA
	Available Format	1920x1080@60Hz
HDMI	Connector	HDMI
	Available Format	1920x1080@60Hz
DP	Connector	DP
	Available Format	1920x1080@60Hz
Audio	Connector	Audio in(1)/out(1)
	Output Signal	Speakers : 4Ω 2.5W x 2

On Screen Display

Functions	VESA™ DPMS Compatible
Language	English, French, German, Italian, Simplified Chinese, Traditional Chinese, Korean, Japanese, Espanola, Portuguese, Russian, Arabic

General

Electrical	Input Voltage	AC 100 ~ 240V(50/60Hz)
	Power Consumption	45W

General

Environmental	Operating Temperature	0 ~ +40°C (+32°F ~ +104°F)
	Operating Humidity	10% ~ 80% (non-condensing)
Mechanical	Dimensions with Stand (WxHxD)	614.7x452.5x224.1mm(24.2x17.8x8.8")
	Dimensions without Stand (WxHxD)	614.7x336.4x50.8mm(24.2x13.2x2")
	Weight	4.54Kg(10lb, with stand), 4.13Kg(9.1lb, without stand)
	Packing Dimension (WxHxD)	675*115*511mm(26.6x4.5x20.1")
	Packing Weight	5.53Kg(12.2lb)
	Cabinet Color	Black
	VESA Mounts Interface	100x100mm