



SMT-3240

32" LED monitor



Key Features

- 32 inch UHD Monitor, support up to 3840×2160@60Hz
- Brightness 300 cd/m² (Typ) , Contrast 700:1 (Min) 1000:1 (Typ)
- Viewing Angle (H/V) : 178°/178°, Response Time : 14ms(Typical)
- Video Input : HDMI, DP
- Frameless design with monitor stand
- Panel Life : 30,000 hours
- Designed and tested on 24/7 operation

SMT-3240

32" LED monitor



Specifications

Display

Type	LED Monitor
Screen Size	32inch
Max. Resolution	3840x2160
Brightness	300 cd/m ²
Contrast Ratio	1000:1
Aspect Ratio	16:9
Viewing Angle (H/V)	178°/178°
Display Color	1.07B
Response Time	14ms
Panel Life	30,000 hours

Interface

Video	Connectors	HDMI(1), DP(1)
HDMI	Connector	HDMI
	Available Format	3840x2160@60Hz
DP	Connector	DP
	Available Format	3840x2160@60Hz
Audio	Connector	Audio Out
	Output Signal	Speakers : 6Ω 2W x 2

On Screen Display

Functions	VESA™ DPMS Compatible
Language	English, French, German, Italian, Simplified Chinese, Traditional Chinese, Korean, Japanese, Espanola, Portuguese, Russian, Arabic

General

Electrical	Input Voltage	AC 100 ~ 240V(50/60Hz)
	Power Consumption	55W
Environmental	Operating Temperature	0 ~ +40°C (+32°F ~ +104°F)
	Operating Humidity	10% ~ 80% (non-condensing)

General

Mechanical	Dimensions with Stand (WxHxD)	714.6x485.7x200.9mm(28.1x19.1x7.9")
	Dimensions without Stand (WxHxD)	714.6x445.6x53.7mm(28.1x17.5x2.1")
	Weight	8.0kg(17.6lb, with stand), 6.5Kg(14.3lb, without stand)
	Packing Dimension (WxHxD)	790*195*503mm(31.1x7.7x19.8")
	Packing Weight	9.38Kg(20.7lb)
	Cabinet Color	Black
	VESA Mounts Interface	100x100mm

SMT-3240

32" LED monitor



CAD

Unit: mm [inch]

