



SMT-4345

Moniteur UHD 43 pouces avec deux fenêtres PIP/PBP



Key Features

- Moniteur UHD de 43 pouces, prise en charge jusqu'à 3840×2160@60Hz
- Luminosité 300 cd/m², contraste 1200:1
- Angle de vision (H/V) : 178°/178°, temps de réponse : 8 ms
- Entrée vidéo : HDMI(2), DP(1), deux fenêtres PIP/PBP
- Durée de vie du panneau : 30 000 heures
- Conçu et testé pour une utilisation 24h/24 et 7j/7

SMT-4345

Moniteur UHD 43 pouces avec deux fenêtres PIP/PBP



Specifications

Display

Type	LED Monitor
Screen Size	43inch
Max. Resolution	3840x2160
Brightness	300 cd/m ²
Contrast Ratio	1200:1
Aspect Ratio	16:9
Viewing Angle (H/V)	178°/178°
Display Color	1.07B
Response Time	8ms
Panel Life	30,000 hours

Interface

Video	Connectors	HDMI(2), DP(1), two windows PIP/PBP
HDMI	Connector	HDMI x 2
	Available Format	3840x2160@60Hz
DP	Connector	DP
	Available Format	3840x2160@60Hz
Audio	Connector	Audio Out
	Output Signal	Speakers : 6Ω 2W x 2
Application Support		Remote controller

On Screen Display

Functions	VESA™ DPMS Compatible
Language	English, French, German, Italian, Simplified Chinese, Traditional Chinese, Korean, Japanese, Espanola, Portuguese, Russian, Arabic

General

Electrical	Input Voltage	AC 100 ~ 240V(50/60Hz)
	Power Consumption	85W

General

Environmental	Operating Temperature	0 ~ +40°C (+32°F ~ +104°F)
	Operating Humidity	10% ~ 80% (non-condensing)
Mechanical	Dimensions without Stand (WxHxD)	954.9x570.3x79.8mm (37.6x22.5x3.2")
	Weight	5.8kg(12.8lb)
	Packing Dimension (WxHxD)	1077x780x200mm (42.4x30.7x7.9")
	Packing Weight	10.5kg(23.2lb)
	Cabinet Color	Black
	VESA Mounts Interface	200x200mm

SMT-4345

Moniteur UHD 43 pouces avec deux
fenêtres PIP/PBP



CAD

Unit: mm [inch]

